

# AUM-S

## SPRAYABLE SEALING AND BONDING MATERIAL BASED ON MS POLYMER.

- Sealant for metal plates based on MS Polymers
- Excellent adhesive power – sprayable
- It contains no silicon and isocyanides
- Paintable with the most of the enamels
- It is possible to restore the sealing and bonding in their original state
- Fast polymerization
- Direct paintable
- The open cartridge keeps for a long time



### NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

# Automotive AUTOSEAL MS

## GENERAL INFORMATION

AUTOSEAL MS is a sealant based on MS polymer with high adhesive power.  
 AUTOSEAL MS can be applied both in thin and thicker layers: both can be refined with

a brush, restoring the sealing in their original state.; it can be also sprayed.  
 AUTOSEAL MS contains less than 7% of aliphatic solvents; it is quite odorless.

## TECHNICAL INFORMATION AND PACKAGING

At 23°C / 50% R.H.  
 Base: MS Polymer  
 Colour: Grey, Beige  
 Consistency: sprayable  
 Density: 1,540kg/m3  
 Curing (23°C / 50% R.H.):  
 3 mm in 24 hours, 5mm in 48 hours.

Skimming time: 15 min  
 E-modulo 100% Mpa: 0,85  
 Temperature resistance: -40°C to +90°C  
 Mechanical resistance: 125 Nw  
 Elongation at break: >250%  
 Hardness (Shore A): 40

## APPLICATION AND USE

- AUTOSEAL MS has been designed to restore all the sealing of the metal plates in the automotive industry.
- AUTOSEAL MS is suitable to seal inside the engine compartment, along the edge of the bonnet, in the doors, inside the luggage compartment, in the wheels etc... The product ensures a perfect holding because of its adhesive and elastic power; it reduces vibrations and noises. Soundproofing and anticorrosive.
- The product can be applied on different kind of surfaces besides the metallic ones, in fact it adheres also on different synthetic materials, glass and plexi. It
- slightly adheres on PP, PE, PPE PTFE  
 USE: the product must be applied on clean, degreased and dry surfaces.

Article nr	Name	Content	Section
------------	------	---------	---------

