

SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2015/830



AQUASOLV

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : AQUASOLV
Registration number REACH : Not applicable (mixture)
Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Cleansing product
Detergent according to Regulation (EC) No 648/2004

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Novatio*
Industrielaan 5B
B-2250 Olen
☎ +32 14 25 76 40
☎ +32 14 22 02 66
info@novatio.be
*NOVATIO is a registered trademark of Novatech International
Industrielaan 5B

Manufacturer of the product

Novatech International N.V.
Industrielaan 5B
B-2250 Olen
☎ +32 14 85 97 37
☎ +32 14 85 97 38
info@tec7.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):
+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Skin Corr.	category 1	H314: Causes severe skin burns and eye damage.

2.2. Label elements



Contains: disodium metasilicate; sodium hydroxide; isotridecanol, ethoxylated (>1<2,5 mol EO).

Signal word Danger

H-statements

H314 Causes severe skin burns and eye damage.

P-statements

P280 Wear protective gloves, protective clothing and eye protection/face protection.
P260 Do not breathe vapours/mist.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

AQUASOLV

P310

Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No other hazards known

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
disodium metasilicate 01-2119449811-37	6834-92-0 229-912-9	C<5 %	Met. Corr. 1; H290 Skin Corr. 1B; H314 STOT SE 3; H335	(1)(6)	Constituent
sodium hydroxide	1310-73-2 215-185-5	C<5 %	Met. Corr. 1; H290 Skin Corr. 1A; H314	(1)(2)(6)(8)	Constituent
2-(2-butoxyethoxy)ethanol 01-2119475104-44	112-34-5 203-961-6	C<5 %	Eye Irrit. 2; H319	(1)(2)(10)	Constituent
propan-2-ol 01-2119457558-25	67-63-0 200-661-7	C<5 %	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Constituent
isotridecanol, ethoxylated (>1<2,5 mol EO) 01-2119976362-32	69011-36-5 500-241-6	5%<C<15%	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 3; H412	(1)(10)	Constituent

(1) For H-statements in full: see heading 16

(2) Substance with a Community workplace exposure limit

(6) Enumerated in Annex VI of Regulation (EC) No. 1272/2008 but the classification has been adapted after evaluation of available test data

(8) Specific concentration limits, see heading 16

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Wash immediately with lots of water (15 minutes)/shower. Remove clothing while washing. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service. If burned surface > 10%: take victim to hospital.

After eye contact:

Rinse immediately with plenty of water for 15 minutes. Do not apply neutralizing agents. Take victim to an ophthalmologist.

After ingestion:

Rinse mouth with water. Do not induce vomiting. Do not give activated charcoal. Do not give chemical antidote. Immediately consult a doctor/medical service.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

No effects known.

After skin contact:

Caustic burns/corrosion of the skin.

After eye contact:

Corrosion of the eye tissue.

After ingestion:

Vomiting. Burns to the gastric/intestinal mucosa. Possible esophageal perforation.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

Reason for revision: 9.1

Publication date: 2003-10-10

Date of revision: 2016-06-15

Revision number: 0502

Product number: 36577

2 / 18

AQUASOLV

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Water spray. Polyvalent foam. BC powder. Carbon dioxide.

5.1.2 Unsuitable extinguishing media:

No unsuitable extinguishing media known.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO₂ are formed.

5.3. Advice for firefighters

5.3.1 Instructions:

No specific fire-fighting instructions required.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Corrosion-proof suit. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No naked flames.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Corrosion-proof suit.

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Contain released product. Dam up the liquid spill. Try to reduce evaporation. Take account of toxic/corrosive precipitation water. Prevent soil and water pollution. Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Keep away from naked flames/heat. Observe strict hygiene. Keep container tightly closed.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Keep container in a well-ventilated place. Protect against frost. Keep locked up. Unauthorized persons are not admitted. Meet the legal requirements.

7.2.2 Keep away from:

Heat sources, oxidizing agents, reducing agents, (strong) acids, (strong) bases.

7.2.3 Suitable packaging material:

No data available

7.2.4 Non suitable packaging material:

Metal.

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

2-(2-Butoxyethoxy)ethanol	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	10 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	67.5 mg/m ³
	Short time value (Indicative occupational exposure limit value)	15 ppm

Reason for revision: 9.1

Publication date: 2003-10-10

Date of revision: 2016-06-15

Revision number: 0502

Product number: 36577

3 / 18

AQUASOLV

2-(2-Butoxyethoxy)ethanol	Short time value (Indicative occupational exposure limit value)	101.2 mg/m ³
---------------------------	---	-------------------------

Belgium

2-(2-Butoxyéthoxy)éthanol	Time-weighted average exposure limit 8 h	10 ppm
	Time-weighted average exposure limit 8 h	67.5 mg/m ³
	Short time value	15 ppm
	Short time value	101.2 mg/m ³
Alcool isopropylique	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	500 mg/m ³
	Short time value	400 ppm
	Short time value	1000 mg/m ³
Sodium (hydroxyde de)	Time-weighted average exposure limit 8 h	2 mg/m ³ (M)

La mention "M" indique que lors d'une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d'intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l'exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d'échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d'échantillonnage.

The Netherlands

2-(2-butoxyethoxy)ethanol	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	7.4 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	50 mg/m ³
	Short time value (Public occupational exposure limit value)	15 ppm
	Short time value (Public occupational exposure limit value)	100 mg/m ³
2-Propanol	Time-weighted average exposure limit 8 h (Private occupational exposure limit value)	260 ppm
	Time-weighted average exposure limit 8 h (Private occupational exposure limit value)	650 mg/m ³

France

2-(2-Butoxyéthoxy)éthanol	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	10 ppm
	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	67.5 mg/m ³
	Short time value (VRI: Valeur réglementaire indicative)	15 ppm
	Short time value (VRI: Valeur réglementaire indicative)	101.2 mg/m ³
Alcool isopropylique	Short time value (VL: Valeur non réglementaire indicative)	400 ppm
	Short time value (VL: Valeur non réglementaire indicative)	980 mg/m ³
Sodium (hydroxyde de)	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	2 mg/m ³

Germany

2-(2-Butoxyethoxy)ethanol	Time-weighted average exposure limit 8 h (TRGS 900)	10 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	67 mg/m ³
Propan-2-ol	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	500 mg/m ³

UK

2-(2-Butoxyethoxy)ethanol	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	10 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	67.5 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	15 ppm
	Short time value (Workplace exposure limit (EH40/2005))	101.2 mg/m ³
Propan-2-ol	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	999 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1250 mg/m ³
Sodium hydroxide	Short time value (Workplace exposure limit (EH40/2005))	2 mg/m ³

USA (TLV-ACGIH)

2-propanol	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	200 ppm
	Short time value (TLV - Adopted Value)	400 ppm
Diethylene glycol monobutyl ether	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	10 ppm (IFV)
Sodium hydroxide	Momentary value (TLV - Adopted Value)	2 mg/m ³

(IFV): Inhalable fraction and vapor

b) National biological limit values

If limit values are applicable and available these will be listed below.

Reason for revision: 9.1

Publication date: 2003-10-10

Date of revision: 2016-06-15

Revision number: 0502

Product number: 36577

4 / 18

AQUASOLV

Germany

Propan-2-ol (Aceton)	Urin: expositionsende, bzw. schichtende	25 mg/l	11/2012 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG
Propan-2-ol (Aceton)	Vollblut: expositionsende, bzw. schichtende	25 mg/l	11/2012 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG
Vitamin K-Antagonisten (Quick-Wert)	Vollblut: keine beschränkung	Reduktion auf nicht weniger als 70%	11/2012 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG

USA (BEI-ACGIH)

2-Propanol (Acetone)	Urine: end of shift at end of workweek	40 mg/L	
----------------------	--	---------	--

8.1.2 Sampling methods

If applicable and available it will be listed below.

Isopropanol (Volatile Organic compounds)	NIOSH	2549
Isopropyl Alcohol (Alcohols I)	NIOSH	1400
Isopropyl Alcohol	OSHA	109

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 DNEL/PNEC values

DNEL/DMEL - Workers

disodium metasilicate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects dermal	1.49 mg/kg bw/day	
	Long-term systemic effects inhalation	6.22 mg/m ³	

sodium hydroxide

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term local effects inhalation	1 mg/m ³	

2-(2-butoxyethoxy)ethanol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	67.5 mg/m ³	
	Long-term local effects inhalation	67.5 mg/m ³	
	Acute local effects inhalation	101.2 mg/m ³	
	Long-term systemic effects dermal	83 mg/kg bw/day	

propan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	500 mg/m ³	
	Long-term systemic effects dermal	888 mg/kg bw/day	

isotridecanol, ethoxylated (>1<2,5 mol EO)

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	294 mg/m ³	
	Long-term systemic effects dermal	2080 mg/kg bw/day	

DNEL/DMEL - General population

disodium metasilicate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects dermal	0.74 mg/kg bw/day	
	Long-term systemic effects inhalation	1.55 mg/m ³	
	Long-term systemic effects oral	0.74 mg/kg bw/day	

sodium hydroxide

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term local effects inhalation	1 mg/m ³	

2-(2-butoxyethoxy)ethanol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	40.5 mg/m ³	
	Long-term local effects inhalation	40.5 mg/m ³	
	Acute local effects inhalation	60.7 mg/m ³	
	Long-term systemic effects dermal	50 mg/kg bw/day	
	Long-term systemic effects oral	5 mg/kg bw/day	

propan-2-ol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	89 mg/m ³	
	Long-term systemic effects dermal	319 mg/kg bw/day	
	Long-term systemic effects oral	26 mg/kg bw/day	

Reason for revision: 9.1

Publication date: 2003-10-10

Date of revision: 2016-06-15

Revision number: 0502

Product number: 36577

5 / 18

AQUASOLV

isotridecanol, ethoxylated (>1<2,5 mol EO)

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	87 mg/m ³	
	Long-term systemic effects dermal	1250 mg/kg bw/day	
	Long-term systemic effects oral	25 mg/kg bw/day	

PNEC

disodium metasilicate

Compartments	Value	Remark
Fresh water	7.5 mg/l	
Marine water	1 mg/l	
Aqua (intermittent releases)	7.5 mg/l	
STP	1000 mg/l	

2-(2-butoxyethoxy)ethanol

Compartments	Value	Remark
Fresh water	1.1 mg/l	
Marine water	0.11 mg/l	
Aqua (intermittent releases)	11 mg/l	
STP	200 mg/l	
Fresh water sediment	4.4 mg/kg sediment dw	
Marine water sediment	0.44 mg/kg sediment dw	
Soil	0.32 mg/kg soil dw	
Food	56 mg/kg food	

propan-2-ol

Compartments	Value	Remark
Fresh water	140.9 mg/l	
Marine water	140.9 mg/l	
Aqua (intermittent releases)	140.9 mg/l	
STP	2251 mg/l	
Fresh water sediment	552 mg/kg sediment dw	
Marine water sediment	552 mg/kg sediment dw	
Soil	28 mg/kg soil dw	
Oral	160 mg/kg food	

isotridecanol, ethoxylated (>1<2,5 mol EO)

Compartments	Value	Remark
Fresh water	0.074 mg/l	
Salt water	0.0074 mg/l	
Aqua (intermittent releases)	0.015 mg/l	
STP	1.4 mg/l	
Fresh water sediment	0.604 mg/kg sediment dw	
Marine water sediment	0.0604 mg/kg sediment dw	
Soil	0.1 mg/kg soil dw	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

8.2.2 Individual protection measures, such as personal protective equipment

Observe strict hygiene. Keep container tightly closed. Do not eat, drink or smoke during work.

a) Respiratory protection:

Wear gas mask with filter type A if conc. in air > exposure limit.

b) Hand protection:

Gloves.

Materials	Breakthrough time	Thickness
nitrile rubber	>480 minutes	0.35 mm

- materials (good resistance)

Nitrile rubber.

c) Eye protection:

Protective goggles.

d) Skin protection:

Head/neck protection. Corrosion-proof clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

Reason for revision: 9.1

Publication date: 2003-10-10

Date of revision: 2016-06-15

Revision number: 0502

Product number: 36577

6 / 18

AQUASOLV

9.1. Information on basic physical and chemical properties

Physical form	Liquid
Odour	Characteristic odour
Odour threshold	No data available
Colour	No data available on colour
Particle size	Not applicable (liquid)
Explosion limits	
Flammability	Non-flammable
Log Kow	Not applicable (mixture)
Dynamic viscosity	1 mPa.s ; 20 °C
Kinematic viscosity	1 mm ² /s ; 20 °C
Melting point	0 °C
Boiling point	78 °C - 233 °C
Flash point	> 65 °C
Evaporation rate	1.3 ; butyl acetate
Relative vapour density	No data available
Vapour pressure	43 hPa ; 20 °C
Solubility	water ; Complete
Relative density	1.0 ; 20 °C
Decomposition temperature	No data available
Auto-ignition temperature	200 °C
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
pH	12.9

9.2. Other information

Absolute density	1031 kg/m ³ ; 20 °C
------------------	--------------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Heating increases the fire hazard. Substance has basic reaction.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Keep away from naked flames/heat.

10.5. Incompatible materials

Oxidizing agents, reducing agents, (strong) acids, (strong) bases.

10.6. Hazardous decomposition products

Upon combustion: CO and CO₂ are formed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

AQUASOLV

No (test)data on the mixture available

disodium metasilicate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	770 mg/kg bw - 820 mg/kg bw		Mouse (male/female)	Experimental value	
Dermal	LD50		> 5000 mg/kg bw	24 h	Rat (male/female)	Read-across	
Inhalation (vapours)	LC50		> 2.06 mg/l air	4 h	Rat (male/female)	Read-across	

sodium hydroxide

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral						Data waiving	
Dermal						Data waiving	
Inhalation						Data waiving	

Reason for revision: 9.1

Publication date: 2003-10-10

Date of revision: 2016-06-15

Revision number: 0502

Product number: 36577

7 / 18

AQUASOLV

2-(2-butoxyethoxy)ethanol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	2410 mg/kg bw - 5530 mg/kg bw		Mouse (male)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	2764 mg/kg bw		Rabbit (male)	Experimental value	
Inhalation (aerosol)	IRT (inhalation risk test)	BASF test	> 29 ppm	2 h	Mouse	Experimental value	

propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	5840 mg/kg bw		Rat	Experimental value	
Dermal	LD50	Equivalent to OECD 402	13120 mg/kg bw	24 h	Rabbit	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 10000 ppm	6 h	Rat (male/female)	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Not classified for acute toxicity

Corrosion/irritation

AQUASOLV

No (test)data on the mixture available

disodium metasilicate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Corrosive	Other	0.17 minutes	30 minutes; 1; 2; 4 hours; daily (14 days)	Rabbit	Inconclusive, insufficient data	
Skin	Corrosive	OECD 404	4 h	1; 24; 48; 72 hours	Rabbit	Experimental value	
Inhalation (dust)	Irritating; STOT SE cat.3					Annex VI	

sodium hydroxide

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	OECD 405		24; 48; 72 hours	Rabbit	Expert judgement	2 % aqueous solution
Eye	Highly corrosive					Expert judgement	Aqueous solution
Skin	Highly corrosive					Expert judgement	

2-(2-butoxyethoxy)ethanol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Highly irritating	OECD 405		24; 48; 72 hours	Rabbit	Weight of evidence	
Skin	Slightly irritating	OECD 404		24; 48; 72 hours	Rabbit	Experimental value	

propan-2-ol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	Equivalent to OECD 405		24 hours	Rabbit	Experimental value	Single treatment
Skin	Not irritating		4 h	4; 24; 48; 72 hours	Rabbit	Experimental value	

isotridecanol, ethoxylated (>1<2,5 mol EO)

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Serious eye damage	OECD 405	72 h	24; 48; 72 hours	Rabbit	Experimental value	
Skin	Irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

Classification is based on the pH

Conclusion

Causes severe skin burns and eye damage.

Respiratory or skin sensitisation

AQUASOLV

No (test)data on the mixture available

Reason for revision: 9.1

Publication date: 2003-10-10

Date of revision: 2016-06-15

Revision number: 0502

Product number: 36577

8 / 18

AQUASOLV

disodium metasilicate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 429			Mouse (female)	Experimental value	

sodium hydroxide

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing		24 h		Human (male)	Experimental value	

2-(2-butoxyethoxy)ethanol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406		24; 48 hours	Guinea pig (male/female)	Experimental value	

propan-2-ol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406	3 weeks (6h/day, 1 day/week)	24; 48 hours	Guinea pig (male/female)	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Not classified as sensitizing for skin

Specific target organ toxicity

AQUASOLV

No (test)data on the mixture available

disodium metasilicate

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral	NOAEL	Equivalent to OECD 408	> 227 mg/kg bw/day	General	No effect	3 month(s)	Rat (male/female)	Experimental value
Dermal								Data waiving
Inhalation								Data waiving

sodium hydroxide

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral								Data waiving
Dermal								Data waiving
Inhalation								Data waiving

2-(2-butoxyethoxy)ethanol

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (drinking water)	NOAEL	OECD 408	250 mg/kg bw/day		No effect	90 days (continuous)	Rat (male/female)	Experimental value
Dermal	NOAEL	Equivalent to OECD 411	< 200 mg/kg bw/day	Skin	Not irritating	13 weeks (daily, 5 days/week)	Rat (male/female)	Experimental value
					No adverse systemic effects			
Inhalation	NOAEL	OECD 413	14 ppm	Lungs	No effect	90 days (6h/day)	Rat (male/female)	Experimental value

propan-2-ol

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral								Data waiving
Dermal								Data waiving
Inhalation (vapours)	NOAEC	OECD 451	5000 ppm		No effect	104 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value
Inhalation (vapours)	NOAEL	OECD 413	5000 ppm		No effect	13 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value
Inhalation (vapours)	Dose level	OECD 403	5000 ppm	Central nervous system	Drowsiness, dizziness	6 h	Rat (male/female)	Experimental value

Judgement is based on the relevant ingredients

Conclusion

Not classified for subchronic toxicity

Mutagenicity (in vitro)

AQUASOLV

No (test)data on the mixture available

Reason for revision: 9.1

Publication date: 2003-10-10

Date of revision: 2016-06-15

Revision number: 0502

Product number: 36577

9 / 18

AQUASOLV

disodium metasilicate

Result	Method	Test substrate	Effect	Value determination
Negative	OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value

sodium hydroxide

Result	Method	Test substrate	Effect	Value determination
				Data waiving

2-(2-butoxyethoxy)ethanol

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)		Experimental value
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value

propan-2-ol

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)	No effect	Experimental value

Mutagenicity (in vivo)

AQUASOLV

No (test)data on the mixture available

disodium metasilicate

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 475	24 h	Mouse (male)		Experimental value

sodium hydroxide

Result	Method	Exposure time	Test substrate	Organ	Value determination
					Data waiving

2-(2-butoxyethoxy)ethanol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 475		Mouse (male/female)		Experimental value

propan-2-ol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 474		Mouse (male/female)		Experimental value

Judgement is based on the relevant ingredients

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

AQUASOLV

No (test)data on the mixture available

disodium metasilicate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Oral (drinking water)	Dose level		150 mg/kg bw/day	14 month(s)	Rat (male/female)	No effect		

sodium hydroxide

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation								Data waiving
Dermal								Data waiving
Oral								Data waiving

propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOEL	Equivalent to OECD 451	5000 ppm	104 weeks (6h/day, 5 days/week)	Mouse (male/female)	No carcinogenic effect		Experimental value

Judgement is based on the relevant ingredients

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

Reason for revision: 9.1

Publication date: 2003-10-10

Date of revision: 2016-06-15

Revision number: 0502

Product number: 36577

10 / 18

AQUASOLV

AQUASOLV

No (test)data on the mixture available

disodium metasilicate

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL		> 200 mg/kg bw/day	18 day(s)	Mouse (male/female)	No effect		Experimental value
Maternal toxicity	NOAEL		12.5 mg/kg bw/day	18 day(s)	Mouse (female)	No effect		Experimental value
Effects on fertility	NOAEL (P)		> 159 mg/kg bw/day		Rat (female)	No effect		Read-across

sodium hydroxide

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity								Data waiving
Maternal toxicity								Data waiving
Effects on fertility								Data waiving

2-(2-butoxyethoxy)ethanol

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	633 mg/kg bw/day	21 days (gestation, daily)	Rat	No effect		Experimental value
						No effect		
Maternal toxicity	NOAEL	Equivalent to OECD 414	633 mg/kg bw/day	21 days (gestation, daily)	Rat	No effect		Experimental value
	NOAEL	Equivalent to OECD 414	1000 mg/kg bw/day	12 days (gestation, daily)	Rabbit	No effect		Experimental value
Effects on fertility	NOAEL (P)	NTP continuous breeding protocol	720 mg/kg bw/day	14 week(s)	Mouse (male/female)	No effect		Read-across

propan-2-ol

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect	Foetus	Experimental value
	NOAEL	Equivalent to OECD 414	480 mg/kg bw/day	13 day(s)	Rabbit	No effect	Foetus	Experimental value
Maternal toxicity	NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat (female)	No effect		Experimental value
Effects on fertility	NOAEL	Equivalent to OECD 415	853 mg/kg bw/day	21 day(s) - 70 day(s)	Rat (male/female)	No effect		Experimental value

Judgement is based on the relevant ingredients

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

AQUASOLV

No (test)data on the mixture available

Chronic effects from short and long-term exposure

AQUASOLV

No effects known.

SECTION 12: Ecological information

12.1. Toxicity

AQUASOLV

No (test)data on the mixture available

AQUASOLV

disodium metasilicate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	ISO 7346-1	210 mg/l	96 h	Brachydanio rerio	Semi-static system	Fresh water	Experimental value
Acute toxicity invertebrates	EC50	EU Method C.2	1700 mg/l	48 h	Daphnia magna	Static system	Fresh water	Read-across; GLP
Toxicity algae and other aquatic plants	ECO	DIN 38412-9	> 345.4 mg/l	72 h	Desmodesmus subspicatus		Fresh water	Read-across; Growth rate

sodium hydroxide

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Other	45.4 mg/l	96 h	Salmo gairdneri	Static system	Fresh water	Experimental value; Solution >=50%
Acute toxicity invertebrates	EC50	Other	40.4 mg/l	48 h	Ceriodaphnia sp.			Experimental value; Nominal concentration

2-(2-butoxyethoxy)ethanol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	1300 mg/l	96 h	Lepomis macrochirus	Static system	Fresh water	Experimental value
Acute toxicity invertebrates	EC50	Equivalent to OECD 202	4950 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value
Toxicity algae and other aquatic plants	EC50	OECD 201	> 100 mg/l	96 h	Desmodesmus subspicatus	Static system	Fresh water	Experimental value
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic invertebrates								Data waiving
Toxicity aquatic micro-organisms	EC10	Equivalent to OECD 209	> 1995 mg/l	30 minutes	Activated sludge	Static system	Fresh water	Experimental value

propan-2-ol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	9640 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Lethal
Acute toxicity invertebrates	LC50	Equivalent to OECD 202	> 10000 mg/l	24 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ECO		1800 mg/l	7 day(s)	Scenedesmus quadricauda	Static system	Fresh water	Experimental value; Toxicity test
Toxicity aquatic micro-organisms	EC50	ISO 8192	41676 mg/l	30 minutes	Bacteria			Experimental value; Activated sludge

isotridecanol, ethoxylated (>1<2,5 mol EO)

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	EU Method C.1	2.5 mg/l	96 h	Danio rerio	Semi-static system	Fresh water	Read-across; GLP
Acute toxicity invertebrates	EC50	EU Method C.2	1.5 mg/l	48 h	Daphnia magna	Static system	Fresh water	Read-across; GLP
Toxicity algae and other aquatic plants	EL50	EU Method C.3	2.5 mg/l	72 h	Desmodesmus subspicatus	Static system	Fresh water	Read-across; GLP
	NOELR	EU Method C.3	1.7 mg/l	72 h	Desmodesmus subspicatus	Static system	Fresh water	Read-across; GLP
Long-term toxicity fish	EC20	Other	1.097 mg/l	30 day(s)	Pimephales promelas		Fresh water	QSAR; Lethal
Long-term toxicity aquatic invertebrates	EC20		0.74 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR

Judgement of the mixture is based on the relevant ingredients

Conclusion

pH shift

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

AQUASOLV

2-(2-butoxyethoxy)ethanol

Biodegradation water

Method	Value	Duration	Value determination
OECD 301C: Modified MITI Test (I)	> 80 %	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN	3.4 h	1500000 /cm ³	Experimental value

propan-2-ol

Biodegradation water

Method	Value	Duration	Value determination
OECD 301E: Modified OECD Screening Test	95 %	21 day(s)	Experimental value

isotridecanol, ethoxylated (>1<2,5 mol EO)

Biodegradation water

Method	Value	Duration	Value determination
OECD 301B: CO2 Evolution Test	82 %	28 day(s)	Experimental value

Conclusion

The surfactant(s) is/are biodegradable

12.3. Bioaccumulative potential

AQUASOLV

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

disodium metasilicate

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable			

sodium hydroxide

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

2-(2-butoxyethoxy)ethanol

Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 107		1	20 °C	Test data

propan-2-ol

Log Kow

Method	Remark	Value	Temperature	Value determination
Other		0.05	25 °C	Weight of evidence approach

isotridecanol, ethoxylated (>1<2,5 mol EO)

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		6.4	22 °C	Weight of evidence approach

Conclusion

No straightforward conclusion can be drawn based upon the available numerical values

12.4. Mobility in soil

2-(2-butoxyethoxy)ethanol

Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level I	0.01 %	0 %	0.01 %	0.32 %	99.66 %	QSAR

Conclusion

Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Other adverse effects

AQUASOLV

Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

AQUASOLV

sodium hydroxide

Ground water

Ground water pollutant

2-(2-butoxyethoxy)ethanol

Ground water

Ground water pollutant

propan-2-ol

Ground water

Ground water pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

20 01 29* (separately collected fractions (except 15 01): detergents containing hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Neutralize. Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber with energy recovery. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Treat using the best available techniques before discharge into drains or the aquatic environment.

13.1.3 Packaging/Container

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1. UN number

UN number	1719
-----------	------

14.2. UN proper shipping name

Proper shipping name	Caustic alkali liquid, n.o.s. (sodium hydroxide)
----------------------	--

14.3. Transport hazard class(es)

Hazard identification number	80
Class	8
Classification code	C5

14.4. Packing group

Packing group	II
Labels	8

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	274
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Rail (RID)

14.1. UN number

UN number	1719
-----------	------

14.2. UN proper shipping name

Proper shipping name	Caustic alkali liquid, n.o.s. (sodium hydroxide)
----------------------	--

14.3. Transport hazard class(es)

Hazard identification number	80
Class	8
Classification code	C5

14.4. Packing group

Packing group	II
Labels	8

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	274
--------------------	-----

Reason for revision: 9.1

Publication date: 2003-10-10

Date of revision: 2016-06-15

Revision number: 0502

Product number: 36577

14 / 18

AQUASOLV

Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
--------------------	--

Inland waterways (ADN)

14.1. UN number	
UN number	1719
14.2. UN proper shipping name	
Proper shipping name	Caustic alkali liquid, n.o.s. (sodium hydroxide)
14.3. Transport hazard class(es)	
Class	8
Classification code	C5
14.4. Packing group	
Packing group	II
Labels	8
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	274
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Sea (IMDG/IMSBC)

14.1. UN number	
UN number	1719
14.2. UN proper shipping name	
Proper shipping name	Caustic alkali liquid, n.o.s. (sodium hydroxide)
14.3. Transport hazard class(es)	
Class	8
14.4. Packing group	
Packing group	II
Labels	8
14.5. Environmental hazards	
Marine pollutant	-
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	274
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
Annex II of MARPOL 73/78	

Air (ICAO-TI/IATA-DGR)

14.1. UN number	
UN number	1719
14.2. UN proper shipping name	
Proper shipping name	Caustic alkali liquid, n.o.s. (sodium hydroxide)
14.3. Transport hazard class(es)	
Class	8
14.4. Packing group	
Packing group	II
Labels	8
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	A3
Special provisions	A803
Passenger and cargo transport: limited quantities: maximum net quantity per packaging	0.5 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
4.60 %	
86.62 g/l	

Reason for revision: 9.1

Publication date: 2003-10-10

Date of revision: 2016-06-15

Revision number: 0502

Product number: 36577

15 / 18

AQUASOLV

Ingredients according to Regulation (EC) No 648/2004 and amendments
5-15% non-ionic surfactants, <5% EDTA and salts thereof, perfumes, citral

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· 2-(2-butoxyethoxy)ethanol · propan-2-ol · isotridecanol, ethoxylated (>1<2,5 mol EO)	Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects,2. Articles not complying with paragraph 1 shall not be placed on the market.3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with R65 or H304,4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life- threatening lung damage"; b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'
· propan-2-ol	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopie" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs.2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: "For professional users only".3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
· 2-(2-butoxyethoxy)ethanol	2-(2-butoxyethoxy)ethanol (DEGBE)	1. Shall not be placed on the market for the first time after 27 June 2010, for supply to the general public, as a constituent of spray paints or spray cleaners in aerosol dispensers in concentrations equal to or greater than 3 % by weight.2. Spray paints and spray cleaners in aerosol dispensers containing DEGBE and not conforming to paragraph 1 shall not be placed on the market for supply to the general public after 27 December 2010.3. Without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that paints other than spray paints containing DEGBE in concentrations equal to or greater than 3 % by weight of that are placed on the market for supply to the general public are visibly, legibly and indelibly marked by 27 December 2010 as follows: "Do not use in paint spraying equipment".

National legislation Belgium

AQUASOLV

No data available

National legislation The Netherlands

AQUASOLV

Waste identification (the Netherlands)	LWCA (the Netherlands): KGA category 03
--	---

Reason for revision: 9.1

Publication date: 2003-10-10

Date of revision: 2016-06-15

Revision number: 0502

Product number: 36577

16 / 18

AQUASOLV

Waterbezwaarlijkheid	11
<u>2-(2-butoxyethoxy)ethanol</u>	
Huidopname (wettelijk)	2-(2-butoxyethoxy)ethanol; H

National legislation France

AQUASOLV

No data available

National legislation Germany

AQUASOLV

WGK	2; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4)
-----	---

disodium metasilicate

TA-Luft	5.2.1
---------	-------

2-(2-butoxyethoxy)ethanol

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	2-(2-Butoxyethoxy)ethanol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

propan-2-ol

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Propan-2-ol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

National legislation United Kingdom

AQUASOLV

No data available

Other relevant data

AQUASOLV

No data available

propan-2-ol

IARC - classification	3; Isopropanol
TLV - Carcinogen	2-propanol; A4

15.2. Chemical safety assessment

No chemical safety assessment is required.

SECTION 16: Other information

Full text of any H-statements referred to under headings 2 and 3:

- H225 Highly flammable liquid and vapour.
- H290 May be corrosive to metals.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

(*) = INTERNAL CLASSIFICATION BY BIG

PBT-substances = persistent, bioaccumulative and toxic substances

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

Specific concentration limits CLP

sodium hydroxide	C ≥ 5 %	Skin Corr. 1A; H314	CLP Annex VI (ATP 0)
	2 % ≤ C < 5%	Skin Corr. 1B; H314	CLP Annex VI (ATP 0)
	0,5 % ≤ C < 2%	Skin Irrit. 2; H315	CLP Annex VI (ATP 0)
	0,5 % ≤ C < 2 %	Eye Irrit. 2; H319	CLP Annex VI (ATP 0)

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 9.1

Publication date: 2003-10-10

Date of revision: 2016-06-15

Revision number: 0502

Product number: 36577

17 / 18

AQUASOLV

Reason for revision: 9.1

Publication date: 2003-10-10

Date of revision: 2016-06-15

Revision number: 0502

Product number: 36577

18 / 18