SAFETY DATA SHEET



Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2015/830

NOVALUBE BRUSH

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : NOVALUBE BRUSH **Registration number REACH** : Not applicable (mixture)

Product type REACH : Special container containing a substance/mixture : The information refers to the substance/mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Lubricant

Anti-corrosion agent

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Novatio*

Industrielaan 5B

B-2250 Olen

2 +32 14 25 76 40

4 +32 14 22 02 66

info@novatio.be

*NOVATIO is a registered trademark of Novatech International

Industrielaan 5B

Manufacturer of the product

Novatech International N.V. Industrielaan 5B

B-2250 Olen

2 +32 14 85 97 37

4 +32 14 85 97 38

info@tec7.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):

+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	lazard statements	
Aerosol	category 1	H229: Pressurised container: May burst if heated.	
Eye Dam.	category 1	H318: Causes serious eye damage.	
Aquatic Chronic	category 2	H411: Toxic to aquatic life with long lasting effects.	

2.2. Label elements





Contains: calciumdihydroxide.

Signal word

H-statements

H229 Pressurised container: May burst if heated.

Causes serious eye damage. H318

H411 Toxic to aquatic life with long lasting effects.

P-statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

P251 Do not pierce or burn, even after use.

Wear eye protection

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel http://www.big.be

© BIG vzw

Reason for revision: CLP-ATP4-II

Revision number: 0100

Publication date: 2012-10-08 Date of revision: 2015-08-20

Product number: 51866

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P410 + P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C/ 122°F.

2.3. Other hazards

Press-pack contains (extremely) flammable propellant

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
calciumdihydroxide	1305-62-0 215-137-3	C<10 %	STOT SE 3; H335 Skin Irrit. 2; H315 Eye Dam. 1; H318	(1)(2)	Constituent
copper	7440-50-8 231-159-6	C<5 %	Aquatic Acute 1; H400	(1)(2)	Constituent
lithium 12-hydroxystearate	7620-77-1 231-536-5	C<5 %	Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315	(1)(2)	Constituent
aluminium powder (stabilised)	7429-90-5 231-072-3	C<5 %	Flam. Sol. 1; H228 Water-react. 2; H261	(1)(2)(10)	Constituent
zinc oxide	1314-13-2 215-222-5	C<5 %	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	(1)(2)	Constituent
butane 01-2119474691-32	106-97-8 203-448-7	C<2 %	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant in press- pack
propane 01-2119486944-21	74-98-6 200-827-9	C<2 %	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant in press- pack

⁽¹⁾ For H-statements in full: see heading 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Rinse with water. Soap may be used. Take victim to a doctor if irritation persists.

After eye contact:

Rinse immediately with plenty of water for 15 minutes. Do not apply neutralizing agents. Take victim to an ophthalmologist.

After ingestion:

 $Rinse\ mouth\ with\ water.\ Do\ not\ induce\ vomiting.\ Consult\ a\ doctor/medical\ service\ if\ you\ feel\ unwell.$

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

No effects known.

After skin contact:

No effects known.

After eye contact: Corrosion of the eye tissue.

After ingestion:

No effects known.

4.2.2 Delayed symptoms

No effects known.

Reason for revision: CLP-ATP4-II Publication date: 2012-10-08
Date of revision: 2015-08-20

Revision number: 0100 Product number: 51866 2 / 16

⁽²⁾ Substance with a Community workplace exposure limit

⁽¹⁰⁾ Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Water spray. Dry chemical powder. Carbon dioxide. Alcohol-resistant foam.

5.1.2 Unsuitable extinguishing media:

Solid water jet ineffective as extinguishing medium.

5.2. Special hazards arising from the substance or mixture

On burning: release of toxic and corrosive gases/vapours (nitrous vapours, carbon monoxide - carbon dioxide) and formation of metallic fumes. Pressurised container: May burst if heated.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistant risk of physical explosion. Dilute toxic gases with water spray. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Safety glasses. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No naked flames.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Safety glasses. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Contain leaking substance. Dam up the solid spill. Prevent soil and water pollution. Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

Scoop solid spill into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Keep away from naked flames/heat. Observe normal hygiene standards. Keep container tightly closed. Do not discharge the waste into the drain.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a dry area. Keep container in a well-ventilated place. Fireproof storeroom. Keep only in the original container. Store at room temperature. Keep container tightly closed. Meet the legal requirements.

7.2.2 Keep away from:

 $\label{thm:condition} \mbox{Heat sources, oxidizing agents, (strong) acids, (strong) bases.}$

7.2.3 Suitable packaging material:

No data available

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

Reason for revision: CLP-ATP4-II Publication date: 2012-10-08
Date of revision: 2015-08-20

Revision number: 51866 3 / 16

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

The Netherlands

Aluminium	Time-weighted average exposure limit 8 h (Private occupational exposure limit value)	10 mg/m³
Calciumdihydroxide	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	5 mg/m³
Koper en anorganische koperverbindingen (inhaleerbaar)	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	0.1 mg/m³
Stearaten (uitgez. die van toxische metalen)	Time-weighted average exposure limit 8 h (Private occupational exposure limit value)	5 mg/m³
Zinkoxide (rook)	Time-weighted average exposure limit 8 h (Private occupational exposure limit value)	5 mg/m³

EU

Calcium dihydroxide	Time-weighted average exposure limit 8 h (Indicative occupational	5 mg/m³
	exposure limit value)	

Belgium

Aluminium (métal et composés insolubles, fraction alvéolaire)	Time-weighted average exposure limit 8 h	1 mg/m³
Calcium (hydroxyde de)	Time-weighted average exposure limit 8 h	5 mg/m³
Cuivre (fumées) (en Cu)	Time-weighted average exposure limit 8 h	0.2 mg/m ³
Cuivre (poussières et brouillards de) (en Cu)	Time-weighted average exposure limit 8 h	1 mg/m³
Silicium (tétrahydrure de)	Time-weighted average exposure limit 8 h	5 ppm
	Time-weighted average exposure limit 8 h	6.7 mg/m³
Zinc (oxyde de) (fumées)	Time-weighted average exposure limit 8 h	2 mg/m³
	Short time value	10 mg/m³

USA (TLV-ACGIH)

Aluminium, Metal	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	1 mg/m³ (R)
Calcium hydroxide	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	5 mg/m³
Copper fume	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	0.2 mg/m³
Stearates (not of toxic metals)	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	10 mg/m³
Zinc oxide	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	2 mg/m³ (R)
	Short time value (TLV - Adopted Value)	10 mg/m³ (R)

⁽R): Respirable fraction

Germany

alciumdihydroxid	Time-weighted average exposure limit 8 h (TRGS 900)	1 mg/m³	l
------------------	-----------------------------------------------------	---------	---

France

Aluminium (métal)	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	10 mg/m³
Aluminium (pulvérulent)	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	5 mg/m³
Calcium (hydroxyde de)	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	5 mg/m³
Cuivre (fumées)	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	0.2 mg/m ³
Zinc (oxyde de, fumées)	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	5 mg/m³
Zinc (oxyde de, poussières)	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	10 mg/m³

UK

Aluminium metal inhalable dust	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	10 mg/m³
Aluminium metal respirable dust	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	4 mg/m³
Calcium hydroxide	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	5 mg/m³
Copper and compounds: dusts and mists (as Cu)	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1 mg/m³
	Short time value (Workplace exposure limit (EH40/2005))	2 mg/m³
Copper fume	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	0.2 mg/m ³

Reason for revision: CLP-ATP4-II Publication date: 2012-10-08

Date of revision: 2015-08-20

Revision number: 0100 Product number: 51866 4 / 16

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

If applicable and available it will be listed below.

Aluminium	NIOSH	7013
Aluminum (Al)	NIOSH	8310
Aluminum (Elements)	NIOSH	7300
Aluminum (Elements, aqua regia ashing)	NIOSH	7301
Aluminum (Elements, hot block/HCI/HNO3 digestion)	NIOSH	7303
Aluminum	OSHA	ID121
Calciumdihydroxide	NIOSH	7020
Copper (Cu)	NIOSH	8005
Copper (Cu)	NIOSH	8310
Copper (Elements on wipes)	NIOSH	9102
Copper (Elements)	NIOSH	7300
Copper (Elements, aqua regia ashing)	NIOSH	7301
Copper (Elements, hot block/HCI/HNO3 digestion)	NIOSH	7303
Copper Dust and fume	NIOSH	7029
Copper	OSHA	1006
Copper	OSHA	ID 105
Copper	OSHA	ID 121
Copper	OSHA	ID 125G
Copper	OSHA	ID 206
vary depending upon the compound: alumina	NIOSH	8013
Zinc (Elements)	NIOSH	7300
Zinc Oxide	NIOSH	7030
Zinc Oxide	NIOSH	7502
Zinc Oxide	OSHA	ID 121

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 DNEL/PNEC values

DNEL/DMEL - Workers

calciumdihydroxide

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term local effects inhalation	1 mg/m³	
	Acute local effects inhalation	4 mg/m³	

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Acute systemic effects inhalation	20 mg/m³	
	Long-term local effects inhalation	1 mg/m³	
	Acute local effects inhalation	1 mg/m³	
	Long-term systemic effects dermal	137 mg/kg bw/day	
	Acute systemic effects dermal	273 mg/kg bw/day	

aluminium powder (stabilised)

	Effect level (DNEL/DMEL)	Туре	Value	Remark
	DNEL	Long-term local effects inhalation	3.72 mg/m ³	
<u>zi</u>	nc oxide			_

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	5 mg/m³	
	Long-term systemic effects dermal	83 mg/kg bw/day	

DNEL/DMEL - General population

calciumdihydroxide

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term local effects inhalation	1 mg/m³	
	Acute local effects inhalation	4 mg/m³	

copper

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Acute systemic effects inhalation	20 mg/m³	
	Long-term local effects inhalation	1 mg/m³	
	Acute local effects inhalation	1 mg/m³	
	Acute systemic effects dermal	273 mg/kg bw/day	
	Acute systemic effects inhalation	18.2 mg/m³	
	Long-term systemic effects dermal	137 mg/kg bw/day	

aluminium powder (stabilised)

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	3.95 mg/m³	

Reason for revision: CLP-ATP4-II Publication date: 2012-10-08
Date of revision: 2015-08-20

 Revision number: 0100
 Product number: 51866
 5 / 16

zinc oxide

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	2.5 mg/m³	
	Long-term systemic effects dermal	83 mg/kg bw/day	
	Long-term systemic effects oral	0.83 mg/kg bw/day	

PNEC

calciumdihydroxide

Compartments	Value	Remark
Fresh water	0.49 mg/l	
Marine water	0.32 mg/l	
Aqua (intermittent releases)	0.49 mg/l	
STP	3 mg/l	
Soil	1080 mg/kg soil dw	

copper

Compartments	Value	Remark
Fresh water	7.8 μg/l	
Marine water	5.2 μg/l	
STP	230 μg/l	
Fresh water sediment	87 mg/kg sediment dw	
Marine water sediment	676 mg/kg sediment dw	
Soil	65 mg/kg sediment dw	

aluminium powder (stabilised)

Compartments	Value	Remark
	20 mg/l	

zinc oxide

Compartments	Value	Remark
Fresh water	20.6 μg/l	
Marine water	6.1 μg/l	
STP	100 μg/l	
Fresh water sediment	117.8 mg/kg sediment dw	
Marine water sediment	56.5 mg/kg sediment dw	
Soil	35.6 mg/kg soil dw	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Keep container tightly closed. Do not eat, drink or smoke during work.

a) Respiratory protection:

Respiratory protection not required in normal conditions.

b) Hand protection:

Gloves.

Materials	Breakthrough time	Thickness
nitrile rubber	480 minutes	0.4 mm

- materials (good resistance)

Nitrile rubber.

c) Eye protection:

Safety glasses.

d) Skin protection:

Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Press-pack
	Paste
Odour	Oil-like odour
Odour threshold	No data available
Colour	Grey
Particle size	No data available
Explosion limits	No data available

Reason for revision: CLP-ATP4-II Publication date: 2012-10-08
Date of revision: 2015-08-20

Revision number: 0100 Product number: 51866 6 / 16

Flammability	Contains (highly) flammable component(s)
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	No data available
Boiling point	No data available
Flash point	No data available
Evaporation rate	No data available
Relative vapour density	No data available
Vapour pressure	5.5 hPa ; 20 °C
Solubility	water ; insoluble
Relative density	1.2; 20°C
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
рН	No data available

9.2. Other information

lAbsolute density	l1200 kg/m³ : 20 °C	
Absolute delisity	1200 kg/iii , 20 C	

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

Unstable on exposure to heat.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Keep away from naked flames/heat.

10.5. Incompatible materials

Oxidizing agents, (strong) acids, (strong) bases.

10.6. Hazardous decomposition products

On burning: release of toxic and corrosive gases/vapours (nitrous vapours, carbon monoxide - carbon dioxide) and formation of metallic fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

NOVALUBE BRUSH

No (test)data on the mixture available

calciumdihydroxide

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	OECD 425	> 2000 mg/kg bw		Rat (female)	Experimental value	
Dermal	LD50	OECD 402	> 2500 mg/kg bw	24 h	Rabbit	Experimental value	•
					(male/female)		

copper

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD 423	300 mg/kg bw - 500 mg/kg bw		Rat (male/female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 2000 mg/kg bw	24 h	Rat (male/female)	Experimental value	
Inhalation (dust)	LC50	Equivalent to OECD	4.74 mg/l air	4 h	Rat (male/female)	Experimental value	

aluminium powder (stabilised)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	1	Equivalent to OECD 401	> 15900 mg/kg bw		Rat (male/female)	Read-across	
Inhalation (aerosol)	1	Equivalent to OECD 403	> 888 mg/m³	4 h	Rat (male/female)	Experimental value	

Reason for revision: CLP-ATP4-II

Publication date: 2012-10-08

Date of revision: 2015-08-20

Revision number: 51806 7 / 16

zinc oxide

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD	> 5000 mg/kg		Rat (male/female)	Experimental value	
		401					
Dermal	LD50	OECD 402	> 2000 mg/kg bw	24 h	Rat (male/female)	Experimental value	
Inhalation (dust)	LC50	Equivalent to OECD	> 5.7 mg/l	4 h	Rat (male/female)	Experimental value	
		403	_				

Judgement is based on the relevant ingredients

Conclusion

Not classified for acute toxicity

Corrosion/irritation

NOVALUBE BRUSH

No (test)data on the mixture available

calciumdihydroxide

Ī	Route of exposure	Result	Method	Exposure time	Time point	Species	Value	Remark		
							determination			
ı	ye	Irritating	OECD 405	4 h	1; 24; 48; 72 hours	Rabbit	Experimental value			
[ikin	Irritating	OECD 404	4 h	1; 24; 48; 72 hours	Rabbit	Experimental value			

copper

pper										
Route of exposure	Result	Method	Exposure time	Time point	Species	Value	Remark			
						determination				
Eye] 0 , 0	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Experimental value				
Skin		Equivalent to OECD 404	4 h	72 hours	Rabbit	Experimental value				

lithium 12-hydroxystearate

Route of exposure	Result	Method	Exposure time	Time point	 Value determination	Remark
Eye	Irritating				Literature study	
Skin	Irritating				Literature study	
Inhalation	Irritating				Literature study	

aluminium powder (stabilised)

Route of exposure	Result	Method	Exposure time	Time point	Species	Value	Remark
						determination	
Eye	Not irritating	Other		24; 48; 72 hours	Rabbit	Read-across	
Skin	Not irritating	Equivalent to OECD	24 h	24; 48; 72 hours	Rabbit	Read-across	
		404					

zinc oxide

Route of exposure	Result	Method	Exposure time	Time point	Species	Value	Remark
						determination	
Eye	Not irritating	OECD 405	24 h	24; 72 hours	Rabbit	Experimental value	
Skin	Not irritating	OECD 404	24 h	24 hours	Rabbit	Experimental value	
Not applicable (in vitro test)	Not corrosive	OECD 431	3 minutes		Reconstructed human epidermis	Experimental value	

Classification is based on the relevant ingredients

Conclusion

Causes serious eye irritation.

Not classified as irritating to the skin

Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

NOVALUBE BRUSH

No (test)data on the mixture available

copper

Route of exposure	Result	Method	 Observation time point	Species	Value determination	Remark
Skin		Equivalent to OECD 406		Guinea pig (male)	Experimental value	

aluminium powder (stabilised)

Route of exposure	Result	Method	•	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Other		24 hours	Guinea pig (male)	Read-across	
Intratracheal instillation	Not sensitizing				Mouse (male)	Read-across	

Reason for revision: CLP-ATP4-II

Publication date: 2012-10-08

Date of revision: 2015-08-20

Revision number: 0100 Product number: 51866 8 / 16

zinc oxide

Route of exposure	Result	Method	Exposure time	Observation time	Species	Value determination	Remark
				point			
Skin	Not sensitizing	OECD 406			Guinea pig (female)	Experimental value	
Skin	Not sensitizing	Human observation	2 days	72 hours	Human	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Not classified as sensitizing for skin Not classified as sensitizing for inhalation

Specific target organ toxicity

NOVALUBE BRUSH

No (test)data on the mixture available

copper

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral	NOAEL	Other	1000 ppm		No effect	92 day(s)	Mouse (male/female)	Experimental value
Oral	LOAEL	Other	2000 ppm		Body weight reduction	92 day(s)	Mouse (male/female)	Experimental value
Oral	NOAEL	Other	1000 ppm		No effect	92 day(s)	Rat (male/female)	Experimental value
Oral	LOAEL	Other	2000 ppm		Body weight reduction	92 day(s)	Rat (male/female)	Experimental value
Dermal								Data waiving
Inhalation								Data waiving

aluminium powder (stabilised)

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (drinking water)	NOAEL	Equivalent to OECD 452	30 mg/kg bw/day	General	No effect		Rat (male/female)	Read-across
Oral (drinking water)	LOAEL	Equivalent to OECD 452	100 mg/kg bw/day	General	Myasthenia	15 day(s)	Rat (male/female)	Read-across
Oral (stomach tube)	NOAEL	OECD 422	200 mg/kg bw/day	Stomach	No effect	28-53 day(s)	Rat (male/female)	Read-across
Oral (stomach tube)	LOAEL	OECD 422	1000 mg/kg bw/day	Stomach	Irritation of the gastric/intestina I mucosa	28-53 day(s)	Rat (male/female)	Read-across
Inhalation (dust)	LOAEC	Equivalent to OECD 413	50 mg/m³ air	Lungs	affection/degen	25-52 weeks (6h/day, 5 days/week)	Rat	Experimental value

zinc oxide

o omac									
Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time		Value determination	
Oral (diet)	NOEL	OECD 408	3000 ppm		No effect	(//	Rat (male/female)	Read-across	
Inhalation (aerosol)	NOAEL	OECD 413	1.5 mg/m³ air			13 weeks (6h/day, 5 days/week)	` ′	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Not classified for subchronic toxicity

Mutagenicity (in vitro)

NOVALUBE BRUSH

No (test)data on the mixture available

calciumdihydroxide

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic	OECD 471	Bacteria (S.typhimurium)		Experimental value
activation, negative without				
metabolic activation				

copper

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value
activation, negative without				
metabolic activation				

9/16

Reason for revision: CLP-ATP4-II

Publication date: 2012-10-08

Date of revision: 2015-08-20

Revision number: 0100 Product number: 51866

aluminium powder (stabilised)

Result	Method	Test substrate	Effect	Value determination
Positive without metabolic	Equivalent to OECD 473	Human lymphocytes		Read-across
activation				
Positive without metabolic	OECD 487	Human lymphocytes		Read-across
activation				
Negative	!	Mouse (lymphoma L5178Y cells)	No effect	Read-across
Negative	OECD 476	· '	No effect	Read-across

zinc oxide

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value
activation, negative without				
metabolic activation				

Mutagenicity (in vivo)

NOVALUBE BRUSH

No (test)data on the mixture available

copper

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD		Rat (male)		Experimental value
	486				
Negative	Other		Mouse (male/female)		Experimental value

aluminium powder (stabilised)

Result	Method	Exposure time	Test substrate	Organ	Value determination
Positive	OECD 474		Rat (female)	Bone marrow	Read-across

zinc oxide

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	OECD 474		Mouse (male)	Bone marrow	Experimental value

Carcinogenicity

NOVALUBE BRUSH

No (test)data on the mixture available

aluminium powder (stabilised)

Route of	Parameter	Method	Value	Exposure time	Species	Value	Organ	Effect
exposure						determination		
Inhalation	LOAEC	OECD 413	100 mg/m³ air	25-52 weeks	Rat	Experimental	Lungs	Lung tissue
(dust)				(6h/day, 5		value		affection/degene
				days/week)				ration

Reproductive toxicity

NOVALUBE BRUSH

No (test)data on the mixture available

copper

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value
								determination
Developmental toxicity	NOAEL	Other	15 mg/kg		Rabbit (female)	No effect		Experimental
			bw/day					value
	NOAEL	Equivalent to	6 mg/kg		Rabbit (female)	No effect		Experimental
		OECD 414	bw/day					value
Effects on fertility	NOAEL	OECD 416	1500 ppm	70 day(s)	Rat	No effect		Experimental
	(P/F1/F2)				(male/female)			value

aluminium powder (stabilised)

	Parameter	Method	Value	Exposure time	Species	Effect	- 0-	Value determination
Developmental toxicity	_	Equivalent to OECD 414	266 mg/kg bw/day	10 day(s)	Rat	No effect	Foetus	Read-across
Effects on fertility	NOAEL	OECD 422	1000 mg/kg bw/day	/ (- /	Rat (male/female)	No effect		Read-across

Reason for revision: CLP-ATP4-II Publication date: 2012-10-08

Date of revision: 2015-08-20

Revision number: 0100 Product number: 51866 10 / 16

zinc oxide

	Parameter	Method	Value	Exposure time	Species	Effect	1- 0-	Value determination
Developmental toxicity	NOAEC		7.5 mg/kg bw/day	14 days (6h/day)	Rat	No effect	1	Experimental value
Maternal toxicity	NOAEC		7.5 mg/kg bw/day	14 days (6h/day)	Rat	No effect	1	Experimental value
Effects on fertility	NOAEL (F1)	Equivalent to OECD 416	7.5 mg/kg bw/day		Rat (male/female)	No effect		Read-across

Judgement is based on the relevant ingredients

Conclusion CMR

Not classified for carcinogenicity

Not classified for mutagenic or genotoxic toxicity

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

NOVALUBE BRUSH

No (test)data on the mixture available

Chronic effects from short and long-term exposure

NOVALUBE BRUSH

No effects known.

SECTION 12: Ecological information

12.1. Toxicity

NOVALUBE BRUSH

No (test)data on the mixture available

<u>calciumdihydroxide</u>

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	50.6 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; GLP
Acute toxicity invertebrates	EC50	OECD 202	49.1 mg/l	48 h	Daphnia magna	Static system		Experimental value; GLP
Toxicity algae and other aquatic plants	EC50	OECD 201	184.57 mg/l	72 h	Pseudokirchnerie Ila subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity aquatic invertebrates	NOEC	Other	32 mg/l	14 day(s)	Crangon sp.	Semi-static system	Salt water	Experimental value; Growth
Toxicity aquatic micro- organisms	EC50	OECD 209	300.4 mg/l	3 h	Activated sludge	Static system	Fresh water	Experimental value; GLP

copper

	Parameter	Method	Value	Duration	Species	_	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		200 μg/l	96 h	Ŭ	Flow-through system	Fresh water	Weight of evidence; Lethal
Acute toxicity invertebrates	EC50	OECD 202	109 μg/l - 798 μg/l	48 h	Daphnia magna	Static system		Weight of evidence; Locomotor effect
Toxicity algae and other aquatic plants	EC50	OECD 201	230 μg/l	72 h	Pseudokirchnerie Ila subcapitata	Static system		Weight of evidence; Growth rate
Long-term toxicity fish	NOEC	OECD 204	22 μg/l - 45 μg/l	61 day(s)		Flow-through system		Weight of evidence; Growth rate
Long-term toxicity aquatic invertebrates	NOEC		12.6 μg/l	21 day(s)		Flow-through system		Weight of evidence; Growth
luminium powder (stabilised)	-		-	-	-	-	-	

Parameter Method Value Duration Species Test design Fresh/salt Value determination water Acute toxicity fishes LC50 ASTM > 218.64 mg/l 96 h Pimephales Semi-static Fresh water Weight of evidence; promelas system

Reason for revision: CLP-ATP4-II Publication date: 2012-10-08
Date of revision: 2015-08-20

Revision number: 51866 11/16

zinc oxide

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	ASTM E729- 88	0.169 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Read-across; Zinc ion
Acute toxicity invertebrates	EC50	OECD 202	1.7 mg/l - 9 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Zinc ion
Toxicity algae and other aquatic plants	IC50	OECD 201	0.136 mg/l	72 h	Pseudokirchnerie Ila subcapitata	Static system	Fresh water	Experimental value; Zinc ion
	NOEC	OECD 201	0.024 mg/l	3 day(s)	Pseudokirchnerie Ila subcapitata	Static system	Fresh water	Experimental value; Zinc ion
Long-term toxicity fish	NOEC	OECD 215	0.039 mg/l - 0.095 mg/l	30 day(s)		Flow-through system	Fresh water	Read-across; Zinc ion
Long-term toxicity aquatic invertebrates	NOEC	OECD 211	0.048 mg/l - 0.156 mg/l	21 day(s)		Semi-static system	Fresh water	Read-across; Zinc ion
Toxicity aquatic micro- organisms	EC50	OECD 209	> 1000 mg/l	3 h	Activated sludge	Static system	Fresh water	Experimental value; GLP

Classification is based on the relevant ingredients

Conclusion

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No test data of component(s) available

12.3. Bioaccumulative potential

NOVALUBE BRUSH

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

calciumdihydroxide

Log Kow

-6.00										
Method	Remark	Value	Temperature	Value determination						
	No data available									

copper

Log Kow

Method	Remark	Value	Temperature	Value determination	
	Not applicable (inorganic)				

aluminium powder (stabilised)

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable			

zinc oxide

BCF other aquatic organisms

Parameter	Method	Value	Duration	Species	Value determination
BCF		38 - 277	28 day(s)	Palaemon elegans	Read-across

Log Kow

Method	Remark	Value	Temperature	Value determination
		1.53		Estimated value

No straightforward conclusion can be drawn based upon the available numerical values

12.4. Mobility in soil

zinc oxide

(log) Koc

Parameter	Method	Value	Value determination
log Koc		2.2	Literature study

Conclusion

Contains component(s) that adsorb(s) into the soil

Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Other adverse effects

NOVALUBE BRUSH

Global warming potential (GWP)

Reason for revision: CLP-ATP4-II Date of revision: 2015-08-20

Revision number: 0100 Product number: 51866 12 / 16

Publication date: 2012-10-08

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EC) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

calciumdihydroxide

Global warming potential (GWP)

Not included in the list of fluorinated greenhouse gases (Regulation (EC) No 517/2014)

Ground water

Ground water pollutant

copper

Global warming potential (GWP)

Not included in the list of fluorinated greenhouse gases (Regulation (EC) No 517/2014)

aluminium powder (stabilised)

Global warming potential (GWP)

Not included in the list of fluorinated greenhouse gases (Regulation (EC) No 517/2014)

zinc oxide

Global warming potential (GWP)

Not included in the list of fluorinated greenhouse gases (Regulation (EC) No 517/2014)

Ground water

Ground water pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

12 01 12* (wastes from shaping and physical and mechanical surface treatment of metals and plastics: spent waxes and fats). Depending on branch of industry and production process, also other waste codes may be applicable. Hazardous waste according to Regulation (EU) No 1357/2014.

13.1.2 Disposal methods

Recycle/reuse. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Specific treatment. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Hazard identification number	
Class	2
Classification code	5A
14.4. Packing group	
Packing group	
Labels	2.2
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Reason for revision: CLP-ATP4-II Publication date: 2012-10-08

Date of revision: 2015-08-20

Revision number: 0100 Product number: 51866 13 / 16

Rail (RID) 14.1. UN number UN number 1950 14.2. UN proper shipping name Proper shipping name Aerosols 14.3. Transport hazard class(es) 20 Hazard identification number Class Classification code 5A 14.4. Packing group Packing group Labels 2.2 14.5. Environmental hazards Environmentally hazardous substance mark yes 14.6. Special precautions for user Special provisions 190 Special provisions 327 344 Special provisions 625 Special provisions Limited quantities Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass) Inland waterways (ADN) 14.1. UN number UN number 1950 14.2. UN proper shipping name Proper shipping name Aerosols 14.3. Transport hazard class(es) Class 5A Classification code 14.4. Packing group Packing group Labels 2.2 14.5. Environmental hazards Environmentally hazardous substance mark yes 14.6. Special precautions for user Special provisions 190 Special provisions 327 344 Special provisions Special provisions 625 Limited quantities Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass) Sea (IMDG/IMSBC) 14.1. UN number UN number 1950 14.2. UN proper shipping name Proper shipping name aerosols 14.3. Transport hazard class(es) Class 2.2 14.4. Packing group Packing group Labels 2.2 14.5. Environmental hazards Marine pollutant Environmentally hazardous substance mark yes 14.6. Special precautions for user Special provisions 63 190 Special provisions Special provisions 277 Special provisions 327 Special provisions 344 Special provisions 959 Limited quantities Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass) 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Reason for revision: CLP-ATP4-II

Publication date: 2012-10-08

Date of revision: 2015-08-20

Annex II of MARPOL 73/78

 Revision number: 0100
 Product number: 51866
 14 / 16

Not applicable

Air (ICAO-TI/IATA-DGR)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols, non-flammable
14.3. Transport hazard class(es)	
Class	2.2
14.4. Packing group	
Packing group	
Labels	2.2
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	A98
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport: limited quantities: maximum net quantity per packaging	30 kg G

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

and use of certain dangerous substances, mixtures and articles.				
I	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction		
		1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopee" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — strink bombs. 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: "For professional users only".3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.		

National legislation The Netherlands

NOVALUBE BRUSH

Waste identification (the	LWCA (the Netherlands): KGA category 06
Netherlands)	
Waterbezwaarliikheid	6

National legislation Germany

NOVALUBE BRUSH

		Stoffe (VwVwS) of 27 July 2005 (Anhang 4)			
calciumdihydroxide					
	TA-Luft	5.2.1			
<u>cc</u>	copper				
	Schwangerschaft Gruppe	c			
	MAK 8-Stunden-Mittelwert mg/m³	Kupfer und seine anorganischen Verbindungen; 0.1 mg/m³; gemessen als einatembare Fraktion (vgl. Abschn. Vd) S. 191)			
	TA-Luft	5.2.1			

Reason for revision: CLP-ATP4-II Publication date: 2012-10-08

Date of revision: 2015-08-20

Revision number: 51866 15 / 16

aluminium powder (stabilised)

Schwangerschaft Gruppe	D
Schwangerschaft Gruppe	D
MAK 8-Stunden-Mittelwert mg/m³	Aluminium-, Aluminiumoxid-, Aluminiumhydroxidhaltige Ställ ube (alveolengäll ngige Fraktion); 1.5 mg/m³; gemessen als alveolengängige Fraktion (vgl. Abschn. Vd) S. 191)
	Aluminium-, Aluminiumoxid-, Aluminiumhydroxidhaltige Ställ ube (einatembare Fraktion); 4 mg/m³; gemessen als einatembare Fraktion (vgl. Abschn. Vd) S. 191)
TA-Luft	5.2.1

zinc oxide

THE ONLIGE			
Schwangerschaft Gruppe	С		
Schwangerschaft Gruppe	С		
	Zink und seine anorganischen Verbindungen (alveolengängige Fraktion); 0,1 mg/m³; gemessen als alveolengängige Fraktion (vgl. Abschn. Vd) S. 191)		
	Zink und seine anorganischen Verbindungen (einatembare Fraktion); 2 mg/m³; gemessen als einatembare Fraktion (vgl. Abschn. Vd) S. 191)		
TA-Luft	5.2.1		

National legislation France

NOVALUBE BRUSH

No data available

National legislation Belgium

NOVALUBE BRUSH

No data available

Other relevant data

NOVALUBE BRUSH

No data available

lithium 12-hydroxystearate

	TLV - Carcinogen	Stearates (not of toxic metals); A4	
<u>a</u>	uminium powder (stabilised)		
	TLV - Carcinogen	Aluminium, Metal; A4	

15.2. Chemical safety assessment

No chemical safety assessment is required.

SECTION 16: Other information

Full text of any H-statements referred to under headings 2 and 3:

H220 Extremely flammable gas.

H228 Flammable solid.

H229 Pressurised container: May burst if heated.

 $\label{eq:H261} \textbf{In contact with water releases flammable gases}.$

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

 $\,$ H410 $\,$ Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

(*) = INTERNAL CLASSIFICATION BY BIG

PBT-substances = persistent, bioaccumulative and toxic substances

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

M-factor

zinc oxide	1	Acute	ECHA
zinc oxide	1	Chronic	ECHA

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: CLP-ATP4-II Publication date: 2012-10-08
Date of revision: 2015-08-20

Revision number: 0100 Product number: 51866 16 / 16