

SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2015/830

NOVAFILL FLEX 2 (white)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : NOVAFILL FLEX 2 (white)
Registration number REACH : Not applicable (mixture)
Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Primer

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Novatio*
Industrielaan 5B
B-2250 Olen
☎ +32 14 25 76 40
☎ +32 14 22 02 66
info@novatio.be
*NOVATIO is a registered trademark of Novatech International
Industrielaan 5B

Manufacturer of the product

Novatech International N.V.
Industrielaan 5B
B-2250 Olen
☎ +32 14 85 97 37
☎ +32 14 85 97 38
info@tec7.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):
+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.

2.2. Label elements



Contains: acetone.

Signal word

Danger

H-statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

P-statements

NOVAFILL FLEX 2 (white)

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear eye protection
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

Supplemental information

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
acetone 01-2119471330-49	67-64-1 200-662-2	10%<C<30%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Constituent
butanone 01-2119457290-43	78-93-3 201-159-0	1%<C<5%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Constituent
n-butyl acetate 01-2119485493-29	123-86-4 204-658-1	1%<C<5%	Flam. Liq. 3; H226 STOT SE 3; H336	(1)(2)(10)	Constituent
4-methylpentan-2-one	108-10-1 203-550-1	10%<C<30%	Flam. Liq. 2; H225 Acute Tox. 3; H331 Eye Irrit. 2; H319 STOT SE 3; H335	(1)(2)(10)	Constituent
dimethyl ether 01-2119472128-37	115-10-6 204-065-8	30%<C<60%	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
butane 01-2119474691-32	106-97-8 203-448-7	1%<C<5%	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
propane 01-2119486944-21	74-98-6 200-827-9	1%<C<5%	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant

(1) For H-statements in full: see heading 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

If you feel unwell, seek medical advice.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Wash immediately with lots of water. Soap may be used. Take victim to a doctor if irritation persists.

After eye contact:

Rinse immediately with plenty of water. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Consult a doctor/medical service if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

EXPOSURE TO HIGH CONCENTRATIONS: Central nervous system depression. Headache. Dizziness. Coordination disorders. Feeling of weakness. Nausea.

After skin contact:

ON CONTINUOUS EXPOSURE/CONTACT: Dry skin. Cracking of the skin.

Reason for revision: 2.2

Publication date: 2013-05-23

Date of revision: 2016-04-07

Revision number: 0200

Product number: 54076

2 / 22

NOVAFILL FLEX 2 (white)

After eye contact:

Irritation of the eye tissue.

After ingestion:

No effects known.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Water spray. BC powder. Sand/earth.

5.1.2 Unsuitable extinguishing media:

No unsuitable extinguishing media known.

5.2. Special hazards arising from the substance or mixture

Upon combustion CO and CO₂ are formed (carbon monoxide - carbon dioxide). Pressurised container: May burst if heated.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective goggles. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Protective goggles. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Dam up the liquid spill.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards. Remove contaminated clothing immediately.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Store in a dry area. Fireproof storeroom. Ventilation at floor level. Keep out of direct sunlight. Meet the legal requirements.

7.2.2 Keep away from:

Heat sources, ignition sources, oxidizing agents, (strong) acids, (strong) bases.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

NOVAFILL FLEX 2 (white)

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

4-Methylpentan-2-one	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	20 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	83 mg/m ³
	Short time value (Indicative occupational exposure limit value)	50 ppm
	Short time value (Indicative occupational exposure limit value)	208 mg/m ³
Acetone	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	500 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1210 mg/m ³
Butanone	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	200 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	600 mg/m ³
	Short time value (Indicative occupational exposure limit value)	300 ppm
	Short time value (Indicative occupational exposure limit value)	900 mg/m ³
Dimethylether	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1000 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1920 mg/m ³

Belgium

2-Butanone	Time-weighted average exposure limit 8 h	200 ppm
	Time-weighted average exposure limit 8 h	600 mg/m ³
	Short time value	300 ppm
	Short time value	900 mg/m ³
4-Méthyl-2-pentanone	Time-weighted average exposure limit 8 h	20 ppm
	Time-weighted average exposure limit 8 h	83 mg/m ³
	Short time value	50 ppm
	Short time value	208 mg/m ³
Acétate de n-butyle	Time-weighted average exposure limit 8 h	150 ppm
	Time-weighted average exposure limit 8 h	723 mg/m ³
	Short time value	200 ppm
	Short time value	964 mg/m ³
Acétone	Time-weighted average exposure limit 8 h	500 ppm
	Time-weighted average exposure limit 8 h	1210 mg/m ³
	Short time value	1000 ppm
	Short time value	2420 mg/m ³
Hydrocarbures aliphatiques sous forme gazeuse : (Alcanes C1-C4)	Time-weighted average exposure limit 8 h	1000 ppm
Oxyde de diméthyle	Time-weighted average exposure limit 8 h	1000 ppm
	Time-weighted average exposure limit 8 h	1920 mg/m ³

The Netherlands

2-Butanon	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	197 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	590 mg/m ³
	Short time value (Public occupational exposure limit value)	300 ppm
	Short time value (Public occupational exposure limit value)	900 mg/m ³
4-Methyl-2-pentanone	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	25 ppm

Reason for revision: 2.2

Publication date: 2013-05-23

Date of revision: 2016-04-07

Revision number: 0200

Product number: 54076

4 / 22

NOVAFILL FLEX 2 (white)

4-Methyl-2-pentanon	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	104 mg/m ³
	Short time value (Public occupational exposure limit value)	50 ppm
	Short time value (Public occupational exposure limit value)	208 mg/m ³
Aceton	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	501 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	1210 mg/m ³
	Short time value (Public occupational exposure limit value)	1002 ppm
	Short time value (Public occupational exposure limit value)	2420 mg/m ³
Dimethylether	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	496 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	950 mg/m ³
	Short time value (Public occupational exposure limit value)	783 ppm
	Short time value (Public occupational exposure limit value)	1500 mg/m ³
n-Butaan	Time-weighted average exposure limit 8 h (Private occupational exposure limit value)	592 ppm
	Time-weighted average exposure limit 8 h (Private occupational exposure limit value)	1430 mg/m ³
n-Butylacetaat	Time-weighted average exposure limit 8 h (Private occupational exposure limit value)	99 ppm
	Time-weighted average exposure limit 8 h (Private occupational exposure limit value)	480 mg/m ³

France

Acétate de n-butyle	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	150 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	710 mg/m ³
	Short time value (VL: Valeur non réglementaire indicative)	200 ppm
	Short time value (VL: Valeur non réglementaire indicative)	940 mg/m ³
Acétone	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	500 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	1210 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	1000 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	2420 mg/m ³
Méthyléthylcétone	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	200 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	600 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	300 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	900 mg/m ³
Méthylisobutylcétone	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	20 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	83 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	50 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	208 mg/m ³
n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	800 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1900 mg/m ³
Oxyde de diméthyle	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1000 ppm
	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1920 mg/m ³

Germany

4-Methylpentan-2-on	Time-weighted average exposure limit 8 h (TRGS 900)	20 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	83 mg/m ³
Aceton	Time-weighted average exposure limit 8 h (TRGS 900)	500 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1200 mg/m ³
Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m ³

Reason for revision: 2.2

Publication date: 2013-05-23

Date of revision: 2016-04-07

Revision number: 0200

Product number: 54076

5 / 22

NOVAFILL FLEX 2 (white)

Butanon	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	600 mg/m ³
Dimethylether	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1900 mg/m ³
n-Butylacetat	Time-weighted average exposure limit 8 h (TRGS 900)	62 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	300 mg/m ³
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m ³

UK

4-Methylpentan-2-one	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	50 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	208 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	100 ppm
	Short time value (Workplace exposure limit (EH40/2005))	416 mg/m ³
Acetone	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	500 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1210 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	1500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	3620 mg/m ³
Butan-2-one (methyl ethyl ketone)	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	200 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	300 ppm
	Short time value (Workplace exposure limit (EH40/2005))	899 mg/m ³
Butane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	750 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m ³
Butyl acetate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	150 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	724 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	200 ppm
	Short time value (Workplace exposure limit (EH40/2005))	966 mg/m ³
Dimethyl ether	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	766 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	958 mg/m ³

USA (TLV-ACGIH)

Acetone	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	250 ppm
	Short time value (TLV - Adopted Value)	500 ppm
Butane, all isomers	Short time value (TLV - Adopted Value)	1000 ppm
Methyl ethyl ketone (MEK)	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	200 ppm
	Short time value (TLV - Adopted Value)	300 ppm
Methyl isobutyl ketone	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	20 ppm
	Short time value (TLV - Adopted Value)	75 ppm
n-Butyl acetate	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	150 ppm
	Short time value (TLV - Adopted Value)	200 ppm

b) National biological limit values

If limit values are applicable and available these will be listed below.

Germany

4-Methylpentan-2-on (4-Methylpentan-2-on)	Urin: expositionsende, bzw. schichtende	0,7 mg/l	05/2015 DFG
---	---	----------	-------------

Reason for revision: 2.2

Publication date: 2013-05-23

Date of revision: 2016-04-07

Revision number: 0200

Product number: 54076

6 / 22

NOVAFILL FLEX 2 (white)

Aceton (Aceton)	Urin: expositionsende, bzw. schichtende	80 mg/l	11/2012 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG
Butanon (2-Butanon; Ethylmethylketon) (Butanon (2-Butanon))	Urin: expositionsende, bzw. schichtende	2 mg/l	05/2015 DFG

USA (BEI-ACGIH)

Acetone (Acetone)	Urine: end of shift	20 mg/L	Nonspecific - Intended changes
Acetone (Acetone)	Urine: end of shift	25 mg/L	
Methyl ethyl ketone (MEK)	urine: end of shift	2 mg/L	
Methyl isobutyl ketone (MIBK) (MIBK)	urine: end of shift	1 mg/L	

8.1.2 Sampling methods

If applicable and available it will be listed below.

2-Butanone (MEK) (Methyl ethyl ketone)	NIOSH	2500
2-Butanone (Methyl ethyl ketone)	OSHA	84
2-Butanone (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
2-Butanone (Volatile Organic compounds)	NIOSH	2549
2-Butanone	OSHA	1004
2-Butanone	OSHA	13
Acetone (ketones 1)	NIOSH	1300
Acetone (ketones I)	NIOSH	2555
Acetone (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
Acetone (Volatile Organic compounds)	NIOSH	2549
ACETONE and METHYL ETHYL KETONE in urine	NIOSH	8319
Acetone	OSHA	69
Butyl acetate (Volatile Organic compounds)	NIOSH	2549
Hexone	OSHA	1004
MEK	NIOSH	8002
Methyl Ethyl Ketone (ketones I)	NIOSH	2555
Methyl Ethyl Ketone	OSHA	16
Methyl Isobutyl Ketone (Hexone) (Ketones I)	NIOSH	1300
Methyl Isobutyl Ketone (ketones I)	NIOSH	2555
Methyl isobutyl ketone (Volatile Organic compounds)	NIOSH	2549
n-Butyl Acetate (Esters I)	NIOSH	1450
n-Butyl Acetate	OSHA	1009

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 DNEL/PNEC values

DNEL/DMEL - Workers

acetone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Acute local effects inhalation	2420 mg/m ³	
	Long-term systemic effects dermal	186 mg/kg bw/day	
	Long-term systemic effects inhalation	1210 mg/m ³	

butanone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	600 mg/m ³	
	Long-term systemic effects dermal	1161 mg/kg bw/day	

n-butyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	480 mg/m ³	

4-methylpentan-2-one

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Acute systemic effects inhalation	208 mg/m ³	
	Acute local effects inhalation	208 mg/m ³	
	Long-term systemic effects dermal	11.8 mg/kg bw/day	
	Long-term systemic effects inhalation	83 mg/m ³	
	Long-term local effects inhalation	83 mg/m ³	

DNEL/DMEL - General population

Reason for revision: 2.2

Publication date: 2013-05-23

Date of revision: 2016-04-07

Revision number: 0200

Product number: 54076

7 / 22

NOVAFILL FLEX 2 (white)

acetone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects dermal	62 mg/kg bw/day	
	Long-term systemic effects inhalation	200 mg/m ³	
	Long-term systemic effects oral	62 mg/kg bw/day	

butanone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	106 mg/m ³	
	Long-term systemic effects dermal	412 mg/kg bw/day	
	Long-term systemic effects oral	31 mg/kg bw/day	

n-butyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects dermal	3.4 mg/kg bw/day	
	Long-term systemic effects inhalation	12 mg/m ³	
	Long-term systemic effects oral	3.4 mg/kg bw/day	

4-methylpentan-2-one

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Acute systemic effects inhalation	155.2 mg/m ³	
	Acute local effects inhalation	155.2 mg/m ³	
	Long-term systemic effects dermal	4.2 mg/kg bw/day	
	Long-term systemic effects inhalation	14.7 mg/m ³	
	Long-term systemic effects oral	4.2 mg/kg bw/day	
	Long-term local effects inhalation	14.7 mg/m ³	

PNEC

acetone

Compartments	Value	Remark
Fresh water	10.6 mg/l	
Marine water	1.06 mg/l	
Aqua (intermittent releases)	21 mg/l	
Fresh water sediment	30.4 mg/kg sediment dw	
Marine water sediment	3.04 mg/kg sediment dw	
Soil	29.5 mg/kg soil dw	
STP	100 mg/l	

butanone

Compartments	Value	Remark
Fresh water	55.8 mg/l	
Marine water	55.8 mg/l	
Aqua (intermittent releases)	55.8 mg/l	
STP	709 mg/l	
Fresh water sediment	284.74 mg/kg sediment dw	
Marine water sediment	284.7 mg/kg sediment dw	
Soil	22.5 mg/kg soil dw	
Food	1000 mg/kg food	

n-butyl acetate

Compartments	Value	Remark
Fresh water	0.18 mg/l	
Marine water	0.018 mg/l	
Fresh water sediment	0.981 mg/kg sediment dw	
Marine water sediment	0.0981 mg/kg sediment dw	
Soil	0.0903 mg/kg soil dw	
STP	35.6 mg/l	

4-methylpentan-2-one

Compartments	Value	Remark
Fresh water	0.6 mg/l	
Marine water	0.06 mg/l	
Aqua (intermittent releases)	1.5 mg/l	
STP	27.5 mg/l	
Fresh water sediment	8.27 mg/kg sediment dw	
Marine water sediment	0.83 mg/kg sediment dw	
Soil	1.3 mg/kg soil dw	

8.1.5 Control banding

Reason for revision: 2.2

Publication date: 2013-05-23

Date of revision: 2016-04-07

Revision number: 0200

Product number: 54076

8 / 22

NOVAFILL FLEX 2 (white)

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

a) Respiratory protection:

Wear gas mask with filter type A if conc. in air > exposure limit.

b) Hand protection:

Gloves.

c) Eye protection:

Protective goggles.

d) Skin protection:

Head/neck protection. Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available
Colour	White
Particle size	No data available
Explosion limits	0.8 - 9.0 vol % ; Liquid
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	No data available
Boiling point	No data available
Flash point	No data available
Evaporation rate	No data available
Relative vapour density	> 1
Vapour pressure	No data available
Solubility	water ; insoluble
Relative density	< 1.0
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
pH	No data available

9.2. Other information

Absolute density	< 1000 kg/m ³
------------------	--------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

NOVAFILL FLEX 2 (white)

10.5. Incompatible materials

Oxidizing agents, (strong) acids, (strong) bases.

10.6. Hazardous decomposition products

Upon combustion CO and CO₂ are formed (carbon monoxide - carbon dioxide).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

NOVAFILL FLEX 2 (white)

No (test)data on the mixture available

acetone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	5800 mg/kg		Rat (female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	20000 mg/kg		Rabbit (male)	Experimental value	
Dermal	LD50		> 7426 mg/kg bw		Rabbit (female)	Weight of evidence	
Inhalation (vapours)	LC50	Other	76 mg/l	4 h	Rat (female)	Experimental value	
Inhalation (vapours)	LCL0	Other	16000 ppm	4 h	Rat	Experimental value	

butanone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 423	2193 mg/kg bw		Rat (male/female)	Read-across	
Dermal	LD50	Equivalent to OECD 402	> 10 ml/kg bw	24 h	Rabbit (male)	Experimental value	
Inhalation (vapours)						Data waiving	

n-butyl acetate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 423	10760 mg/kg bw - 12789 mg/kg bw		Rat (male/female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	14112 mg/kg bw		Rabbit (male/female)	Experimental value	

4-methylpentan-2-one

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	2080 mg/kg		Rat	Experimental value	
Dermal	LD50	OECD 402	≥ 2000 mg/kg bw	24 h	Rat (male/female)	Experimental value	
Inhalation (vapours)	LC50		8.2 mg/l - 16.4 mg/l	4 h	Rat	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Not classified for acute toxicity

Corrosion/irritation

NOVAFILL FLEX 2 (white)

No (test)data on the mixture available

acetone

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	OECD 405		24; 48; 72 hours	Rabbit	Weight of evidence	
Skin	Not irritating	Other	3 day(s)	24; 48; 72 hours	Guinea pig	Weight of evidence	
Inhalation	Slightly irritating	Human observation study	20 minutes		Human	Literature	

NOVAFILL FLEX 2 (white)

butanone

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	Equivalent to OECD 405		24; 72 hours	Rabbit	Experimental value	Single exposure
Skin	Not irritating	OECD 404	4 h	4; 24; 48; 72 hours	Rabbit	Read-across	

n-butyl acetate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405		24; 48; 72 hours	Rabbit	Experimental value	
Dermal	Not irritating	Equivalent to OECD 404		24; 48; 72 hours	Rabbit	Experimental value	

4-methylpentan-2-one

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Slightly irritating	OECD 405		24; 48; 72 hours	Rabbit	Experimental value	
Eye	Irritating	Human observation	15 minutes		Human	Experimental value	
Skin	Not irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	
Inhalation (vapours)	Irritating	Human observation	15 minutes		Human	Experimental value	

Classification is based on the relevant ingredients

Conclusion

Causes serious eye irritation.

Not classified as irritating to the skin

Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

NOVAFILL FLEX 2 (white)

No (test)data on the mixture available

acetone

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Guinea pig maximisation test		48 hours	Hamster (female)	Experimental value	
Skin	Not sensitizing	Human observation			Human	Literature	

butanone

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406		24; 48 hours	Guinea pig (female)	Experimental value	

n-butyl acetate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 408			Guinea pig	Experimental value	

4-methylpentan-2-one

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406	21 day(s)	24; 48 hours	Guinea pig (female)	Experimental value	
Inhalation						Not relevant, expert judgement	

Judgement is based on the relevant ingredients

Conclusion

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

Specific target organ toxicity

NOVAFILL FLEX 2 (white)

No (test)data on the mixture available

Reason for revision: 2.2

Publication date: 2013-05-23

Date of revision: 2016-04-07

Revision number: 0200

Product number: 54076

11 / 22

NOVAFILL FLEX 2 (white)

acetone

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral	NOAEL	Equivalent to OECD 408	20 mg/l		No effect	13 week(s)	Mouse (male/female)	Experimental value
Dermal								Not relevant, expert judgement
Inhalation (vapours)	NOAEC	Other	19000 ppm		No effect	8 week(s)	Rat (male)	Literature
Inhalation (vapours)		Human observation study	361 ppm	Central nervous system	neurotoxic effects	2 day(s)	Human	Inconclusive, insufficient data

butanone

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral								Data waiving
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	5041 ppm		No effect	13 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value
Inhalation (vapours)			STOT SE cat.3	Central nervous system	Drowsiness, dizziness			Annex VI

n-butyl acetate

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Inhalation	NOAEC	EPA OTS 798.2450	500 ppm		No adverse systemic effects	13 weeks (daily, 5 days/week)	Rat (male/female)	Experimental value

4-methylpentan-2-one

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral	NOAEL	Equivalent to OECD 408	250 mg/kg bw/day		Weight changes	90 day(s)	Rat (male/female)	Experimental value
Oral	NOEL	Equivalent to OECD 408	50 mg/kg bw/day		No effect	90 day(s)	Rat (male/female)	Experimental value
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	1840 mg/m ³		No neoplastic effects	102 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value

Classification is based on the relevant ingredients

Conclusion

May cause drowsiness or dizziness.
Not classified for subchronic toxicity

Mutagenicity (in vitro)

NOVAFILL FLEX 2 (white)

No (test)data on the mixture available

acetone

Result	Method	Test substrate	Effect	Value determination
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value
Negative	Equivalent to OECD 473	Chinese hamster ovary (CHO)	No effect	Experimental value

butanone

Result	Method	Test substrate	Effect	Value determination
Negative	Equivalent to OECD 473	Rat liver cells	No effect	Experimental value
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value

n-butyl acetate

Result	Method	Test substrate	Effect	Value determination
Negative	OECD 471	Bacteria (S.typhimurium)		Experimental value
Negative	OECD 473	Chinese hamster lung fibroblasts		Experimental value

Reason for revision: 2.2

Publication date: 2013-05-23

Date of revision: 2016-04-07

Revision number: 0200

Product number: 54076

12 / 22

NOVAFILL FLEX 2 (white)

4-methylpentan-2-one

Result	Method	Test substrate	Effect	Value determination
Ambiguous	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)		Experimental value
Negative	Equivalent to OECD 473	Rat liver cells		Experimental value
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value

Mutagenicity (in vivo)

NOVAFILL FLEX 2 (white)

No (test)data on the mixture available

acetone

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative		13 week(s)	Mouse (male/female)		Literature

butanone

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 474		Mouse (male/female)		Experimental value

n-butyl acetate

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	OECD 474		Mouse (male/female)		Read-across

4-methylpentan-2-one

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 474		Mouse (male/female)		Experimental value

Carcinogenicity

NOVAFILL FLEX 2 (white)

No (test)data on the mixture available

acetone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Dermal	NOEL	Other	79 mg	51 week(s)	Mouse (female)	No effect		Literature

4-methylpentan-2-one

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOAEC	OECD 451	1840 mg/m ³	50 weeks (6h/day, 5 days/week)	Rat (male/female)	No neoplastic effects		Experimental value

Reproductive toxicity

NOVAFILL FLEX 2 (white)

No (test)data on the mixture available

acetone

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEC	Equivalent to OECD 414	11000 ppm	6 days (gestation, daily) - 19 days (gestation, daily)	Rat (male/female)			Experimental value
Effects on fertility	NOAEL	Other	900 mg/kg bw/day	13 week(s)	Rat (male)	No effect		Literature

butanone

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEC	Equivalent to OECD 414	1002 ppm	10 days (7h/day)	Rat	No effect	Foetus	Experimental value
Maternal toxicity	NOAEC	Equivalent to OECD 414	1002 ppm	10 days (7h/day)	Rat (female)	No effect		Experimental value
Effects on fertility	NOAEL	Equivalent to OECD 416	1644 mg/kg bw/day - 1771 mg/kg bw/day		Rat (male/female)	No effect		Read-across

Reason for revision: 2.2

Publication date: 2013-05-23

Date of revision: 2016-04-07

Revision number: 0200

Product number: 54076

13 / 22

NOVAFILL FLEX 2 (white)

n-butyl acetate

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	LOAEC	Equivalent to OECD 414	1500 ppm		Rat	Body weight, organ weight, food consumption		Experimental value
	NOAEC	Equivalent to OECD 414	1500 ppm		Rabbit			Experimental value
Effects on fertility	NOAEC	OECD 416	2000 ppm	> 90 day(s)	Rat (male/female)	No effect		Experimental value

4-methylpentan-2-one

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	3000 ppm	10 days (6h/day)	Rat (male/female)	No effect		Experimental value
Effects on fertility	NOAEL	Equivalent to OECD 416	1000 ppm	20 days (6h/day) - 90 days (6h/day)	Rat (male/female)	No effect		Experimental value

Judgement is based on the relevant ingredients

Conclusion CMR

Not classified for reprotoxic or developmental toxicity
 Not classified for mutagenic or genotoxic toxicity
 Not classified for carcinogenicity

Toxicity other effects

NOVAFILL FLEX 2 (white)

No (test)data on the mixture available

acetone

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
			Skin	Skin dryness or cracking			Literature study

butanone

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
	Equivalent to OECD 404		Skin	Skin dryness or cracking			Read-across

n-butyl acetate

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
NOEC	EPA OTS 798.6050	1500 ppm		Hypoactivity	6 h	Rat (male/female)	Experimental value
NOAEC	EPA OTS 798.6050	500 ppm		no neurotoxic effects	13 week(s)	Rat (male/female)	Experimental value

Classification is based on the relevant ingredients

Conclusion

Repeated exposure may cause skin dryness or cracking.

Chronic effects from short and long-term exposure

NOVAFILL FLEX 2 (white)

No effects known.

SECTION 12: Ecological information

12.1. Toxicity

NOVAFILL FLEX 2 (white)

No (test)data on the mixture available

NOVAFILL FLEX 2 (white)

acetone

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	EU Method C.1	5540 mg/l	96 h	Salmo gairdneri	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity invertebrates	LC50	Other	12600 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	EC50		> 7000 mg/l	96 h	Selenastrum capricornutum	Static system	Fresh water	Experimental value; Nominal concentration

butanone

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	2993 mg/l	96 h	Pimephales promelas	Static system	Fresh water	Experimental value; GLP
Acute toxicity invertebrates	EC50	OECD 202	308 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	ErC50	OECD 201	1972 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
Toxicity aquatic micro-organisms	EC0	DIN 38412-8	1150 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value

n-butyl acetate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	18 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value
Acute toxicity invertebrates	EC50	Other	44 mg/l	48 h	Daphnia sp.	Static system	Fresh water	Experimental value
Toxicity algae and other aquatic plants	EC50	Other	674.7 mg/l	72 h	Desmodesmus subspicatus	Static system	Fresh water	Experimental value
	NOEC	Other	200 mg/l	72 h	Desmodesmus subspicatus	Static system	Fresh water	Experimental value
Long-term toxicity aquatic invertebrates	NOEC	OECD 211	23 mg/l	21 day(s)	Daphnia magna		Fresh water	Read-across

	Parameter	Method	Value	Duration	Species	Value determination
Toxicity terrestrial plants	EC50	Equivalent to OECD 208	> 1000 mg/kg soil dw	14 day(s)	Lactuca sativa	Experimental value

4-methylpentan-2-one

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	> 179 mg/l	96 h	Danio rerio	Static system	Fresh water	Experimental value; GLP
Acute toxicity invertebrates	EC50	OECD 202	> 200 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EC50		400 mg/l	96 h	Selenastrum capricornutum			Literature study; Growth rate
Long-term toxicity aquatic invertebrates	NOEC	Equivalent to OECD 211	78 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Nominal concentration
Toxicity aquatic micro-organisms	EC0	DIN 38412-8	275 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Weight of evidence; Nominal concentration

Judgement is based on the relevant ingredients

Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

acetone

Biodegradation water

Method	Value	Duration	Value determination
OECD 301B: CO2 Evolution Test	90.9 %	28 day(s)	Experimental value

Reason for revision: 2.2

Publication date: 2013-05-23

Date of revision: 2016-04-07

Revision number: 0200

Product number: 54076

15 / 22

NOVAFILL FLEX 2 (white)

butanone

Biodegradation water

Method	Value	Duration	Value determination
OECD 301D: Closed Bottle Test	98 %; GLP	28 day(s)	Experimental value

n-butyl acetate

Biodegradation water

Method	Value	Duration	Value determination
OECD 301D: Closed Bottle Test	83 %	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	3.3 day(s)	500000 /cm ³	Experimental value

4-methylpentan-2-one

Biodegradation water

Method	Value	Duration	Value determination
OECD 301C: Modified MITI Test (I)	84 %	14 day(s)	Experimental value
OECD 301F: Manometric Respirometry Test	83 %; GLP	28 day(s)	Experimental value

Half-life soil (t1/2 soil)

Method	Value	Primary degradation/mineralisation	Value determination
	1 day(s) - 7 day(s)		Literature study

Conclusion

Contains readily biodegradable component(s)

12.3. Bioaccumulative potential

NOVAFILL FLEX 2 (white)

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

acetone

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		0.69		Pisces	

BCF other aquatic organisms

Parameter	Method	Value	Duration	Species	Value determination
BCF	BCFWIN	3			Calculated value

Log Kow

Method	Remark	Value	Temperature	Value determination
		-0.24		Test data

butanone

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		0.3	40 °C	Experimental value

n-butyl acetate

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		15.3			Calculated value

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		2.3	25 °C	Test data

4-methylpentan-2-one

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		2 - 5		Pisces	Estimated value

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		1.9		Experimental value

Conclusion

Does not contain bioaccumulative component(s)

12.4. Mobility in soil

NOVAFILL FLEX 2 (white)

butanone

(log) Koc

Parameter	Method	Value	Value determination
log Koc		1.53	Calculated value

n-butyl acetate

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	1.268 - 1.844	QSAR

Volatility (Henry's Law constant H)

Value	Method	Temperature	Remark	Value determination
28.5 Pa.m ³ /mol		25 °C		Experimental value

4-methylpentan-2-one

(log) Koc

Parameter	Method	Value	Value determination
Koc		101.85	Weight of evidence
log Koc		2.008	Weight of evidence

Volatility (Henry's Law constant H)

Value	Method	Temperature	Remark	Value determination
18.75 Pa.m ³ /mol		20 °C		Calculated value

Conclusion

Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Other adverse effects

NOVAFILL FLEX 2 (white)

Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

butanone

Ground water

Ground water pollutant

n-butyl acetate

Ground water

Ground water pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 01 11* (wastes from MFSU and removal of paint and varnish: waste paint and varnish containing organic solvents or other hazardous substances).

16 05 04* (gases in pressure containers and discarded chemicals: gases in pressure containers (including halons) containing hazardous substances).

Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Recycle/reuse. Specific treatment. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1. UN number

Reason for revision: 2.2

Publication date: 2013-05-23

Date of revision: 2016-04-07

Revision number: 0200

Product number: 54076

17 / 22

NOVAFILL FLEX 2 (white)

UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Hazard identification number	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Rail (RID)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Hazard identification number	23
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Inland waterways (ADN)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

NOVAFILL FLEX 2 (white)

Sea (IMDG/IMSBC)

14.1. UN number	UN number	1950
14.2. UN proper shipping name	Proper shipping name	Aerosols
14.3. Transport hazard class(es)	Class	2.1
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Marine pollutant	-
	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	63
	Special provisions	190
	Special provisions	277
	Special provisions	327
	Special provisions	344
	Special provisions	959
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	Annex II of MARPOL 73/78	Not applicable

Air (ICAO-TI/IATA-DGR)

14.1. UN number	UN number	1950
14.2. UN proper shipping name	Proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	Class	2.1
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	A145
	Special provisions	A167
	Special provisions	A802
	Passenger and cargo transport: limited quantities: maximum net quantity per packaging	30 kg G

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2004/42/EC

Maximum value	EC limit value	Category	Subcategory	Notation
839 g/l	840 g/l	IIB	e: Special finishes	2004/42/IIB(e)(840)839

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
<ul style="list-style-type: none"> acetone butanone n-butyl acetate 4-methylpentan-2-one 	Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:

Reason for revision: 2.2

Publication date: 2013-05-23

Date of revision: 2016-04-07

Revision number: 0200

Product number: 54076

19 / 22

NOVAFILL FLEX 2 (white)

	1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	— can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with R65 or H304,4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: “Keep lamps filled with this liquid out of the reach of children”; and, by 1 December 2010, “Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life- threatening lung damage”; b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: “Just a sip of grill lighter may lead to life threatening lung damage”; c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.’
· acetone · butanone · n-butyl acetate · 4-methylpentan-2-one	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — “whoopie” cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs.2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: “For professional users only”.3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

National legislation Belgium

NOVAFILL FLEX 2 (white)

No data available

National legislation The Netherlands

NOVAFILL FLEX 2 (white)

Waste identification (the Netherlands) LWCA (the Netherlands): KGA category 06

Waterbezwaarlijkheid 11

butanone

Huidopname (wettelijk) H

National legislation France

NOVAFILL FLEX 2 (white)

No data available

butanone

VME - Risque de pénétration percutanée PP

National legislation Germany

NOVAFILL FLEX 2 (white)

WGK 1; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4)

Reason for revision: 2.2

Publication date: 2013-05-23

Date of revision: 2016-04-07

Revision number: 0200

Product number: 54076

20 / 22

NOVAFILL FLEX 2 (white)

acetone

Schwangerschaft Gruppe	D
MAK 8-Stunden-Mittelwert ppm	Aceton; 500 ppm
MAK 8-Stunden-Mittelwert mg/m ³	Aceton; 1200 mg/m ³
TA-Luft	5.2.5
Risiko der Fruchtschädigung	Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

butanone

Schwangerschaft Gruppe	C
MAK 8-Stunden-Mittelwert ppm	2-Butanon; 200 ppm
MAK 8-Stunden-Mittelwert mg/m ³	2-Butanon; 600 mg/m ³
TA-Luft	5.2.5
Risiko der Fruchtschädigung	Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
Hautresorptive Stoffe	H; Hautresorptiv

n-butyl acetate

Schwangerschaft Gruppe	C
MAK 8-Stunden-Mittelwert ppm	1-Butylacetat; 100 ppm
MAK 8-Stunden-Mittelwert mg/m ³	1-Butylacetat; 480 mg/m ³
TA-Luft	5.2.5; I
Risiko der Fruchtschädigung	Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

4-methylpentan-2-one

Schwangerschaft Gruppe	C
MAK 8-Stunden-Mittelwert ppm	4-Methylpentan-2-on; 20 ppm
MAK 8-Stunden-Mittelwert mg/m ³	4-Methylpentan-2-on; 83 mg/m ³
TA-Luft	5.2.5
Risiko der Fruchtschädigung	Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
Hautresorptive Stoffe	H; Hautresorptiv

National legislation United Kingdom

NOVAFILL FLEX 2 (white)

No data available

butanone

Skin absorption	Sk
-----------------	----

4-methylpentan-2-one

Skin absorption	Sk
-----------------	----

Other relevant data

NOVAFILL FLEX 2 (white)

No data available

acetone

TLV - Carcinogen	Acetone; A4
------------------	-------------

4-methylpentan-2-one

TLV - Carcinogen	Methyl isobutyl ketone; A3
IARC - classification	2B; Methyl isobutyl ketone

15.2. Chemical safety assessment

No chemical safety assessment is required.

SECTION 16: Other information

Full text of any H-statements referred to under headings 2 and 3:

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.

Reason for revision: 2.2

Publication date: 2013-05-23

Date of revision: 2016-04-07

Revision number: 0200

Product number: 54076

21 / 22

NOVAFILL FLEX 2 (white)

H229 Pressurised container: May burst if heated.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

(*) = INTERNAL CLASSIFICATION BY BIG

PBT-substances = persistent, bioaccumulative and toxic substances

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 2.2

Publication date: 2013-05-23

Date of revision: 2016-04-07

Revision number: 0200

Product number: 54076

22 / 22