

TIX

UNIQUE TRANSPARENT PASTY GLUE FOR BONDING AND REPAIRING WITH VERY HIGH ELASTICITY (700%)!

- Remains flexible, also at extreme temperature fluctuations - even on polypropylene (without primer).
- Bonds on both porous and polished surfaces.
- Can be painted.
- Polymerizes at ambient temperature.
- Can be used under water.



TRANSFIX

GENERAL INFORMATION

TRANSFIX is a single component transparent paste, curing at ambient temperature. TRANSFIX adheres to most common materials, such as metal, wood, glass, leather, linen, canvas, vinyl and even polypropylene.

TRANSFIX provides, after curing, a clear transparent adhesive or sealing joint with exceptional flexibility and elasticity.

TRANSFIX is therefore very appropriate for bonding, sealing or repairing of materials having a different coefficient of expansion.

TECHNICAL INFORMATION AND PACKAGING

Hardness: 75-85 Shore A.
 Tensile strength: 21 N/mm².
 Elongation: 700%.
 Dielectric resistance: 500 Volt/mm (25 Micron).
 Temperature resistance: -84°C till +100°C.
 Working time: 10 minutes.
 Curing (20°C): 8 hours - 70%; 24 hours - 100%.
 Chemical resistance: excellent
 nitric acid (20%)
 acetates (10%)
 sulphuric acid (10%)
 lactic acid (5%)

hydrochloric acid (20%)
 boric acid
 alcohols
 food
 oils
 seawater
 phenols

Shelf life: 24 months, in sealed package, keep dry, cool and frost-proof.

Safety measures: consult the Safety Data Sheet.

APPLICATION AND USE

- repair of tarpaulins
- repair of seat upholsteries
- connecting of materials with a different coefficient of expansion
- repair of holes and cracks in synthetic fabrics (rubber dinghies, nuoyos, rainproof clothing)
- application for electrical insulation

Article nr	Name	Content	Section
N505020	Transfix	95ml	ADHESIVES AND SEALANTS



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

