

## WSG

### WATERPROOF AND HEAT **RESISTANT GREASE**

- Unique 360° jet spray. Can be applied at any angle.
- Good penetrating characteristics.
- Reduces friction and wear to a minimum. Cannot be rinsed away, not even with hot water.
- Does not dry out, does not harden.
- · Prevents corrosion.
- Excellent for high and low temperature applications. (between -35°C and +185°C)
- · Contains no acids.
- Safe on plastics and rubber. •

to heat and moisture.

Excellent for hard to reach areas, subject



# WHITE SUPREME GREASE

## **GENERAL INFORMATION**

WHITE SUPREME GREASE is a multi-purpose heavy-duty high penetrating capacity. The product flows out as a lubricant, based on calcium. It is easy to use, the spray can deliver an even coverage, prevents waste and contamination.

WHITE SUPREME GREASE has a

## **TECHNICAL INFORMATION AND PACKAGING**

Appearance: white grease in aerosol. Base: calcium. Specific weight at 20°C: 1.120 g/cm<sup>3</sup> DIN51757. Flow temperature: 185°C. Solidification temperature: -35°C. 4 Ball test DIN 51350: 300-320 kg.

#### **APPLICATION AND USE**

- WHITE SUPREME GREASE is especially adapted for use on: hinges
  - window-slides

Article nr

N231111

- lock mechanismus
- machine parts and chains
- MOTORCYCLES BICYCLES: clutch and gas regulators, rev. counters and speedometer cables, driving chains, gearings, pedals, ball-bearings, bicycle gears, ...

Name White Supreme Grease







Water resistance DIN 51807 at +90°C: total.

Shelf life: 12 months, keep dry, cool and frost-proof. Safety measures: consult the Safety Data Sheet.

- INDUSTRY: everywhere where the exposure to heat, water or dampness is frequent for ventilators, gears, bearings, conveyors, ....
- CARS: window-slides, locks, hinges, windscreen wipers and wiper motors, clutches, brakes, gas regulators, heater cocks, wheel bearings, water pumps, generator bearings, ...

Section

LUBRICANTS

Conter	nt
400ml	

## NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.





WWW.TECH-MASTERS.EU