

BLU

EFFICIENT SEALING TAPE FOR PERMANENT REPAIR AND PROTECTION

- Very high, immediate adhesiveness.
- Special butyl rubber body.
- Very high tear resistance.
- Excellent U.V. resistance.
- Aluminium support reinforced with synthetic materials.
- Lead coloured.
- High temperature resistance: -30°C to +100°C.
- Adheres to most materials: concrete, stone, lead, zinc, steel, aluminium and glass.
- Easy to apply, also in corners and bends.
- Can be painted.



BUTALU TAPE

GENERAL INFORMATION

BUTALU is a sealing tape which consists of a modified butyl rubber body and a complex aluminium support reinforced with synthetic material, and a silicon protective film.

Due to the unique composition of the butyl rubber mass, a very high initial adhesion is obtained. The extreme flexible rubber mass adapts itself to each

form and fills smoothly irregularities in the surface.

The aluminium support is reinforced with synthetic material and is therefore tear resistant, unalterable and extremely weatherproof. The carrier is lead coloured and can be painted on.

BUTALU allows sealing of leaks or finishing off of joints in a quick and very effective way.

TECHNICAL INFORMATION AND PACKAGING

Thickness: +/- 0.7 mm.

Aluminium support: complex aluminium film reinforced with synthetic material.

Adhesive mass: modified butyl rubber cold adhesive.

Specific weight: 1100 g/m².

Peeling force on fireproof cement: at 90°C and 200 mm/min >= 10 N/cm.

Temperature resistance: -30°C to +100°C.

Application temperature: +5°C to +40°C.

Chemical resistance: water: excellent; weather

conditions: excellent; hydrocarbons: not resistant.

First test foundations based on PE, PP, silicones and bitumen for adhesion (see each tape).

Shelf life: 24 months, keep dry, cool and frost-proof.

Safety measures: consult the Safety Data Sheet.

APPLICATION AND USE

- sealing roof joints at:
 - gutter - zinc - lead
 - domes
 - chimneys
- sealing pipe connections and canals in ventilation, airco, heating systems
- sealing glass or polycarbonate in veranda and greenhouse construction
- thermal insulation and corrosion protection in pipelines
- sealing and bonding of hinged or moving connections
- sealing leaks in waste pipes/feed-through pipes
- grates
- lead flashings

Article nr	Name	Content	Section
N603039	Butalu Tape 30mm x 10m	1pc.	TAPES
N603059	Butalu Tape 50mm x 10m	1pc.	TAPES
N603159	Butalu Tape 150mm x 10m	1pc.	TAPES
N603259	Butalu Tape 100mm x 10m	1pc.	TAPES



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



TAPES

WWW.TECH-MASTERS.EU

