

# LTP22

## THE LIGHT WEIGHT AND HAND HELD TORCH SYSTEM

- Automatic piezo ignition
- Trigger on/off function no waste of LP gas
- Operates in all positions
- Wide range of quick changeable burners
- For disposable cartridges.
- Ergonomic light weight composite handle or sturdy heavy duty metal handle
- Provides a temperature of 2200° C



# **LOTPISTOLE ULTRAMAPP 2200**

## **GENERAL INFORMATION**

Metaljet and Ultramapp gas form together the most powerful and efficient torch system on the market. A combination of modern combustion technology and unique gas mixture gives you a flame temperature of 2200°C. Sturdy metal handle with

#### **TECHNICAL INFORMATION**

Working pressure: 2 bar For ultragas catridge (not included): 2206 Can be used with all burners.

### **TECHNICAL INFORMATION BURNER**

- 8702: Pin-point burner for small soft soldering jobs. Gives a precise and stable flame Burner diameter: 15mm
   Gas consumption, at 2 bar: 40g/h Effect, at 2 bar: 0,5kW
   Soft soldering at 2 bar: 10mm
- 8704: Standard burner for soft soldering and other small heating jobs. For soft soldering and other small heating jobs. Burner diameter: 16 m Gas consumption, at 2 bar: 90g/h Effect, at 2 bar: 1,2kW Soft soldering at 2 bar: 18mm
- 8706: Cyclone burner for brazing and soft soldering. Intensive and effective short flame that reaches around the pipe.
  Burner diameter: 14 mm
  Gas consumption, at 2 bar: 170g/h
  Effect, at 2 bar: 2,2 kW
  Soft soldering: 40 mm
- Brazing at 2 bar: 18mm
  8707: Cyclone burner for brazing and soft soldering. High efficient cyclone burner with increased tip diameter.
  Burner diameter: 16 mm Gas consumption, at 2 bar: 230g/h Effect, at 2 bar: 2,9kW Soft soldering: 40 mm Brazing at 2 bar:18mm

stainless steel high efficient cyclone burner 8707 for instant heat around the pipe. Heating, brazing and soldering works will be done with highest quality efficiency. PLEASE NOTE: Before using upside down, warm up 30 sec.

NO BURNER INCLUDED!

- 8708: Hot-air burner or shrinking and paint stripping. Powerful and wind stable hot-air stream.
- Burner diameter: 38mm Gas consumption, at 2 bar: 130g/h Effect, at 2 bar: 1,7kW
- 8710: Soft flame burner or shrinking and heating jobs. Powerful and wind stable soft flame. Burner diameter: 24 mm Gas consumption, at 2 bar: 230g/h Effect, at 2 bar: 3,5 kW
  - Soft soldering at 2 bar: 22 mm
- Copper bit: Made f copper with one pointed and one flat end. For use with burner 8702.

Article nr	Name	Content	Section	
Y902155	Lotpistole Ultramapp 2200	1 pc.	TOOLS	
Y902206	Ultramapp 2200°C	750 ml	TOOLS	
Y908702	Pin-Point Burner	1 pc.	TOOLS	
Y908704	Standard Burner	1 pc.	TOOLS	
Y908706	Cyclon Burner	1 pc.	TOOLS	
Y908708	Hot-Air Burner	1 pc.	TOOLS	
Y908710	Soft Flame Burner	1 pc.	TOOLS	
Y908843	Copper Bit	1 pc.	TOOLS	
Y993257	Case (empty)	1 pc.	TOOLS	

T908708

T908702

### NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



T908706

TOOLS WWW.TECH-MASTERS.EU

T908707

T908704