techniqua HANDELS-GmbH

Safety data sheet According to 1907/2006 EEC Article 31

Printing date: 23.02.2018

Version: 31

Revision: 23.02.2018



Printing date: 23.02.2018

Version: 31

Revision: 23.02.2018

Trade name: ZINC GUARD

Signal word D	(Contd. of page 1)
0	mining components of labelling:
Acetone	mining components of tabelling.
Hydrocarbons,	C9.aromatics
butanol	
Hazard stater	nents
	xtremely flammable aerosol. Pressurised container: May burst if heated.
	auses serious eye irritation.
H336 M	lay cause drowsiness or dizziness.
H411 To	oxic to aquatic life with long lasting effects.
Precautionary	y statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves / eye protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P403	Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
Additional inf	
	ated exposure may cause skin dryness or cracking.
2.3 Other haz	
	T and vPvB assessment
PBT: Not appl	
vPvB: Not app	אורמטוב.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

*

• **Description:** Active substance with propellant

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	25-<50%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	- 10-<25%
	•	(Contd. on page 3)

Printing date: 23.02.2018

Version: 31

Revision: 23.02.2018

Trade name: ZINC GUARD

		(Contd. of page 2)
EC number: 918-668-5	Hydrocarbons,C9,aromatics	2.5-<10%
Reg.nr.: 01-2119455851-35	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	
CAS: 7440-66-6	zinc powder -zinc dust (stabilized)	1-<2.5%
EINECS: 231-175-3 Reg.nr.: 01-2119467174-37	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 71-36-3	butanol	1-<2.5%
EINECS: 200-751-6	Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302;	
Reg.nr.: 01-2119484630-38	Acute Tox. 4, H332; Škin Irrit. 2, H315; STOT SE 3, H335- H336	
EC number: 918-481-9	Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene	0.1-<1%
Reg.nr.: 01-2119457273-39	<0.1%	
	Asp. Tox. 1, H304	
CAS: 7779-90-0	trizinc bis(orthophosphate)	≥0.25-<1%
EINECS: 231-944-3	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
Reg.nr.: 01-2119463881-32		
CAS: 1314-13-2	zinc oxide	≥0.1-<0.25%
EINECS: 215-222-5	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
Reg.nr.: 01-2119463881-32		

· Additional information:

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Do not induce vomiting; call for medical help immediately.
- \cdot 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- \cdot **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Printing date: 23.02.2018

Version: 31

Revision: 23.02.2018

(Contd. of page 3)

Trade name: ZINC GUARD

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

- Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- 7.2 Conditions for safe storage, including any incompatibilities • Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility:
- Observe official regulations on storing packagings with pressurised containers.
- \cdot Further information about storage conditions:
- Keep receptacle tightly sealed.
- Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

 Ingredients with limit values that require monitor 	ing at the	e workplace:
--	------------	--------------

67-64-1 Acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

106-97-8 butane (containing < 0.1% butadiene (203-450-8))

- WEL Short-term value: 1810 mg/m³, 750 ppm
 - Long-term value: 1450 mg/m³, 600 ppm
 - Carc (if more than 0.1% of buta-1.3-diene)

(Contd. on page 5)

GB

Printing date: 23.02.2018

Version: 31

Revision: 23.02.2018

Trade name: ZINC GUARD

74-98-6 pi	ropane		(Contd. of pag
OEL Sho	rt-term value: 3600 m		
	g-term value: 1800 m	g/m³, 1	1000 ppm
71-36-3 bı			
WEL Sho Sk	rt-term value: 154 mg	g/m ³ , 50) ppm
•			yclic,<2% aromates, Benzene <0.1%
OEL Sho	rt-term value: 1200 m	ng/m³,	184 ppm
DNELs			
67-64-1 A	cetone		
Oral	DNEL Long term-sy	stemic	62 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-sy	stemic	62 mg/kg bw/day (Consumer)
			186 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local		2,420 mg/m3 (Worker)
	DNEL Long term-sy	stemic	200 mg/m3 (Consumer)
	- •		1,210 mg/m3 (Worker)
Hydrocar	bons,C9,aromatics		
Oral	DNEL Long term-sy	stemic	11 mg/kg bw/day (Consumer)
Dermal			11 mg/kg bw/day (Consumer)
	Ç ,		25 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-sy	stemic	32 mg/m3 (Consumer)
	6 7		100 mg/m3 (Worker)
7440-66-6	zinc powder -zinc d	ust (st	
Oral	•		50 mg/kg bw/day (Worker)
Dermal			5,000 mg/kg bw/day (Consumer)
	6,		5,000 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-sv	stemic	2.5 mg/m3 (Consumer)
			5 mg/m3 (Worker)
71-36-3 bı	itanol		
Oral		stemic	3.125 mg/kg bw/day (Worker)
	DNEL Long term-loo		310 mg/m3 (Consumer)
	21(22 20ng toni 10)		55 mg/m3 (Worker)
PNECs			
67-64-1 A	antono		
		1.06.(Undefind)
		``	Undefind)
		`	Undefind)
		,	Undefind)
	zinc powder -zinc d		
			Undefind)
			Undefind)
			Undefind)
PNEC Soil			(Undefind)
	vage Treatment Plant		
FINEC Mai	rine water sediment	30.3 ((Undefind)
			(Contd. on pag

Printing date: 23.02.2018

Version: 31

Revision: 23.02.2018

Trade name: ZINC GUARD

Addi	(Contd. of page tional information: The lists valid during the making were used as basis.
	xposure controls
	onal protective equipment:
	eral protective and hygienic measures:
	away from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing
	hands before breaks and at the end of work.
	ot inhale gases / fumes / aerosols.
	d contact with the eyes.
	d contact with the eyes and skin.
	iratory protection:
	se of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure
	elf-contained respiratory protective device.
	uitable respiratory protective device in case of insufficient ventilation. A/P2
	ection of hands:
	gloves for the protection against chemicals according to EN 374
wear	groves for the protection against chemicals according to EAV 374
ſ	n la construction de la construc
1115	Protective gloves
	ent resistant gloves
	tion of the glove material on consideration of the penetration times, rates of diffusion and the degradation
	erial of gloves
	election of the suitable gloves does not only depend on the material, but also on further marks of quality
	aries from manufacturer to manufacturer. As the product is a preparation of several substances, the
	ance of the glove material can not be calculated in advance and has therefore to be checked prior to the
	cation. e rubber, NBR
	mmended thickness of the material: $\geq 0.5 \text{ mm}$
	tration time of glove material
	ontinuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the
	rence given to a breakthrough time greater than 480 minutes. For short-term or splash guard we
	nmend the same. We are aware that suitable gloves that offer this level of protection may not be availab
	at case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and
	y replacement are followed. The thickness of the gloves is not a good measure of the resistance of the
	against a chemical substance, because this depends on the exact composition of the material from whi
	loves are made.
	exact break trough time has to be found out by the manufacturer of the protective gloves and has to be
obser	
	protection:
Safet	y glasses
Nime-	Tightly cooled coorder
	Tightly sealed goggles
Body	protection: Use protective suit. (EN-13034/6)

Printing date: 23.02.2018

Version: 31

Revision: 23.02.2018

Trade name: ZINC GUARD

(Contd. of page 6)

SECTION 9: Physical and chemical properties • 9.1 Information on basic physical and chemical properties • General Information	
Form:	Aerosol
Colour:	According to product specification Characteristic
· Odour: · Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	Not applicable, as aerosol.
· Flash point:	-97 °C
· Flammability (solid, gas):	Not applicable.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
· Explosion limits:	
Lower:	0.7 Vol %
Upper:	13 Vol %
· Vapour pressure at 20 °C:	4 hPa
· Density at 20 °C:	0.71 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
 Evaporation rate 	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	90.3 %
Solids content:	7.4 %
• 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- \cdot 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 8)

GE

Version: 31

Revision: 23.02.2018

Trade name: ZINC GUARD

Printing date: 23.02.2018

(Contd. of page 7)

(Contd. on page 9)

GB

		toxicological effects I on available data, the classification criteria are not met.
LD/LC50	values rel	evant for classification:
67-64-1 A	cetone	
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	7,800 mg/kg (rbt)
Inhalative	LC50/4h	>20 mg/l (rat)
Hydrocar	bons,C9,a	romatics
Oral	LD50	3,295 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rat)
7440-66-6	zinc pow	der -zinc dust (stabilized)
Oral	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4h	>5.4 mg/l (rat)
71-36-3 bi	utanol	
Oral	LD50	2,292 mg/kg (rat)
Dermal	LD50	3,430 mg/kg (rbt)
Inhalative	LC50/4 h	>17.76 mg/l (rat)
7779-90-0	trizinc bi	s(orthophosphate)
Oral	LD50	5,000 mg/kg (rat)
Serious ey Causes ser Respirato CMR effe Germ cell Carcinoge Reproduc STOT-sin May cause STOT-rep	osion/irrit. /e damage ious eye ir ry or skin cts (carcin mutageni enicity Bas tive toxici gle exposu e drowsines beated exp	 ation Based on available data, the classification criteria are not met. /irritation ritation. sensitisation Based on available data, the classification criteria are not met. nogenity, mutagenicity and toxicity for reproduction) city Based on available data, the classification criteria are not met. sed on available data, the classification criteria are not met. ty Based on available data, the classification criteria are not met.
SECTIC		cological information

8,800 mg/l (Daphnia magna)

3.2 mg/l (Daphnia magna)

354 ug/l (Daphnia Magna 48h)

1 mg/l (Pseudokirchneriella subcapitata)

9.2 mg/l (Oncorhynchus mykiss (96h))

8,300 mg/l (Fish)

7440-66-6 zinc powder -zinc dust (stabilized)

Hydrocarbons,C9,aromatics

EC50

NOELR (72h)

EL50(48h)

LL50 (96h)

EC50

Printing date: 23.02.2018

Version: 31

Revision: 23.02.2018

Trade name: ZINC GUARD

	(Contd. of page 8)			
NOEC/21d	178 ug/l (Crustaceeen-Palaemon elegans)			
NOEC (72h)	9 mg/l (Ceratophyllum demersum)			
	0.017 mg/l (Pseudokirchneriella subcapitata)			
NOEC/72h	72.9 ug/l (Pseudokirchneriella subcapitata)			
NOEC/4w	8.3 ug/l (Cyprinus carpio)			
EC10/21d	9.2 ug/l (Daphnia magna)			
EC10/72h	27.3 ug/l (algae)			
EC50 (72h)	0.17 mg/l (Selenastrum capricornatum (72 h))			
LC50/96h	0.41 mg/l (Oncorhynchus mykiss)			
EC50/48h	1 mg/l (Daphnia magna)			
EC50/96h	0.527 mg/l (algae)			
LC50	238-269 ug/l (Pimephales promelas (96 h))			
71-36-3 butanol				
NOEC (21 days)	4.1 mg/l (Daphnia magna)			
LC50/96h	1,376 mg/l (Pimephales promelas)			
EC50/48h	1,328 mg/l (Daphnia magna)			
EC50	225 mg/l (Selenastrum capricornatum (72 h))			
7779-90-0 trizin	c bis(orthophosphate)			
LC50/96h	0.14 mg/l (Oncorhynchus mykiss (96h))			
EC50/48h	2.34 mg/l (Daphnia magna)			
ErC(50) (72h)	0.14 mg/l (Desmodesmus subspicatus)			
 12.3 Bioaccumu 12.4 Mobility in Ecotoxical effec Remark: Toxic Additional ecolo General notes: Water hazard cla Do not allow pro Danger to drinkii Also poisonous f Toxic for aquatic 12.5 Results of I PBT: Not applic vPvB: Not applic 	for fish ogical information: ass 2 (German Regulation) (Self-assessment): hazardous for water duct to reach ground water, water course or sewage system. ng water if even small quantities leak into the ground. for fish and plankton in water bodies. c organisms PBT and vPvB assessment able.			
SECTION 13 13.1 Waste trea Recommendation				
Must not be disp	osed together with household garbage. Do not allow product to reach sewage system.			

Uncleaned packaging:
Recommendation: Disposal must be made according to official regulations.

(Contd. on page 10)

GB

Printing date: 23.02.2018

Version: 31

Revision: 23.02.2018

(Contd. of page 9)

Trade name: ZINC GUARD

14.1 UN-Number ADR, ADN, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR, ADN	UN1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
IMDG	AEROSOLS (Hydrocarbons,C9,aromatics, zinc powder - zinc dust (stabilized)), MARINE POLLUTANT
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1 2.1
ADN	
ADN/R Class:	2 5F
IMDG	
Class	2.1
Label	2.1
Class	2.1
Label	2.1
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Product contains environmentally hazardous substances: zinc powder -zinc dust (stabilized)
Marine pollutant:	Yes Symbol (fish and tree) Symbol (fish and tree)
Special marking (ADR):	-
14.6 Special precautions for user Danger code (Kemler):	Warning: Gases.
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from"

(Contd. on page 11) GB

Printing date: 23.02.2018 Version: 31

Revision: 23.02.2018

Trade name: ZINC GUARD

	(Contd. of page 10
	class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
• 14.7 Transport in bulk according to A	Annex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
·IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category
- P3a FLAMMABLE AEROSOLS
- E2 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40

· National regulations:

Class	Share in %
NK	75-<100

- **VOC-CH** 90.31 %
- · VOC-EU 642.1 g/l
- · Danish MAL Code 5-3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.

(Contd. on page 12)

Safety data sheet According to 1907/2006 EEC Article 31

Printing date: 23.02.2018

Version: 31

Revision: 23.02.2018

Trade name: ZINC GUARD

(Contd. of page 11)
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
1411 Toxic to aquate the with long lasting effects.
· Abbreviations and acronyms:
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the
International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International
Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1: Flammable gases – Category 1
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2
* * Data compared to the previous version altered. *
GB