Page 1/8

Safety data sheet according to 1907/2006/EC, Article 31



Printing date 23.05.2016

Version number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: Putty HD 1000g · 1.2 Relevant identified uses of the substance or mixture and uses advised against • Sector of Use SU21 Consumer uses: Private households / general public / consumers • Product category PC9a Coatings and paints, thinners, paint removers · Application of the substance / the mixture Knife filler/ Surfacer \cdot 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: TECHNIQUA HANDELS GmbH Hartleitnerstraße 3 A-4653 Eberstalzell *Tel:* +43 (0) 7241 213 79 E-Mail: office@techniqua.at 1.4 Emergency telephone number: Poisoning Information Centre (VIZ), Stubenring 6, A-1010 Vienna, Emergency call 0-24 hrs: +43 1 406 43 43 *Office hours: Monday to Friday, 8 to 16 hrs, Tel.: +43 1 406 68 98* **SECTION 2:** Hazards identification · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS08 health hazard H361d Suspected of damaging the unborn child. Repr. 2 STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure. GHS07 Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labelling: styrene · Hazard statements H226 Flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H361d Suspected of damaging the unborn child. (Contd. on page 2) GB

Page 2/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.05.2016

Version number 1

Revision: 23.05.2016

Trade name: Putty HD 1000g

(Contd	l. of page 1)
72 Causes damage to the hearing organs through prolonged or repeated exposure.	
cautionary statements	
01 If medical advice is needed, have product container or label at hand.	
02 Keep out of reach of children.	
0 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking	,.
50 Do not breathe vapours.	
30 Wear protective gloves / eye protection.	
81 Use personal protective equipment as required.	
4 Get medical advice/attention if you feel unwell.	
05 Store locked up.	
1 Dispose of contents / container in accordance with regional regulations.	
Other hazards	
ults of PBT and vPvB assessment	
T: Not applicable.	

- **PDI**: Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous com	ponents:
-----------------	----------

· Dangerous components.		
CAS: 100-42-5	styrene	10-<12.5%
EINECS: 202-851-5	🛞 Flam. Liq. 3, H226	
Index number: 601-026-00-0	 Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; 	
	STOT SE 3, H335	
	Aquatic Chronic 3, H412	
CAS: 7727-43-7	barium sulphate, natural	5-<10%
EINECS: 231-784-4	substance with a Community workplace exposure limit	
Reg.nr.: 01-2119491274-35		

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, bluspoeder of waterstraal. Grotere brand met waterstraal of met schuim. Vaten met water afkoelen.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters -

(Contd. on page 3)

GB

Page 3/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.05.2016

Version number 1

Revision: 23.05.2016

Trade name: Putty HD 1000g

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Do not flush with water or aqueous cleansing agents Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
 • 6.4 Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

• *Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

· Storage class: 3

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

100-42-5 styrene

WEL Short-term value: 1080 mg/m³, 250 ppm Long-term value: 430 mg/m³, 100 ppm

7727-43-7 barium sulphate, natural

WEL Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols.
- · Respiratory protection:

Filter A/P2

Use suitable respiratory protective device in case of insufficient ventilation.

(Contd. on page 4)

(Contd. of page 2)

Page 4/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.05.2016

Version number 1

Revision: 23.05.2016

(Contd. of page 3)

GB

Trade name: Putty HD 1000g

• Protection of hands:

In case of contact with spray dust protective gloves made of butyl shoud be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products



Protective gloves

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves Fluorocarbon rubber (Viton)

Penetration time of glove material Butyl rubber gloves with a thickness of 0.4 mm are resistant to: Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Safety glasses

SECTION 9: Physical and chemical properties

• General Information	
· Appearance:	
Form:	Pasty
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	145 °C
· Flash point:	31 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	480 °C
• Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	8.9 Vol %
· Vapour pressure at 20 °C:	6 hPa
· Density at 20 °C:	1.9 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.05.2016

Version number 1

Revision: 23.05.2016

Trade name: Putty HD 1000g

		(Contd. of page 4
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/v	water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic at 20 •C:	60 s (DIN 53211/4)	
· Solvent content:		
VOC-(EU)		
	220.3 g/l	
· VOC-EU%	11.60 %	
· Solids content:	88.4 %	
• 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- \cdot 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

100-42-5 styrene

Oral LD50 5000 mg/kg (rat)

Inhalative LC50/4 h 24 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- \cdot Serious eye damage/irritation
- Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity
- Suspected of damaging the unborn child.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure

Causes damage to the hearing organs through prolonged or repeated exposure.

• Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity: No further relevant information available.

(Contd. on page 6)

Page 6/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.05.2016

Version number 1

Revision: 23.05.2016

(Contd. of page 5)

Trade name: Putty HD 1000g

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- \cdot Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

\cdot European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

15 01 04 metallic packaging

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, IMDG, IATA	UN3269
	0110205
· 14.2 UN proper shipping name · ADR	UN3269 POLYESTER RESIN KIT
·IMDG	POLYESTER RESIN KIT
·IATA	Polyester resin kit
· 14.3 Transport hazard class(es)	
ADR	
· Class	3 (FT3) Flammable liquids.
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
ADR, IMDĞ, IATA	III
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Flammable liquids.

Page 7/8

Safety data sheet according to 1907/2006/EC, Article 31

Version number 1

Revision: 23.05.2016

Trade name: Putty HD 1000g

Printing date 23.05.2016

	(Contd. of page 6)
· Danger code (Kemler):	-
· Stowage Category	A
· 14.7 Transport in bulk according to A	nnex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
\cdot Excepted quantities (EQ)	Code: See
· Transport category	3
• Tunnel restriction code	E
· IMDG	
\cdot Limited quantities (LQ)	5L
\cdot Excepted quantities ($\widetilde{E}Q$)	Code: See SP340
· UN "Model Regulation":	UN 3269 POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

- H372 Causes damage to the hearing organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- · Contact: QHSE

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LC50: Lethal concentration, 50 p

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

(Contd. on page 8)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.05.2016

Version number 1

Revision: 23.05.2016

Trade name: Putty HD 1000g

(Contd. of page 7) Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Repr. 2: Reproductive toxicity, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1 Asp. Tox. 1: Aspiration hazard, Hazard Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3