

## Automotive PUTTY HD

## PUU

### 2K UNIVERSAL FILLER

- Adheres on most surfaces, such as stainless steel, galvanized iron, metal, aluminium, galvanised plate, polyester, most synthetic materials, even on wood, stone, ...
- Easy to use
- Leaves large surfaces smooth and free of pores
- Easy to sand
- Excellent sag resistance on vertical surfaces
- Free of asbestos and silicone



### GENERAL INFORMATION

PUTTY HD is a versatile professional polyester putty for filling and fine filling at the same time. PUTTY HD is a 2-component putty

and primer based on polyester, half-flexible, high reactive, polyester resin with different mineral, non-polluting filler material (asbestos and silicone free).

### TECHNICAL INFORMATION


Basic: Polyester resin with mineral filler  
 Colour: beige  
 Odour: characteristic  
 Form: soft, thixotrop  
 Pot life at 20°C: approx. 4 - 5 minutes  
 Drying time (at 20°C, 50% relative air humidity):  
 Grindable after approx. 20 - 30 minutes  
 Boiling point: 145°C  
 Flash point: approx. 31°C (putty);  
 for hardener not applicable  
 Density at 20°C: 1,9 g/cm³

Concentration at 20°C: Putty material 1,8 kg/dm³,  
 Hardener 1,15 g/cm³  
 Hardener addition: 2 - 3 % (best mixture 2,5 %)  
 Temperature-resistant of the cured material:  
 to 160°C  
 Shelf life: 12 month if appropriate storage provided  
 (=10°-25°C, relative air humidity of max. 60%)  
 in unopened original bundle.  
 Protect from direct sunlight, frost and humidity  
 Safety measures: Consult the Safety Data Sheet

### APPLICATION AND USE

- USE  
 Rust should be removed from the surface and it should be clean, dry, free of grease and sanded  
 Take the required amount of material from the pack and mix thoroughly with the appropriate hardener.  
 Apply the mixture with the desired thickness.  
 Clean equipment immediately after use, wash putty off with nitro thinner if necessary  
 Do not return the mixture to the tin
- The puttied surface can be drilled, sanded, sawed, filed and painted after 20 minutes
- Suitable for filling pores and imperfections for bare metal, wood, concrete, old paintwork, GPR, etc.  
 Suitable for pre-treated surfaces when repairing of body parts, metal surfaces, repair and restoration of wood or concrete surfaces

Article nr	Name	Content	Section
T124001	Putty HD + Hardener	1kg	SURFACE PROTECTION AND TREATMENT
T124002	Putty HD + Hardener	1,3kg	SURFACE PROTECTION AND TREATMENT
T124101	Hardener for Putty	25g	SURFACE PROTECTION AND TREATMENT



### NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.