

# Revision nr. 5

Dated 16/03/2021

Printed on 16/03/2021

Page n. 1/13

Replaced revision:4 (Dated: 04/12/2017)

# PU PLAST black 5 min - Part B

# Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

**1.1. Product identifier** Product name Chemical name and synonym

PU Plast black 5 min Part B PU Plast black 5 min Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against Intended use Polyurethane adhesive

1.3. Details of the supplier of the safety data sheet TECHNIQUA HANDELS GmbH Hartleitnerstraße 3
A-4653 Eberstalzell
Tel: +43 (0) 7241 213 79
E-Mail: office@techniqua.at

**1.4. Emergency telephone number** Poisoning Information Centre (VIZ), Stubenring 6, A-1010 Vienna Emergency call 0-24 hrs: +43 1 406 43 43 Office hours: Monday to Friday, 8 to 16 hrs, Tel.: +43 1 406 68 98

# **SECTION 2. Hazards identification**

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication: Carcinogenicity, category 2 H351 Suspected of causing cancer. Acute toxicity, category 4 H332 Harmful if inhaled. Specific target organ toxicity - repeated exposure, category 2 May cause damage to organs through prolonged or repeated H373 exposure. Eye irritation, category 2 H319 Causes serious eye irritation. Skin irritation, category 2 Causes skin irritation. H315 Specific target organ toxicity - single exposure, category 3 May cause respiratory irritation. H335 Respiratory sensitization, category 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

			Revision nr. 5
			Dated 16/03/2021
		unin Dant D	Printed on 16/03/2021
	PU PLAST black 5 min - Part B		Page n. 2/13
1			Replaced revision:4 (Dated: 04/12/2017)
Skin sensitization, category 1A	H317	May cause an allergic ski	n reaction.
2.2. Label elements			

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H351	Suspected of causing cancer.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
EUH204	Contains isocyanates. May produce an allergic reaction.

Precautionary statements:

P201	Obtain special instructions before use.
P284	[In case of inadequate ventilation] wear respiratory protection.
P304+P340	IF INHALED: remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice / attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
Contains:	4,4` diphenylmethanediisocyanate, isomere, homologe and mixtures

As from 24 August 2023 adequate training is required before industrial or professional use.

# 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

# **SECTION 3. Composition/information on ingredients**

# 3.2. Mixtures

Contains:

		Revision nr. 5
		Dated 16/03/2021
		Printed on 16/03/2021
	PU PLAST black 5 min - Part B	Page n. 3/13
1		Replaced revision:4 (Dated: 04/12/2017)

Identification	x = Conc. %	Classification 1272/2008 (CLP)
4,4` diphenylmethanediisocyanate, isomere, homologe and mixtures		
CAS 9016-87-9	55 ≤ x < 100	Carc. 2 H351, Acute Tox. 4 H332, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1A H317
EC 618-498-9		
INDEX -		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

# **SECTION 4. First aid measures**

# 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. It can irritate the respiratory tract. Suspected of causing cancer. May cause damage to organs through prolonged exposure or repeated.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

# **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

## 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

	Revision nr. 5
	Dated 16/03/2021
	Printed on 16/03/2021
PU PLAST black 5 min - Part B	Page n. 4/13
	Replaced revision:4 (Dated: 04/12/2017)

#### 5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

# **SECTION 6.** Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

# 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage**

### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use.

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep the product in clearly labelled containers. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany): 10

#### 7.3. Specific end use(s)

Information not available

# **SECTION 8. Exposure controls/personal protection**

		Revision nr. 5
		Dated 16/03/2021
		Printed on 16/03/2021
	PU PLAST black 5 min - Part B	Page n. 5/13
1		Replaced revision:4 (Dated: 04/12/2017)

## 8.1. Control parameters

Regulatory References:

TLV-ACGIH

ACGIH 2020

Туре	Country	TWA/8h		STEL/15min		Remarks Observati		
		mg/m3	ppm	mg/m3	ppm			
TLV-ACGIH			0,005					
Predicted no-effect concent	ration - PNEC							
Normal value in fresh water				1	mg/	1		
Normal value in marine wat	er			0,1	mg/	1		
Normal value of STP micro	organisms			1	mg/	1		
Normal value for the terrest	rial compartment			1	mg/	kg		
Health - Derived no-eff	ect level - DNEL / D	MEL						
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	VND	20 mg/kg bw/d				*		
Inhalation	0,05 mg/m3	VND	0,025 mg/m3	0,025 mg/m3	0,1 mg/m3	0,1 mg/m3	0,05 mg/m3	0,05 mg/m3
Skin	17,2 mg/cm2	25 mg/kg bw/d			28,7 mg/cm2	50 mg/kg bw/d		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION Protect hands with category III work gloves (see standard EN 374).

Material: Nitrile rubber Breakthrough time: 240 min Glove thickness: 0.5mm

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

		Revision nr. 5
		Dated 16/03/2021
		Printed on 16/03/2021
	PU PLAST black 5 min - Part B	Page n. 6/13
1		Replaced revision:4 (Dated: 04/12/2017)

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

# **SECTION 9.** Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance	liquid
Colour	copper
Odour	Not available
Odour threshold	Not available
рН	Not available
Melting point / freezing point	Not available
Initial boiling point	> 300 °C
Boiling range	Not available
Flash point	205 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	0,01 Pa
Vapour density	Not available
Relative density	1,2 g/cm3
Solubility	Not available
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	> 600 °C
Decomposition temperature	Not available

Revision nr. 5	
----------------	--

# PU PLAST black 5 min - Part B

Dated 16/03/2021

Printed on 16/03/2021

Page n. 7/13

Replaced revision:4 (Dated: 04/12/2017)

Viscosity	
Explosive properties	
Oxidising properties	

4000 mPas Not available Not available

#### 9.2. Other information

Information not available

# **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

#### 10.5. Incompatible materials

Information not available

#### 10.6. Hazardous decomposition products

Information not available

# **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

		Revision nr. 5
		Dated 16/03/2021
	PU PLAST black 5 min - Part B	Printed on 16/03/2021
		Page n. 8/13
1		Replaced revision:4 (Dated: 04/12/2017)

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

#### Interactive effects

Information not available

### ACUTE TOXICITY

ATE (Inhalation) of the mixture: 15,71 mg/l ATE (Oral) of the mixture: Not classified (no significant component) ATE (Dermal) of the mixture: Not classified (no significant component)

4,4` diphenylmethanediisocyanate, isomere, homologe and mixtures

LD50 (Oral) > 5000 mg/kg

LD50 (Dermal) > 9400 mg/kg

LC50 (Inhalation) 0,49 mg/l/4h

# **SKIN CORROSION / IRRITATION**

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

## RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin Sensitising for the respiratory system

### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

# CARCINOGENICITY

Suspected of causing cancer

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

	Revision nr. 5
	Dated 16/03/2021
PITPLAST black 5 min - Part B	Printed on 16/03/2021
	Page n. 9/13
	Replaced revision:4 (Dated: 04/12/2017)

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

May cause damage to organs

#### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

# **SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

### 12.1. Toxicity

Information not available

## 12.2. Persistence and degradability

Information not available

# 12.3. Bioaccumulative potential

Information not available

## 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

#### 12.6. Other adverse effects

Information not available

# **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

	Revision nr. 5
	Dated 16/03/2021
PU PLAST black 5 min - Part B	Printed on 16/03/2021
	Page n. 10/13
	Replaced revision:4 (Dated: 04/12/2017)

# CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

## 14.1. UN number

Not applicable

## 14.2. UN proper shipping name

Not applicable

### 14.3. Transport hazard class(es)

Not applicable

# 14.4. Packing group

Not applicable

# 14.5. Environmental hazards

Not applicable

## 14.6. Special precautions for user

Not applicable

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

		Revision nr. 5
		Dated 16/03/2021
	PU PLAST black 5 min - Part B	Printed on 16/03/2021
		Page n. 11/13
1		Replaced revision:4 (Dated: 04/12/2017)

Information not relevant

# **SECTION 15. Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point 3 Contained substance Point 56 4,4` diphenylmethanediiso cyanate, isomere, homologe and mixtures Point 74 DIISOCYANATES Substances in Candidate List (Art. 59 REACH) On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%. Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

### Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

# 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

# Revision nr. 5

Dated 16/03/2021

#### Printed on 16/03/2021

# Page n. 12/13

Replaced revision:4 (Dated: 04/12/2017)

# PU PLAST black 5 min - Part B

# **SECTION 16.** Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Carc. 2	Carcinogenicity, category 2
Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1A	Skin sensitization, category 1A
H351	Suspected of causing cancer.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
EUH204	Contains isocyanates. May produce an allergic reaction.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

			Revision nr. 5
			Dated 16/03/2021
		Printed on 16/03/2021	
		PU PLAST black 5 min - Part B	Page n. 13/13
			Replaced revision:4 (Dated: 04/12/2017)

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. 10th Edition Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition

IFA GESTIS website

ECHA website

Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

15.