

FIP

TRANSPARENT PRIMER TO GLUE DIFFICULT PLASTICS

- transparent primer to glue difficult plastics
- opens the pores in plastics
- improves adhesive strength
- easy to use



FIX PRIMER

GENERAL INFORMATION

FIX PRIMER prevents gluing problems when glueing difficult materials such as: Polyethylene (PE), Polypropylene (PP), PMMA, bakelite, Polycarbonate, Viton rubber, polyolefins, PTFE, silicone, etc.
FIX PRIMER provides very good adhesion strength.
FIX PRIMER seldom leaves traces behind.
FIX PRIMER can be used

during gluing with AL-Fix, Al-Fix Gel, Al-Fix Flexible and Al-Fix Black.

FIX PRIMER can also provide good results in combination with High Tech Tape, High Tech Tape Transparent, HCS Tape, etc.

FIX PRIMER handicaps adhesion on untreated metals and stainless steel.

Technical Information

Solvent base: heptane
Colour: transparent
Vaporisation time: < 10 seconds
Viscosity: 3-6 cps
Flash point: -12°C
Shelf life: 2 months at 20°C

Drying time: < 30 seconds

Drawing strength: depending on the material
3-10 N/mm

Optimum drawing strength: after 24 hours

APPLICATION AND USE

- FIX PRIMER promotes adhesion when glueing most synthetic materials: Polyethylene (PE), Polypropylene (PP), Nitrile, Neoprene, silicone rubbers, ABS, soft PVC, POM (polyoxymethylene), PET and EVA (Ethylene Vinyl Acetate), PMMA, Bakelite, Polycarbonate, Viton rubber, Polyolefins, Poly Tetra Fluor Ethylene (PTFE), the newest thermoplastic elastomers, etc..
But also wood, stone and metals on the above materials and all of these plastics synthetic materials mutually.

- Surfaces must be clean, dry and grease free. Degrease with Novatio Sure Clean. Roughening promotes adhesion. Apply Fix Primer thinly on both surfaces. Allow Fix Primer to dry before applying the glue. Apply glue or tape.

| Article nr | Name | Content | Section |
|------------|------------|---------|------------------------|
| N502110 | Fix Primer | 50ml | ADHESIVES AND SEALANTS |

NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

