

# LB1

## LUBRICANT APPROVED FOR USE IN THE FOOD INDUSTRY

- Clear, non-staining.
- Non-adhesive anti-static lubricant.
- High viscosity.
- Very good temperature and water resistance.
- Does not contain any silicone! Odourless.
- Permitted in the food industry.
- NSF approved.



# LUBRICANT H1

## GENERAL INFORMATION

LUBRICANT H1 is an NSF H1 registered lubricant, formulated from ingredients which are all NSF registered.  
 LUBRICANT H1 has been developed to offer an optimum lubricating capacity at high stresses and is simple to apply in locations that are difficult to reach.

LUBRICANT H1 can be used in a large range of temperatures, without a change in its viscosity. LUBRICANT H1 also protects against corrosion by forming a thin layer, and yet penetrates deeply in the object to be lubricated.

## Technical Information

NSF registration number: Category H1.  
 Compliant with: FDA, Title 21, Section 178.3570.  
 Free of: lead, animal fat and synthetic oils.  
 Form: aerosol  
 Colour: white  
 Explosion limits: 0,8 - 9,0 Vol%

Relative vapour density: > 2  
 Odour: typical.  
 Operating temperature: -20°C to +110°C  
 Shelf life: 24 months, keep dry, cool and frost-proof.  
 Safety measures: consult the Safety Data Sheet.

## APPLICATION AND USE

- LUBRICANT H1 is ideal for use in all food processing companies and firms which design, repair and maintain machinery and accessories, e.g.:
- bottle manufacturing plants
- cardboard factories
- production companies for machines and equipment
- wrapping, packaging, seals, O-rings, bearings etc.
- heavy-duty lubrication inside and outside
- very effective with periodic and inaccessible lubrication points
- suitable for most types of industry, especially with open mechanisms, cables, guides, couplings, sliding rods, hinges, locking mechanisms.
- especially useful when installations have to withstand heavy conditions in extreme circumstances, contact with acids, alkalis, hot and cold water, seat
- all food companies
- abattoirs
- dairy factories
- bakeries
- canneries
- breweries
- and high pressure loads.

Article nr	Name	Content	Section
N214601	Lubricant H1	400ml	LUBRICANTS



## NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



LUBRICANTS

WWW.TECH-MASTERS.EU

