

MUS

AGAINST RUST, DAMP, MOISTURE AND LEAKAGE CURRENTS

- Superfast acting.
- Works by cold shrinkage.
- Colourless and practically odour-free.
- 360° spray direction



MULTISPRAY

GENERAL INFORMATION

MULTISPRAY is fast and effective in contact with rust, tar, grease and water. MULTISPRAY contains no silicones and is safe to use on plastics, lacquers ...

MULTISPRAY combines penetrating power, lubrication, protection, cleaning, rust removal, drives away moisture and the cold shrinkage results in time saving.

TECHNICAL INFORMATION

Water solubility: insoluble
 Density at 20°C: 0.811
 Odour: characteristic
 Partial pressure: 8,53 bar
 Boiling point: 187 - 300°C
 Relative density at 20°C: 0.81g
 Temperature resistance: -80°C to +190°C

Dynamic viscosity at 20°C: 1 mPas
 Kinematic viscosity at 20°C: 1 mPas
 Based on mineral oil
 Storage life: 36 months if kept dry, cool and frost-free
 Safety measures: Please consult the safety card

APPLICATION AND USE

- Shake well before use. Spray and briefly allow it penetrate.
- If necessary, allow the propellant gasses to evaporate.

Article nr	Name	Content	Section
N236116	Multispray	600ml	LUBRICANTS



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



LUBRICANTS

WWW.TECH-MASTERS.EU

