

## NLU

### HEATPROOF CORROSIONPROTECTOR

- A combination of pure aluminium and selected synthetic resins.
- Stops rust - prevents corrosion - scratch resistant.
- Aluminium deposits on metals due to added synthetic resin.
- Ideal for applications at high temperatures.
- With temperatures up to 970°C, the pure aluminium (99,5%) will melt together with the metal surface.
- Gives a bright, brilliant aluminium effect.
- Non-toxic.



## NOVALU 100

### GENERAL INFORMATION

NOVALU 100 gives metal surfaces cathodic rust protection and allows simple, quick and economical application. After spraying only once, a protective coating of 99,5% pure aluminium is formed. The fine aluminium particles deposit on the base material and firmly adhere to

it, due to synthetic resin additives. Exposed to higher temperatures, the resin will vaporize, leaving a coating of pure aluminium, melted together with the metal surface. NOVALU 100 withstands temperatures of up to 800°C and up to 970°C for intermittent periods.

### Technical Information


Composition: aluminium pf 99,5% purity with synthetic resin and solvent additives plus ozonsafe propellant.  
Best application results: use under room temperature.  
Spraying distance: 20 to 25 cm.  
Curing time: fast drying.

Heat resistance: up to 800°C: continuous; up to 970°C: during short time.  
Shelf life: 12 months, keep dry, cool and frost-proof.  
Safety measures: consult the Safety Data Sheet.

### APPLICATION AND USE

- NOVALU 100 coats excellently almost any material, such as ferrous and non ferrous metals, wood, cardboard paper, plastics, ceramics, etc.
- air conditioning and ventilation equipment
- furnaces and ovens
- pipes (steam pipes)
- machine casings
- exhausts
- containers
- motorcar bodies, wheels and coach-work
- arts and craft

Article nr	Name	Content	Section
N112001	Novalu 100	400ml	SURFACE PROTECTION AND TREATMENT



### NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

