TECH-MASTERS Trading GmbH
Perfektastraße 55, A-1230 Wien
Tel: +43 (0)1 / 867 29 07
office@tech-masters.com
www.tech-masters.eu

TFX

TRIMFIX

THE VERSATILE SPRAY-ON ADHESIVE

- Ideal for bonding of large surfaces.
- No spreading - no brushing out - no stringing - does not drip.
- Heat, cold and moisture resistant. and does not dry out.
- Ideal for non-permanent gluing.



GENERAL INFORMATION

TRIMFIX is an air spray adhesive based on synthetic rubber.
TRIMFIX offers a wide variety of applications.
TRIMFIX bonds durably, quick and without any strings or dripping.
TRIMFIX is appropriate for bonding large surfaces where a thin and transparent glue is recommended.

Technical Information

Basis: synthetic rubber in a solution.
Specific weight: 0,77 kg/dm³.
Solid materials: 22,5 - 24,5%.
Viscosity: 100-300 Cps at 20°C.
Colour: milky white.
Drying time: ca. 5 minutes at 20°C.
Open working time: max. 45 minutes.
Temp. resistance: 80°C constant - peak load: 100°C.
Consumption: 1,5 to 2 m2 per aerosol (one-sided).
Detergent: Novatio Safety Clean.
Shelf life: 12 months, keep dry, cool and frost-proof.
Safety measures: consult the Safety Data Sheet.

APPLICATION AND USE

- is suitable for gluing: paper, textile, cardboard, foam plastics, polyurethane, cork, polystyrene, felt, vinyl, plastic foil, reproductions ... to glass, metal, ceramics, wood, concrete, ...

Article nr	Name	Content	Section
N511001	Trimfix	500ml	ADHESIVES AND SEALANTS





NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.