TECH-MASTERS Trading GmbH Perfektastraße 55, A-1230 Wien Tel: +43 (0)1 / 867 29 07 office@tech-masters.com www.tech-masters.eu

SRP

FOR A SMOOTH TRANSITION ON PAINTED AREAS

- Varnish thinner.
- Old and new varnish flow easily together.
- Prefect for using after Novaclear Coat.
- Easy to polish.
- Quick to sand.



GENERAL INFORMATION

SPOTREPAIR is perfect for overlapping wet areas after using Novaclear Coat. SPOTREPAIR has excellent thinning properties to let old

Technical Information

Appearance: Aerosol. Colour: Clear. Odour: Specific. Vapour pressure (at 20 °C): 5200 hPa. Density (at 20 °C): 0.75 g/cm³.

APPLICATION AND USE

sand the surface to be treated with a No. 2000 grain

and new varnish flow freely together. SPOTREPAIR facilitates polishing. SPOTREPAIR is essential for good results and saves time.

Solubility in water: None. Mixability in water: Poor. EU VOC: 751,4 g/l. Safety measures: Consult the safety data sheet.

 apply 2 to 3 thin layers on the transit zones of the fresh Novaclear Coat and the existing varnish to obtain a homogenous coat remove residue with Novacare RC1

Article nr	Name	Content	Section
N120920	Spotrepair	400ml	SURFACE PROTECTION AND
			TREATMENT



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.





SURFACE PROTECTION AND TREATMENT WWW.TECH-MASTERS.EU



SPOTREPAIR