

TFT-2K

SYNTHETIC TRANSPARENT VARNISH

- High-gloss, extremely scratch-resistant 2-component clear coat with very high resistance to petrol, UV rays and weathering
- Prevents against oxidation on stone, iron, copper, brass, aluminium, silver, bronze...
- Repairs scratches on equipments like ski, ski boots, snowboards, helmets, decoration, displays, letterings...
- Long pot life
- Fast drying time
- Very good flow
- Easy to polish



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

TECHNO FINISHER 2K

GENERAL INFORMATION

TECHNO FINISHER 2K is a high-gloss, extremely scratch-resistant 2-component clear coat with very high resistance to petrol, UV rays and weathering. Due to its quick drying time, very good flow and easy polishing, TECHNO FINISHER 2 K is ideal for

protection of different kind of surfaces: iron, Silver, copper, aluminium, bronze, plastic, paint surface, stones, textile, paper, wood, ...
 TECHNO FINISHER 2K clear coat is particularly suitable for spot repairs. Previous paintwork has to be fully dry.

TECHNICAL INFORMATION

Basis of binder: Acrylic
 Colour: transparent
 Smell: solvent
 Degree of gloss: (at measurement angle 60° acc. to DIN 67530
 glossy: 85 gloss-units
 Efficiency:
 Depending on consistence and colour of the ground:
 200 ml are sufficient for approx. 0,3 - 0,4 m²
 Substrate:
 solvent- and water-based base coats
 Drying time (at 20°C, 50% relative air humidity):
 Dust-dry: after approx. 5 minutes
 Dry to touch: after approx. 5 hours

The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
 Temperature resistance: to 120°C
 VOC-value: 118,6g
 Shelf life (after mixing):
 24 hours at room temperature (20 - 25°C)
 5 days at cool storage (6°C)
 Before using again warm up to room temperature (20 - 25°C).
 Storage:
 36 month if appropriate storage provided
 (= 10°-25°C, relative air humidity of max. 60%)
 Safety measures: consult the Safety Data Sheet
 FOR PROFESSIONAL USE ONLY!

APPLICATION AND USE

- **APPLICATIONS:**
 To avoid the oxidation on metal surfaces like iron, silver, copper, aluminum, bronze...
 Excellent for protection and waterproofing of hard textiles like camping tents, boat roofs, car roofs, ...
 To protect wooden surfaces for long time. (waterproof)
 To renovate and to protect ski, snow board, ski boots (to repair the scratches). Use TECHNO FINISHER and it will look like new!
 Spray plast can be used also to protect electric instruments.

- **MIXING A COMPONENTS WITH HARDENER.**
 Remove the protection cap from the bottom of the can and pull the pin out fully with the help of the inserted ring. This will release the knife, which will penetrate the wall of the aluminium cartridge. The cartridge will then rotate 360°, be completely open and release the hardener. Shake the can vigorously to mix the A components with the hardener in the proper, predetermined ratio. Shake can vigorously for 2 minutes. Carry out spray test. Ideal for spot repairs and refinishing areas.

Base coatings can be recoated with TECHNO FINISHER 2K clear coat after drying for 30 minutes
 2-3 full coats, 50µ
 Leave to dry for 2 minutes between coats.

Article nr	Name	Content	Section
T122002	Techno Finisher 2K	200ml	SURFACE PROTECTION AND TREATMENT

