

VFX

VELCRO SYSTEM FOR FAST AND EASY MOUNTING AND DISMOUNTING

- Up to 10.000 times opening and closing.
- 100 % polyamide tissue.
- Provided with an acrylate adhesive.
- Good temperature resistance.
- Good adhesion, also on uneven surfaces.
- Adhesive layer does not damage the surface.
- Ideal for "blind" fixings.
- 4 types available:
 hook band
 loop band (to be used with hook band special "harpoon" design for a direct adhesion on carpets back-to-back for bundling and keeping together.



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

HL-FIX

GENERAL INFORMATION

HL-FIX is a high-quality Velcro system woven of 100% polyamide and is provided with an acrylate adhesive water-based layer.

Due to the fine weaving structure, HL-FIX shows no elongation or shrinkage, and

can therefore also be applied on uneven surfaces. HL-FIX has a very high tensile strain. Yet it can be opened easily.

HL-FIX can be opened and closed up to 10.000 times.

Technical Information

ACRYLATE ADHESIVE:

Material: acrylate water based adhesive.

Temp. resistance: -15°C to +110°C.

Application temp.: +20°C.

To be applied: on a clean, degreased, solid and dry surface. Press on very well.

Apply at room temperature.

Max. bonding strength: after 72 hours.

Resistance: UV: good; aliphatic solvents: good;

aromates: good; water (cold): moderate.

Removal: dissolves in hot water (90°C).

First test foundations based on PE, PP, silicones and bitumen for adhesion (see each tape).

HOOK AND LOOP BAND:

Material: 100% polyamide.

Temp. resistance: -30°C to +140°C.

Tensile strength: 2.3 N/cm width.

Peel off force: 10 N/cm².

Thickness: 3 mm (+/- 0.5 mm) (after closing).

Shelf life: 24 months, keep dry, cool and frost-proof.

Safety measures: consult the Safety Data Sheet.

APPLICATION AND USE

- HL-FIX back to back is an ideal bundling system for cables, hoses and other objects. It can always be reopened and reused and is therefore ideal for bundling cable bundles of computers, audio/video, where, due the minor press-on force, no damage to the conductor is possible.
- HL-FIX harpoon band is specially developed for a direct adhesion on loopshaped woven carpet. Therefore, damage of the carpet is prevented in case of temporary or permanent fixing and dismounting becomes very easy.

Article nr	Name	Content	Section
N562058	HL-Fix Loop 25mm x 5m	1pc.	TAPES
N562158	HL-Fix Hook 25mm x 5m	1pc.	TAPES
N562258	HL-Fix Harpoon 25mm x 5m	1pc.	TAPES
N562358	HL-Fix Hook & Loop 25mm x 5m	1pc.	TAPES



TAPES

WWW.TECH-MASTERS.EU

