TECH-MASTERS Trading GmbH Perfektastraße 55, A-1230 Wien Tel: +43 (0)1 / 867 29 07 office@tech-masters.com www.tech-masters.eu



MSE

LOW SURFACE ENERGY TAPE

- Permanent bonding
- High adhesion on PE/PP
- Can replace welding
- UV resistant
- High solvent resistance
- · High moisture resistance



GENERAL INFORMATION

DOUBLE FIX MSE TAPE is especially designed for permanent bonding in interior and exterior applications.

DOUBLE FIX MSE TAPE can replace reveting, welding, liquid glues and other permanent fasteners. DOUBLE FIX MSE

TECHNICAL INFORMATION

Coulor: Anthracite Adhesive strength: 29,4 N/25 mm Dynamic shear strength: 6,6 kgf/cm² Service temperature range: -20°C to +100°C Solvent resistance: good UV resistance: good Moisture resistance: good Carrier: 1,05 mm polyethylene foam Density: 100 kg/m³ Adhesive:

APPLICATION AND USE

 CAR: Fixing exterior trims and bodyside mouldings
Emblem and badge mountings
INDUSTRY: Signs and panels
Interior and exterior use

TAPE is suitable for various kinds of substances, such as metal, wood, glass and many plastics, but is espacially suitable for low surface energy (LSE)

DOUBLE FIX MS

- Modified cross-linked acrylic adhesive
- Pressure sensitive, providing high tack
- Excellent shear performance

surfaces such as PE and PP.

- MSE Liner:
 - iner:
- Low density polyethyleneEasy to release
- white
- Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hours at +23°C.

Article nr	Name	Content	Section	
T590006	Double Fix MSE 6	1 pc.	TAPES	
T590009	Double Fix MSE 9	1 pc.	TAPES	
T590012	Double Fix MSE 12	1 pc.	TAPES	
T590019	Double Fix MSE 19	1 pc.	TAPES	
T590025	Double Fix MSE 25	1 pc.	TAPES	



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.





WWW.TECH-MASTERS.EU