

# **LBF**

### **FINE MACHINE OIL**

- 100% pure high quality mineral oil.
- Replaces oiling can.
- Ideal for fine atomized lubrication on hard to reach areas.
- Appropriate for lubrication of pneumatic tools.
- No more flowing out, leaking and refilling.



# LUBRIFINE

### **GENERAL INFORMATION**

LUBRIFINE is a low viscosity mineral lubricating oil of high quality. Due to its low viscosity and high penetrating capacity, it may be used perfectly on areas where a normal lubricating oil cannot be used. LUBRIFINE is a high quality universal lubricant. It offers an easy, accurate and

economical lubrication on all types of machines, small bearings with a light load, etc. It is ideal for use on hard to reach areas.

LUBRIFINE replaces the traditional oiling can in workshops, garages and on the road.

LUBRIFINE is appropriate for the daily lubrication of pneumatic tools.

#### **Technical Information**

Basis: mineral naphtenic oil. Kinematic viscosity: at 40°C: 26.1; at 100°C: 3.9. Pour point: -33°C. Shelf life: 12 months, keep dry, cool and frost-proof. Safety measures: consult the Safety Data Sheet.

### **APPLICATION AND USE**

- · all types of machines
- small bearings with a light load
- · classic oil injecctor in workshops, garages, etc.
- lubication of pneumatic equipment

Article nr	Name	Content	Section
N231121	Lubrifine	400ml	LUBRICANTS



### NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



