

SS1

THE UNIVERSAL LUBRICATION AND PROTECTION

- Odourless and colourless.
- 100% water resistant.
- Avoids oxidation and rust.
- Highly temperature resistant from -50°C to +250°C.
- Superfine, transparent lubrication.
- NSF approved.



SILICONE SPRAY H1

GENERAL INFORMATION

SILICONE SPRAY H1 is an NSF H1 registered lubricant, formulated from ingredients which are all NSF registered.

SILICONE SPRAY H1 has excellent lubricating

and side capacity with a good temperature resistance. SILICONE SPRAY H1 provides a good adhesion and sustainability, because of its low surface.

Technical Information

NSF registration number: 140738, Category H1.
Compliant with: FDA, Title 21, Section 178.3570.
Free of: lead, animal fat.
Odour: typical.
Resists: water and salt water.

Temperature resistance: -50°C to +250°C.
Shelf life: 12 month, keep dry, cool and frost-proof.
Safety measures: Consult the Safety Data Sheet.

APPLICATION AND USE

- SILICON SPRAY H1 is suitable for all food processing companies and companies that design, repair and maintain packaging systems, machinery and accessories for the food industry such as:
 - all food companies
 - abattoirs
 - dairy factories
 - bakeries
- canneries
- breweries
- bottle manufacturing plants
- cardboard factories

Article nr	Name	Content	Section
N201501	Silicone Spray H1	400ml	LUBRICANTS



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



LUBRICANTS

WWW.TECH-MASTERS.EU

