

Automotive

BENZINE HP

ADB

HIGH PERFORMANCE CLEANER FOR ALL PETROL ENGINES

- Removes deposits and oxidation residue in fuel lines, injection needles, cylinders, spark plugs and combustion chambers.
- Shown to reduce NOx emissions and hence guarantee optimal combustion
- Safeguards fuel quality
- Increases octane rating and improves performance
- Safeguards the economical, ecological and safe functioning of the entire fuel system
- Extends catalytic converter and lambda probe service life by ensuring optimal combustion
- Saves fuel thanks to precision fuel injection and even combustion



General Information

BENZINE HP is a high performance additive for all petrol engines, that cleans all

components having contact with fuel and safeguards technically reliable and economic operation.

Technical Information

Physical state: liquid Odour: amine-like pH-Value (at 20 °C): not determined DIN 19268 Changes in the physical state Initial boiling point and boiling range: 82 °C Flash point: Upper explosion limits: 12 vol. % Oxidizing properties Not oxidizing. Density (at 20 °C): 0,756 g/cm³ DIN 51757 Water solubility: insoluble Viscosity / kinematic (at 40 °C): < 7 mm²/s DIN EN ISO 3104

Application and Use

USING STRONG:

Replace the fuel filter:

Pour in the filter, a part of the bottle BENZINE HP up to 50 ml, in any case not higher than 20/25% of the content of the filter add fuel to fill the filter, and reassemble.

Pour the remaining approximately 250 ml product in the tank car.

Start up the engine for about 30-45 sec. Then turn off. Leave it off for at least 5 minutes so that the mixture concentrated (Benzine HP + petrol) injectors act more aggressively, to melt even the most tenacious deposits.


Start up the engine and run it until the regime has not been regularized.

If possible at this stage perceive a scheme and irregular beats of the engine.

Application:
If fuel consumption increases.
Can be used in every service as a preventative.
In cases in which unsuitable fuel is suspected.
If E10 fuel is used:
Recommended for direct injection petrol engines

Article nr	Name	Content	Section	
T710001	Benzine HP	300ml	ADDITIVES	
T710002	Benzine HP	51	ADDITIVES	





Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



