

SEALTAP

STA

MOST VERSATILE REPAIR TAPE

- UV-resistant.
- · Permanent waterproof airtight.
- · Usable under water.
- Resist fuels, oil, acids, solvents and salt.
- Flexible up to 300%
- · Pressure resistant up to 8 bar.
- · Insulates 8.000 Volts.
- Temperature resistance from 65° C to + 260° C.



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

GENERAL INFORMATION

SEALTAPE is the most versatil repair tape for emergencies and all-purpose repairs. Just by stretching and wrapping it around an object onto itself, it will quickly and easily create a permanent airtight, waterproof seal in

just seconds! It can even be used on dirty and wet surfaces. It will remain flexible and not become brittle after being exposed to sunlight. SEALTAPE is easy to remove and leaves no residues.

TECHNICAL INFORMATION

Colour: transparent; coloured Temperature range: - 65°C to + 260°C Brittle point: - 65°C (ASTM D-2137)

Flash point: 260°C Hardness: 50 Shore A Realtive density: 1.15 Tensile strength: 700psi (ASTM D-412) Elongation at tear: 300% (ASTM D-412) Pressure resistance: 10 Bar (maximum)

Shelf life: 12 month

Safety measures: Consult the Safety Data Sheet

APPLICATION AND USE

SEALTAPE saves time and money by securing, protecting or repairing almost anything,, everwhere and in any condition.
Use it on electrical wires as shrink-tube, protect tool handles, connectors, fittings. For cable bundling and rope-end protection, anti slip coatings, safety and color-marking etc.
It is perfect for boats, cars, trucks, caravans/campers, aircrafts, agriculture industry, plumbing, military, general industry, rescue teams.

 Use: Unwind SEALTAPE and remove the plastic liner from tape.

Wrap SEALTAPE around the object by stretching and overlapping one layer. Press for good bonding. For high pressure leaks stretch to maximum (at least 300 %). The tighter the tape is wrapped, the quicker and stronger it will fuse.

Article nr	Name	Content	Section
T556101	Sealtape black	1 pc.	TAPES
T556121	Sealtape green	1 pc.	TAPES
T556201	Sealtape white	1 pc.	TAPES
T556301	Seal Tape blue	1 pc.	TAPES
T556601	Sealtape transparent	1 pc.	TAPES
T556701	Sealtape red	1 pc.	TAPES
T556801	Sealtape yellow	1 pc.	TAPES





















