

# SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878



## NOVA POWER PAINT

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** : NOVA POWER PAINT  
**Registration number REACH** : Not applicable (mixture)  
**Product type REACH** : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1 Relevant identified uses

Lacquer/varnish

##### 1.2.2 Uses advised against

No uses advised against known

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier of the safety data sheet

Novatio\*  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 25 76 40  
☎ +32 14 22 02 66  
info@novatio.be  
\*NOVATIO is a registered trademark of Novatech International N.V.

##### Manufacturer of the product

Novatech International N.V.  
Industrielaan 5B  
B-2250 Olen  
☎ +32 14 85 97 37  
☎ +32 14 85 97 38  
info@novatech.be

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :  
+32 14 58 45 45 (BIG)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.

#### 2.2. Label elements



Contains: acetone.

##### Signal word

Danger

##### H-statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

##### P-statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P280 Wear eye protection.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel

<http://www.big.be>

© BIG vzw

Reason for revision: 2.2, 3.2, 8, 15

Revision number: 0800

Publication date: 2000-05-05

Date of revision: 2022-01-28

BIG number: 32011

1 / 27

878-16239-032-en

# NOVA POWER PAINT

P304 + P340  
P410 + P412

IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

## Supplemental information

EUH066  
EUH211

Repeated exposure may cause skin dryness or cracking.  
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

## 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
acetone 01-2119471330-49	67-64-1 200-662-2	30% <C<60%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	(1)(2)(10)	Constituent	
dimethyl ether 01-2119472128-37	115-10-6 204-065-8	30% <C<60%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	
4-methylpentan-2-one 01-2119473980-30	108-10-1 203-550-1	10% <C<30%	Flam. Liq. 2; H225 Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335 EUH066	(1)(2)(10)	Constituent	ATE inhalation (vapour): 11 mg/l
2-methoxy-1-methylethyl acetate 01-2119475791-29	108-65-6 203-603-9	1%<C<5%	Flam. Liq. 3; H226	(1)(2)(10)	Constituent	
2-butoxyethanol 01-2119475108-36	111-76-2 203-905-0	1%<C<5%	Acute Tox. 4; H332 Acute Tox. 4; H312 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319	(1)(2)(10)	Constituent	ATE oral: 1200 mg/kg
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] 01-2119489379-17	13463-67-7 236-675-5	1%<C<5%	Carc. 2; H351	(1)(2)	Constituent	
methyl methacrylate 01-2119452498-28	80-62-6 201-297-1	C<1%	Flam. Liq. 2; H225 Skin Sens. 1; H317 Skin Irrit. 2; H315 STOT SE 3; H335	(1)(2)(10)	Constituent	

- (1) For H- and EUH-statements in full: see section 16  
(2) Substance with a Community workplace exposure limit  
(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

#### After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

#### After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

#### After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

#### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

##### After inhalation:

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

2 / 27

# NOVA POWER PAINT

Dizziness. Drowsiness.

**After skin contact:**

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Cracking of the skin.

**After eye contact:**

Irritation of the eye tissue.

**After ingestion:**

No effects known.

**4.2.2 Delayed symptoms**

No effects known.

**4.3. Indication of any immediate medical attention and special treatment needed**

If applicable and available it will be listed below.

## SECTION 5: Firefighting measures

**5.1. Extinguishing media**

**5.1.1 Suitable extinguishing media:**

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

**5.2. Special hazards arising from the substance or mixture**

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

**5.3. Advice for firefighters**

**5.3.1 Instructions:**

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion.

**5.3.2 Special protective equipment for fire-fighters:**

Gloves (EN 374). Protective goggles (EN 166). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

**6.1.1 Protective equipment for non-emergency personnel**

See section 8.2

**6.1.2 Protective equipment for emergency responders**

Gloves (EN 374). Protective goggles (EN 166). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

**6.2. Environmental precautions**

Contain released product. Dam up the liquid spill.

**6.3. Methods and material for containment and cleaning up**

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

**6.4. Reference to other sections**

See section 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

**7.1. Precautions for safe handling**

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Avoid prolonged and repeated contact with skin.

**7.2. Conditions for safe storage, including any incompatibilities**

**7.2.1 Safe storage requirements:**

Storage temperature: < 50 °C. Meet the legal requirements. Keep container in a well-ventilated place. Fireproof storeroom. Keep out of direct sunlight.

**7.2.2 Keep away from:**

Heat sources, ignition sources, oxidizing agents.

**7.2.3 Suitable packaging material:**

Aerosol.

**7.2.4 Non suitable packaging material:**

No data available

**7.3. Specific end use(s)**

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

3 / 27

# NOVA POWER PAINT

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

#### EU

2-Butoxyethanol	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	20 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	98 mg/m <sup>3</sup>
	Short time value (Indicative occupational exposure limit value)	50 ppm
	Short time value (Indicative occupational exposure limit value)	246 mg/m <sup>3</sup>
2-Methoxy-1-methylethylacetate	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	50 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	275 mg/m <sup>3</sup>
	Short time value (Indicative occupational exposure limit value)	100 ppm
	Short time value (Indicative occupational exposure limit value)	550 mg/m <sup>3</sup>
4-Methylpentan-2-one	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	20 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	83 mg/m <sup>3</sup>
	Short time value (Indicative occupational exposure limit value)	50 ppm
	Short time value (Indicative occupational exposure limit value)	208 mg/m <sup>3</sup>
Acetone	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	500 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1210 mg/m <sup>3</sup>
Dimethylether	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1000 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1920 mg/m <sup>3</sup>
Methyl methacrylate	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	50 ppm
	Short time value (Indicative occupational exposure limit value)	100 ppm

#### Belgium

# NOVA POWER PAINT

2-Butoxyéthanol	Time-weighted average exposure limit 8 h	20 ppm
	Time-weighted average exposure limit 8 h	98 mg/m <sup>3</sup>
	Short time value	50 ppm
	Short time value	246 mg/m <sup>3</sup>
4-Méthyl-2-pentanone	Time-weighted average exposure limit 8 h	20 ppm
	Time-weighted average exposure limit 8 h	83 mg/m <sup>3</sup>
	Short time value	50 ppm
	Short time value	208 mg/m <sup>3</sup>
Acétate de 2-(1-méthoxy)propyle	Time-weighted average exposure limit 8 h	50 ppm
	Time-weighted average exposure limit 8 h	275 mg/m <sup>3</sup>
	Short time value	100 ppm
	Short time value	550 mg/m <sup>3</sup>
Acétone <i>shall apply from 2022-01-01</i>	Time-weighted average exposure limit 8 h	246 ppm
Acétone <i>shall apply until 2021-12-31</i>	Time-weighted average exposure limit 8 h	500 ppm
	Time-weighted average exposure limit 8 h	1210 mg/m <sup>3</sup>
Acétone <i>shall apply from 2022-01-01</i>	Time-weighted average exposure limit 8 h	594 mg/m <sup>3</sup>
Acétone <i>shall apply until 2021-12-31</i>	Short time value	1000 ppm
Acétone <i>shall apply from 2022-01-01</i>	Short time value	492 ppm
	Short time value	1187 mg/m <sup>3</sup>
Acétone <i>shall apply until 2021-12-31</i>	Short time value	2420 mg/m <sup>3</sup>
Méthacrylate de méthyle	Time-weighted average exposure limit 8 h	50 ppm
	Time-weighted average exposure limit 8 h	208 mg/m <sup>3</sup>
	Short time value	100 ppm
	Short time value	416 mg/m <sup>3</sup>
Oxyde de diméthyle	Time-weighted average exposure limit 8 h	1000 ppm
	Time-weighted average exposure limit 8 h	1920 mg/m <sup>3</sup>
Titane (dioxyde de)	Time-weighted average exposure limit 8 h	10 mg/m <sup>3</sup>

## The Netherlands

1-Methoxy-2-propylacetaat	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	100 ppm
1-methoxy-2-propylacetaat	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	550 mg/m <sup>3</sup>
2-Butoxyethanol	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	20 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	100 mg/m <sup>3</sup>
	Short time value (Public occupational exposure limit value)	50 ppm
	Short time value (Public occupational exposure limit value)	246 mg/m <sup>3</sup>
4-Methyl-2-pentanon	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	25 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	104 mg/m <sup>3</sup>
	Short time value (Public occupational exposure limit value)	50 ppm
	Short time value (Public occupational exposure limit value)	208 mg/m <sup>3</sup>
Aceton	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	500 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	1210 mg/m <sup>3</sup>
	Short time value (Public occupational exposure limit value)	1002 ppm
	Short time value (Public occupational exposure limit value)	2420 mg/m <sup>3</sup>
Dimethylether	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	496 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	950 mg/m <sup>3</sup>
	Short time value (Public occupational exposure limit value)	783 ppm
	Short time value (Public occupational exposure limit value)	1500 mg/m <sup>3</sup>
Methylmethacrylaat	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	49.2 ppm

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

5 / 27

# NOVA POWER PAINT

Methylmethacrylaat	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	205 mg/m <sup>3</sup>
	Short time value (Public occupational exposure limit value)	98.5 ppm
	Short time value (Public occupational exposure limit value)	410 mg/m <sup>3</sup>

## France

2-Butoxyéthanol	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	10 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	49 mg/m <sup>3</sup>
	Short time value (VRC: Valeur réglementaire contraignante)	50 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	246 mg/m <sup>3</sup>
Acétate de 2-méthoxy-1-méthyléthyle	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	50 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	275 mg/m <sup>3</sup>
	Short time value (VRC: Valeur réglementaire contraignante)	100 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	550 mg/m <sup>3</sup>
Acétone	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	500 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	1210 mg/m <sup>3</sup>
	Short time value (VRC: Valeur réglementaire contraignante)	1000 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	2420 mg/m <sup>3</sup>
Méthacrylate de méthyle	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	50 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	205 mg/m <sup>3</sup>
	Short time value (VRC: Valeur réglementaire contraignante)	100 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	410 mg/m <sup>3</sup>
Méthylisobutylcétone	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	20 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	83 mg/m <sup>3</sup>
	Short time value (VRC: Valeur réglementaire contraignante)	50 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	208 mg/m <sup>3</sup>
Oxyde de diméthyle	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1000 ppm
	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1920 mg/m <sup>3</sup>
Titane (dioxyde de), en Ti	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	10 mg/m <sup>3</sup>

## Germany

2-Butoxyethanol	Time-weighted average exposure limit 8 h (TRGS 900)	10 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	49 mg/m <sup>3</sup>
2-Methoxy-1-methylethylacetat	Time-weighted average exposure limit 8 h (TRGS 900)	50 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	270 mg/m <sup>3</sup>
4-Methylpentan-2-on	Time-weighted average exposure limit 8 h (TRGS 900)	20 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	83 mg/m <sup>3</sup>
Aceton	Time-weighted average exposure limit 8 h (TRGS 900)	500 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1200 mg/m <sup>3</sup>
Dimethylether	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1900 mg/m <sup>3</sup>
Methyl-methacrylat	Time-weighted average exposure limit 8 h (TRGS 900)	50 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	210 mg/m <sup>3</sup>

## Austria

1-Methoxypropylacetat-2	Tagesmittelwert (MAK)	50 ppm
	Tagesmittelwert (MAK)	275 mg/m <sup>3</sup>
	Kurzzeitwert 5(Mow) 8x (MAK)	100 ppm
	Kurzzeitwert 5(Mow) 8x (MAK)	550 mg/m <sup>3</sup>
2-Butoxyethanol	Tagesmittelwert (MAK)	20 ppm
	Tagesmittelwert (MAK)	98 mg/m <sup>3</sup>
	Kurzzeitwert 30(Miw) 4x (MAK)	40 ppm
	Kurzzeitwert 30(Miw) 4x (MAK)	200 mg/m <sup>3</sup>
4-Methylpentanon-2	Tagesmittelwert (MAK)	20 ppm
	Tagesmittelwert (MAK)	83 mg/m <sup>3</sup>
	Kurzzeitwert 15(Miw) 4x (MAK)	50 ppm

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

# NOVA POWER PAINT

4-Methylpentanon-2	Kurzzeitwert 15(Miw) 4x (MAK)	208 mg/m <sup>3</sup>
Aceton	Tagesmittelwert (MAK)	500 ppm
	Tagesmittelwert (MAK)	1200 mg/m <sup>3</sup>
	Kurzzeitwert 15(Miw) 4x (MAK)	2000 ppm
	Kurzzeitwert 15(Miw) 4x (MAK)	4800 mg/m <sup>3</sup>
Dimethylether	Tagesmittelwert (MAK)	1000 ppm
	Tagesmittelwert (MAK)	1910 mg/m <sup>3</sup>
	Kurzzeitwert 60(Mow) 3x (MAK)	2000 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3820 mg/m <sup>3</sup>
Methylmethacrylat	Tagesmittelwert (MAK)	50 ppm
	Tagesmittelwert (MAK)	210 mg/m <sup>3</sup>
	Kurzzeitwert 5(Mow) 8x (MAK)	100 ppm
	Kurzzeitwert 5(Mow) 8x (MAK)	420 mg/m <sup>3</sup>
Titandioxid (Alveolarstaub)	Tagesmittelwert (MAK)	5 mg/m <sup>3</sup>
	Kurzzeitwert 60(Miw) 2x (MAK)	10 mg/m <sup>3</sup>

## UK

1-Methoxypropyl acetate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	50 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	274 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	100 ppm
	Short time value (Workplace exposure limit (EH40/2005))	548 mg/m <sup>3</sup>
2-Butoxyethanol	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	25 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	123 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	50 ppm
	Short time value (Workplace exposure limit (EH40/2005))	246 mg/m <sup>3</sup>
4-Methylpentan-2-one	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	50 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	208 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	100 ppm
	Short time value (Workplace exposure limit (EH40/2005))	416 mg/m <sup>3</sup>
Acetone	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	500 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1210 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	1500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	3620 mg/m <sup>3</sup>
Dimethyl ether	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	766 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	958 mg/m <sup>3</sup>
Methyl methacrylate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	50 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	208 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	100 ppm
	Short time value (Workplace exposure limit (EH40/2005))	416 mg/m <sup>3</sup>
Titanium dioxide respirable	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	4 mg/m <sup>3</sup>
Titanium dioxide total inhalable	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	10 mg/m <sup>3</sup>

## USA (TLV-ACGIH)

2-Butoxyethanol	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	20 ppm
Acetone	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	250 ppm
	Short time value (TLV - Adopted Value)	500 ppm
Methyl isobutyl ketone	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	20 ppm
	Short time value (TLV - Adopted Value)	75 ppm
Methyl methacrylate	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	50 ppm
	Short time value (TLV - Adopted Value)	100 ppm
Titanium dioxide	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	10 mg/m <sup>3</sup>

## b) National biological limit values

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

7 / 27

# NOVA POWER PAINT

If limit values are applicable and available these will be listed below.

## Germany

2-Butoxyethanol (Butoxyessigsäure (nach Hydrolyse))	Urin: expositionsende, bzw. schichtende bei langzeitexposition: nach mehreren vorangegangenen schichten	150 mg/g Kreatinin	
4-Methylpentan-2-on (4-Methylpentan-2-on)	Urin: expositionsende, bzw. schichtende	0,7 mg/l	
Aceton (Aceton)	Urin: expositionsende, bzw. schichtende	80 mg/l	

## UK

2-Butoxyethanol (butoxyacetic acid)	Urine: post shift	240 mmol/mol creatinine	
4-methylpentan-2-one (4-methylpentan-2-one)	Urine: post shift	20 µmol/L	

## USA (BEI-ACGIH)

2-butoxyethanol (Butoxyacetic acid (BAA))	urine: end of shift	200 mg/g creatinine	With hydrolysis
Acetone (Acetone)	Urine: end of shift	25 mg/L	Nonspecific
Methyl isobutyl ketone (Methyl isobutyl ketone)	urine: end of shift	1 mg/L	

### 8.1.2 Sampling methods

Product name	Test	Number
1-Methoxy-2-Propyl Acetate	OSHA	99
2-Butoxyethanol (Alcohols IV)	NIOSH	1403
2-Butoxyethanol (Butyl Cellosolve solvent)	OSHA	83
Acetone (ketones 1)	NIOSH	1300
Acetone (ketones I)	NIOSH	2555
Acetone (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
Acetone (Volatile Organic compounds)	NIOSH	2549
ACETONE and METHYL ETHYL KETONE in urine	NIOSH	8319
Acetone	OSHA	69
Butoxyacetic acid	NIOSH	8316
Butyl cellosolve (Volatile Organic compounds)	NIOSH	2549
Butyl Cellosolve	OSHA	83
Hexone	OSHA	1004
Methyl ester of methacrylic acid	NIOSH	2537
Methyl Isobutyl Ketone (Hexone) (Ketones I)	NIOSH	1300
Methyl Isobutyl Ketone (ketones I)	NIOSH	2555
Methyl isobutyl ketone (Volatile Organic compounds)	NIOSH	2549
Methyl Methacrylate	NIOSH	2537
Methyl Methacrylate	NON	36
Methyl Methacrylate	OSHA	94
Propylene glycol monomethyl ether acetate (glycol ethers)	NIOSH	2554
TiO2	NIOSH	7302
TiO2	NIOSH	7304

### 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

### 8.1.4 Threshold values

#### DNEL/DMEL - Workers

##### acetone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	1210 mg/m <sup>3</sup>	
	Acute local effects inhalation	2420 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	186 mg/kg bw/day	

##### 4-methylpentan-2-one

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	83 mg/m <sup>3</sup>	
	Acute systemic effects inhalation	208 mg/m <sup>3</sup>	
	Long-term local effects inhalation	83 mg/m <sup>3</sup>	
	Acute local effects inhalation	208 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	11.8 mg/kg bw/day	

##### 2-methoxy-1-methylethyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	275 mg/m <sup>3</sup>	
	Acute local effects inhalation	550 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	796 mg/kg bw	

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

8 / 27

# NOVA POWER PAINT

## 2-butoxyethanol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	98 mg/m <sup>3</sup>	
	Acute systemic effects inhalation	1091 mg/m <sup>3</sup>	
	Acute local effects inhalation	246 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	125 mg/kg bw/day	
	Acute systemic effects dermal	89 mg/kg bw/day	

## methyl methacrylate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	348.4 mg/m <sup>3</sup>	
	Long-term local effects inhalation	208 mg/m <sup>3</sup>	
	Acute local effects inhalation	146 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	13.67 mg/kg bw/day	
	Long-term local effects dermal	1.5 mg/cm <sup>2</sup>	
	Acute local effects dermal	1.5 mg/cm <sup>2</sup>	

## DNEL/DMEL - General population

### acetone

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	200 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	62 mg/kg bw/day	
	Long-term systemic effects oral	62 mg/kg bw/day	

### 4-methylpentan-2-one

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	14.7 mg/m <sup>3</sup>	
	Acute systemic effects inhalation	155.2 mg/m <sup>3</sup>	
	Long-term local effects inhalation	14.7 mg/m <sup>3</sup>	
	Acute local effects inhalation	155.2 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	4.2 mg/kg bw/day	
	Long-term systemic effects oral	4.2 mg/kg bw/day	

### 2-methoxy-1-methylethyl acetate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	33 mg/m <sup>3</sup>	
	Long-term local effects inhalation	33 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	320 mg/kg bw	
	Long-term systemic effects oral	36 mg/kg bw	
	Acute systemic effects oral	500 mg/kg bw/day	

## 2-butoxyethanol

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	59 mg/m <sup>3</sup>	
	Acute systemic effects inhalation	426 mg/m <sup>3</sup>	
	Acute local effects inhalation	147 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	75 mg/kg bw/day	
	Acute systemic effects dermal	89 mg/kg bw/day	
	Long-term systemic effects oral	6.3 mg/kg bw/day	
	Acute systemic effects oral	26.7 mg/kg bw/day	

## methyl methacrylate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	74.3 mg/m <sup>3</sup>	
	Long-term local effects inhalation	104 mg/m <sup>3</sup>	
	Acute local effects inhalation	208 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	8.2 mg/kg bw/day	
	Long-term local effects dermal	1.5 mg/cm <sup>2</sup>	
	Acute local effects dermal	1.5 mg/cm <sup>2</sup>	
	Long-term systemic effects oral	8.2 mg/kg bw/day	

## PNEC

### acetone

Compartments	Value	Remark
Fresh water	10.6 mg/l	
Marine water	1.06 mg/l	
Fresh water (intermittent releases)	21 mg/l	
STP	100 mg/l	
Fresh water sediment	30.4 mg/kg sediment dw	
Marine water sediment	3.04 mg/kg sediment dw	
Soil	29.5 mg/kg soil dw	

# NOVA POWER PAINT

## 4-methylpentan-2-one

Compartments	Value	Remark
Fresh water	0.6 mg/l	
Marine water	0.06 mg/l	
Fresh water (intermittent releases)	1.5 mg/l	
STP	27.5 mg/l	
Fresh water sediment	8.27 mg/kg sediment dw	
Marine water sediment	0.83 mg/kg sediment dw	
Soil	1.3 mg/kg soil dw	

## 2-methoxy-1-methylethyl acetate

Compartments	Value	Remark
Fresh water	0.635 mg/l	
Marine water	0.064 mg/l	
Fresh water (intermittent releases)	6.35 mg/l	
STP	100 mg/l	
Fresh water sediment	3.29 mg/kg sediment dw	
Marine water sediment	0.329 mg/kg sediment dw	
Soil	0.29 mg/kg soil dw	

## 2-butoxyethanol

Compartments	Value	Remark
Fresh water	8.8 mg/l	
Marine water	0.88 mg/l	
Fresh water (intermittent releases)	26.4 mg/l	
STP	463 mg/l	
Fresh water sediment	34.6 mg/kg sediment dw	
Marine water sediment	3.46 mg/kg sediment dw	
Soil	2.33 mg/kg soil dw	
Oral	20 mg/kg food	

## methyl methacrylate

Compartments	Value	Remark
Fresh water	0.94 mg/l	
Fresh water (intermittent releases)	0.94 mg/l	
Marine water	0.94 mg/l	
STP	10 mg/l	
Fresh water sediment	5.74 mg/kg sediment dw	
Soil	1.47 mg/kg soil dw	

### 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

### 8.2.2 Individual protection measures, such as personal protective equipment

Avoid prolonged and repeated contact with skin. Do not eat, drink or smoke during work.

#### a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

#### b) Hand protection:

Protective gloves against chemicals (EN 374).

#### c) Eye protection:

Protective goggles (EN 166).

#### d) Skin protection:

Protective clothing (EN 14605 or EN 13034). Head/neck protection.

### 8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Solvent-like odour
Odour threshold	No data available in the literature
Colour	Variable in colour, depending on the composition
Particle size	Not applicable (aerosol)
Explosion limits	3.3 - 26.2 vol % ; Propellant
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	Not applicable (aerosol)

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

10 / 27

# NOVA POWER PAINT

Kinematic viscosity	Not applicable (aerosol)
Melting point	No data available in the literature
Boiling point	No data available in the literature
Relative vapour density	> 1
Vapour pressure	5133 hPa ; Propellant
Solubility	Water ; No data available in the literature
Relative density	No data available in the literature
Absolute density	No data available in the literature
Decomposition temperature	No data available in the literature
Auto-ignition temperature	Not applicable (aerosol)
Flash point	Not applicable (aerosol)
pH	Not applicable (aerosol)

## 9.2. Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

#### Precautionary measures

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

### 10.5. Incompatible materials

Oxidizing agents.

### 10.6. Hazardous decomposition products

Upon combustion: CO and CO<sub>2</sub> are formed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### 11.1.1 Test results

#### Acute toxicity

##### NOVA POWER PAINT

No (test) data on the mixture available

Judgement is based on the relevant ingredients

##### acetone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		5800 mg/kg		Rat (female)	Experimental value	
Dermal	LD50		> 15800 mg/kg bw	24 h	Rabbit (male)	Experimental value	
Inhalation (vapours)	LC50		76 mg/l	4 h	Rat (female)	Weight of evidence	
					(male)		

##### 4-methylpentan-2-one

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	2080 mg/kg		Rat	Experimental value	
Dermal	LD50	OECD 402	≥ 2000 mg/kg bw	24 h	Rat (male / female)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	11.6 mg/l	4 h	Rat (male)	Experimental value	

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

11 / 27

# NOVA POWER PAINT

## 2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	6190 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 5000 mg/kg bw	24 h	Rabbit (male / female)	Experimental value	
Inhalation	LC0	Equivalent to OECD 403	10.8 mg/l	3 h	Rat (male)	Experimental value	

## 2-butoxyethanol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	1746 mg/kg bw		Rat (male)	Experimental value	
Dermal			category 4			Annex VI	
Dermal	LD50	OECD 402	> 2000 mg/kg bw		Rat (male / female)	Experimental value	
Inhalation (vapours)	LC50		> 4.26 mg/l	4 h	Rat (male / female)	Experimental value	

## titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	> 2000 mg/kg bw		Rat (male / female)	Experimental value	
Dermal						Data waiving	
Inhalation (dust)	LC50	OECD 403	> 5.09 mg/l	4 h	Rat (male)	Experimental value	

## methyl methacrylate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		9400 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 5000 mg/kg bw	24 h	Rabbit (male)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	29.8 mg/l air	4 h	Rat (male / female)	Experimental value	

### Conclusion

Not classified for acute toxicity

### Corrosion/irritation

#### NOVA POWER PAINT

No (test) data on the mixture available

Classification is based on the relevant ingredients

#### acetone

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	OECD 405	24 h	24; 72 hours	Rabbit	Experimental value	Single treatment with rinsing
Skin	Not irritating		3 day(s)	24; 48; 72 hrs; 4 days	Guinea pig	Weight of evidence	
Inhalation	Slightly irritating	Human observation study	20 minutes		Human	Literature study	

#### 4-methylpentan-2-one

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Slightly irritating	OECD 405		24; 48; 72 hours	Rabbit	Experimental value	Single treatment without rinsing
Eye	Irritating; category 2					Annex VI	
Skin	Not irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	
Inhalation (vapours)	Irritating	Human observation	15 minutes		Human	Experimental value	
Inhalation (vapours)	Irritating; STOT SE cat.3					Annex VI	

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

12 / 27

# NOVA POWER PAINT

## 2-methoxy-1-methylethyl acetate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Experimental value	Single treatment
Skin	Not irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

## 2-butoxyethanol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating	OECD 405	24 h	24; 48; 72 hours	Rabbit	Experimental value	Single treatment with rinsing
Skin	Irritating	EU Method B.4	4 h	24; 48; 72 hours	Rabbit	Experimental value	

## titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	OECD 405		1; 24; 48; 72 hours	Rabbit	Experimental value	
Skin	Not irritating	Equivalent to OECD 404	4 h	48 hours	Rabbit	Experimental value	

## methyl methacrylate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating			24; 48; 72 hours	Rabbit	Experimental value	Single treatment without rinsing
Skin	Irritating		4 h	24; 72 hours	Rabbit	Experimental value	
Inhalation	Irritating; STOT SE cat.3					Annex VI	

### Conclusion

Causes serious eye irritation.

Not classified as irritating to the skin

Not classified as irritating to the respiratory system

### Respiratory or skin sensitisation

#### NOVA POWER PAINT

No (test) data on the mixture available

Judgement is based on the relevant ingredients

#### acetone

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Guinea pig maximisation test			Guinea pig (female)	Experimental value	
Skin	Not sensitizing	Human observation			Human	Experimental value	

#### 4-methylpentan-2-one

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (female)	Experimental value	

#### 2-methoxy-1-methylethyl acetate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406			Guinea pig (male / female)	Experimental value	

#### 2-butoxyethanol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (male / female)	Experimental value	

#### titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 429			Mouse (female)	Experimental value	
Inhalation (dust)	Not sensitizing				Mouse (female)	Experimental value	

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

13 / 27

# NOVA POWER PAINT

## methyl methacrylate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Dermal (on the ears)	Sensitizing	Equivalent to OECD 429			Mouse	Experimental value	

### Conclusion

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

### Specific target organ toxicity

#### NOVA POWER PAINT

No (test) data on the mixture available

Classification is based on the relevant ingredients

#### acetone

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (drinking water)	NOAEL	Equivalent to OECD 408	4.86 mg/kg bw/day - 5.95 mg/kg bw/day		No effect	13 week(s)	Mouse (male / female)	Experimental value
Oral (drinking water)	LOAEL	Equivalent to OECD 408	11.3 mg/kg bw/day	Liver	Histopathology		Mouse (female)	Experimental value
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Subchronic toxicity test	19000 ppm		No effect	8 weeks (5 days / week)	Rat (male)	Experimental value
Inhalation (vapours)	Dose level	Human observation study	361 ppm	Central nervous system	neurotoxic effects	2 day(s)	Human	Epidemiological study

#### 4-methylpentan-2-one

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	Equivalent to OECD 408	250 mg/kg bw/day	Kidney	No effect	90 day(s)	Rat (male / female)	Experimental value
Oral (stomach tube)	NOEL	Equivalent to OECD 408	50 mg/kg bw/day		No effect	90 day(s)	Rat (male / female)	Experimental value
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	1840 mg/m <sup>3</sup>	Kidney	No effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value

#### 2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	OECD 422	≥ 1000 mg/kg		No effect	41 day(s) - 45 day(s)	Rat (male / female)	Experimental value
Oral (stomach tube)	Dose level	US EPA	500 mg/kg bw/day		Drowsiness, dizziness		Rat (male / female)	Experimental value
Dermal	NOAEL	Equivalent to OECD 411	1838 mg/kg bw/day		No effect	13 weeks (5 days / week)	Rabbit (male)	Read-across
Dermal	LOAEL	Equivalent to OECD 411	3676 mg/kg bw/day		Overall effects	13 weeks (6h / day, 5 days / week)	Rabbit (male)	Read-across
Inhalation (vapours)	NOEL	OECD 453	300 ppm		No effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across

#### 2-butoxyethanol

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (drinking water)	NOAEL	Equivalent to OECD 408	< 69 mg/kg bw/day		No effect	90 days (continuous)	Rat (male)	Experimental value
Oral (drinking water)	NOAEL	Equivalent to OECD 408	< 82 mg/kg bw/day		No effect	90 day(s)	Rat (female)	Experimental value
Dermal	NOAEL	Equivalent to OECD 411	> 150 mg/kg bw/day		No effect	13 weeks (5 days / week)	Rabbit (male / female)	Experimental value
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	< 31 ppm		No effect	14 weeks (6h / day, 5 days / week)	Rat (female)	Experimental value
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	62.5 ppm		No effect	14 weeks (6h / day, 5 days / week)	Rat (male)	Experimental value

#### titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	OECD 408	> 1000 mg/kg bw/day		No effect	90 day(s)	Rat (male / female)	Experimental value
Dermal								Data waiving

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

14 / 27

# NOVA POWER PAINT

## methyl methacrylate

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (drinking water)	NOAEL		≥ 124.1 mg/kg bw/day		No effect	104 week(s)	Rat (male)	Experimental value
Oral (drinking water)	NOAEL		≥ 164 mg/kg bw/day		No effect	104 week(s)	Rat (female)	Experimental value
Inhalation (vapours)	NOAEC systemic effects	Equivalent to OECD 453	1640 mg/m <sup>3</sup> air		No adverse systemic effects	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation (vapours)	LOAEC local effects	Equivalent to OECD 453	416 mg/m <sup>3</sup> air	Nose	Affection of the nasal septum	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation (vapours)	NOAEC local effects	Equivalent to OECD 453	104 mg/m <sup>3</sup> air	Nose	No effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value

### **Conclusion**

May cause drowsiness or dizziness.  
Not classified for subchronic toxicity

### **Mutagenicity (in vitro)**

#### NOVA POWER PAINT

No (test) data on the mixture available  
Judgement is based on the relevant ingredients  
acetone

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	

#### 4-methylpentan-2-one

Result	Method	Test substrate	Effect	Value determination	Remark
Ambiguous	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)		Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value	

#### 2-methoxy-1-methylethyl acetate

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative without metabolic activation	Equivalent to OECD 482	Rat liver cells	No effect	Experimental value	

#### 2-butoxyethanol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)		Experimental value	

#### titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 473	Chinese hamster ovary (CHO)		Experimental value	
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S.typhimurium)		Experimental value	

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

15 / 27

# NOVA POWER PAINT

## methyl methacrylate

Result	Method	Test substrate	Effect	Value determination	Remark
Ambiguous	Equivalent to OECD 473	Chinese hamster ovary (CHO)		Experimental value	
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Literature study	

## Mutagenicity (in vivo)

### NOVA POWER PAINT

No (test) data on the mixture available

Judgement is based on the relevant ingredients

#### acetone

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Oral (drinking water))	Micronucleus test	13 week(s)	Mouse (male / female)		Literature study

#### 2-butoxyethanol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Intraperitoneal)	Equivalent to OECD 474	3 dose(s)/24-hour interval	Mouse (male)		Experimental value

#### titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Oral (stomach tube))	OECD 474		Mouse (male / female)		Experimental value

#### methyl methacrylate

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Inhalation (vapours))	Equivalent to OECD 478	5 days (6h / day)	Mouse (male)		Experimental value

## Conclusion

Not classified for mutagenic or genotoxic toxicity

## Carcinogenicity

### NOVA POWER PAINT

No (test) data on the mixture available

The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.

#### acetone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Dermal	NOEL	Carcinogenic toxicity study	79 mg	51 weeks (3 times / week)	Mouse (female)	No carcinogenic effect		Literature study

#### 2-methoxy-1-methylethyl acetate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOEL	OECD 453	3000 ppm	104 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect		Read-across

#### 2-butoxyethanol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	> 125 ppm	104 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect		Experimental value

#### titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (aerosol)		Equivalent to OECD 453		105 weeks (6h / day, 5 days / week)	Rat (male)	Lung tissue affection/degeneration	Lungs	Experimental value
Inhalation (aerosol)	NOAEC	Equivalent to OECD 453	5 mg/m <sup>3</sup> air	104 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect	Lungs	Experimental value
Oral (diet)	NOEL	Carcinogenic toxicity study	50000 ppm	103 weeks (7 days / week)	Rat (male / female)	No carcinogenic effect		Experimental value

#### methyl methacrylate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	≥ 2.05 mg/l air	102 weeks (6h / day, 5 days / week)	Rat (male / female)	No carcinogenic effect		Experimental value
Oral (drinking water)	NOAEL	Carcinogenic toxicity study	≥ 90.3 mg/kg bw/day	104 weeks (daily)	Rat (male)	No carcinogenic effect		Experimental value
Oral (drinking water)	NOAEL	Carcinogenic toxicity study	≥ 193.8 mg/kg bw/day	104 weeks (daily)	Rat (female)	No carcinogenic effect		Experimental value

## Conclusion

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

16 / 27

# NOVA POWER PAINT

Not classified for carcinogenicity

## Reproductive toxicity

### NOVA POWER PAINT

No (test) data on the mixture available

Judgement is based on the relevant ingredients  
acetone

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (aerosol))	NOAEC	Equivalent to OECD 414	2200 ppm	14 days (gestation, daily)	Rat	No effect	Foetus	Experimental value
	LOAEC	Equivalent to OECD 414	11000 mg/kg bw/day	14 days (gestation, daily)	Rat	Fetotoxicity	Foetus	Experimental value
Maternal toxicity (Inhalation (aerosol))	NOAEC	Equivalent to OECD 414	2200 ppm	14 days (gestation, daily)	Rat	No effect		Experimental value
	LOAEC	Equivalent to OECD 414	11000 ppm	14 days (gestation, daily)	Rat	Maternal toxicity		Experimental value
Effects on fertility (Oral (drinking water))	NOAEL		900 mg/kg bw/day	13 week(s)	Rat (male)	No effect		Experimental value
	LOAEL		3400 mg/kg bw/day	13 week(s)	Rat (male)	Adverse effects on fertility	Male reproductive organ	Experimental value

### 4-methylpentan-2-one

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEL	Equivalent to OECD 414	1000 ppm	10 days (6h / day)	Rat	No effect	Foetus	Experimental value
Maternal toxicity (Inhalation (vapours))	NOAEL	Equivalent to OECD 414	1000 ppm	10 days (6h / day)	Rat	No effect		Experimental value
Effects on fertility (Inhalation (vapours))	NOAEL	Equivalent to OECD 416	2000 ppm	20 days (6h / day) - 91 days (6h / day)	Rat (male / female)	No effect		Experimental value

### 2-methoxy-1-methylethyl acetate

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation)	NOAEL	Equivalent to OECD 414	> 4000 ppm	10 days (gestation, daily)	Rat	No effect	Foetus	Experimental value
Developmental toxicity (Inhalation (vapours))								
Maternal toxicity (Inhalation (vapours))	NOAEL	Equivalent to OECD 414	500 ppm	10 days (gestation, daily)	Rat	No effect		Experimental value
	LOAEL	Equivalent to OECD 414	2000 ppm	10 days (gestation, daily)	Rat	Maternal toxicity		Experimental value
Effects on fertility (Inhalation (vapours))	NOAEL	OECD 416	300 ppm		Rat (male / female)	No effect		Read-across

### 2-butoxyethanol

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEC	Equivalent to OECD 414	200 mg/kg bw/day	3 days (gestation, daily)	Rat	No effect		Experimental value
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	30 mg/kg bw/day	3 days (gestation, daily)	Rat	No effect		Experimental value
Effects on fertility (Oral (drinking water))	NOAEL	Fertility Assessment	720 mg/kg bw/day	14 weeks (daily)	Mouse (male / female)	No effect		Experimental value

### titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL	OECD 414	1000 mg/kg bw/day	2 weeks (7 days / week)	Rat	No effect		Experimental value
Maternal toxicity (Oral (stomach tube))	NOAEL	OECD 414	1000 mg/kg bw/day	2 weeks (7 days / week)	Rat	No effect		Experimental value
Effects on fertility (Oral (diet))	NOAEL	OECD 443	≥ 1000 mg/kg bw/day	14 day(s)	Rat (male / female)	No effect		Experimental value

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

17 / 27

# NOVA POWER PAINT

## methyl methacrylate

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEC	OECD 414	8.44 mg/l air	10 days (6h / day)	Rat	No effect	Foetus	Experimental value
Maternal toxicity (Inhalation (vapours))	NOAEC	OECD 414	8.44 mg/l air	10 days (6h / day)	Rat	No effect		Experimental value
Effects on fertility (Oral (stomach tube))	NOAEL	OECD 416	400 mg/kg bw/day		Rat (male / female)	No effect		Experimental value

### Conclusion

Not classified for reprotoxic or developmental toxicity

### Toxicity other effects

#### NOVA POWER PAINT

Classification is based on the relevant ingredients

#### acetone

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Skin				Skin	Skin dryness or cracking			Literature study

### Conclusion

Repeated exposure may cause skin dryness or cracking.

### Chronic effects from short and long-term exposure

#### NOVA POWER PAINT

No effects known.

### 11.2. Information on other hazards

No evidence of endocrine disrupting properties

## SECTION 12: Ecological information

### 12.1. Toxicity

#### NOVA POWER PAINT

No (test) data on the mixture available

Judgement of the mixture is based on the relevant ingredients

#### acetone

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	6210 mg/l - 8120 mg/l	96 h	Pimephales promelas	Flow-through system	Fresh water	Experimental value; Measured concentration
Acute toxicity crustacea	LC50		8800 mg/l	48 h	Daphnia pulex	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	NOEC		530 mg/l		Algae		Fresh water	
Long-term toxicity aquatic crustacea	NOEC	Equivalent to OECD 211	2212 mg/l	28 day(s)	Daphnia magna	Flow-through system	Fresh water	Experimental value
Toxicity aquatic micro-organisms	EC50	Equivalent to OECD 209	61.15 g/l	30 minutes	Activated sludge	Static system	Fresh water	Experimental value

#### 4-methylpentan-2-one

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	> 179 mg/l	96 h	Danio rerio	Static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EC50	OECD 202	> 200 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Lethal
Toxicity algae and other aquatic plants	Toxicity threshold		725 mg/l	8 day(s)	Scenedesmus quadricauda	Static system	Fresh water	No reliable data available; Growth inhibition
Long-term toxicity aquatic crustacea	NOEC	Equivalent to OECD 211	78 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro-organisms	Toxicity threshold	Equivalent to DIN 38412/8	275 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Growth inhibition

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

18 / 27

# NOVA POWER PAINT

## 2-methoxy-1-methylethyl acetate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	100 mg/l - 180 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	EU Method C.2	> 500 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	> 1000 mg/l	96 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
	NOEC	OECD 201	≥ 1000 mg/l	96 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOEC	OECD 204	47.5 mg/l	14 day(s)	Oryzias latipes	Flow-through system	Fresh water	Experimental value; Behaviour
Long-term toxicity aquatic crustacea	NOEC	OECD 211	≥ 100 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro-organisms	EC10	Equivalent to OECD 209	> 1000 mg/l	30 minutes	Activated sludge	Static system	Fresh water	Experimental value; Respiration

## 2-butoxyethanol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	1474 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	EC50	OECD 202	1550 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	1840 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
	NOEC	OECD 201	286 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOEC	Equivalent to OECD 204	> 100 mg/l	21 day(s)	Danio rerio	Semi-static system	Fresh water	Experimental value; Nominal concentration
Long-term toxicity aquatic crustacea	NOEC	OECD 211	100 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro-organisms	Toxicity threshold	Equivalent to DIN 38412/8	700 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Nominal concentration

## titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		> 1000 mg/l		Pisces		Fresh water	
Acute toxicity crustacea	EC50		> 1000 mg/l		Invertebrata		Fresh water	
Toxicity algae and other aquatic plants	EC50	OECD 201	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
	NOEC	OECD 201	≥ 100 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate

## methyl methacrylate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		> 100 mg/l		Pisces			Literature study
Acute toxicity crustacea	EC50	EPA OTS 797.1300	69 mg/l	48 h	Daphnia magna	Flow-through system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	EC50	OECD 201	> 110 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
	NOEC	OECD 201	110 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity aquatic crustacea	NOEC	OECD 211	37 mg/l	21 day(s)	Daphnia magna	Flow-through system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro-organisms	Dose level	OECD 301C	100 mg/l	14 day(s)	Activated sludge	Static system	Fresh water	Experimental value
	EC50		> 178 mg/l	48 h	Chilomas sp.			Literature study

### Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

19 / 27

# NOVA POWER PAINT

## 12.2. Persistence and degradability

acetone

### Biodegradation water

Method	Value	Duration	Value determination
OECD 301B	90.9 %	28 day(s)	Experimental value

4-methylpentan-2-one

### Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	83 %; Oxygen consumption	28 day(s)	Experimental value

### Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	14.480 h	1.5E6 /cm <sup>3</sup>	Calculated value

2-methoxy-1-methylethyl acetate

### Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	83 %; Oxygen consumption	28 day(s)	Experimental value

### Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	10.818 h	1.5E6 /cm <sup>3</sup>	Calculated value

### Biodegradation soil

Method	Value	Duration	Value determination
Equivalent to OECD 304A	> 57 %; GLP	1 day(s)	Experimental value

2-butoxyethanol

### Biodegradation water

Method	Value	Duration	Value determination
OECD 301B	90.4 %; Carbon dioxide	28 day(s)	Experimental value

### Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.90	5.459 h	1.5E6 /cm <sup>3</sup>	QSAR

methyl methacrylate

### Biodegradation water

Method	Value	Duration	Value determination
OECD 301C	94 %; Oxygen consumption	14 day(s)	Experimental value

### Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	6.997 h	1.5E6 /cm <sup>3</sup>	QSAR

### Half-life water (t1/2 water)

Method	Value	Primary degradation/mineralisation	Value determination
	53 month(s); pH = 7		Experimental value

## Conclusion

### Water

Contains non readily biodegradable component(s)

## 12.3. Bioaccumulative potential

NOVA POWER PAINT

### Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

acetone

### Log Kow

Method	Remark	Value	Temperature	Value determination
		-0.23		Test data

4-methylpentan-2-one

### Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 117		1.9	20 °C	Experimental value

2-methoxy-1-methylethyl acetate

### Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 117		1.2	20 °C	Experimental value

# NOVA POWER PAINT

## 2-butoxyethanol

### BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
					Data waiving

### Log Kow

Method	Remark	Value	Temperature	Value determination
BASF test		0.81	25 °C	Experimental value

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

### Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

## methyl methacrylate

### Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 107		1.38	20 °C	Experimental value

### Conclusion

Does not contain bioaccumulative component(s)

## 12.4. Mobility in soil

### acetone

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.374 - 0.988	Calculated value

### 4-methylpentan-2-one

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc		2.008	Weight of evidence

### 2-methoxy-1-methylethyl acetate

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.602 - 1.079	Calculated value

#### Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	10.22 %	0 %	0.02 %	0.03 %	89.73 %	Calculated value

## 2-butoxyethanol

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.451 - 0.882	Calculated value

#### Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level I	0.31 %	0 %	0.01 %	0.59 %	99.09 %	QSAR

## methyl methacrylate

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc	EPA OTS 796.2750	0.94 - 1.86	Experimental value

### Conclusion

Contains component(s) with potential for mobility in the soil

Contains component(s) that adsorb(s) into the soil

## 12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

## 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

## 12.7. Other adverse effects

### NOVA POWER PAINT

#### Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

#### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

### acetone

#### Groundwater

Groundwater pollutant

# NOVA POWER PAINT

4-methylpentan-2-one

**Groundwater**

Groundwater pollutant

2-methoxy-1-methylethyl acetate

**Groundwater**

Groundwater pollutant

2-butoxyethanol

**Groundwater**

Groundwater pollutant

methyl methacrylate

**Groundwater**

Groundwater pollutant

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

##### European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 01 11\* (wastes from MFSU and removal of paint and varnish: waste paint and varnish containing organic solvents or other hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste.

Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

#### 13.1.3 Packaging/Container

##### European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

## SECTION 14: Transport information

### Road (ADR)

#### 14.1. UN number

UN number	1950
-----------	------

#### 14.2. UN proper shipping name

Proper shipping name	aerosols
----------------------	----------

#### 14.3. Transport hazard class(es)

Hazard identification number	
Class	2
Classification code	5F

#### 14.4. Packing group

Packing group	
Labels	2.1

#### 14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

#### 14.6. Special precautions for user

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

### Rail (RID)

#### 14.1. UN number

UN number	1950
-----------	------

#### 14.2. UN proper shipping name

Proper shipping name	aerosols
----------------------	----------

#### 14.3. Transport hazard class(es)

Hazard identification number	23
Class	2
Classification code	5F

#### 14.4. Packing group

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

22 / 27

# NOVA POWER PAINT

Packing group	
Labels	2.1
<b>14.5. Environmental hazards</b>	
Environmentally hazardous substance mark	no
<b>14.6. Special precautions for user</b>	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Inland waterways (ADN)

<b>14.1. UN number</b>	
UN number	1950
<b>14.2. UN proper shipping name</b>	
Proper shipping name	aerosols
<b>14.3. Transport hazard class(es)</b>	
Class	2
Classification code	5F
<b>14.4. Packing group</b>	
Packing group	
Labels	2.1
<b>14.5. Environmental hazards</b>	
Environmentally hazardous substance mark	no
<b>14.6. Special precautions for user</b>	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

## Sea (IMDG/IMSBC)

<b>14.1. UN number</b>	
UN number	1950
<b>14.2. UN proper shipping name</b>	
Proper shipping name	aerosols
<b>14.3. Transport hazard class(es)</b>	
Class	2.1
<b>14.4. Packing group</b>	
Packing group	
Labels	2.1
<b>14.5. Environmental hazards</b>	
Marine pollutant	-
Environmentally hazardous substance mark	no
<b>14.6. Special precautions for user</b>	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
<b>14.7. Maritime transport in bulk according to IMO instruments</b>	
Annex II of MARPOL 73/78	Not applicable

## Air (ICAO-TI/IATA-DGR)

<b>14.1. UN number</b>	
UN number	1950
<b>14.2. UN proper shipping name</b>	
Proper shipping name	aerosols, flammable
<b>14.3. Transport hazard class(es)</b>	
Class	2.1
<b>14.4. Packing group</b>	
Packing group	
Labels	2.1
<b>14.5. Environmental hazards</b>	
Environmentally hazardous substance mark	no

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

23 / 27

# NOVA POWER PAINT

## 14.6. Special precautions for user

Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	30 kg G

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

##### Explosives precursors

Due to the presence of one or more components in this mixture, acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

##### VOC content Directive 2010/75/EU

VOC content	Remark
100 %	

##### VOC content Directive 2004/42/EC

Maximum value	EC limit value	Category	Subcategory	Notation
840 g/l	840 g/l	IIB	e: Special finishes	2004/42/IIB(e)(840)840

Indicative occupational exposure limit values (Directive 98/24/EC, 2000/39/EC, 2004/37/EC and amendments)

#### 2-methoxy-1-methylethyl acetate

Product name	Skin resorption
2-Methoxy-1-methylethylacetate	Skin

#### 2-butoxyethanol

Product name	Skin resorption
2-Butoxyethanol	Skin

#### Directive 2012/18/EU (Seveso III)

##### Threshold values under normal circumstances

Substance or category	Low tier (tonnes)	Top tier (tonnes)	Group	For this substance or mixture the summation rule has to be applied for:
P3b FLAMMABLE AEROSOLS	5000 (net)	50000 (net)	None	Flammability

#### REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· acetone · 4-methylpentan-2-one · 2-methoxy-1-methylethyl acetate · 2-butoxyethanol · methyl methacrylate	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
· acetone · 4-methylpentan-2-one	Substances classified as flammable gases category 1 or 2, flammable liquids categories	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

24 / 27

# NOVA POWER PAINT

<ul style="list-style-type: none"> <li>· 2-methoxy-1-methylethyl acetate</li> <li>· methyl methacrylate</li> </ul>	<p>1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.</p>	<p>decorative purposes such as the following:</p> <ul style="list-style-type: none"> <li>— metallic glitter intended mainly for decoration,</li> <li>— artificial snow and frost,</li> <li>— “whoopee” cushions,</li> <li>— silly string aerosols,</li> <li>— imitation excrement,</li> <li>— horns for parties,</li> <li>— decorative flakes and foams,</li> <li>— artificial cobwebs,</li> <li>— stink bombs.</li> </ul> <p>2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: “For professional users only”.</p> <p>3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.</p> <p>4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.</p>
<ul style="list-style-type: none"> <li>· acetone</li> <li>· 4-methylpentan-2-one</li> <li>· 2-butoxyethanol</li> <li>· methyl methacrylate</li> </ul>	<p>Substances falling within one or more of the following points:</p> <p>(a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008:</p> <ul style="list-style-type: none"> <li>— carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation</li> <li>— reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation</li> <li>— skin sensitiser category 1, 1A or 1B</li> <li>— skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2</li> <li>— serious eye damage category 1 or eye irritant category 2</li> </ul> <p>(b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council</p> <p>(c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex.</p> <p>The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.</p>	<p>Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081</p>

## National legislation Belgium

### NOVA POWER PAINT

No data available

#### 2-methoxy-1-methylethyl acetate

Résorption peau	Acétate de 2-(1-méthoxy)propyle; D; La mention “D” signifie que la résorption de l’agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l’exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l’agent dans l’air.
-----------------	--

#### 2-butoxyethanol

Résorption peau	2-Butoxyéthanol; D; La mention “D” signifie que la résorption de l’agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l’exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l’agent dans l’air.
-----------------	--

## National legislation The Netherlands

### NOVA POWER PAINT

Waterbezwaarlijkheid	B (4); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

#### 2-butoxyethanol

Huidopname (wettelijk)	2-Butoxyethanol; H
------------------------	--------------------

## National legislation France

### NOVA POWER PAINT

No data available

#### 2-methoxy-1-methylethyl acetate

Risque de pénétration percutanée	Acétate de 2-méthoxy-1-méthyléthyle; Risque de pénétration percutanée
----------------------------------	---

#### 2-butoxyethanol

Risque de pénétration percutanée	2-Butoxyéthanol; Risque de pénétration percutanée
----------------------------------	---

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

25 / 27

# NOVA POWER PAINT

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

Catégorie cancérogène	Titane (dioxide de), en Ti; C2
-----------------------	--------------------------------

## National legislation Germany

NOVA POWER PAINT

Lagerklasse (TRGS510)	2B: Aerosolpackungen und Feuerzeuge
WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017

acetone

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Aceton; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

4-methylpentan-2-one

TA-Luft	5.2.5/l
TRGS900 - Risiko der Fruchtschädigung	4-Methylpentan-2-on; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
Hautresorptive Stoffe	4-Methylpentan-2-on; H; Hautresorptiv

2-methoxy-1-methylethyl acetate

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	2-Methoxy-1-methylethylacetat; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

2-butoxyethanol

TA-Luft	5.2.5/l
TRGS900 - Risiko der Fruchtschädigung	2-Butoxyethanol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
Hautresorptive Stoffe	2-Butoxyethanol; H; Hautresorptiv

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

TA-Luft	5.2.1
---------	-------

methyl methacrylate

TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Methyl-methacrylat; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

## National legislation Austria

NOVA POWER PAINT

No data available

4-methylpentan-2-one

besondere Gefahr der Hautresorption	4-Methylpentanon-2; H
-------------------------------------	-----------------------

2-methoxy-1-methylethyl acetate

besondere Gefahr der Hautresorption	1-Methoxypropylacetat-2; H
-------------------------------------	----------------------------

2-butoxyethanol

besondere Gefahr der Hautresorption	2-Butoxyethanol; H
-------------------------------------	--------------------

methyl methacrylate

Gefahr der Sensibilisierung der Haut	Methylmethacrylat; Sh
--------------------------------------	-----------------------

## National legislation United Kingdom

NOVA POWER PAINT

No data available

4-methylpentan-2-one

Skin absorption	4-Methylpentan-2-one; Sk
-----------------	--------------------------

2-methoxy-1-methylethyl acetate

Skin absorption	1-Methoxypropyl acetate; Sk
-----------------	-----------------------------

2-butoxyethanol

Skin absorption	2-Butoxyethanol; Sk
-----------------	---------------------

## Other relevant data

NOVA POWER PAINT

No data available

acetone

TLV - Carcinogen	Acetone; A4
------------------	-------------

4-methylpentan-2-one

IARC - classification	2B; Methyl isobutyl ketone
TLV - Carcinogen	Methyl isobutyl ketone; A3

2-butoxyethanol

IARC - classification	3; 2-butoxyethanol
TLV - Carcinogen	2-Butoxyethanol; A3

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]

IARC - classification	2B; Titanium dioxide
TLV - Carcinogen	Titanium dioxide; A4

Reason for revision: 2.2, 3.2, 8, 15

Publication date: 2000-05-05

Date of revision: 2022-01-28

Revision number: 0800

BIG number: 32011

26 / 27

# NOVA POWER PAINT

## methyl methacrylate

IARC - classification	3; Methyl methacrylate
TLV - Skin Sensitisation	Methyl methacrylate; SEN; Sensitization
TLV - Carcinogen	Methyl methacrylate; A4

## 15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

## SECTION 16: Other information

### Full text of any H- and EUH-statements referred to under section 3:

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H229 Pressurised container: May burst if heated.  
H280 Contains gas under pressure; may explode if heated.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer if inhaled.  
EUH066 Repeated exposure may cause skin dryness or cracking.  
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.