

NLB

THE BEST SOLUTION FOR RUST, CORROSION AND WEAR PROBLEMS

- Contains no nickel - special blend of metal powders.
- Resists high pressure (2300 kg/cm²).
- Extreme temperature range (-180°C / +1200°C).
- Prevents galvanic action and corrosion.
- Unique lubrication characteristics - reduces friction and wear - Ball bearing effect.
- Resists water, chemical vapours, salt, solvents, atmospheric action, etc.
- Prevents seizing. Even in extreme circumstances, the viscosity does not change.
- Saves time and money.
- Simplifies assembly and disassembly.
- Economical in use.



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

NOVA LUBE

General Information

NOVA LUBE is a protective and lubricating compound made of micronized pure metal particles and a synthetic carrier which protects against corrosion and oxidation.

NOVA LUBE penetrates the smallest pores and crevices of the metal and forms a fine dividing film that is protective and long lasting. Assembled units can be easily taken apart with standard tools, even after years. There are no more problems with corrosion or seizure.

NOVA LUBE is a heat conductor and cannot be destroyed. It resists temperatures ranging from -180°C to +1200°C and withstands exposure to water, salt water, acids, caustic solutions, vapours, gases, oils, most chemical products and solvents.

It may not be used on oxygen or acetylen installations. NOVA LUBE is non-toxic, it does not contain any lead or nickel.

NOVA LUBE seals, does not drip and is very economical in use.

Technical Information

Physical form: aerosol
 Explosion limits: 1,5-11,2 vol %
 Vapour pressure (at 20°C): > 1200 hPa
 Relative density (at 20°C): 0,6
 Absolute density (at 20°C): 600 kg/m³

Physical form: paste
 Colour: grey
 Relative density: 1,2
 Auto-ignition temperature: > 200°C
 Flash point 170°C; ISO 2592

Solidity: NLGI CLASS 1 test method.
 Specific weight (at 20°C): 1.6 g/cm³ DIN 51757.
 Pressure test: 4000 N VKA TEST.
 Flow temperature: 1200°C.
 Freezing temperature: -180°C.
 Water resistance test acc. to DIN 51807-1.
 Shelf life: 24 months, keep dry, cool and frost-proof.
 Safety measures: consult the Safety Data Sheet.

Application and Use

- Multiple uses in the following areas:
- Steel, paper, chemical, gas works, refineries and petrochemical plants, power plants.
- Automobile industry, in the production of sanitary installations, water treatment equipment, workshops for the repair of engines.
- Equipment for road construction, maintenance shops, garages.
- Food and packaging industry, marine workshops, mines, glass factories, etc.

Article nr	Name	Content	Shelf Life	Catalog
N221000	Nova Lube	10g	-	LUBRICANTS
N221001	Nova Lube	100ml	-	LUBRICANTS
N221002	Nova Lube	120g	-	LUBRICANTS
N221005	Nova Lube Brush	202g	-	LUBRICANTS
N221101	Nova Lube	400ml	-	LUBRICANTS
N221302	Nova Lube	450g	-	LUBRICANTS
N221404	Nova Lube	1,8kg	-	LUBRICANTS



LUBRICANTS

WWW.TECH-MASTERS.EU

