according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Apr 2023 Print date: 26 May 2023

Version: 1 Page 1/13



Top Plast Eco black 3,5min. 50ml (Comp. A)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Top Plast Eco black 3,5min. 50ml (Comp. A)

Article No.:

T910203

UFI:

H4HV-PKQ4-F24X-U793

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Adhesive

1.3. Details of the supplier of the safety data sheet

Supplier:

Techniqua Handels GmbH

Hartleitnerstraße 3 4653 Eberstalzell

Austria

Telephone: +43 (0) 7241 213 79 E-mail: office@techniqua.at

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Respiratory or skin sensitisation (Skin Sens. 1)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
Acute toxicity (inhalative) (Acute Tox. 4)	H332: Harmful if inhaled.	
STOT-single exposure (STOT SE 3)	H335: May cause respiratory irritation.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



Exclamation mark **Signal word:** Warning

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Apr 2023 Print date: 26 May 2023

Version: 1 Page 2/13



Top Plast Eco black 3,5min. 50ml (Comp. A)

Hazard components for labelling:

calcium oxide; Polyisocyanate, aliphatic

carefully oxide, i of 150e full atte		
Hazard statements for health hazards		
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	

Supplemental hazard information		
EUH204 Contains isocyanates. May produce an allergic reaction.		

Precautionary statements Prevention		
P261	Avoid breathing vapours and spray.	
P280	Wear protective gloves and eye/face protection.	

Precautionary statements Response		
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P312	Call a POISON CENTER if you feel unwell.	

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. The product does not contain any substances with endocrine-disrupting properties in concentrations of \geq 0.1%.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 28182-81-2 EC No.: 931-274-8 REACH No.: 01-2119485796-17	Polyisocyanate, aliphatic Acute Tox. 4 (H332), STOT SE 3 (H335), Skin Sens. 1 (H317) Warning	70 - 90 Vol-%
CAS No.: 1305-78-8 EC No.: 215-138-9 REACH No.: 01-2119475325-36	calcium oxide Eye Dam. 1 (H318), STOT SE 3 (H335), Skin Irrit. 2 (H315) Danger	1 - 2 Vol-%
CAS No.: 13463-67-7 EC No.: 236-675-5 Index No.: 022-006-00-2 REACH No.: 01-2119489379-17	Titanium dioxide; [in powder form with at least 1% particles with aerodynamic diameter ≤ 10 μm] Carc. 2 (H351) ❖ Warning	0.1 - < 1 Vol-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Never give anything by mouth to an unconscious person!

Following inhalation:

Fresh air supply, consult a doctor in case of complaints.

In case of skin contact:

Wash with plenty of soap and water. Immediately remove any contaminated clothing, shoes or stockings. In case of skin irritation, consult a physician.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Apr 2023 Print date: 26 May 2023

Version: 1 Page 3/13



Top Plast Eco black 3,5min. 50ml (Comp. A)

After eye contact:

First rinse with water for a long time, (remove contact lenses if this is easily possible), then consult a doctor.

Following ingestion:

Rinse mouth thoroughly with water. Drink plenty of water. Call a physician immediately.

Self-protection of the first aider:

First aider: Pay attention to self-protection!

4.2. Most important symptoms and effects, both acute and delayed

If applicable, delayed symptoms and effects can be found in section 11. or in the routes of intake under section 4.1.

Symptoms of poisoning may not appear for many hours, therefore medical monitoring for at least 48 hours after an accident.

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Adapt fire extinguishing measures to the surroundings.

Water spray jet, Foam, Carbon dioxide (CO2), Dry extinguishing powder

Unsuitable extinguishing media:

None known

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products:

Carbon oxides, Nitrogen oxides, Hydrogen cyanide (hydrocyanic acid), toxic gases

5.3. Advice for firefighters

Personal protection equipment: see section 8. Do not inhale explosion and combustion gases. Use suitable breathing apparatus.

Cool endangered containers with water spray. Fire residues and contaminated extinguishing water must be disposed of in accordance with official regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear personal protection equipment (refer to section 8). Provide adequate ventilation. Remove all sources of ignition. Avoid dust formation with solid or powdery products. Wear protective equipment. Keep unprotected persons away. Avoid contact with skin, eyes and clothes. If necessary, observe the risk of slipping.

Emergency procedures:

Leave the danger zone as far as possible, use existing emergency plans if necessary.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8.

6.2. Environmental precautions

Contain in case of escape of larger quantities. Stop leak if safe to do so. Do not allow to enter into surface water or drains. Prevent the product from entering waste water, surface water, ground water. In case of spillage into water or sewage system, inform the competent authorities.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Apr 2023 Print date: 26 May 2023

Version: 1 Page 4/13



Top Plast Eco black 3,5min. 50ml (Comp. A)

6.4. Reference to other sections

See section 7 for further information on safe handling.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Ensure good ventilation/extraction at the workplace. Avoid contact with skin, eyes and clothes. When using do not eat, drink, smoke, sniff. Take care for the labels and safety data sheets of the chemicals to be used.

Advices on general occupational hygiene

The usual precautions when handling chemicals must be observed. Wash hands before breaks and after work. Keep away from food, drink and animal feed. Remove contaminated clothing and protective equipment before entering areas where food will be served.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Prevent access for unauthorised persons.

Requirements for storage rooms and vessels:

Do not store product in passageways and stairways. Keep only in the original container in a cool, well-ventilated place. Store at room temperature. Store in a dry place.

Storage class (TRGS 510, Germany): 10 - Combustible liquids that cannot be assigned to any of the above storage classes

7.3. Specific end use(s)

Recommendation:

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
MAK (AT) from 25 Sept 2018	calcium oxide CAS No.: 1305-78-8 EC No.: 215-138-9	① 1 mg/m³ ⑤ (einatembare Fraktion)
MAK (AT)	calcium oxide CAS No.: 1305-78-8 EC No.: 215-138-9	② 4 mg/m³ ⑤ (einatembare Fraktion max. 8x5 min./Schicht, Momentanwert)
IOELV (EU) from 21 Feb 2017	calcium oxide CAS No.: 1305-78-8 EC No.: 215-138-9	① 1 mg/m³ ② 4 mg/m³ ⑤ (respirable fraction)
MAK (AT) from 11 Sept 2007	Titanium dioxide; [in powder form with at least 1% particles with aerodynamic diameter ≤ 10 μm] CAS No.: 13463-67-7 EC No.: 236-675-5	② 10 mg/m³ ⑤ (alveolengängige Fraktion, max. 2x60 min./Schicht)

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Apr 2023 Print date: 26 May 2023 Version: 1

Page 5/13



Top Plast Eco black 3,5min. 50ml (Comp. A)

Limit value type (country of origin)		 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
MAK (AT) from 11 Sept 2007	Titanium dioxide; [in powder form with at least 1% particles with aerodynamic diameter ≤ 10 μm] CAS No.: 13463-67-7 EC No.: 236-675-5	① 5 mg/m³ ⑤ (alveolengängige Fraktion)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
Polyisocyanate, aliphatic CAS No.: 28182-81-2 EC No.: 931-274-8	0.5 mg/m³	① DNEL worker ② Long-term – inhalation, local effects
Polyisocyanate, aliphatic CAS No.: 28182-81-2 EC No.: 931-274-8	1 mg/m³	DNEL worker Acute - inhalation, local effects
calcium oxide CAS No.: 1305-78-8 EC No.: 215-138-9	1 mg/m³	DNEL worker Long-term – inhalation, local effects
calcium oxide CAS No.: 1305-78-8 EC No.: 215-138-9	1 mg/m³	DNEL Consumer Long-term – inhalation, local effects
calcium oxide CAS No.: 1305-78-8 EC No.: 215-138-9	4 mg/m³	① DNEL worker ② Acute - inhalation, local effects
calcium oxide CAS No.: 1305-78-8 EC No.: 215-138-9	4 mg/m³	DNEL Consumer Acute - inhalation, local effects
Titanium dioxide; [in powder form with at least 1% particles with aerodynamic diameter ≤ 10 μm] CAS No.: 13463-67-7 EC No.: 236-675-5	700 mg/kg bw/ day	① DNEL worker ② Long-term – inhalation, systemic effects
Titanium dioxide; [in powder form with at least 1% particles with aerodynamic diameter ≤ 10 μm] CAS No.: 13463-67-7 EC No.: 236-675-5	10 mg/m³	① DNEL worker ② Long-term – inhalation, local effects

Substance name	PNEC Value	① PNEC type
Polyisocyanate, aliphatic CAS No.: 28182-81-2 EC No.: 931-274-8	0.127 mg/L	① PNEC aquatic, freshwater
Polyisocyanate, aliphatic CAS No.: 28182-81-2 EC No.: 931-274-8	0.0127 mg/L	① PNEC aquatic, marine water
Polyisocyanate, aliphatic CAS No.: 28182-81-2 EC No.: 931-274-8	38.3 mg/L	① PNEC sewage treatment plant
Polyisocyanate, aliphatic CAS No.: 28182-81-2 EC No.: 931-274-8	266,700 mg/ kg	① PNEC sediment, freshwater

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Apr 2023 Print date: 26 May 2023

Version: 1 Page 6/13



Top Plast Eco black 3,5min. 50ml (Comp. A)

Substance name	PNEC Value	① PNEC type
Polyisocyanate, aliphatic CAS No.: 28182-81-2 EC No.: 931-274-8	26,670 mg/kg	① PNEC sediment, marine water
Polyisocyanate, aliphatic CAS No.: 28182-81-2 EC No.: 931-274-8	53,182 mg/kg	① PNEC soil
Polyisocyanate, aliphatic CAS No.: 28182-81-2 EC No.: 931-274-8	1.27 mg/L	① PNEC aquatic, intermittent release
calcium oxide CAS No.: 1305-78-8 EC No.: 215-138-9	0.37 mg/L	① PNEC aquatic, freshwater
calcium oxide CAS No.: 1305-78-8 EC No.: 215-138-9	0.24 mg/L	① PNEC aquatic, marine water
calcium oxide CAS No.: 1305-78-8 EC No.: 215-138-9	2.27 mg/L	① PNEC sewage treatment plant
calcium oxide CAS No.: 1305-78-8 EC No.: 215-138-9	817.4 mg/kg	① PNEC soil
Titanium dioxide; [in powder form with at least 1% particles with aerodynamic diameter ≤ 10 μm] CAS No.: 13463-67-7 EC No.: 236-675-5	0.184 mg/L	① PNEC aquatic, freshwater
Titanium dioxide; [in powder form with at least 1% particles with aerodynamic diameter ≤ 10 μm] CAS No.: 13463-67-7 EC No.: 236-675-5	0.0184 mg/L	① PNEC aquatic, marine water
Titanium dioxide; [in powder form with at least 1% particles with aerodynamic diameter ≤ 10 μm] CAS No.: 13463-67-7 EC No.: 236-675-5	100 mg/L	① PNEC sewage treatment plant
Titanium dioxide; [in powder form with at least 1% particles with aerodynamic diameter ≤ 10 μm] CAS No.: 13463-67-7 EC No.: 236-675-5	1,000 mg/kg	① PNEC sediment, freshwater
Titanium dioxide; [in powder form with at least 1% particles with aerodynamic diameter ≤ 10 μm] CAS No.: 13463-67-7 EC No.: 236-675-5	100 mg/kg	① PNEC sediment, marine water
Titanium dioxide; [in powder form with at least 1% particles with aerodynamic diameter ≤ 10 μm] CAS No.: 13463-67-7 EC No.: 236-675-5	100 mg/kg	① PNEC soil
Titanium dioxide; [in powder form with at least 1% particles with aerodynamic diameter ≤ 10 μm] CAS No.: 13463-67-7 EC No.: 236-675-5	0.193 mg/L	① PNEC aquatic, intermittent release

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure good ventilation. This can be achieved by local exhaust ventilation or general exhaust air. If this is not sufficient to keep the concentration below the occupational exposure limits (OEL), suitable respiratory

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Apr 2023 Print date: 26 May 2023

Version: 1 Page 7/13



Top Plast Eco black 3,5min. 50ml (Comp. A)

protection must be worn. Applies only if exposure limits are listed here. Appropriate assessment methods for verifying the effectiveness of the protective measures taken include metrological and non-measured methods of determination. Such methods are described by e.g. EN 14042, TRGS 402 (Germany). EN 14042 "Workplace atmospheres. Guidance for the application and use of methods and equipment for the determination of chemical and biological agents". TRGS 402 (Germany) "Determining and assessing the hazards of activities involving hazardous substances - Inhalation exposure".

8.2.2. Personal protection equipment

Eye/face protection:

Safety goggles with side shields (EN 166).

Skin protection:

Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Glove material:

Butyl caoutchouc (butyl rubber)

Neoprene®

NBR (Nitrile rubber) PVC (polyvinyl chloride)

Thickness of the glove material: 0,5mm

Breakthrough time: >= 480 min.

The determined breakthrough times according to EN 16523-1 were not carried out under practical conditions. A maximum wearing time corresponding to 50% of the breakthrough time is recommended. Hand protection cream recommended.

Additional information on hand protection - No tests have been carried out. For mixtures, the selection was made to the best of our knowledge and based on the information provided by the ingredients. For substances, the selection was derived from the glove manufacturer's information. Final selection of glove material must be made with consideration of breakthrough times, permeation rates and degradation. The selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer. In the case of mixtures, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use. The exact breakthrough time of the glove material must be obtained from the protective glove manufacturer and must be observed.

Body protection:

Protective work clothing (e.g. safety shoes EN ISO 20345, long-sleeved work clothing).

Respiratory protection:

Filter A (EN 14387), brown

Filter B (EN 14387), grey

Filter P3 (EN 143), white

Observe the wear time limits as specified by the manufacturer.

Thermal hazards:

No further relevant information available.

Other protection measures:

The usual precautions when handling chemicals must be observed. Wash hands before breaks and after work. Keep away from food, drink and animal feed. Remove contaminated clothing and protective equipment before entering areas where food will be served.

8.2.3. Environmental exposure controls

No further relevant information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Paste Colour: white

Odour: characteristic

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Apr 2023 Print date: 26 May 2023

Version: 1 Page 8/13



Top Plast Eco black 3,5min. 50ml (Comp. A)

Safety relevant basis data

Parameter	Value	① Method
		② Remark
рН	not determined	
Melting point	not determined	
Freezing point	not determined	
Initial boiling point and boiling range	not determined	
Decomposition temperature	not determined	
Flash point	not determined	
Evaporation rate	not determined	
Auto-ignition temperature	not determined	
Upper/lower flammability or explosive limits	not determined	
Vapour pressure	not determined	
Vapour density	not determined	
Density	not determined	
Relative density	1.21	
Bulk density	not determined	
Water solubility	not determined	
Partition coefficient: n-octanol/water	not determined	
Dynamic viscosity	55 Pa* s	
Kinematic viscosity	not determined	

9.2. Other information

The product is not explosive.

9.2.1. Information with regard to physical hazard classes Oxidizing liquids:

No.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product has not been tested.

10.2. Chemical stability

Chemically stable under conditions of storage, handling and use.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Alkalis, strong oxidants, Acids

10.6. Hazardous decomposition products

No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological information

	Acute Toxicity Estimate for Mixtures	
-	ATE (inhalation, gases): 12.32 ppmV calculated.	
	ATE (inhalation, vapour): 1.68 mg/L calculated.	

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Apr 2023 Print date: 26 May 2023

Version: 1 Page 9/13



Top Plast Eco black 3,5min. 50ml (Comp. A)

Polyisocyanate, aliphatic CAS No.: 28182-81-2 EC No.: 931-274-8

LD₅₀ **oral**: >2,500 mg/kg (Rat) OECD 423

LD₅₀ dermal: >2,000 mg/kg (Rat) OECD 402

LC₅₀ Acute inhalation toxicity (dust/mist): 1.5 mg/L (Rat) OECD 403

calcium oxide CAS No.: 1305-78-8 EC No.: 215-138-9

LD₅₀ oral: >2,000 mg/kg (Rat) OECD 425

LD₅₀ dermal: >2,500 mg/kg (Rabbit) OECD 402

Titanium dioxide; [in powder form with at least 1% particles with aerodynamic diameter ≤ 10 μm]

CAS No.: 13463-67-7 EC No.: 236-675-5 **LD**₅₀ **oral:** >5,000 mg/kg (Rat) OECD 425

LD₅₀ dermal: >5,000 mg/kg (Rabbit)

LC₅₀ Acute inhalation toxicity (dust/mist): >6.8 mg/L (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional information:

No further relevant information available.

11.2. Information on other hazards

Endocrine disrupting properties:

None of the ingredients are included.

SECTION 12: Ecological information

12.1. Toxicity

Polyisocyanate, aliphatic CAS No.: 28182-81-2 EC No.: 931-274-8

LC₅₀: >100 mg/L 4 d (fish, Brachydanio rerio) OECD 203

EC₅₀: >100 mg/L 2 d (crustaceans, Daphnia magna) OECD 202

ErC₅₀: >1,000 mg/L 3 d (Algae/water plant, Scenedesmus subspicatus) DIN 38412 T.9

IC₅₀: >100 mg/L 3 d (Algae/water plant, Scenedesmus subspicatus) OECD 201

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Apr 2023 Print date: 26 May 2023

Version: 1 Page 10/13



Top Plast Eco black 3,5min. 50ml (Comp. A)

calcium oxide CAS No.: 1305-78-8 EC No.: 215-138-9

LC₅₀: 50.6 mg/L 4 d (fish) **LC₅₀:** 457 mg/L 4 d (fish)

EC₅₀: 49.1 mg/L 2 d (crustaceans)

EC₅₀: 158 mg/L 2 d (crustaceans)

NOEC: 32 mg/L (crustaceans)

NOEC: 48 mg/L 3 d (Algae/water plant)

EC₅₀: 184.57 mg/L 3 d

Titanium dioxide; [in powder form with at least 1% particles with aerodynamic diameter \leq 10 µm]

CAS No.: 13463-67-7 EC No.: 236-675-5

LC₅₀: >100 mg/L 4 d (fish, Oncorhynchus mykiss) OECD 203

LC₅₀: >100 mg/L 2 d (crustaceans, Daphnia magna) OECD 202

EC₅₀: 16 mg/L 3 d (Algae/water plant, Pseudokirchnerie lla subcapitata) U.S. EPA-600/9- 78-018

Assessment/classification:

No further relevant information available.

12.2. Persistence and degradability

Polyisocyanate, aliphatic CAS No.: 28182-81-2 EC No.: 931-274-8

Biodegradation: Poorly biodegradable.

Additional information:

No further relevant information available.

12.3. Bioaccumulative potential

Polyisocyanate, aliphatic CAS No.: 28182-81-2 EC No.: 931-274-8

Log K_{OW}: 3.2

Bioconcentration factor (BCF): 376.7

Titanium dioxide; [in powder form with at least 1% particles with aerodynamic diameter ≤ 10 μm]

CAS No.: 13463-67-7 EC No.: 236-675-5 Bioconcentration factor (BCF): 9.6

Accumulation / Evaluation:

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

Polyisocyanate, aliphatic CAS No.: 28182-81-2 EC No.: 931-274-8

Results of PBT and vPvB assessment: —

calcium oxide CAS No.: 1305-78-8 EC No.: 215-138-9

Results of PBT and vPvB assessment: -

Titanium dioxide; [in powder form with at least 1% particles with aerodynamic diameter \leq 10 μ m]

CAS No.: 13463-67-7 EC No.: 236-675-5

Results of PBT and vPvB assessment: -

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

None of the ingredients are included.

12.7. Other adverse effects

No further relevant information available.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Apr 2023 Print date: 26 May 2023

Version: 1 Page 11/13



Top Plast Eco black 3,5min. 50ml (Comp. A)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV Waste code product

08 04 09 * Waste adhesives and sealants containing organic solvents or other dangerous substances

Waste treatment options

Appropriate disposal / Product:

Disposal via waste water is not recommended. Observe local regulations. For example, suitable incineration plant. Cured product: Can be disposed of with household waste.

Appropriate disposal / Package:

Uncleaned packaging: Observe local regulations. Empty container completely. Non-contaminated packaging can be reused. Packaging that cannot be cleaned must be disposed of in the same way as the substance.

SECTION 14: Transport information

Land transport (ADR/RID)	(ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)		
14.1. UN number or	ID number				
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.		
14.2. UN proper shipping name					
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.		
14.3. Transport hazard class(es)					
not relevant	not relevant	not relevant	not relevant		
14.4. Packing group					
not relevant	not relevant	not relevant	not relevant		
14.5. Environmental hazards					
not relevant	not relevant	not relevant	not relevant		
14.6. Special precautions for user					
not relevant	not relevant	not relevant	not relevant		

14.7. Maritime transport in bulk according to IMO instruments not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Observe national regulations/laws on maternity protection (especially the national implementation of Directive 92/85/EEC)! The general hygiene measures for handling chemicals must be applied. Regulation (EU) No. 649/2012 "concerning the export and import of dangerous chemicals" must be observed, as the product contains a substance that falls within the scope of this regulation.

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

^{*:} Evidence for disposal must be provided.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Apr 2023 Print date: 26 May 2023

Version: 1 Page 12/13



Top Plast Eco black 3,5min. 50ml (Comp. A)

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

American Conference of Governmental Industrial Hygienists

European Agreement concerning the International Carriage of Dangerous Goods by Inland ADN

Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

AGW Threshold Limit Value **BCF Bioconcentration Factor** CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging

DIN German Institute for Standardization / German Industrial Standard

derived no-effect level **DNEL** Effective Concentration 50% EC_{50}

ΕN European Standard Exposure scenario ES

EWC European Waste Catalogue Inhibition Concentration 50 % IC_{50}

International Civil Aviation Organization **ICAO** International Maritime Dangerous Goods **IMDG** IMO International Maritime Organization

KG body weight

Lethal (fatal) Concentration 50% LC_{50}

Lethal (fatal) Dose 50% LD_{50}

MAK Maximum concentration in the workplace air (CH)

NFPA National Fire Protection Association

National Institute for Occupational Safety & Health NIOSH

No Observed Effect Concentration NOEC

OFCD Organisation for Economic Cooperation and Development

Threshold Limit Value OEL

Occupational Safety & Health Administration **OSHA** persistent and bioaccumulative and toxic PBT **PNEC** Predicted No Effect Concentration

REACH Registration, Evaluation and Authorization of Chemicals Dangerous goods regulations for transport by rail RID

TRGS Technische Regeln für Gefahrstoffe

UN United Nations

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Respiratory or skin sensitisation (Skin Sens. 1)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
Acute toxicity (inhalative) (Acute Tox. 4)	H332: Harmful if inhaled.	
STOT-single exposure (STOT SE 3)	H335: May cause respiratory irritation.	

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 6 Apr 2023 Print date: 26 May 2023

Version: 1 Page 13/13



Top Plast Eco black 3,5min. 50ml (Comp. A)

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements			
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H318	Causes serious eye damage.		
H332	Harmful if inhaled.		
H335	May cause respiratory irritation.		
H351	Suspected of causing cancer.		

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.