

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1

Page 1/18



Power Clean 500ml

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Power Clean 500ml

Article No.:

T499001

UFI:

Q5AA-SYFV-2T0X-RREE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Cold cleaner

1.3. Details of the supplier of the safety data sheet

Supplier:

Techniqua Handels GmbH

Hartleitnerstraße 3

4653 Eberstälzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: office@techniqua.at

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aerosols (<i>Aerosol 1</i>)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Aspiration hazard (<i>Asp. Tox. 1</i>)	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation (<i>Skin Irrit. 2</i>)	H315: Causes skin irritation.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 2</i>)	H411: Toxic to aquatic life with long lasting effects.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1

Page 2/18



Power Clean 500ml

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS07
Exclamation mark



GHS09
Environment

Signal word: Danger

Hazard components for labelling:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic, Consisting of: 110-82-7 cyclohexane (2%); (R)-(+)-Limonene; pentane; propan-2-ol

Hazard statements for physical hazards

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

Hazard statements for health hazards

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Hazard statements for environmental hazards

H411	Toxic to aquatic life with long lasting effects.
------	--

Precautionary statements Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection.

Precautionary statements Response

P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.

Precautionary statements Storage

P403	Store in a well-ventilated place.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary statements Disposal

P501	Dispose of contents/container to an appropriate recycling or disposal facility.
------	---

Additional information:

The product contains: Notifiable explosives precursors. Provision, transfer, possession and use in accordance with Regulation (EU) 2019/1148, Article 9.

Formation of explosive mixtures possible without adequate ventilation.

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1

Page 3/18



Power Clean 500ml

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description:

Cleaning agent

Additional information:

Regulation (EC) No. 648/2004 [Detergents regulation]:

≥ 30% aliphatic hydrocarbons

< 5% Fragrances

Aerosols and containers fitted with a solid nebuliser containing substances or mixtures classified as hazardous by aspiration must not be labelled for this hazard.

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 64742-49-0 EC No.: 927-510-4 Index No.: 649-328-00-1 REACH No.: 01-2119475515-33	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic, Consisting of: 110-82-7 cyclohexane (2%) Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 2 (H225), STOT SE 3 (H336), Skin Irrit. 2 (H315) Danger	25 - 50 Vol-%
CAS No.: 67-63-0 EC No.: 200-661-7 Index No.: 603-117-00-0 REACH No.: 01-2119457558-25	propan-2-ol Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger	25 - 50 Vol-%
CAS No.: 109-66-0 EC No.: 203-692-4 Index No.: 601-006-00-1 REACH No.: 01-2119459286-30	pentane Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger EUH066	10 - 25 Vol-%
EC No.: 931-254-9 REACH No.: 01-2119484651-34	Hydrocarbons, C6, iso-alkanes <5% n-hexane Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 2 (H225), STOT SE 3 (H336), Skin Irrit. 2 (H315) Danger	10 - 25 Vol-%
CAS No.: 67-64-1 Index No.: 606-001-00-8 REACH No.: 01-2119471330-49	Acetone Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger EUH066	10 - 25 Vol-%
CAS No.: 124-38-9 EC No.: 204-696-9	carbon dioxide Press. Gas (Liq.) (H280) Warning	2.5 - 10 Vol-%
CAS No.: 5989-27-5 EC No.: 227-813-5 REACH No.: 01-2119529223-47	(R)-(+)-Limonene Aquatic Acute 1 (H400), Aquatic Chronic 3 (H412), Asp. Tox. 1 (H304), Flam. Liq. 3 (H226), Skin Irrit. 2 (H315), Skin Sens. 1B (H317) Danger	1 - 2.5 Vol-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Following inhalation:

Fresh air supply, consult a doctor in case of complaints.

If unconscious, position and transport in stable lateral position.

In case of skin contact:

Wash with plenty of soap and water.

After eye contact:

Rinse opened eye for several minutes under running water. Consult a doctor if symptoms persist

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1

Page 4/18



Power Clean 500ml

Following ingestion:

Do not induce vomiting, seek medical help immediately.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water mist, Extinguishing powder, Carbon dioxide, alcohol resistant foam

Unsuitable extinguishing media:

Water in full jet

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Special protective equipment: Put on breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear protective equipment. Keep unprotected persons away.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of spillage into water or sewage system, inform the competent authorities.

6.3. Methods and material for containment and cleaning up

For cleaning up:

Do not wash away with water or aqueous detergents.

Other information:

Provide adequate ventilation.

6.4. Reference to other sections

Further information on proper storage: see section 7.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Ensure good ventilation/extraction at the workplace.

Fire prevent measures:

Do not spray on naked flames or any incandescent material. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Container is under pressure. Protect from sunlight and temperatures above 50°C (e.g. from incandescent lamps). Do not open by force or burn even after use.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1

Page 5/18



Power Clean 500ml

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Store in a cool place. The official regulations for the storage of pressurised gas packages must be observed.

Hints on storage assembly:

The official regulations for the storage of pressurised gas packages must be observed.

Storage class (TRGS 510, Germany): 2B - Aerosol dispensers and lighters

Further information on storage conditions:

Store in a cool dry place. Protect from heat and direct sunlight.

7.3. Specific end use(s)

Recommendation:

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	Hydrocarbons,C7,n-alkanes,isoalkanes,cyclic, Consisting of: 110-82-7 cyclohexane (2%) CAS No.: 64742-49-0 EC No.: 927-510-4	① 200 mL/m ³ ② 400 mL/m ³ ⑤ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von weniger als 1 %, an n-Hexan von weniger als 5 % und an Cyclo-/ Isohexanen von weniger als 25 %)
MAK (AT)	Hydrocarbons,C7,n-alkanes,isoalkanes,cyclic, Consisting of: 110-82-7 cyclohexane (2%) CAS No.: 64742-49-0 EC No.: 927-510-4	① 170 mL/m ³ ② 340 mL/m ³ ⑤ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von weniger als 1 %, an n-Hexan von weniger als 5 % und an Cyclo-/ Isohexanen von 25 % oder mehr)
MAK (AT)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	② 800 ppm (2,000 mg/m ³) ⑤ (max. 4x15 min./Schicht)
MAK (AT)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	① 200 ppm (500 mg/m ³)
MAK (AT)	pentane CAS No.: 109-66-0 EC No.: 203-692-4	② 1,200 ppm (3,600 mg/m ³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
IOELV (EU)	pentane CAS No.: 109-66-0 EC No.: 203-692-4	① 1,000 ppm (3,000 mg/m ³)
MAK (AT)	pentane CAS No.: 109-66-0 EC No.: 203-692-4	① 600 ppm (1,800 mg/m ³)
MAK (AT)	Acetone CAS No.: 67-64-1	② 2,000 ppm (4,800 mg/m ³) ⑤ (max. 4x15 min./Schicht)
IOELV (EU)	Acetone CAS No.: 67-64-1	① 500 ppm (1,210 mg/m ³)
MAK (AT)	Acetone CAS No.: 67-64-1	① 500 ppm (1,200 mg/m ³)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1



Page 6/18

Power Clean 500ml

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9	① 5,000 ppm (9,000 mg/m ³)
MAK (AT)	carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9	② 10,000 ppm (18,000 mg/m ³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
IOELV (EU)	carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9	① 5,000 ppm (9,000 mg/m ³)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
Hydrocarbons,C7,n-alkanes,isoalkanes,cyclic, Consisting of: 110-82-7 cyclohexane (2%) CAS No.: 64742-49-0 EC No.: 927-510-4	2,085 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
Hydrocarbons,C7,n-alkanes,isoalkanes,cyclic, Consisting of: 110-82-7 cyclohexane (2%) CAS No.: 64742-49-0 EC No.: 927-510-4	477 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
Hydrocarbons,C7,n-alkanes,isoalkanes,cyclic, Consisting of: 110-82-7 cyclohexane (2%) CAS No.: 64742-49-0 EC No.: 927-510-4	300 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Hydrocarbons,C7,n-alkanes,isoalkanes,cyclic, Consisting of: 110-82-7 cyclohexane (2%) CAS No.: 64742-49-0 EC No.: 927-510-4	149 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
Hydrocarbons,C7,n-alkanes,isoalkanes,cyclic, Consisting of: 110-82-7 cyclohexane (2%) CAS No.: 64742-49-0 EC No.: 927-510-4	149 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	500 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	89 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	888 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	319 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	26 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1



Page 7/18

Power Clean 500ml

Substance name	DNEL value	① DNEL type ② Exposure route
pentane CAS No.: 109-66-0 EC No.: 203-692-4	3,000 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
pentane CAS No.: 109-66-0 EC No.: 203-692-4	643 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
pentane CAS No.: 109-66-0 EC No.: 203-692-4	432 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
pentane CAS No.: 109-66-0 EC No.: 203-692-4	214 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
pentane CAS No.: 109-66-0 EC No.: 203-692-4	214 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
Hydrocarbons, C6, iso-alkanes <5% n-hexane EC No.: 931-254-9	5,306 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
Hydrocarbons, C6, iso-alkanes <5% n-hexane EC No.: 931-254-9	1,131 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
Hydrocarbons, C6, iso-alkanes <5% n-hexane EC No.: 931-254-9	13,964 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Hydrocarbons, C6, iso-alkanes <5% n-hexane EC No.: 931-254-9	1,377 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
Hydrocarbons, C6, iso-alkanes <5% n-hexane EC No.: 931-254-9	1,301 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
Acetone CAS No.: 67-64-1	1,210 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
Acetone CAS No.: 67-64-1	200 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
Acetone CAS No.: 67-64-1	2,420 mg/m ³	① DNEL worker ② Long-term - inhalation, local effects
Acetone CAS No.: 67-64-1	186 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Acetone CAS No.: 67-64-1	62 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
Acetone CAS No.: 67-64-1	62 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
(R)-(+)-Limonene CAS No.: 5989-27-5 EC No.: 227-813-5	33.3 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
(R)-(+)-Limonene CAS No.: 5989-27-5 EC No.: 227-813-5	8.3 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
(R)-(+)-Limonene CAS No.: 5989-27-5 EC No.: 227-813-5	0.222 mg/kg	① DNEL worker ② Acute - dermal, local effects
(R)-(+)-Limonene CAS No.: 5989-27-5 EC No.: 227-813-5	0.111 mg/kg	① DNEL Consumer ② Acute - dermal, local effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1



Page 8/18

Power Clean 500ml

Substance name	DNEL value	① DNEL type ② Exposure route
(R)-(+)-Limonene CAS No.: 5989-27-5 EC No.: 227-813-5	4.76 mg/kg	① DNEL Consumer ② Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	2,251 mg/L	① PNEC sewage treatment plant
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	28 mg/kg	① PNEC soil
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, intermittent release
pentane CAS No.: 109-66-0 EC No.: 203-692-4	0.23 mg/L	① PNEC aquatic, freshwater
pentane CAS No.: 109-66-0 EC No.: 203-692-4	0.23 mg/L	① PNEC aquatic, marine water
pentane CAS No.: 109-66-0 EC No.: 203-692-4	3.6 mg/L	① PNEC sewage treatment plant
pentane CAS No.: 109-66-0 EC No.: 203-692-4	1.2 mg/kg bw/ day	① PNEC sediment, freshwater
pentane CAS No.: 109-66-0 EC No.: 203-692-4	1.2 mg/kg	① PNEC sediment, marine water
pentane CAS No.: 109-66-0 EC No.: 203-692-4	0.55 mg/kg	① PNEC soil
pentane CAS No.: 109-66-0 EC No.: 203-692-4	0.88 mg/L	① PNEC aquatic, intermittent release
Acetone CAS No.: 67-64-1	10.6 mg/L	① PNEC aquatic, freshwater
Acetone CAS No.: 67-64-1	1.06 mg/L	① PNEC aquatic, marine water
Acetone CAS No.: 67-64-1	100 mg/L	① PNEC sewage treatment plant
Acetone CAS No.: 67-64-1	30.4 mg/L	① PNEC sediment, freshwater
Acetone CAS No.: 67-64-1	3.04 mg/L	① PNEC sediment, marine water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1



Page 9/18

Power Clean 500ml

Substance name	PNEC Value	① PNEC type
Acetone CAS No.: 67-64-1	29.5 mg/kg	① PNEC soil
(R)-(+)-Limonene CAS No.: 5989-27-5 EC No.: 227-813-5	0.0054 mg/L	① PNEC aquatic, freshwater
(R)-(+)-Limonene CAS No.: 5989-27-5 EC No.: 227-813-5	0.00054 mg/L	① PNEC aquatic, marine water
(R)-(+)-Limonene CAS No.: 5989-27-5 EC No.: 227-813-5	1.8 mg/L	① PNEC sewage treatment plant
(R)-(+)-Limonene CAS No.: 5989-27-5 EC No.: 227-813-5	1.32 mg/kg	① PNEC sediment, freshwater
(R)-(+)-Limonene CAS No.: 5989-27-5 EC No.: 227-813-5	0.13 mg/kg	① PNEC sediment, marine water
(R)-(+)-Limonene CAS No.: 5989-27-5 EC No.: 227-813-5	0.262 mg/kg	① PNEC soil
(R)-(+)-Limonene CAS No.: 5989-27-5 EC No.: 227-813-5	3.33 mg/kg	① PNEC secondary poisoning

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No further details. See section 7.

8.2.2. Personal protection equipment



Eye/face protection:

Safety goggles (EN-166)

Skin protection:

Hand protection:

Gloves / solvent resistant

Breakthrough times and swelling properties of the material must be taken into consideration.

Glove material:

The selection of a suitable glove depends not only on the material but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Glove material: NBR (Nitrile rubber)

Recommended material thickness: $\geq 0,5\text{mm}$

Permeation time (maximum wear duration):

For continuous contact we recommend gloves with a breakthrough time of at least 240 minutes, with the preference for a breakthrough time greater than 480 minutes. For short term or splash protection we recommend the same. We are aware that suitable gloves offering this protection are not available. In this case, a shorter breakthrough time is permissible, provided the procedures for maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance the gloves give against a chemical substance, as this depends on the exact composition of the material of the gloves. The exact breakthrough time should be checked with the glove manufacturer and adhered to.

Body protection:

Use protective suit. (EN-13034/6)

Antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688 EN13034-6).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1

Page 10/18



Power Clean 500ml

Respiratory protection:

In case of inadequate ventilation wear respiratory protection.
Filter A2/P2

Other protection measures:

General protective and hygienic measures:
Keep away from food, drink and animal feed.
Remove contaminated, saturated clothing immediately.
Wash hands before breaks and after work.
Do not inhale gases/vapours/aerosols.
Avoid contact with eyes and skin.
General ventilation.

8.2.3. Environmental exposure controls

Use a suitable container to prevent environmental pollution.

8.3. Additional information

No further relevant information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Aerosol

Colour: colourless

Odour: characteristic

Odour threshold: not determined

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	<i>not applicable</i>		② Mixture is not polar/aprotic.
Melting point	<i>not determined</i>		
Freezing point	<i>not determined</i>		
Initial boiling point and boiling range	36 °C		② pentane (109-66-0)
Decomposition temperature	<i>not determined</i>		
Flash point	-26 °C		
Evaporation rate	<i>not determined</i>		
Auto-ignition temperature	> 200 °C		
Upper/lower flammability or explosive limits	0.6 - 13 Vol-%		
Vapour pressure	246 hPa	20 °C	
Vapour density	<i>not determined</i>		
Density	0.75 g/cm ³	20 °C	
Relative density	<i>not determined</i>		
Bulk density	<i>not determined</i>		
Water solubility	Immiscible		
Partition coefficient: n-octanol/water	<i>not determined</i>		
Dynamic viscosity	<i>not determined</i>		
Kinematic viscosity	≤ 20.5 mm ² /s	40 °C	

9.2. Other information

The product is not self-igniting. The product is not explosive, but the formation of explosive vapour/air mixtures is possible. formation of explosive vapour/air mixtures is possible.

Organic solvents: 96,0%

Solid content: 0,0%

9.2.1. Information with regard to physical hazard classes

Explosives:

Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1

Page 11/18



Power Clean 500ml

Flammable gases:

Not applicable

Aerosols:

Extremely flammable aerosol. Pressurized container: May burst if heated.

Oxidizing gases:

Not applicable

Gases under pressure:

Not applicable

Flammable liquids:

Not applicable

Flammable solids:

Not applicable

Self-reactive substances and mixtures:

Not applicable

Pyrophoric liquids:

Not applicable

Pyrophoric solids:

Not applicable

Self-heating substances and mixtures:

Not applicable

Substances or mixtures which, in contact with water, emit flammable gases:

Not applicable

Oxidizing liquids:

Not applicable

Oxidizing solids:

Not applicable

Organic peroxides:

Not applicable

Corrosive to metals:

Not applicable

Desensitised explosives:

Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

Thermal decomposition / Conditions to avoid: No decomposition when used as directed.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No dangerous decomposition products known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1

Page 12/18



Power Clean 500ml

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic, Consisting of: 110-82-7 cyclohexane (2%) CAS No.: 64742-49-0 EC No.: 927-510-4
LD₅₀ oral: ≥5,000 mg/kg (Rat)
LD₅₀ dermal: >2,920 mg/kg (Rat)
LC₅₀ Acute inhalation toxicity (vapour): >23.3 mg/L 4 h (Rat)
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
LD₅₀ oral: >2,000 mg/kg (Rat)
LD₅₀ dermal: >2,000 mg/kg (Rat)
LC₅₀ Acute inhalation toxicity (gas): >25 ppmV (Rat)
LC₅₀ Acute inhalation toxicity (vapour): >20 mg/L (Rat)
pentane CAS No.: 109-66-0 EC No.: 203-692-4
LD₅₀ oral: >5,000 mg/kg (Rat)
LD₅₀ dermal: >2,000 mg/kg (Rat)
LC₅₀ Acute inhalation toxicity (vapour): >25.3 mg/L 4 h (Rat) OECD 403
Hydrocarbons, C6, iso-alkanes <5% n-hexane EC No.: 931-254-9
ATE (inhalation, vapour): 259,354 mg/L
LD₅₀ oral: ≥5,000 mg/kg (Rat) OECD 401
LD₅₀ dermal: ≥5,000 mg/kg (Rabbit) OECD 402
LC₅₀ Acute inhalation toxicity (dust/mist): ≥50 mg/L (Rat) OECD 403
Acetone CAS No.: 67-64-1
LD₅₀ oral: ≥5,000 mg/kg (Rat)
LD₅₀ dermal: >20 mg/kg (Rat)
LC₅₀ Acute inhalation toxicity (gas): >20 ppmV 4 h (Rat)
LC₅₀ Acute inhalation toxicity (vapour): >50 mg/L 4 h (Rat)
LC₅₀ Acute inhalation toxicity (dust/mist): 76 mg/L 4 h (Rat)
carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9
ATE (inhalation, vapour): 259,354 mg/L
LD₅₀ oral: ≥5,000 mg/kg (Ratte)
LD₅₀ dermal: ≥5,000 mg/kg (Kaninchen)
LC₅₀ Acute inhalation toxicity (dust/mist): ≥50 mg/L 4 h (Ratte)
(R)-(+)-Limonene CAS No.: 5989-27-5 EC No.: 227-813-5
LD₅₀ oral: >2,000 mg/kg (Rat)
LD₅₀ dermal: >5,000 mg/kg (Rabbit)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

May cause an allergic skin reaction.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1

Page 13/18



Power Clean 500ml

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties:

None of the ingredients are included.

SECTION 12: Ecological information

12.1. Toxicity

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic, Consisting of: 110-82-7 cyclohexane (2%)

CAS No.: 64742-49-0 EC No.: 927-510-4

NOEC: 0.17 mg/L (Algae/water plant, Daphnia magna)

LOEC: 0.32 mg/L (Algae/water plant)

LC₅₀: >13.4 mg/L (fish)

EC₅₀: 3 mg/L (crustaceans, Daphnia magna)

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

LC₅₀: 9,640 mg/L 4 d (fish, Pimephales promelas)

LC₅₀: >1,000 mg/L 4 d (fish)

EC₅₀: >100 mg/L (Algae/water plant)

EC₅₀: >100 mg/L 2 d (crustaceans, Daphnia magna)

EC₅₀: >1,000 mg/L 2 d (crustaceans)

ErC₅₀: >100 mg/L 3 d (Algae/water plant, Desmodemus subspicatus)

LOEC: 1,000 mg/L (Algae/water plant, Algae)

pentane CAS No.: 109-66-0 EC No.: 203-692-4

LC₅₀: 4.26 mg/L 4 d (fish, Oncorhynchus mykiss)

EC₅₀: 10.7 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

EC₅₀: 2.7 mg/L 2 d (crustaceans, Daphnia magna)

NOEC: 7.51 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

Hydrocarbons, C6, iso-alkanes <5% n-hexane EC No.: 931-254-9

LC₅₀: >2 mg/L 4 d (fish)

EC₅₀: 31.9 mg/L 2 d (crustaceans, Daphnia magna)

ErC₅₀: 13.6 mg/L 3 d (Algae/water plant, Pseudokirchnerella subcapitata)

Acetone CAS No.: 67-64-1

LC₅₀: 8,300 mg/L 4 d

LC₅₀: 5,540 mg/L 4 d (fish, Oncorhynchus mykiss)

LC₅₀: 4,042 mg/L (fish)

EC₅₀: 8,800 mg/L 2 d (crustaceans, Daphnia magna)

EC₅₀: 8,300 mg/L (fish)

EC₅₀: 302 mg/L 4 d (Algae/water plant)

NOEC: 2,212 mg/L (crustaceans, Daphnia pulex)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1

Page 14/18



Power Clean 500ml

(R)-(+)-Limonene CAS No.: 5989-27-5 EC No.: 227-813-5

LC₅₀: 0.72 mg/L 4 d (fish, *Pimephales promelas*)

EC₅₀: 0.307 mg/L 2 d (crustaceans, *Daphnia magna*)

EC₅₀: 0.32 mg/L (Algae/water plant, *Pseudokirchneriella subcapitata*)

ErC₅₀: 150 mg/L 3 d (Algae/water plant, *Desmodesmus subspicatus*)

Additional ecotoxicological information:

No further relevant information available.

12.2. Persistence and degradability

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Biodegradation: Yes, rapidly

Remark: Readily biodegradable (according to OECD criteria).

pentane CAS No.: 109-66-0 EC No.: 203-692-4

Biodegradation: Yes, rapidly

Hydrocarbons, C6, iso-alkanes <5% n-hexane EC No.: 931-254-9

Biodegradation: Yes, rapidly

Acetone CAS No.: 67-64-1

Biodegradation: Yes, rapidly

(R)-(+)-Limonene CAS No.: 5989-27-5 EC No.: 227-813-5

Biodegradation: Yes, rapidly

Biodegradation:

Not readily biodegradable.

12.3. Bioaccumulative potential

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Log K_{OW}: 0.05

pentane CAS No.: 109-66-0 EC No.: 203-692-4

Log K_{OW}: 3.39

Hydrocarbons, C6, iso-alkanes <5% n-hexane EC No.: 931-254-9

Log K_{OW}: 3.6

Acetone CAS No.: 67-64-1

Log K_{OW}: -0.23

Bioconcentration factor (BCF): 3

(R)-(+)-Limonene CAS No.: 5989-27-5 EC No.: 227-813-5

Log K_{OW}: 4.83

Bioconcentration factor (BCF): 660

Bioconcentration factor (BCF):

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic, Consisting of: 110-82-7 cyclohexane (2%)

CAS No.: 64742-49-0 EC No.: 927-510-4

Results of PBT and vPvB assessment: —

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Results of PBT and vPvB assessment: —

pentane CAS No.: 109-66-0 EC No.: 203-692-4

Results of PBT and vPvB assessment: —

Hydrocarbons, C6, iso-alkanes <5% n-hexane EC No.: 931-254-9

Results of PBT and vPvB assessment: —

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1



Page 15/18

Power Clean 500ml

Acetone CAS No.: 67-64-1
Results of PBT and vPvB assessment: —
carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9
Results of PBT and vPvB assessment: —
(R)-(+)-Limonene CAS No.: 5989-27-5 EC No.: 227-813-5
Results of PBT and vPvB assessment: —

not applicable

12.6. Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties.

12.7. Other adverse effects

Toxic to aquatic life.

Toxic to fish.

Drinking water hazard even when small quantities leak into the subsoil.

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Must not be disposed of together with household waste. Do not allow to enter into surface water or drains.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Directive 2008/98/EC (Waste Framework Directive)

HP 3	Flammable
HP 4	Irritant — skin irritation and eye damage
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 14	Ecotoxic

Waste code packaging





15 01 04	metallic packaging
----------	--------------------

Waste treatment options

Other disposal recommendations:

Uncleaned packaging: Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name			
AEROSOLS, ENVIRONMENTALLY HAZARDOUS ((R)-(+)-Limonene)	AEROSOLS, ENVIRONMENTALLY HAZARDOUS	AEROSOLS, MARINE POLLUTANT ((R)-(+)-Limonene)	AEROSOLS, flammable
14.3. Transport hazard class(es)			
 2.1	 2.1	 2.1	 2.1
14.4. Packing group			
		-	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1

Page 16/18



Power Clean 500ml

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.5. Environmental hazards			
	No	 MARINE POLLUTANT	No
14.6. Special precautions for user			
Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F Tunnel restriction code: (D) Remark: Attention: Gases	Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F Remark: Attention: Gases	Special Provisions: 63 190 277 327 344 381 959 Limited quantity (LQ): 1L Excepted Quantities (EQ): E0 EmS-No.: F-D,S-U Remark: Attention: Gases	Special Provisions: A145 A167 Remark: Attention: Gases

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Directive 2012/18/EU

Named dangerous substances - ANNEX I: None of the ingredients are included.

Restrictions on use:

Regulation (EC) No 1907/2006 ANNEX XVII: Restriction conditions: 3

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II:

None of the ingredients are included.

Regulation (EU) 2019/1148

Annex I - RESTRICTED EXPORT SUBSTANCES FOR EXPLOSIVES (upper concentration limit for a permit pursuant to Article 5(3)): None of the ingredients are included.

Annex II - EXPLOSIVES REPORTABLE FOR EXPLOSIVES: 67-64-1 Acetone

Regulation (EC) No 273/2004 on drug precursors: 67-64-1 Acetone

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade in drug precursors between the Community and third countries: 67-64-1 Acetone

Other regulations (EU):

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive], Hazard categories:

- P3b 'Flammable' aerosols Category 1 or 2, not containing flammable gases Category 1 or 2 nor flammable liquids Category 1
- E2 Hazardous to the Aquatic Environment in Category Chronic 2

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 720 g/L

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1

Page 17/18



Power Clean 500ml

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DNEL	derived no-effect level
EC ₅₀	Effective Concentration 50%
EN	European Standard
ES	Exposure scenario
EWC	European Waste Catalogue
IC ₅₀	Inhibition Concentration 50 %
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
KG	body weight
LC ₅₀	Lethal (fatal) Concentration 50%
LD ₅₀	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OEL	Threshold Limit Value
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations
VOC	Volatile organic compounds
ZNS	central nervous system

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aerosols (<i>Aerosol 1</i>)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Aspiration hazard (<i>Asp. Tox. 1</i>)	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation (<i>Skin Irrit. 2</i>)	H315: Causes skin irritation.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 3 May 2023

Print date: 19 Jun 2023

Version: 1



Page 18/18

Power Clean 500ml

Hazard classes and hazard categories	Hazard statements	Classification procedure
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 2</i>)	H411: Toxic to aquatic life with long lasting effects.	

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.