TECH-MASTERS Trading GmbH Perfektastraße 55. A-1230 Wien Tel: +43 (0)1 / 867 29 07 office@tech-masters.com www.tech-masters.eu

CPS

ANTI-CORROSION SPRAYGREASE WITH A HIGH AMOUNT OF COPPER PARTICLES

- · Extremly high temperature resistance, up to +1100°C
- Conducts electrical current.
- Prevents seizure and squeaking.
- Protects metals against seizure, corrosion, heat and water.
- Promotes future dismantling of threaded fastenings.



General Information

COPPER SPRAY is a long-lasting high-temperature lubricant and anti-seize compound. COPPER SPRAY builds an effective gliding and separating film on insert tools, wear bushings, screw, plug and bayonet connections of all kinds, which protects the functional surfaces from corrosion and fretting corrosion. COPPER SPRAY protects metal components from

Technical Information

Base: Mixture of greases, mineral oils, copper particles, Color: Copper corrosion inhibitors Pressure (20°C): 4 Bar Propellant: Propane - butane Appearance: Grease

Application and Use

- Use COPPER SPRAY at room temperature, shake well before and apply on the place to be protected or lubricated.
- After the solvents of COPPER SPRAY are evaporated (approximately 5 minutes), a thick and protective layer has been formed. Avoid excess application of COPPER SPRAY and
- remove unneeded lubricant with a cloth.

Article nr Name T114002

Copper Spray

COPPER SPRAY

seizure, rust, water, heat and acid. COPPER SPRAY conducts electrical current and prevents squeaking. COPPER SPRAY promotes future dismantling of threaded fastenings. COPPER SPRAY is easy to use and comes with an additional tube to access hard to reach places perfectly.

Spray pattern: Jet, non dripping grease Temperature range: -40°C - + 1100°C

- · When COPPER SPRAY is used on screw threads, make sure that it reaches the bottom, to create the best sealing effect.
- APPLICATIONS: wheel nuts and bolts, exhaust brackets, flanges and on external hinges, screws, nuts, bolts..
- IMPORTANT: COPPER SPRAY IS NOT SUITABLE FOR ABS BRAKE SYSTEMS!

Content Cection LUBRICANTS 500ml











Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.





WWW.TECH-MASTERS.EU