

MT6

MULTIPURPOSE RELEASE AGENT

- Super Fast acting
- Lubricant
- Anticorrosion
- Protectant
- Release Fluid
- Water-repellent - Anti Humidity
- Cleaning Fluid
- 360° Application
- Rubbers and Plastics
- Metals
- Textiles
- Painted Surfaces



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

MULTI TECH 6

General Information

MULTI TECH 6 comprises four products in one: lubricant - protectant - release fluid - water-repellent - anticorrosion - anti-humidity - cleaning fluid.

Technical Information

AEROSOL

Physical state: Aerosol
 Colour: brown
 Odour: sweetish
 Initial boiling point: -40°C
 Flash point: -80°C
 Upper/lower flammability or explosive limits: 0.6 - 15 Vol-%
 Density (at 20°C): 0,783 g/cm³
 Kinematic viscosity: < 7 mm²/s
 electric strength = 42 kV
 Temperature resistance: - 30°C to +130°C

LIQUID

Physical state: Liquid
 Colour: light brown
 Odour: vanilla
 Initial boiling point: 110°C
 Flash point: 30°C ISO 3679
 Upper/lower flammability or explosive limits: 0.5 - 7 Vol-%
 Density (bei 20°C): 0,788 g/cm³
 Kinematic viscosity (at 40°C): < 7 mm²/s DIN EN ISO 3104
 Electric strenght: 42 kV

Application and Use

- Lubricant - Anticorrosion - Protectant
 The product forms a durable film that provides protection against water, frost, humidity and rust or oxidation. It protects metals and their microscopic imperfections.
- Release Fluid
 Attacks rust and all other types of oxidation, facilitating the release of any locked, rusted or frozen component or mechanism.
- Water-repellent - Anti Humidity
 Forms a protective film between the surface and the humidity.
- Cleaning Fluid
 Its formula enables it to be used to clean all surfaces, eliminating grease and grime and preventing the formation of an oxidation layer.
- USE
 Shake well before use (Aerosol) and apply product to surface to be treated, allow a contact time of 1 minute and proceed and carry out the required action. Eliminates rust and oxidation. Loosens blocked mechanical functions. Drives out moisture on electrical contacts.

Article nr	Name	Content	Shelf Life	Catalog
T206001	Multi Tech 6	500ml	see imprint + 36 months	LUBRICANTS
T206005	Multi Tech 6	5l	see imprint + 36 months	LUBRICANTS

