#### **TECH-MASTERS Trading GmbH** Perfektastraße 55. A-1230 Wien Tel: +43 (0)1 / 867 29 07 office@tech-masters.com www.tech-masters.eu

## EGL

### STRONG-PERFORMING **GLIDING AGENT**

- · Easy cable installation.
- Reduces the friction resistance.
- Facilitates easy assembly and
- disassembly. Volatile and evaporates without leaving a residue.
- No dirty grease smears are left on the wires.
- Does not attack aluminum, rubber or varnish/paint.
- Perfect for merging POLO-KAL and PVC pipes.



### **General Information**

EASY GLIDE is a lubrication agent for an easy assembeling of any synthetic materials. EASY GLIDE makes it easier to push/pull cables and many other materials through pipes and channels. It reduces friction and prevents the materials from scratches and fracture.

#### **Technical Information**

Form: aerosol Base: volatile silicon oils, water, emulsifiers, preservatives, anti corrosion additives Propellant: propane - butane Colour: white Odour: characteristic Boiling point: -44,5°C Lower explosion limit: 0,6 Vol% Upper explosion limit: 10,9 Vol% Flash point: -97°C

### Application and Use

- · EASY GLIDE enables fast and easy push/pull of cables through pipes.
- EASY GLIDE even prevents the central core of coaxial cables to break when under heavy operation.

Article nr Name T233985 Easy Glide





Content

500ml



#### Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.







# EASY GLIDE

EASY GLIDE is usable for all tasks and applications where a lighter friction is needed. It makes push/pull usage way more faster.

EASY GLIDE is a lubricant for all types of cables and industries, such as electric industry, sanitary industry, etc..

Ignition temperature: > 200°C Dynamic viscosity (at 20°C): 0 Pas Kinematic viscosity (at 40°C):  $\leq$  20,5 mm<sup>2</sup>/s Organic solvents: 30% Pressure (at 20°C): 4 bar Spray rate (at 20°C): 1,5 g/sec Density (at 20°C): ca. 0,88 g/ml

Application temperature: 10 - 35°C Shelf life: 12 months Storage: cool (10°C - 20°C) and dry

· EASY GLIDE can be used in generell to assemble varoius rubbers, such as in verandas or greenhouses.

EASY GLIDE guarantees an easy application of all electric installing.

Shelf Life see imprint + 36 months

Catalog

LUBRICANTS

WWW.TECH-MASTERS.EU