

PGR1

UNIVERSAL GREASE

- High temperature range from -30°C to +140°C
- Works stable based on lithium soap
- Offers excellent protection against rust, corrosion and wear
- Acid-free
- Classification K 2 K-30 as per DIN 51 825
- Classification ISO-L-XCCHA 2 as per ISO/DIS 6743-9



POWER GREASE 1600

General Information

POWER GREASE 1600 is a high quality lithium grease which is specially formulated from the highest quality paraffin base oils and special additives. It withstands pounding pressures of equipment operating under boundary conditions without failure. Because of the special formulation POWER GREASE 1600 has a long life span that reduces maintenance cost and also gives a longer life to the lubricated parts. POWER GREASE 1600 is your product for all your

lubrication applications where performance is needed, for example roller and slide bearings at low and high revolutions, low and high temperatures, used as universal grease for the general lubrication of machines as well as for demanding lubricating points. POWER GREASE 1600 guarantees good sealing and stability in wet and dusty conditions. It is easily pumpable even through long lubrication lines.

Technical Information

Physical state: Paste
 Color: yellow-brown
 Thickening agent: Lithium soap
 Odour: characteristic
 Flash point: > 190 °C / EN ISO 2592
 Density (at 15°C): 0.9 g/cm³
 Water solubility: practically insoluble
 Operating temperature range: -30°C - +140°C
 NLGI-class / DIN 51 818: 2
 Base oil viscosity/40°C/ ASTM D 7042: 110 mm²/s
 Water content / DIN 51 777/T1: < 0,1%
 Dropping point / DIN ISO 2176: 190°C
 Worked penetration/0.1mm, 60 double strokes / DIN ISO 2137: 280

Worked penetration/0.1mm, 60 000 double strokes / DIN ISO 2137: 300
 Water resistance / DIN 51807-1: Evaluation level 1
 Flow pressure at -30°C / DIN 51 805: 800 hPa
 Corrosion protection behaviour (EMCOR-test) / DIN 51 802: 0/0
 Oxidation resistance 100°C/100h / DIN 51 808: 0.2 bar
 VKA welding load / DIN 51 350/T4: 1600N
 Shelf life: 36 months, always keep the lid closed, store under shade away from direct heat.
 Safety measures: consult the Safety Data Sheet.


Application and Use

- POWER GREASE 1600 is recommended for use in: lubrication of slide and roller bearings at normal loads. The product can be used at low and high revolutions, low and high temperatures, as universal grease for the general lubrication of machines as well as for demanding lubricating points.
- Outperforms and outlasts conventional greases in everyday lubrication functions. It is a lubricant formulated for the most severe operating conditions. Inventory is reduced with one superior quality, multi-purpose lubricant. Life of equipment is increased and maintenance costs reduced.

| Article nr | Name | Content | Shelf Life | Catalog |
|------------|----------------------|---------|-------------------------|------------|
| T306010 | Power Grease 1600 | 400g | see imprint + 36 months | LUBRICANTS |
| T306011 | Power Grease 1600 | 5kg | see imprint + 36 months | LUBRICANTS |
| T306012 | Power Grease 1600 | 25kg | see imprint + 36 months | LUBRICANTS |
| T306110 | Power Grease 1600 LS | 400g | see imprint + 36 months | LUBRICANTS |

Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



LUBRICANTS

WWW.TECH-MASTERS.EU

