

## UTS

### ONE PRODUCT FOR CLEANING AND ETCHING

- Powerful solvent cleaner and diluent
- Perfectly suitable for etching before glueing or using lacquers, etc.
- Creates a good adherence to most lacquers, such as powder coating and synthetic materials through etching
- Can be used as diluent for epoxys
- Evaporates quickly



### Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

## ULTRASOLV

### General Information

ULTRASOLV is the ideal combination product for efficient cleaning and etching of surfaces. Due to its powerful formulation ULTRASOLV can be used as etching agent before glueing or using lacquers. In addition ULTRASOLV is perfectly suitable as a diluent

for epoxys. ULTRASOLV also works as a fluid abrasive on various lacquers and synthetic materials. ULTRASOLV offers a strong cleaning performance and evaporates quickly.

### Technical Information

Aggregate State: Liquid  
 Colour: colourless  
 Odour: characteristic  
 Melting point: < -86 °C  
 Initial boiling point and boiling range: 78 - 80 °C  
 Flash point: -7 °C

Upper/lower flammability or explosive limits: 1 - 11 Vol-%  
 Vapour pressure: 10,5 kPa (20 °C)  
 Density: 0,804 - 0,808 g/cm<sup>3</sup> (20 °C)  
 Partition coefficient: n-octanol/water: 0,3  
 Refractive index (20°C): 1,3720 - 1,3820  
 Shelf life: 12 months

### Application and Use

- Ideal for finishing of epoxys
- Removes hardened polyurethane
- Fluid abrasive for hardened epoxys such as MORTAR FIX, lacquers etc.

| Article nr | Name      | Content | Shelf Life              | Catalog                 |
|------------|-----------|---------|-------------------------|-------------------------|
| T689001    | Ultrasolv | 1l      | see imprint + 36 months | CLEANERS AND DEGREASERS |
| T689005    | Ultrasolv | 5l      | see imprint + 36 months | CLEANERS AND DEGREASERS |

