

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 16 Aug 2023

Print date: 19 Jan 2024

Version: 2

Page 1/11



Shine-X 500ml

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Shine-X 500ml

Article No.:

T106001

UFI:

V30X-0GRM-ENDR-1WXE

1.2. Relevant identified uses of the substance or mixture and uses advised against

No data available

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH

Hartleitnerstraße 3

4653 Eberstälzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: msds@kando.eu

Supplier:

TECH-MASTERS Austria GmbH

Gewerbestraße 1

4720 Kallham

Austria

Telephone: +43 7733 20090

Telefax: +43 7733 20092

E-mail: info@tech-masters.at

Website: www.tech-masters.eu/at

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aerosols (<i>Aerosol 1</i>)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 16 Aug 2023

Print date: 19 Jan 2024

Version: 2



Page 2/11

Shine-X 500ml

Signal word: Danger

Hazard statements for physical hazards

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

Supplemental hazard information

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

Precautionary statements Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.

Precautionary statements Storage

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
-------------	--

2.3. Other hazards

Other adverse effects:

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Additional information:

aliphatic hydrocarbons $\geq 30\%$

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 75-28-5 EC No.: 200-857-2 REACH No.: 01-2119485395-27	isobutane Flam. Gas 1A (H220), Press. Gas (Liq.) (H280) Danger	25 - < 50 Vol-%
CAS No.: 74-98-6 EC No.: 200-827-9 REACH No.: 01-2119486944-21	propane Flam. Gas 1A (H220), Press. Gas (Liq.) (H280) Danger	5 - < 10 Vol-%
CAS No.: 106-97-8 EC No.: 203-448-7 Index No.: 601-004-00-0 REACH No.: 01-2119474691-32	butane Flam. Gas 1A (H220), Press. Gas (Liq.) (H280) Danger	1 - < 3 Vol-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

Following inhalation:

Remove person to fresh air and keep comfortable for breathing. When in doubt or if symptoms are observed, get medical advice.

In case of skin contact:

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. When in doubt or if symptoms are observed, get medical advice.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 16 Aug 2023

Print date: 19 Jan 2024

Version: 2

Page 3/11



Shine-X 500ml

After eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If symptoms occur or persist, consult an ophthalmologist.

Following ingestion:

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

Self-protection of the first aider:

First aider: Pay attention to self-protection!

4.2. Most important symptoms and effects, both acute and delayed

Headache, Nausea, Dizziness, Fatigue, Skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water mist, Foam, Carbon dioxide (CO₂), Extinguishing powder

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis can produce gases of varying toxicity. In the case of products containing hydrocarbons, e.g. CO, CO₂, aldehydes and soot. These can be very dangerous if inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

Do not inhale explosion and combustion gases. Move undamaged containers from immediate hazard area if it can be done safely.

In case of fire: Wear self-contained breathing apparatus.

5.4. Additional information

Pressurised container: May burst if heated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

First aider: Pay attention to self-protection!

Protective equipment:

Wear personal protection equipment (refer to section 8).

6.1.2. For emergency responders

Personal protection equipment:

Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

For containment:

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up:

Clean contaminated articles and floor according to the environmental legislation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 16 Aug 2023

Print date: 19 Jan 2024

Version: 2

Page 4/11



Shine-X 500ml

Other information:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Further information on proper storage: see section 7.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Observe instructions for use. Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. When using do not eat, drink, smoke, sniff. Wear personal protection equipment (refer to section 8). In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Fire prevent measures:

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Advices on general occupational hygiene

Avoid exposure - obtain special instructions before use. Wear suitable work clothing. Draw up and observe skin protection programme. Avoid contact with eyes and skin.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Keep container tightly closed. The official regulations for the storage of pressurised gas packages must be observed.

Hints on storage assembly:

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Food and feedingstuffs.

Storage class (TRGS 510, Germany): 2B - Aerosol dispensers and lighters

Further information on storage conditions:

Protect from frost. Protect from direct sunlight. Store in a cool dry place. The official regulations for the storage of pressurised gas packages must be observed.

7.3. Specific end use(s)

Recommendation:

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	isobutane CAS No.: 75-28-5 EC No.: 200-857-2	② 1,600 ppm (3,800 mg/m ³) ⑤ (max. 3x60 min./SchichtMomentanwert)
MAK (AT)	isobutane CAS No.: 75-28-5 EC No.: 200-857-2	① 800 ppm (1,900 mg/m ³)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 16 Aug 2023

Print date: 19 Jan 2024

Version: 2



Page 5/11

Shine-X 500ml

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	propane CAS No.: 74-98-6 EC No.: 200-827-9	② 2,000 ppm (3,600 mg/m ³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
MAK (AT)	propane CAS No.: 74-98-6 EC No.: 200-827-9	① 1,000 ppm (1,800 mg/m ³)
MAK (AT)	butane CAS No.: 106-97-8 EC No.: 203-448-7	① 800 ppm (1,900 mg/m ³)
MAK (AT)	butane CAS No.: 106-97-8 EC No.: 203-448-7	② 1,600 ppm (3,800 mg/m ³) ⑤ (max. 3x60 min./Schicht, Momentanwert)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

No data available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

8.2.2. Personal protection equipment



Eye/face protection:

Suitable eye protection: Safety goggles with side shields (EN 166).

Skin protection:

Hand protection:

Preventive skin protection through the use of skin protectants is recommended. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Glove material: NBR (Nitrile rubber)

Breakthrough time: 480 min

Thickness of the glove material: 0,45 mm

EN ISO 374

Body protection:

Wear suitable protective clothing when working. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection:

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

If the relevant occupational exposure limits are exceeded, the following must be observed: Suitable respiratory protective device: Combination filter device (DIN EN 141). Filter unit with filter or blower filter unit type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal rules and regulations.

8.2.3. Environmental exposure controls

Observe legal rules and regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 16 Aug 2023

Print date: 19 Jan 2024

Version: 2



Page 6/11

Shine-X 500ml

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Aerosol

Colour: colourless

Odour: characteristic

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	No data available		
Initial boiling point and boiling range	-40 °C		
Flash point	-80 °C		
Evaporation rate	No data available		
Upper/lower flammability or explosive limits	1.5 – 9.4 Vol-%		
Vapour pressure	No data available		
Density	0.862 g/cm ³	20 °C	① DIN 51757
Bulk density	not applicable		
Water solubility	practically insoluble		
Kinematic viscosity	70 mm ² /s	40 °C	

9.2. Other information

The data refer to the technical active substance: relative density, colour, odour, viscosity, pH-value.

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable, Risk of ignition.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharge.

10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis can produce gases of varying toxicity. In the case of products containing hydrocarbons, e.g. CO, CO₂, aldehydes and soot. These can be very dangerous if inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

isobutane CAS No.: 75-28-5 EC No.: 200-857-2
LD₅₀ oral: >15,000 mg/kg
LD₅₀ dermal: >5,000 mg/kg
LC₅₀ Acute inhalation toxicity (vapour): >4,951 mg/L

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 16 Aug 2023

Print date: 19 Jan 2024

Version: 2

Page 7/11



Shine-X 500ml

propane CAS No.: 74-98-6 EC No.: 200-827-9
LD₅₀ oral: 5,840 mg/kg (Rat)
LD₅₀ dermal: 13,900 mg/kg (Rabbit)
LC₅₀ Acute inhalation toxicity (gas): >25 ppmV 4 h (Rat)
LC₅₀ Acute inhalation toxicity (vapour): ≥50 mg/L 4 h (Rat)
butane CAS No.: 106-97-8 EC No.: 203-448-7
LC₅₀ Acute inhalation toxicity (gas): 658 ppmV (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional information:

No data available

11.2. Information on other hazards

Endocrine disrupting properties:

This product contains a substance that has endocrine disrupting properties with respect to non-target organisms.

SECTION 12: Ecological information

12.1. Toxicity

isobutane CAS No.: 75-28-5 EC No.: 200-857-2
LC₅₀: 91.42 mg/L 4 d (fish, Fish, no other information)
LC₅₀: 100 mg/L 4 d (fish, Danio rerio)
EC₅₀: 69.43 mg/L 2 d (crustaceans, Daphnia sp.)
EC₅₀: 1,000 mg/L 2 d (fish, Daphnia magna)
ErC₅₀: 19.37 mg/L 4 d (Algae/water plant, Algae)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 16 Aug 2023

Print date: 19 Jan 2024

Version: 2



Page 8/11

Shine-X 500ml

propane CAS No.: 74-98-6 EC No.: 200-827-9

LC₅₀: 9,640 mg/L 4 d (fish, *Pimephales promelas*)

LC₅₀: 0.41 mg/L 4 d (fish, *Oncorhynchus mykiss*)

LC₅₀: 49.9 mg/L 4 d (fish)

EC₅₀: >100 mg/L (Algae/water plant, Bacteria)

EC₅₀: 0.17 mg/L 3 d (Algae/water plant, *Selenastrum capricornutum*)

EC₅₀: 69.43 mg/L 2 d (crustaceans, *Daphnia*)

NOEC: 0.017 mg/L 3 d (Algae/water plant, *Pseudokirchneriella subcapitata*)

ErC₅₀: 19.37 mg/L 4 d (Algae/water plant)

LOEC: 1,000 mg/L (Algae/water plant, Algae)

LOEC: 1,000 mg/L (Algae/water plant, Alge)

butane CAS No.: 106-97-8 EC No.: 203-448-7

LC₅₀: 49.9 mg/L 4 d (fish)

EC₅₀: 69.43 mg/L 2 d (crustaceans, *Daphnia* sp.)

ErC₅₀: 19.37 mg/L 4 d (Algae/water plant)

Aquatic toxicity:

The product is not: Ecotoxic

Assessment/classification:

No further relevant information available.

12.2. Persistence and degradability

propane CAS No.: 74-98-6 EC No.: 200-827-9

Biodegradation: Yes, rapidly

butane CAS No.: 106-97-8 EC No.: 203-448-7

Biodegradation: Yes, rapidly

Abiotic degradation:

No further relevant information available.

Additional information:

AOX (mg/l): 0

12.3. Bioaccumulative potential

isobutane CAS No.: 75-28-5 EC No.: 200-857-2

Log K_{ow}: 1.09

propane CAS No.: 74-98-6 EC No.: 200-827-9

Log K_{ow}: 1.09

butane CAS No.: 106-97-8 EC No.: 203-448-7

Log K_{ow}: 1.09

Accumulation / Evaluation:

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

isobutane CAS No.: 75-28-5 EC No.: 200-857-2

Results of PBT and vPvB assessment: —

propane CAS No.: 74-98-6 EC No.: 200-827-9

Results of PBT and vPvB assessment: —

butane CAS No.: 106-97-8 EC No.: 203-448-7

Results of PBT and vPvB assessment: —

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 16 Aug 2023

Print date: 19 Jan 2024

Version: 2



Page 9/11

Shine-X 500ml

12.6. Endocrine disrupting properties

This product contains a substance that has endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

16 05 04 *	Gases in pressure containers (including halons) containing hazardous substances
------------	---

*: Evidence for disposal must be provided.

Waste code packaging

15 01 04	metallic packaging
----------	--------------------

Waste treatment options





Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package:

Uncleaned packaging: Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name			
AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable
14.3. Transport hazard class(es)			
 2.1	 2.1	 2.1	 2.1
14.4. Packing group			
		-	
14.5. Environmental hazards			
No	No	No	No
14.6. Special precautions for user			
Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F Tunnel restriction code: (D)	Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F	Special Provisions: 63 190 277 327 344 381 959 Limited quantity (LQ): 1000 mL Excepted Quantities (EQ): E0 EmS-No.: F-D, S-U	Special Provisions: A145 A167 A802 Limited quantity (LQ): Y203 Excepted Quantities (EQ): E0 Remark: IATA Packing Instructions - Passenger: 203 IATA Maximum Quantity - Passenger: 75 kg IATA-Verpackungsanweisung - Cargo: 203

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 16 Aug 2023

Print date: 19 Jan 2024

Version: 2



Page 10/11

Shine-X 500ml

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
			IATA Maximum Quantity - Cargo: 150 kg

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Restrictions on use (REACH, Annex XVII) Entry 28, Entry 40

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
AOX	Adsorbable Organic halogen compounds
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DIN	German Institute for Standardization / German Industrial Standard
DNEL	derived no-effect level
EC ₅₀	Effective Concentration 50%
EN	European Standard
ES	Exposure scenario
EWC	European Waste Catalogue
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
ISO	International Standards Organisation
KG	body weight
LC ₅₀	Lethal (fatal) Concentration 50%
LD ₅₀	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations
ZNS	central nervous system

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 16 Aug 2023

Print date: 19 Jan 2024

Version: 2



Page 11/11

Shine-X 500ml

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aerosols (<i>Aerosol 1</i>)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.