

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2



Page 1/16

Copper Guard 500ml

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Copper Guard 500ml

Article No.:

T112002

UFI:

SGSV-TEG8-ET0F-TRJ6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Aerosol coating

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH

Hartleitnerstraße 3

4653 Eberstälzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

| Hazard classes and hazard categories | Hazard statements | Classification procedure |
|---|--|--------------------------|
| Aerosols (<i>Aerosol 1</i>) | H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated. | |
| Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>) | H319: Causes serious eye irritation. | |
| STOT-single exposure (<i>STOT SE 3</i>) | H335: May cause respiratory irritation. | |
| STOT-single exposure (<i>STOT SE 3</i>) | H336: May cause drowsiness or dizziness. | |
| Hazardous to the aquatic environment (<i>Aquatic Chronic 1</i>) | H410: Very toxic to aquatic life with long lasting effects. | |

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS07
Exclamation mark



GHS09
Environment

Signal word: Danger

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2



Page 2/16

Copper Guard 500ml

Hazard components for labelling:

acetone; Hydrocarbons, C9, aromatics; n-butyl acetate

Hazard statements for physical hazards

| | |
|------|---|
| H222 | Extremely flammable aerosol. |
| H229 | Pressurised container: May burst if heated. |

Hazard statements for health hazards

| | |
|------|------------------------------------|
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |

Hazard statements for environmental hazards

| | |
|------|---|
| H410 | Very toxic to aquatic life with long lasting effects. |
|------|---|

Supplemental hazard information

| | |
|--------|---|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
|--------|---|

Precautionary statements Prevention

| | |
|------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P211 | Do not spray on an open flame or other ignition source. |
| P251 | Do not pierce or burn, even after use. |
| P260 | Do not breathe mist/vapours/spray. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/protective clothing and eye protection/face protection. |

Precautionary statements Response

| | |
|--------------------|--|
| P304 + P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |

Precautionary statements Storage

| | |
|-------------|--|
| P403 | Store in a well-ventilated place. |
| P410 + P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. |

Precautionary statements Disposal

| | |
|------|---|
| P501 | Dispose of contents/container to an appropriate recycling or disposal facility. |
|------|---|

Additional information:

Formation of explosive mixtures possible without adequate ventilation.

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description:

Active ingredient mixture with propellant gas

Additional information:

Aerosols and containers fitted with a solid nebuliser containing substances or mixtures classified as hazardous by aspiration must not be labelled for this hazard.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2



Page 3/16

Copper Guard 500ml

Hazardous ingredients / Hazardous impurities / Stabilisers:

| Product identifiers | Substance name Classification according to Regulation (EC) No 1272/2008 [CLP] | Concentration |
|---|---|---------------------|
| CAS No.: 67-64-1 EC No.: 200-662-2 Index No.: 606-001-00-8 REACH No.: 01-2119471330-49 | acetone Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger EUH066 | 25 - < 50 Vol-% |
| CAS No.: 106-97-8 EC No.: 203-448-7 Index No.: 601-004-00-0 REACH No.: 01-2119474691-32 | Butane (with < 0,1 % butadiene (203-450-8)) Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger | 10 - < 25 Vol-% |
| CAS No.: 74-98-6 EC No.: 200-827-9 Index No.: 601-003-00-5 REACH No.: 01-2119486944-21 | propane Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger | 10 - < 25 Vol-% |
| CAS No.: 128601-23-0 EC No.: 918-668-5 REACH No.: 01-2119455851-35 | Hydrocarbons, C9, aromatics Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 3 (H226), STOT SE 3 (H335, H336) Danger | 10 - < 25 Vol-% |
| CAS No.: 123-86-4 EC No.: 204-658-1 REACH No.: 01-2119485493-29-XXXX | n-butyl acetate Substance with a community workplace exposure limit. | 2.5 - < 10 Vol-% |
| CAS No.: 7440-50-8 EC No.: 231-159-6 REACH No.: 01-2119480154-42 | copper Acute Tox. 3 (H331), Acute Tox. 4 (H302), Aquatic Acute 1 (H400), Aquatic Chronic 1 (H410), Eye Irrit. 2 (H319) Danger M-factor (acute): 1 M-factor (chronic): 10 | 2.5 - < 10 Vol-% |
| CAS No.: 75-28-5 EC No.: 200-857-2 REACH No.: 01-2119485395-27 | Isobutane (with < 0.1 % butadiene (203-450-8)) Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger | 2.5 - < 10 Vol-% |

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Following inhalation:

Fresh air supply, consult a doctor in case of complaints.

In case of skin contact:

In general, the product is not irritating to skin.

After eye contact:

Rinse opened eye for several minutes under running water. Consult a doctor if symptoms persist

Following ingestion:

Do not induce vomiting, seek medical help immediately.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water mist, Extinguishing powder, Carbon dioxide, alcohol resistant foam

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2



Page 4/16

Copper Guard 500ml

Unsuitable extinguishing media:

Water in full jet

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Special protective equipment: Put on breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear protective equipment. Keep unprotected persons away.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of spillage into water or sewage system, inform the competent authorities.

6.3. Methods and material for containment and cleaning up

Other information:

Provide adequate ventilation. Do not wash away with water or aqueous detergents.

6.4. Reference to other sections

See section 7 for further information on safe handling.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Ensure good ventilation/extraction at the workplace.

Fire prevent measures:

Do not spray on naked flames or any incandescent material. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Container is under pressure. Protect from sunlight and temperatures above 50°C (e.g. from incandescent lamps). Do not open by force or burn even after use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Store in a cool place. The official regulations for the storage of pressurised gas packages must be observed.

Hints on storage assembly:

The official regulations for the storage of pressurised gas packages must be observed.

Storage class (TRGS 510, Germany): 2B - Aerosol dispensers and lighters

Further information on storage conditions:

Store in a cool, dry place in well-sealed containers. Protect from heat and direct sunlight.

7.3. Specific end use(s)

Recommendation:

No further relevant information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2



Page 5/16

Copper Guard 500ml

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

| Limit value type (country of origin) | Substance name | ① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark |
|--|---|--|
| MAK (AT) | acetone CAS No.: 67-64-1 EC No.: 200-662-2 | ② 2,000 ppm (4,800 mg/m ³) ⑤ (max. 4x15 min./Schicht) |
| IOELV (EU) | acetone CAS No.: 67-64-1 EC No.: 200-662-2 | ① 500 ppm (1,210 mg/m ³) |
| MAK (AT) | acetone CAS No.: 67-64-1 EC No.: 200-662-2 | ① 500 ppm (1,200 mg/m ³) |
| MAK (AT) | Butane (with < 0,1 % butadiene (203-450-8)) CAS No.: 106-97-8 EC No.: 203-448-7 | ① 800 ppm (1,900 mg/m ³) |
| MAK (AT) | Butane (with < 0,1 % butadiene (203-450-8)) CAS No.: 106-97-8 EC No.: 203-448-7 | ② 1,600 ppm (3,800 mg/m ³) ⑤ (max. 3x60 min./Schicht, Momentanwert) |
| MAK (AT) | propane CAS No.: 74-98-6 EC No.: 200-827-9 | ② 2,000 ppm (3,600 mg/m ³) ⑤ (max. 3x60 min./Schicht, Momentanwert) |
| MAK (AT) | propane CAS No.: 74-98-6 EC No.: 200-827-9 | ① 1,000 ppm (1,800 mg/m ³) |
| MAK (AT) from 10 Apr 2021 | n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | ① 50 ppm (241 mg/m ³) ② 100 ppm (480 mg/m ³) |
| IOELV (EU) from 20 Nov 2019 | n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | ① 50 ppm (241 mg/m ³) ② 150 ppm (723 mg/m ³) |
| MAK (AT) | copper CAS No.: 7440-50-8 EC No.: 231-159-6 | ① 1 mg/m ³ ② 4 mg/m ³ ⑤ (einatembare Fraktion, max. 4x15 min./Schicht) |
| MAK (AT) | copper CAS No.: 7440-50-8 EC No.: 231-159-6 | ① 0.1 mg/m ³ ② 0.4 mg/m ³ ⑤ (alveolengängige Fraktion max. 4x15 min./Schicht) |
| MAK (AT) | Isobutane (with < 0.1 % butadiene (203-450-8)) CAS No.: 75-28-5 EC No.: 200-857-2 | ② 1,600 ppm (3,800 mg/m ³) ⑤ (max. 3x60 min./Schicht Momentanwert) |
| MAK (AT) | Isobutane (with < 0.1 % butadiene (203-450-8)) CAS No.: 75-28-5 EC No.: 200-857-2 | ① 800 ppm (1,900 mg/m ³) |

8.1.2. Biological limit values

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2



Page 6/16

Copper Guard 500ml

8.1.3. DNEL-/PNEC-values

| Substance name | DNEL value | ① DNEL type ② Exposure route |
|---|-------------------------|---|
| acetone CAS No.: 67-64-1 EC No.: 200-662-2 | 1,210 mg/m ³ | ① DNEL worker ② Long-term - inhalation, systemic effects |
| acetone CAS No.: 67-64-1 EC No.: 200-662-2 | 200 mg/m ³ | ① DNEL Consumer ② Long-term - inhalation, systemic effects |
| acetone CAS No.: 67-64-1 EC No.: 200-662-2 | 2,420 mg/m ³ | ① DNEL worker ② Acute - inhalation, local effects |
| acetone CAS No.: 67-64-1 EC No.: 200-662-2 | 186 mg/kg bw/ day | ① DNEL worker ② Long-term - dermal, systemic effects |
| acetone CAS No.: 67-64-1 EC No.: 200-662-2 | 62 mg/kg bw/ day | ① DNEL Consumer ② Long-term - dermal, systemic effects |
| acetone CAS No.: 67-64-1 EC No.: 200-662-2 | 62 mg/kg bw/ day | ① DNEL Consumer ② Long-term - oral, systemic effects |
| Hydrocarbons, C9, aromatics CAS No.: 128601-23-0 EC No.: 918-668-5 | 100 mg/m ³ | ① DNEL worker ② Long-term - inhalation, systemic effects |
| Hydrocarbons, C9, aromatics CAS No.: 128601-23-0 EC No.: 918-668-5 | 32 mg/m ³ | ① DNEL Consumer ② Long-term - inhalation, systemic effects |
| Hydrocarbons, C9, aromatics CAS No.: 128601-23-0 EC No.: 918-668-5 | 25 mg/kg bw/ day | ① DNEL worker ② Long-term - dermal, systemic effects |
| Hydrocarbons, C9, aromatics CAS No.: 128601-23-0 EC No.: 918-668-5 | 11 mg/kg bw/ day | ① DNEL Consumer ② Long-term - dermal, systemic effects |
| Hydrocarbons, C9, aromatics CAS No.: 128601-23-0 EC No.: 918-668-5 | 11 mg/kg bw/ day | ① DNEL Consumer ② Long-term - oral, systemic effects |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 300 mg/m ³ | ① DNEL worker ② Long-term - inhalation, systemic effects |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 35.7 mg/m ³ | ① DNEL Consumer ② Long-term - inhalation, systemic effects |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 600 mg/m ³ | ① DNEL worker ② Acute - inhalation, systemic effects |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 859.7 mg/m ³ | ① DNEL Consumer ② Acute - inhalation, systemic effects |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 300 mg/m ³ | ① DNEL worker ② Long-term - inhalation, local effects |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 35.7 mg/m ³ | ① DNEL Consumer ② Long-term - inhalation, local effects |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 600 mg/m ³ | ① DNEL worker ② Acute - inhalation, local effects |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 300 mg/m ³ | ① DNEL Consumer ② Acute - inhalation, local effects |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2



Page 7/16

Copper Guard 500ml

| Substance name | DNEL value | ① DNEL type ② Exposure route |
|--|-----------------------|--|
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 11 mg/kg bw/ day | ① DNEL worker ② Long-term - dermal, systemic effects |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 5 mg/kg bw/ day | ① DNEL Consumer ② Long-term - dermal, systemic effects |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 11 mg/kg bw/ day | ① DNEL worker ② Acute - dermal, systemic effects |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 5 mg/kg bw/ day | ① DNEL Consumer ② Acute - dermal, systemic effects |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 2 mg/kg bw/ day | ① DNEL Consumer ② Long-term - oral, systemic effects |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 2 mg/kg bw/ day | ① DNEL Consumer ② Acute - oral, systemic effects |
| copper CAS No.: 7440-50-8 EC No.: 231-159-6 | 20 mg/m ³ | ① DNEL worker ② Acute - inhalation, systemic effects |
| copper CAS No.: 7440-50-8 EC No.: 231-159-6 | 20 mg/m ³ | ① DNEL Consumer ② Acute - inhalation, systemic effects |
| copper CAS No.: 7440-50-8 EC No.: 231-159-6 | 1 mg/m ³ | ① DNEL Consumer ② Long-term - inhalation, local effects |
| copper CAS No.: 7440-50-8 EC No.: 231-159-6 | 1 mg/m ³ | ① DNEL Consumer ② Acute - inhalation, local effects |
| copper CAS No.: 7440-50-8 EC No.: 231-159-6 | 137 mg/kg bw/ day | ① DNEL worker ② Long-term - dermal, systemic effects |
| copper CAS No.: 7440-50-8 EC No.: 231-159-6 | 137 mg/kg bw/ day | ① DNEL Consumer ② Long-term - dermal, systemic effects |
| copper CAS No.: 7440-50-8 EC No.: 231-159-6 | 273 mg/kg bw/ day | ① DNEL worker ② Acute - dermal, systemic effects |
| copper CAS No.: 7440-50-8 EC No.: 231-159-6 | 273 mg/kg bw/ day | ① DNEL Consumer ② Acute - dermal, systemic effects |
| copper CAS No.: 7440-50-8 EC No.: 231-159-6 | 0.041 mg/kg bw/day | ① DNEL Consumer ② Long-term - oral, systemic effects |

| Substance name | PNEC Value | ① PNEC type |
|---|------------|-------------------------------|
| acetone CAS No.: 67-64-1 EC No.: 200-662-2 | 10.6 mg/L | ① PNEC aquatic, freshwater |
| acetone CAS No.: 67-64-1 EC No.: 200-662-2 | 1.06 mg/L | ① PNEC aquatic, marine water |
| acetone CAS No.: 67-64-1 EC No.: 200-662-2 | 100 mg/L | ① PNEC sewage treatment plant |
| acetone CAS No.: 67-64-1 EC No.: 200-662-2 | 30.4 mg/kg | ① PNEC sediment, freshwater |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2



Page 8/16

Copper Guard 500ml

| Substance name | PNEC Value | ① PNEC type |
|--|--------------|--------------------------------------|
| acetone CAS No.: 67-64-1 EC No.: 200-662-2 | 3.04 mg/kg | ① PNEC sediment, marine water |
| acetone CAS No.: 67-64-1 EC No.: 200-662-2 | 29.5 mg/kg | ① PNEC soil |
| acetone CAS No.: 67-64-1 EC No.: 200-662-2 | 21 mg/L | ① PNEC aquatic, intermittent release |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 0.18 mg/L | ① PNEC aquatic, freshwater |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 0.015 mg/L | ① PNEC aquatic, marine water |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 35.6 mg/L | ① PNEC sewage treatment plant |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 0.981 mg/L | ① PNEC sediment, freshwater |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 0.0981 mg/L | ① PNEC sediment, marine water |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 0.0903 mg/kg | ① PNEC soil |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 | 0.36 | ① PNEC aquatic, intermittent release |

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No further details. See section 7.

8.2.2. Personal protection equipment



Eye/face protection:

Safety goggles (EN-166)

Skin protection:

Hand protection:

Gloves / solvent resistant

Breakthrough times and swelling properties of the material must be taken into consideration.

Glove material:

The selection of a suitable glove depends not only on the material but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use. NBR (Nitrile rubber)

Recommended material thickness: $\geq 0,5$ mm

Permeation time (maximum wear duration):

For continuous contact we recommend gloves with a breakthrough time of at least 240 minutes, with the preference for a breakthrough time greater than 480 minutes. For short term or splash protection we recommend the same. We are aware that suitable gloves offering this protection are not available. In this case, a shorter breakthrough time is permissible, provided the procedures for maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance the

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2



Page 9/16

Copper Guard 500ml

gloves give against a chemical substance, as this depends on the exact composition of the material of the gloves. The exact breakthrough time should be checked with the glove manufacturer and adhered to.

Body protection:

Use protective suit. (EN-13034/6)

Antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149 EN340&EN ISO 13688 EN13034-6).

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Filter A2/P2

Other protection measures:

General protective and hygienic measures:

Keep away from food, drink and animal feed.

Remove contaminated, saturated clothing immediately.

Wash hands before breaks and after work.

Do not inhale gases/vapours/aerosols.

Avoid contact with eyes and skin.

General ventilation.

8.2.3. Environmental exposure controls

Use a suitable container to prevent environmental pollution.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Aerosol

Colour: According to product designation

Odour: characteristic

Safety relevant basis data

| Parameter | Value | at °C | ① Method ② Remark |
|--|--------------------------|-------|--|
| pH | <i>not applicable</i> | | ② Mixture is not polar/aprotic. |
| Initial boiling point and boiling range | -44.5 °C | | |
| Flash point | -97 °C | | |
| Evaporation rate | <i>No data available</i> | | |
| Auto-ignition temperature | 365 °C | | ② Butane (with < 0,1 % butadiene (203-450-8)) (106-97-8) |
| Upper/lower flammability or explosive limits | 0.7 - 13 Vol-% | | |
| Vapour pressure | 8,300 hPa | 20 °C | ② propane (74-98-6) |
| Density | 1.084 g/cm ³ | 20 °C | |
| Bulk density | <i>not applicable</i> | | |
| Water solubility | Immiscible | | |

9.2. Other information

The product is not self-igniting. The product is not explosive, but the formation of explosive vapour/air mixtures is possible. formation of explosive vapour/air mixtures is possible.

Organic solvents: 90,7%

Solid content: 9,6%

9.2.1. Information with regard to physical hazard classes

Explosives:

Not applicable

Flammable gases:

Not applicable

Aerosols:

Extremely flammable aerosol. Pressurized container: May burst if heated.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2



Page 10/16

Copper Guard 500ml

Oxidizing gases:

Not applicable

Gases under pressure:

Not applicable

Flammable liquids:

Not applicable

Flammable solids:

Not applicable

Self-reactive substances and mixtures:

Not applicable

Pyrophoric liquids:

Not applicable

Pyrophoric solids:

Not applicable

Self-heating substances and mixtures:

Not applicable

Substances or mixtures which, in contact with water, emit flammable gases:

Not applicable

Oxidizing liquids:

Not applicable

Oxidizing solids:

Not applicable

Organic peroxides:

Not applicable

Corrosive to metals:

Not applicable

Desensitised explosives:

Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

Thermal decomposition / Conditions to avoid: No decomposition when used as directed.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No dangerous decomposition products known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2

Page 11/16



Copper Guard 500ml

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

| |
|---|
| acetone CAS No.: 67-64-1 EC No.: 200-662-2 |
| ATE (oral): 5,800 mg/kg |
| ATE (dermal): 20,000 mg/kg |
| ATE (inhalation, dust/mist): 76 mg/L |
| LD₅₀ oral: 5,800 mg/kg (Rat) |
| LD₅₀ dermal: >7,800 mg/kg (Rabbit) |
| LC₅₀ Acute inhalation toxicity (dust/mist): 76 mg/L 4 h (Rat) |
| propane CAS No.: 74-98-6 EC No.: 200-827-9 |
| LD₅₀ oral: 5,840 mg/kg (Rat) |
| LD₅₀ dermal: 13,900 mg/kg (Rabbit) |
| LC₅₀ Acute inhalation toxicity (gas): >25 ppmV 4 h (Rat) |
| LC₅₀ Acute inhalation toxicity (vapour): ≥50 mg/L 4 h (Rat) |
| Hydrocarbons, C9, aromatics CAS No.: 128601-23-0 EC No.: 918-668-5 |
| LD₅₀ oral: 3,492 mg/kg (Rat) |
| LD₅₀ dermal: >3,160 mg/kg (Rabbit) |
| LC₅₀ Acute inhalation toxicity (gas): >6,193 ppmV 4 h (Rat) |
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 |
| LD₅₀ oral: >6,400 mg/kg (Rat) |
| LD₅₀ dermal: >5,000 mg/kg (Rabbit) |
| LC₅₀ Acute inhalation toxicity (gas): >23.4 ppmV 4 h (Rat) |
| LC₅₀ Acute inhalation toxicity (vapour): 21.1 mg/L 4 h (Rat) |
| copper CAS No.: 7440-50-8 EC No.: 231-159-6 |
| LD₅₀ oral: >2,000 mg/kg (Rat) |
| LD₅₀ dermal: 300 - 2,500 mg/kg (Rat) |
| LC₅₀ Acute inhalation toxicity (dust/mist): 5.11 mg/L (Rat) |

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2

Page 12/16



Copper Guard 500ml

Aspiration hazard:

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties:

None of the ingredients are included.

SECTION 12: Ecological information

12.1. Toxicity

| | | |
|---|----------------------|-------------------|
| acetone | CAS No.: 67-64-1 | EC No.: 200-662-2 |
| LC ₅₀ : 8,300 mg/L 4 d (fish) | | |
| LC ₅₀ : 8,450 mg/L 2 d (crustaceans) | | |
| EC ₅₀ : 7,200 mg/L 4 d (Algae/water plant) | | |
| propane | CAS No.: 74-98-6 | EC No.: 200-827-9 |
| LC ₅₀ : 9,640 mg/L 4 d (fish, Pimephales promelas) | | |
| LC ₅₀ : 0.41 mg/L 4 d (fish, Oncorhynchus mykiss) | | |
| LC ₅₀ : 49.9 mg/L 4 d (fish) | | |
| EC ₅₀ : >100 mg/L (Algae/water plant, Bacteria) | | |
| EC ₅₀ : 0.17 mg/L 3 d (Algae/water plant, Selenastrum capricornutum) | | |
| EC ₅₀ : 69.43 mg/L 2 d (crustaceans, Daphnia) | | |
| NOEC: 0.017 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata) | | |
| ErC ₅₀ : 19.37 mg/L 4 d (Algae/water plant) | | |
| LOEC: 1,000 mg/L (Algae/water plant, Algae) | | |
| LOEC: 1,000 mg/L (Algae/water plant, Alge) | | |
| Hydrocarbons, C9, aromatics | CAS No.: 128601-23-0 | EC No.: 918-668-5 |
| EC ₅₀ : 3.2 mg/L 2 d (crustaceans, Daphnia magna) | | |
| EC ₅₀ : 2.75 mg/L 3 d (Algae/water plant, Pseudokirchneriella Subcapitata) | | |
| EC ₅₀ : 9.2 mg/L 4 d (fish) | | |
| n-butyl acetate | CAS No.: 123-86-4 | EC No.: 204-658-1 |
| LC ₅₀ : 18 mg/L 4 d (fish, Pimephales promelas) | | |
| EC ₅₀ : 44 mg/L 2 d (crustaceans, Daphnia magna) | | |
| EC ₅₀ : 675 mg/L 3 d (Algae/water plant, Scenedesmus subspicatus) | | |
| NOEC: 23.2 mg/L (crustaceans, Daphnia magna) | | |
| copper | CAS No.: 7440-50-8 | EC No.: 231-159-6 |
| LC ₅₀ : 0.000072 mg/L 2 d (crustaceans, Krustazeen) | | |
| LC ₅₀ : 0.000072 mg/L 2 d (crustaceans, Krustazeen, Adultus) | | |
| LC ₅₀ : 0.000072 mg/L 2 d (crustaceans, Amphipoda) | | |
| EC ₅₀ : 0.0021 mg/L 2 d (crustaceans, Daphnia) | | |
| NOEC: 0.0008 mg/L (fish, Oreochromis niloticus) | | |
| NOEC: 0.0008 mg/L (crustaceans, Krustazeen) | | |
| IC ₅₀ : 0.016 mg/L 3 d (Algae/water plant, Chlorella pyrenoidosa) | | |
| IC ₅₀ : 0.016 mg/L 3 d (Algae/water plant, Chlorella pyrenoidosa) | | |

Aquatic toxicity:

No further relevant information available.

Assessment/classification:

No further relevant information available.

12.2. Persistence and degradability

| | | |
|-------------------------------------|------------------|-------------------|
| acetone | CAS No.: 67-64-1 | EC No.: 200-662-2 |
| Biodegradation: Yes, rapidly | | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2

Page 13/16



Copper Guard 500ml

| |
|---|
| propane CAS No.: 74-98-6 EC No.: 200-827-9 |
|---|

| |
|-------------------------------------|
| Biodegradation: Yes, rapidly |
|-------------------------------------|

| |
|--|
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 |
|--|

| |
|-------------------------------------|
| Biodegradation: Yes, rapidly |
|-------------------------------------|

Biodegradation:

Not readily biodegradable.

12.3. Bioaccumulative potential

| |
|---|
| acetone CAS No.: 67-64-1 EC No.: 200-662-2 |
|---|

| |
|----------------------------------|
| Log K_{ow}: -0.24 |
|----------------------------------|

| |
|---|
| propane CAS No.: 74-98-6 EC No.: 200-827-9 |
|---|

| |
|---------------------------------|
| Log K_{ow}: 1.09 |
|---------------------------------|

| |
|--|
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 |
|--|

| |
|--------------------------------|
| Log K_{ow}: 2.3 |
|--------------------------------|

| |
|--|
| Bioconcentration factor (BCF): 15.3 |
|--|

Accumulation / Evaluation:

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

| |
|---|
| acetone CAS No.: 67-64-1 EC No.: 200-662-2 |
|---|

| |
|--|
| Results of PBT and vPvB assessment: — |
|--|

| |
|---|
| Butane (with < 0,1 % butadiene (203-450-8)) CAS No.: 106-97-8 EC No.: 203-448-7 |
|---|

| |
|--|
| Results of PBT and vPvB assessment: — |
|--|

| |
|---|
| propane CAS No.: 74-98-6 EC No.: 200-827-9 |
|---|

| |
|--|
| Results of PBT and vPvB assessment: — |
|--|

| |
|---|
| Hydrocarbons, C9, aromatics CAS No.: 128601-23-0 EC No.: 918-668-5 |
|---|

| |
|--|
| Results of PBT and vPvB assessment: — |
|--|

| |
|--|
| n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1 |
|--|

| |
|--|
| Results of PBT and vPvB assessment: — |
|--|

| |
|--|
| copper CAS No.: 7440-50-8 EC No.: 231-159-6 |
|--|

| |
|--|
| Results of PBT and vPvB assessment: — |
|--|

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Drinking water hazard even when small quantities leak into the subsoil.

Harmful to fish. Harmful to aquatic life.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Must not be disposed of together with household waste. Do not allow to enter into surface water or drains.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

| | |
|----------|--------------------------------|
| 08 02 99 | Wastes not otherwise specified |
|----------|--------------------------------|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2



Page 14/16

Copper Guard 500ml

Directive 2008/98/EC (Waste Framework Directive)








| | |
|-------|---|
| HP 3 | Flammable |
| HP 4 | Irritant — skin irritation and eye damage |
| HP 5 | Specific Target Organ Toxicity (STOT)/Aspiration Toxicity |
| HP 14 | Ecotoxic |

Waste treatment options

Appropriate disposal / Package:

Uncleaned packaging: Dispose of waste according to applicable legislation.

SECTION 14: Transport information

| Land transport (ADR/RID) | Inland waterway craft (ADN) | Sea transport (IMDG) | Air transport (ICAO-TI / IATA-DGR) |
|--|--|---|--|
| 14.1. UN number or ID number | | | |
| UN 1950 | UN 1950 | UN 1950 | UN 1950 |
| 14.2. UN proper shipping name | | | |
| AEROSOLS, ENVIRONMENTALLY HAZARDOUS (Hydrocarbons, C9, aromatics) | AEROSOLS, ENVIRONMENTALLY HAZARDOUS (Hydrocarbons, C9, aromatics) | AEROSOLS, MARINE POLLUTANT (Hydrocarbons, C9, aromatics) | AEROSOLS, flammable (Hydrocarbons, C9, aromatics) |
| 14.3. Transport hazard class(es) | | | |
|  2.1 |  2.1 |  2.1 |  2.1 |
| 14.4. Packing group | | | |
| | | - | |
| 14.5. Environmental hazards | | | |
|  |  |  MARINE POLLUTANT | No |
| 14.6. Special precautions for user | | | |
| Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F Tunnel restriction code: (D) Remark: Attention: Gases | Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F Remark: Attention: Gases | Special Provisions: 63 190 277 327 344 381 959 Limited quantity (LQ): Siehe SV277 Excepted Quantities (EQ): E0 EmS-No.: F-D, S-U Remark: Attention: Gases | Special Provisions: A145 A167 Limited quantity (LQ): Y203 Excepted Quantities (EQ): E0 Remark: Attention: Gases |

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Directive 2012/18/EU

Named dangerous substances - ANNEX I: None of the ingredients are included.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2



Page 15/16

Copper Guard 500ml

Restrictions on use:

Regulation (EC) No 1907/2006 ANNEX XVII: Restriction conditions: 3

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II: None of the ingredients are included.

Regulation (EU) 2019/1148

Annex I - RESTRICTED EXPORT SUBSTANCES FOR EXPLOSIVES (upper concentration limit for a permit pursuant to Article 5(3)): None of the ingredients are included.

Annex II - EXPLOSIVES REPORTABLE FOR EXPLOSIVES: Acetone (67-64-1)

Regulation (EC) No 273/2004 on drug precursors: Acetone (67-64-1)

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade in drug precursors between the Community and third countries: Acetone (67-64-1)

Other regulations (EU):

Hazard categories:

- P3a 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids
- E2 Hazardous to the Aquatic Environment in Category Chronic 2

Named dangerous substances:

- Liquefied flammable gases, Category 1 or 2 (including liquefied petroleum gas) and natural gas

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 983 g/L

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

| | |
|------------------|---|
| ACGIH | American Conference of Governmental Industrial Hygienists |
| ADN | European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways |
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| BCF | Bioconcentration Factor |
| CAS | Chemical Abstracts Service |
| CLP | Classification, Labelling and Packaging |
| DNEL | derived no-effect level |
| EC ₅₀ | Effective Concentration 50% |
| EN | European Standard |
| ES | Exposure scenario |
| EWC | European Waste Catalogue |
| ICAO | International Civil Aviation Organization |
| IMDG | International Maritime Dangerous Goods |
| IMO | International Maritime Organization |
| KG | body weight |
| LC ₅₀ | Lethal (fatal) Concentration 50% |
| LD ₅₀ | Lethal (fatal) Dose 50% |
| MAK | Maximum concentration in the workplace air (CH) |
| NFPA | National Fire Protection Association |
| NIOSH | National Institute for Occupational Safety & Health |
| NOEC | No Observed Effect Concentration |
| OECD | Organisation for Economic Cooperation and Development |
| OEL | Threshold Limit Value |
| OSHA | Occupational Safety & Health Administration |
| PBT | persistent and bioaccumulative and toxic |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 2 Aug 2023

Print date: 19 Feb 2024

Version: 2



Page 16/16

Copper Guard 500ml

PNEC Predicted No Effect Concentration
REACH Registration, Evaluation and Authorization of Chemicals
RID Dangerous goods regulations for transport by rail
SCL Specific concentration limit
TRGS Technische Regeln für Gefahrstoffe
UN United Nations
ZNS central nervous system

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

| Hazard classes and hazard categories | Hazard statements | Classification procedure |
|---|--|--------------------------|
| Aerosols (<i>Aerosol 1</i>) | H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated. | |
| Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>) | H319: Causes serious eye irritation. | |
| STOT-single exposure (<i>STOT SE 3</i>) | H335: May cause respiratory irritation. | |
| STOT-single exposure (<i>STOT SE 3</i>) | H336: May cause drowsiness or dizziness. | |
| Hazardous to the aquatic environment (<i>Aquatic Chronic 1</i>) | H410: Very toxic to aquatic life with long lasting effects. | |

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

| Hazard statements | |
|---------------------------------|---|
| H220 | Extremely flammable gas. |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H280 | Contains gas under pressure; may explode if heated. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| Supplemental hazard information | |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.