according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 24 Jan 2023 Print date: 15 Feb 2024

Version: 2 Page 1/13



Multi Tech 5 51

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Multi Tech 5 51

Article No.:

T232005

UFI:

SJ5G-6XJ1-CMJC-QHWU

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Lubricating agent

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH

Hartleitnerstraße 3 4653 Eberstalzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (Flam. Liq. 3)	H226: Flammable liquid and vapour.	
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (Aquatic Chronic 3)	H412: Harmful to aquatic life with long lasting effects.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



GHS02 Flame

GHS07 Exclamation mark



GHS08 Health hazard

Signal word: Danger

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 24 Jan 2023 Print date: 15 Feb 2024

Version: 2 Page 2/13



Multi Tech 5 51

Hazard components for labelling:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics; Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Hazard statements for physical hazards	
H226	Flammable liquid and vapour.

Hazard statements for health hazards		
H304	May be fatal if swallowed and enters airways.	
H336	May cause drowsiness or dizziness.	

Hazard statements for environmental hazards		
H412	Harmful to aquatic life with long lasting effects.	

Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.

Precautionary statements Prevention		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P243	Take action to prevent static discharges.	
P261	Avoid breathing vapours.	
P271	Use only outdoors or in a well-ventilated area.	
P273	Avoid release to the environment.	
P280	Wear protective gloves.	

Precautionary stat	Precautionary statements Response		
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.		
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.		
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P312	Call a POISON CENTER if you feel unwell.		
P331	Do NOT induce vomiting.		
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.		

Precautionary statements Disposal		
P501	Dispose of contents/container to an appropriate recycling or disposal facility.	

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers		Concentration
	Classification according to Regulation (EC) No 1272/2008 [CLP]	
CAS No.: 1174921-73-3	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2%	20 - < 100
EC No.: 927-241-2	aromatics	%
REACH No.:	Aquatic Chronic 3 (H412), Asp. Tox. 1 (H304), Flam. Liq. 3 (H226),	
01-2119471843-32	STOT SE 3 (H336)	
	♦ ! \ \ \ \ \ \ \ \ \ \	
	Aliphatic hydrocarbons, fragrances	≥ 30
	The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].	%

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 24 Jan 2023 Print date: 15 Feb 2024

Version: 2 Page 3/13



Multi Tech 5 51

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 64742-48-9 EC No.: 918-481-9 REACH No.: 01-2119463258-33	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics Asp. Tox. 1 (H304) Danger	10 - < 20 %
CAS No.: 1471316-72-9 EC No.: 939-603-7 REACH No.: 01-2119978241-36	Benzenesulphonic acids, di-C10-14-alkyl derivatives, calcium salts Skin Sens. 1B (H317) ↑ Warning Specific concentration limit (SCL) Skin Sens. 1B; H317: 10% ≤ C < 100%	0.1 - < 1

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Following inhalation:

Remove person to fresh air and keep comfortable for breathing. When in doubt or if symptoms are observed, get medical advice.

In case of skin contact:

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. When in doubt or if symptoms are observed, get medical advice.

After eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

Following ingestion:

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

Self-protection of the first aider:

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

4.2. Most important symptoms and effects, both acute and delayed

Headache, Nausea, Dizziness, Fatigue, Skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water mist, Foam, Carbon dioxide (CO2), Extinguishing powder

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis can produce gases of varying toxicity. In the case of products containing hydrocarbons, e.g. CO, CO2, aldehydes and soot. These can be very dangerous if inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

Do not inhale explosion and combustion gases. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 24 Jan 2023 Print date: 15 Feb 2024

Version: 2 Page 4/13 TECH MASTERS

world of innovations

Multi Tech 5 51

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

First aider: Pay attention to self-protection! Wear personal protection equipment (refer to section 8).

6.1.2. For emergency responders

Personal protection equipment:

Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

For containment:

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up:

Clean contaminated articles and floor according to the environmental legislation.

Other information:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Further information on proper storage: see section 7.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

6.5. Additional information

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Observe instructions for use. Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. When using do not eat, drink, smoke, sniff. Wear personal protection equipment (refer to section 8).

Fire prevent measures:

Keep away from sources of ignition - No smoking.

Advices on general occupational hygiene

Avoid exposure - obtain special instructions before use. Wear suitable work clothing. Draw up and observe skin protection programme. Avoid contact with eyes and skin.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Keep container tightly closed.

Hints on storage assembly:

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Food and feedingstuffs.

Storage class (TRGS 510, Germany): 3 - Flammable liquids

Further information on storage conditions:

Store in a cool, dry place in well-sealed containers.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 24 Jan 2023 Print date: 15 Feb 2024

Version: 2 Page 5/13



Multi Tech 5 51

7.3. Specific end use(s)

Recommendation:

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
MAK (AT)	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics CAS No.: 64742-48-9 EC No.: 918-481-9	① 200 mL/m³ ② 400 mL/m³ ⑤ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von weniger als 1 %, an n-Hexan von weniger als 5 % und an Cyclo-/ Isohexanen von weniger als 25 %)
MAK (AT)	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics CAS No.: 64742-48-9 EC No.: 918-481-9	① 170 mL/m³ ② 340 mL/m³ ⑤ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von weniger als 1 %, an n-Hexan von weniger als 5 % und an Cyclo-/ Isohexanen von 25 % oder mehr)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type
		② Exposure route
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics CAS No.: 1174921-73-3 EC No.: 927-241-2	871 mg/m³	① DNEL worker ② Long-term – inhalation, systemic effects
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics CAS No.: 1174921-73-3 EC No.: 927-241-2	185 mg/m³	① DNEL Consumer ② Long-term – inhalation, systemic effects
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics CAS No.: 1174921-73-3 EC No.: 927-241-2	77 mg/kg bw/ day	DNEL worker Long-term - dermal, systemic effects
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics CAS No.: 1174921-73-3 EC No.: 927-241-2	46 mg/kg bw/ day	DNEL Consumer Long-term - dermal, systemic effects
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics CAS No.: 1174921-73-3 EC No.: 927-241-2	46 mg/kg bw/ day	DNEL Consumer Long-term - oral, systemic effects
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics CAS No.: 64742-48-9 EC No.: 918-481-9	871 mg/m³	① DNEL worker ② Long-term – inhalation, systemic effects

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 24 Jan 2023 Print date: 15 Feb 2024

Version: 2 Page 6/13



Multi Tech 5 51

Substance name	DNEL value	① DNEL type	
		② Exposure route	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics CAS No.: 64742-48-9 EC No.: 918-481-9	185 mg/m³	① DNEL Consumer ② Long-term – inhalation, systemic effects	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics CAS No.: 64742-48-9 EC No.: 918-481-9	208 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics CAS No.: 64742-48-9 EC No.: 918-481-9	125 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics CAS No.: 64742-48-9 EC No.: 918-481-9	125 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects	
Benzenesulphonic acids, di-C10-14-alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-603-7	35.26 mg/m ³	① DNEL worker ② Long-term – inhalation, systemic effects	
Benzenesulphonic acids, di-C10-14-alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-603-7	8.7 mg/m ³	① DNEL Consumer ② Long-term – inhalation, systemic effects	
Benzenesulphonic acids, di-C10-14- alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-603-7	25 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects	
Benzenesulphonic acids, di-C10-14- alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-603-7	12.5 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects	
Benzenesulphonic acids, di-C10-14- alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-603-7	1.04 mg/cm ²	① DNEL worker ② Acute - dermal, local effects	
Benzenesulphonic acids, di-C10-14- alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-603-7	0.518 mg/cm ²	① DNEL Consumer ② Acute - dermal, local effects	
Benzenesulphonic acids, di-C10-14- alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-603-7	2.5 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects	
Substance name	PNEC Value	① PNEC type	
Benzenesulphonic acids, di-C10-14- alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-603-7	0.1 mg/L	① PNEC aquatic, freshwater	
Benzenesulphonic acids, di-C10-14-alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-603-7	0.1 mg/L	① PNEC aquatic, marine water	
Benzenesulphonic acids, di-C10-14- alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-603-7	1,000 mg/L	① PNEC sewage treatment plant	

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 24 Jan 2023 Print date: 15 Feb 2024

Version: 2 Page 7/13



Multi Tech 5 51

Substance name	PNEC Value	① PNEC type
Benzenesulphonic acids, di-C10-14- alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-603-7	45,211 mg/kg	① PNEC sediment, freshwater
Benzenesulphonic acids, di-C10-14- alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-603-7	45,211 mg/kg	① PNEC sediment, marine water
Benzenesulphonic acids, di-C10-14- alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-603-7	36,729.74 mg/ kg	① PNEC soil
Benzenesulphonic acids, di-C10-14- alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-603-7	1 mg/L	① PNEC aquatic, intermittent release

8.2. Exposure controls

8.2.1. Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

8.2.2. Personal protection equipment

Eve/face protection:

Safety goggles with side shields (EN 166).

Skin protection:

Hand protection:

Use protective skin cream before handling the product.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber)

Breakthrough time: 480 min.

Body protection:

Wear suitable work clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection:

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

If the relevant occupational exposure limits are exceeded, the following must be observed: Suitable respiratory protective device: Combination filter device (DIN EN 141). Filter unit with filter or blower filter unit type: A

Observe the wear time limits as specified by the manufacturer.

8.2.3. Environmental exposure controls

Observe legal rules and regulations.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid Colour: light brown

Odour: Vanilla

Safety relevant basis data

area, recommendation white			
Parameter	Value		① Method② Remark
рН	No data available		
Melting point	No data available		
Freezing point	No data available		

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 24 Jan 2023 Print date: 15 Feb 2024

Version: 2 Page 8/13



Multi Tech 5 51

Parameter	Value	at °C	1 Method
			② Remark
Initial boiling point and boiling range	110 °C		
Flash point	30 °C		① ISO 3679
Evaporation rate	No data available		
Auto-ignition temperature	No data available		
Upper/lower flammability or explosive limits	0.5 – 7 Vol-%		
Vapour pressure	No data available		
Vapour density	No data available		
Density	0.788 g/cm ³	20 °C	
Bulk density	not applicable		
Water solubility	not applicable		② The study does not need to be conducted because the substance is known to be insoluble in water.
Dynamic viscosity	No data available		
Kinematic viscosity	< 7 mm ² /s	40 °C	① DIN EN ISO 3104

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis can produce gases of varying toxicity. In the case of products containing hydrocarbons, e.g. CO, CO2, aldehydes and soot. These can be very dangerous if inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics CAS No.: 1174921-73-3 EC No.: 927-241-2

LD₅₀ oral: >5,000 mg/kg (Rat) OECD 423

LD₅₀ dermal: >5,000 mg/kg (Rabbit) OECD 402

LC₅₀ Acute inhalation toxicity (vapour): >4,951 mg/L 4 h (Rat)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics CAS No.: 64742-48-9

EC No.: 918-481-9

LD₅₀ oral: >8,000 mg/kg (Rat)

LD₅₀ dermal: >3,160 mg/kg (Rabbit)

LC₅₀ Acute inhalation toxicity (dust/mist): >4,951 mg/L

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 24 Jan 2023 Print date: 15 Feb 2024

Version: 2 Page 9/13



Multi Tech 5 51

Benzenesulphonic acids, di-C10-14-alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-608-7

LD₅₀ oral: >10,000 - <20,000 mg/kg (Rat)

LD₅₀ dermal: >2,000 mg/kg (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics)

STOT-repeated exposure:

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard:

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

No data available

SECTION 12: Ecological information

12.1. Toxicity

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics CAS No.: 1174921-73-3

EC No.: 927-241-2

LC₅₀: >1,000 mg/L 4 d (fish, Oncorhynchus mykiss (Regenbogenforelle))

LC₅₀: >1,000 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout))

EC₅₀: >1,000 mg/L 2 d (crustaceans, Daphnia magna)

NOEC: 0.182 mg/L 28 d (fish, Oncorhynchus mykiss)

ErC₅₀: >1,000 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

ErC₅₀: >1,000 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics CAS No.: 64742-48-9

EC No.: 918-481-9

LC₅₀: >1,000 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout))

LC₅₀: >1,000 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout))

EC₅₀: >1,000 mg/L 2 d (crustaceans, Daphnia magna)

ErC₅₀: >1,000 mg/L 4 d (Algae/water plant, Scenedesmus subspicatus)

Benzenesulphonic acids, di-C10-14-alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-608-7

LC₅₀: >100 mg/L 4 d (fish, Oncorhynchus mykiss)

EC₅₀: >1,000 mg/L 2 d (Algae/water plant, Pseudokirchneriella subcapitata)

ErC₅₀: >1,000 mg/L 3 d (crustaceans)

en / AT

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 24 Jan 2023 Print date: 15 Feb 2024

Version: 2 Page 10/13



Multi Tech 5 51

Assessment/classification:

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics CAS No.: 64742-48-9

EC No.: 918-481-9

Biodegradation: Yes, rapidly

Abiotic degradation:

There are no data available on the mixture itself.

Biodegradation:

There are no data available on the mixture itself.

Additional information:

AOX (mg/l): 0

12.3. Bioaccumulative potential

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics CAS No.: 1174921-73-3

EC No.: 927-241-2

Bioconcentration factor (BCF): 144.3 Species: calculated

Benzenesulphonic acids, di-C10-14-alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-608-7

Log K_{OW}: > 6.91

Bioconcentration factor (BCF): 70.8 Species: Fish, not further specified.

Accumulation / Evaluation:

There are no data available on the mixture itself.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics CAS No.: 1174921-73-3

EC No.: 927-241-2

Results of PBT and vPvB assessment: —

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics CAS No.: 64742-48-9

EC No.: 918-481-9

Results of PBT and vPvB assessment: -

Benzenesulphonic acids, di-C10-14-alkyl derivatives, calcium salts CAS No.: 1471316-72-9 EC No.: 939-608-7

Results of PBT and vPvB assessment: —

Aliphatic hydrocarbons, fragrances

Results of PBT and vPvB assessment: -

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV Waste code product

13 02 05 * mineral-based non-chlorinated engine, gear and lubricating oils

*: Evidence for disposal must be provided.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 24 Jan 2023 Print date: 15 Feb 2024

Version: 2 Page 11/13



Multi Tech 5 51

Waste code packaging

15 01 10 * packaging containing residu *: Evidence for disposal must be provided. packaging containing residues of or contaminated by dangerous substances

Waste treatment options

Appropriate disposal / Package:

Uncleaned packaging: Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or	ID number	•	·
UN 1993	UN 1993	UN 1993	UN 1993
14.2. UN proper ship	ping name	•	•
FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics) 14.3. Transport haza	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics)	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics)	FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics)
3 14.4. Packing group	3	3	3
III	TIII	Tiii	Im
14.5. Environmental	***	III	III
		1	1
No	No	No	No
14.6. Special precau	tions for user		
Special Provisions: 274 601	Special Provisions: 274 601	Special Provisions: 223 274 955	Special Provisions:
Limited quantity (LQ): 5 L	Limited quantity (LQ): 5 L	Limited quantity (LQ): 5 L	Limited quantity (LQ): Y344
Excepted Quantities (EQ): E1	Excepted Quantities (EQ):	Excepted Quantities (EQ):	Excepted Quantities (EQ):
Hazard identification number (Kemler No.): 30 Classification code:	Classification code: F1	EmS-No.: F-E, S-E	Remark: IATA Packing Instructions - Passenger: 355 IATA Maximum Quantity - Passenger: 60 L
F1 Tunnel restriction code: (E)			IATA- Verpackungsanweisung - Cargo: 366 IATA Maximum Quantity - Cargo: 220 L

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Restrictions on use (REACH, Annex XVII) Entry 28, Entry 40, Entry 75

15.1.2. National regulations

No data available

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 24 Jan 2023 Print date: 15 Feb 2024

Version: 2 Page 12/13



Multi Tech 5 51

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

European Agreement concerning the International Carriage of Dangerous Goods by Inland ADN Waterways

European Agreement concerning the International Carriage of Dangerous Goods by Road **ADR**

Adsorbable Organic halogen compounds AOX

Bioconcentration Factor BCF CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging

German Institute for Standardization / German Industrial Standard DIN

DNEL derived no-effect level

Effective Concentration 50% EC_{50}

ΕN European Standard

EWC European Waste Catalogue

International Civil Aviation Organization **ICAO** International Maritime Dangerous Goods **IMDG** IMO International Maritime Organization International Standards Organisation ISO

body weight KG

Lethal (fatal) Concentration 50% LC₅₀

Lethal (fatal) Dose 50% LD_{50}

MAK Maximum concentration in the workplace air (CH)

National Fire Protection Association **NFPA** No Observed Effect Concentration NOEC PRT

persistent and bioaccumulative and toxic

Predicted No Effect Concentration **PNEC**

REACH Registration, Evaluation and Authorization of Chemicals **RID** Dangerous goods regulations for transport by rail

SCL Specific concentration limit

TRGS Technische Regeln für Gefahrstoffe

United Nations UN

ZNS central nervous system

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (Flam. Liq. 3)	H226: Flammable liquid and vapour.	
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (Aquatic Chronic 3)	H412: Harmful to aquatic life with long lasting effects.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements		
H226	Flammable liquid and vapour.	
H304	May be fatal if swallowed and enters airways.	

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 24 Jan 2023 Print date: 15 Feb 2024

Version: 2 Page 13/13



Multi Tech 5 51

Hazard statements		
H317	May cause an allergic skin reaction.	
H336	May cause drowsiness or dizziness.	
H412	Harmful to aquatic life with long lasting effects.	

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.