according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Sept 2023 Print date: 23 Feb 2024

Version: 2 Page 1/11



Techno Solv Eco 251

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Techno Solv Eco 251

Article No.:

T110234

UFI:

37FV-7Q3J-KP0N-XD9Y

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Solvent mixture for removing adhesives

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH

Hartleitnerstraße 3 4653 Eberstalzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
Respiratory or skin sensitisation (Skin Sens. 1B)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



GHS07 Exclamation mark

GHS08 Health hazard

Signal word: Danger

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Sept 2023 Print date: 23 Feb 2024

Version: 2 Page 2/11



Techno Solv Eco 251

Hazard components for labelling:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics; (R)-p-mentha-1,8-diene

,		
Hazard statements for health hazards		
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	

Precautionary statements Prevention		
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.	
P280 Wear protective gloves and eye protection/face protection.		

Precautionary statements Response		
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.	
P331	Do NOT induce vomiting.	
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.	
P337 + P313	If eye irritation persists: Get medical advice/attention.	

2.3. Other hazards

Other adverse effects:

Based on the available information, the product does not contain any PBT or vPvB substances in content percentages $\geq 0.1\%$.

Based on the available information, the product does not contain SVHC substances in percentages \geq 0.1%.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
EC No.: 926-141-6 REACH No.: 01-2119456620-43	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics Asp. Tox. 1 (H304) Danger	50 - ≤ 54 Vol-%
CAS No.: 111-76-2 EC No.: 203-905-0 Index No.: 603-014-00-0 REACH No.: 01-2119475108-36	2-butoxyethanol Acute Tox. 4 (H302, H332), Eye Irrit. 2 (H319), Skin Irrit. 2 (H315) Warning	30 - ≤ 32.5 Vol-%
CAS No.: 5989-27-5 EC No.: 227-813-5 Index No.: 601-096-00-2	(R)-p-mentha-1,8-diene Aquatic Acute 1 (H400), Aquatic Chronic 3 (H412), Asp. Tox. 1 (H304), Flam. Liq. 3 (H226), Skin Irrit. 2 (H315), Skin Sens. 1B (H317) ① ① ② ② Danger M-factor (acute): 1	19.5 - ≤ 21 Vol-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Following inhalation:

The person concerned shall be carried outside, away from the scene of the accident. If breathing stops, artificial respiration shall be given. A doctor must be consulted immediately.

In case of skin contact:

Soiled, soaked clothing must be taken off. One must take a shower immediately. A doctor must be consulted immediately. Wash contaminated clothing before reuse.

After eye contact:

Any contact lenses must be removed. One must immediately and extensively wash with water for at least 15 minutes, opening the eyelids well. Consult a doctor if symptoms persist.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Sept 2023 Print date: 23 Feb 2024

Version: 2 Page 3/11



Techno Solv Eco 251

Following ingestion:

A doctor must be consulted immediately. Do NOT induce vomiting. No medicine may be administered that has not been prescribed by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide (CO2), Foam, Powder, Water spray jet

Unsuitable extinguishing media:

None known.

5.2. Special hazards arising from the substance or mixture

There may be a risk of explosion in containers exposed to fire. Avoid inhalation of combustion products.

5.3. Advice for firefighters

The containers shall be cooled with water jets to prevent the decomposition of the product and the formation of potentially harmful substances. Complete fire protective clothing shall be worn at all times. Extinguishing water that is not allowed to enter the sewage pipes shall be collected. The water used for extinguishing and the fire residues shall be taken up in accordance with the regulations in force.

Personal protection:

Normal firefighting clothing, e.g. an open-circuit compressed air respirator (EN 137) firefighting kit (EN469), firefighting gloves (EN 659) and firefighting boots (HO A 29 or A30)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

The leakage may be blocked if there is no danger. Appropriate protective devices (including personal protective devices as per para. 8 from the safety instructions) shall be put on to prevent contamination of skin, eyes and personal clothing. These instructions apply to both reprocessing supervisors and emergency stop interventions.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Prevent the product from entering waste water, surface water, ground water.

6.3. Methods and material for containment and cleaning up

For cleaning up:

The spilled product must be sucked into a suitable container. The container to be used shall be tested for compatibility with the product, subject to section 10. The residual product shall be absorbed with inert absorbent material. Adequate ventilation of the affected area shall be provided. Contaminated material must be disposed of in accordance with the regulations in section 13.

6.4. Reference to other sections

See section 7 for further information on safe handling.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Sept 2023 Print date: 23 Feb 2024

Version: 2 Page 4/11



Techno Solv Eco 251

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Keep away from heat, sparks and free flame, refrain from smoking and use of matches or lighters. Without the necessary ventilation, vapours may accumulate in the lower layers near the floor and may also ignite remotely with the risk of flashback. Accumulation of electrostatic charges must be avoided. Eating, drinking and smoking are prohibited during product use. Wetted clothing and protective devices must be removed before entering the eating area. Avoid dispersal of the product in the environment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Store only in original containers. Keep the containers closed, in a well-ventilated place, protected from direct sunlight. The containers must be kept away from any incompatible materials, referring to section 10.

Storage class (TRGS 510, Germany): 3 - Flammable liquids

7.3. Specific end use(s)

Recommendation:

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
MAK (AT)	2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	② 40 ppm (200 mg/m³) ⑤ (max. 4x30 min./Schicht, kann über die Haut aufgenommen werden) H
IOELV (EU)	2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	 20 ppm (98 mg/m³) 50 ppm (246 mg/m³) (may be absorbed through the skin)
MAK (AT)	2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	① 20 ppm (98 mg/m³) ⑤ (kann über die Haut aufgenommen werden) H

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

11.5. DIVLE /I NEC-VAIACS			
Substance name	DNEL value	① DNEL type	
		② Exposure route	
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	98 mg/m³	① DNEL worker ② Long-term – inhalation, systemic effects	
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	59 mg/m³	① DNEL Consumer ② Long-term – inhalation, systemic effects	
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	1,091 mg/m ³	① DNEL worker ② Acute - inhalation, systemic effects	

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Sept 2023 Print date: 23 Feb 2024

Version: 2 Page 5/11



Techno Solv Eco 251

Substance name	DNEL value	① DNEL type ② Exposure route
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	426 mg/m ³	DNEL Consumer Acute - inhalation, systemic effects
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	147 mg/m ³	① DNEL Consumer ② Acute - inhalation, local effects
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	10.3 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	26.7 mg/kg bw/day	DNEL Consumer Acute – dermal, systemic effects
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	6.3 mg/kg bw/ day	DNEL Consumer Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	8.8 mg/L	① PNEC aquatic, marine water
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	463 mg/L	① PNEC sewage treatment plant
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	0.88 mg/L	① PNEC sediment, freshwater
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	3.46 mg/L	① PNEC sediment, marine water
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	8.14 mg/kg	① PNEC soil

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Considering that appropriate protective measures should always take precedence over personal protective clothing, ensure that the workplace is well ventilated by effective local exhaust ventilation. For the selection of personal protective equipment, the trusted chemical manufacturers may need to be consulted. The personal protective equipment must be CE marked to indicate its suitability for the applicable regulations.

Emergency stop showers with face-eye-rinsing are to be provided.

8.2.2. Personal protection equipment





Eye/face protection:

The use of penetration-proof goggles is recommended (ref. standard EN 166).

Skin protection:

Hand protection:

The hands must be protected with category III work gloves (ref. standard EN 374). For the final choice of material for the work gloves, the following aspects must be included: Compatibility, degradation, breaking time and permeability. In the case of preparations, the work glove resistance to chemical agents must be tested before use, as it is unpredictable. Glove wear time is conditioned by exposure time and modes of use.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Sept 2023 Print date: 23 Feb 2024

Version: 2 Page 6/11



Techno Solv Eco 251

Skin protection:

Work clothing with long sleeves and category II accident protection shoes must be worn (see Regulation 2016/425 and standard EN ISO 20344). After taking off the protective clothing, one must wash with soap and water.

If the work environment presents a risk of explosion, consider providing antistatic garments.

Respiratory protection:

If the threshold value (e.g. TLV-TWA) of the substance or one or more substances contained in the product is exceeded, it is advisable to wear a mask with a type A filter, the class of which (1, 2 or 3) should be selected according to the highest concentration used. (Ref. standard EN 14387). In the presence of gases or vapours of a different nature and/or gases or vapours containing particles (aerosol, smoke, mist, etc.), use combined filters.

If the technical measures taken are not sufficient to reduce the exposure of the worker to the thresholds considered, the use of respiratory protective devices is necessary. The protection provided by the mask is limited in any case. If the substance under consideration is odourless or its odour threshold exceeds the corresponding TLV-TWA, or in case of emergency, an open-circuit self-operated compressed air respirator (ref. standard EN137) or an external air intake respirator (ref. standard EN138) must be worn. For the correct selection of the respiratory protective device, refer to standard EN 529.

8.2.3. Environmental exposure controls

Emissions from manufacturing processes, including those from ventilation equipment, should be checked for compliance with environmental legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid Colour: transparent

Odour: characteristic

Safety relevant basis data

Parameter	Value	1 Method
		② Remark
рН	No data available	
Melting point	No data available	
Freezing point	No data available	
Initial boiling point and boiling range	No data available	
Flash point	> 62 °C	
Evaporation rate	No data available	
Auto-ignition temperature	No data available	
Upper/lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Vapour density	No data available	
Density	0.83 mg/L	
Bulk density	not applicable	
Water solubility	No data available	
Dynamic viscosity	No data available	
Kinematic viscosity	No data available	

9.2. Other information

No further relevant information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No special reaction hazards with other substances under normal conditions of use.

2-butoxyethanol: Decomposes under the influence of heat.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Sept 2023 Print date: 23 Feb 2024

Version: 2 Page 7/11



Techno Solv Eco 251

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

2-butoxyethanol: May react dangerously with: Aluminium, Oxidizing agent. Forms peroxides with: Air.

10.4. Conditions to avoid

Avoid heating. Accumulation of electrostatic charges must be avoided. Remove all sources of ignition. 2-butoxyethanol: Avoid exposure to: Heat sources, open flames.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

Vapours potentially hazardous to health may be formed by thermal decomposition or in case of fire. 2-butoxyethanol: Can develop: Hydrogen.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological information

Acute Toxicity Estimate for Mixtures

ATE (oral): >2,000 mg/kg

ATE (inhalation, vapour): >20 mg/L

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics EC No.: 926-141-6

LD₅₀ oral: >2,000 mg/kg (Rat)

LD₅₀ dermal: >2,000 mg/kg (Rabbit)

LC₅₀ Acute inhalation toxicity (vapour): 5,000 mg/L (Rat)

2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0

LD₅₀ oral: 300 mg/kg (Kaninchen) LD₅₀ dermal: 2,000 mg/kg (Rabbit)

LC₅₀ Acute inhalation toxicity (vapour): 2.2 mg/L (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

May cause an allergic skin reaction.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Sept 2023 Print date: 23 Feb 2024

Version: 2 Page 8/11



Techno Solv Eco 251

Aspiration hazard:

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties:

According to the available data, the product does not contain substances included in the main European lists of potential or suspected endocrine disruptors with effects on human health currently under evaluation.

SECTION 12: Ecological information

12.1. Toxicity

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics EC No.: 926-141-6

LC₅₀: 1,000 mg/L 4 d (fish, Oncorhynchus mykiss)

EC₅₀: 1,000 mg/L 2 d (crustaceans, Daphnia magna)

EC₅₀: 1,000 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0

LC₅₀: 1,490 mg/L (fish, Lepomis macrochirus)

(R)-p-mentha-1,8-diene CAS No.: 5989-27-5 EC No.: 227-813-5

LC₅₀: 35 mg/L 4 d (fish, Oncorhynchus mykiss) **EC₅₀:** 69.6 mg/L 2 d (crustaceans, Daphnia pulex)

Assessment/classification:

No further relevant information available.

12.2. Persistence and degradability

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics EC No.: 926-141-6

Biodegradation: Yes, rapidly

2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0

Biodegradation: Yes, rapidly

(R)-p-mentha-1,8-diene CAS No.: 5989-27-5 EC No.: 227-813-5

Biodegradation: Yes, rapidly

Biodegradation:

No further relevant information available.

Additional information:

No further relevant information available.

12.3. Bioaccumulative potential

2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0

Log Kow: 0.81

(R)-p-mentha-1,8-diene CAS No.: 5989-27-5 EC No.: 227-813-5

Log Kow: 4.38

Bioconcentration factor (BCF): 1,022

Accumulation / Evaluation:

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment: -

2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0

Results of PBT and vPvB assessment: -

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Sept 2023 Print date: 23 Feb 2024

Version: 2 Page 9/11



Techno Solv Eco 251

(R)-p-mentha-1,8-diene CAS No.: 5989-27-5 EC No.: 227-813-5

Results of PBT and vPvB assessment: —

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

According to the available data, the product does not contain substances included in the main European lists of potential or suspected endocrine disruptors with effects on human health currently under evaluation.

12.7. Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste treatment options

Appropriate disposal / Package:

Uncleaned packaging: Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)	(ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or	ID number		
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.
14.2. UN proper ship	ping name		
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.
14.3. Transport haza	rd class(es)		
not relevant	not relevant	not relevant	not relevant
14.4. Packing group			
not relevant	not relevant	not relevant	not relevant
14.5. Environmental hazards			
not relevant	not relevant	not relevant	not relevant
14.6. Special precautions for user			
not relevant	not relevant	not relevant	not relevant

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Restrictions on the product or substances according to Annex XVII Regulation (EC) 1907/2006:

Product: point 3-40

Substances contained: point 75

Other regulations (EU):

point

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Sept 2023 Print date: 23 Feb 2024

Version: 2 Page 10/11



Techno Solv Eco 251

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 100 Vol-%

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

ACGIH American Conference of Governmental Industrial Hygienists

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland

Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

BCF Bioconcentration Factor
CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging

DNEL derived no-effect level

EC₅₀ Effective Concentration 50%

EN European Standard ES Exposure scenario

ICAO International Civil Aviation Organization
IMDG International Maritime Dangerous Goods
IMO International Maritime Organization

KG body weight

LC₅₀ Lethal (fatal) Concentration 50%

LD₅₀ Lethal (fatal) Dose 50%

MAK Maximum concentration in the workplace air (CH)

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety & Health

OEL Threshold Limit Value

OSHA Occupational Safety & Health Administration PBT persistent and bioaccumulative and toxic

PNEC Predicted No Effect Concentration

REACH Registration, Evaluation and Authorization of Chemicals RID Dangerous goods regulations for transport by rail

TRGS Technische Regeln für Gefahrstoffe

UN United Nations

VOC Volatile organic compounds

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
Respiratory or skin sensitisation (Skin Sens. 1B)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Sept 2023 Print date: 23 Feb 2024

Version: 2 Page 11/11



Techno Solv Eco 251

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.