according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 24 Jan 2025

Version: 4
Page 1/13



Aqua Clean Blue 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Aqua Clean Blue 101

Article No.:

T121010

UFI:

90SH-C3JQ-632H-RY3D

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

All-purpose cleaner without abrasives

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH

Hartleitnerstraße 3 4653 Eberstalzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Skin corrosion/irritation (Skin Corr. 1B)	H314: Causes severe skin burns and eye damage.	

Additional information:

The product is not self-sustainingly combustible. Despite a flash point < 60 °C, classification as flammable is therefore not applicable.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



GHS05 Corrosion

Signal word: Danger

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 24 Jan 2025

Version: 4 Page 2/13



Aqua Clean Blue 10

Hazard components for labelling:

disodium metasilicate

Hazard statements for health hazards	
H314	Causes severe skin burns and eye damage.

Supplemental hazard information: none

Precautionar	Precautionary statements Prevention		
P280 Wear protective gloves/protective clothing and eye protection/face protection.			
Precautionary statements Response			

Precautionary state	Precautionary statements Response			
P301 + P330 + P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.			
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].			
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.			
P310	Immediately call a POISON CENTER.			

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. The inhalation of dust/mist or aerosols causes irritation of the respiratory tract.

SECTION 3: Composition/information on ingredients

* 3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name	Concentration
	Classification according to Regulation (EC) No 1272/2008 [CLP]	
CAS No.: 67-63-0 EC No.: 200-661-7 REACH No.: 01-2119457558-25	propan-2-ol The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP]. Acute Toxicity Estimate ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, gases) > 25 ppmV ATE (inhalation, vapour) > 20 mg/L	5 - < 10 Vol-%
CAS No.: 112-34-5 EC No.: 203-961-6 REACH No.: 01-2119475104-44	2-(2-butoxyethoxy)ethanol Substance with a community workplace exposure limit. Acute Toxicity Estimate ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, vapour) > 20 mg/L	1 - < 5 Vol-%
CAS No.: 6834-92-0 EC No.: 229-912-9 Index No.: 014-010-00-8 REACH No.: 01-2119449811-37	disodium metasilicate Met. Corr. 1 (H290), STOT SE 3 (H335), Skin Corr. 1B (H314) 1 Danger Acute Toxicity Estimate ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, dust/mist) > 5 mg/L	1 - < 5 Vol-%
CAS No.: 68439-50-9	Alkyl polyethoxilate Acute Tox. 4 (H302), Aquatic Chronic 3 (H412), Eye Dam. 1 (H318) Danger Acute Toxicity Estimate ATE (oral) 500 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, dust/mist) > 5 mg/L	1 - < 5 Vol-%
Full toxt of H and FUH phra	Nonionic surfactants The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].	< 5 Vol-%

Full text of H- and EUH-phrases: see section 16.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 24 Jan 2025

Version: 4 Page 3/13



Aqua Clean Blue 10

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Remove contaminated, saturated clothing immediately.

Following inhalation:

Provide fresh air.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap.

Take off contaminated clothing and wash it before reuse.

After eye contact:

Rinse immediately carefully and thoroughly with eye-bath or water.

Following ingestion:

Rinse mouth immediately and drink 1 glass of of water.

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water spray jet, alcohol resistant foam, Carbon dioxide, Extinguishing powder

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products:

Carbon dioxide, Carbon monoxide

5.3. Advice for firefighters

Co-ordinate fire-fighting measures to the fire surroundings.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

General information:

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Emergency procedures:

Ventilate affected area.

6.1.2. For emergency responders

Personal protection equipment:

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 24 Jan 2025

Version: 4 Page 4/13



Aqua Clean Blue 10

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up:

Treat the recovered material as prescribed in the section on waste disposal.

Other information:

Collect in closed and suitable containers for disposal. Ventilate affected area.

6.4. Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Avoid contact with skin, eves and clothes.

Do not mix with other chemicals.

Use personal protection equipment.

When using do not eat, drink, smoke, sniff.

Do not breathe gas/fumes/vapour/spray.

Use only in well-ventilated areas.

Fire prevent measures:

No special fire protection measures are necessary.

Advices on general occupational hygiene

Take off contaminated clothing.

Wash hands before breaks and after work.

When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Keep container tightly closed.

Hints on storage assembly:

No special measures are necessary.

Storage class (TRGS 510, Germany): 8B - Non-combustible corrosive substances

7.3. Specific end use(s)

Recommendation:

Cleaning agent

Industrial sector specific solutions:

Stripper, corrosive, solvent-based

GISCODE:

GG80

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 **Print date:** 24 Jan 2025

Version: 4 Page 5/13



Aqua Clean Blue 10

SECTION 8: Exposure controls/personal protection

* 8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
MAK (AT)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	② 800 ppm (2,000 mg/m³) ⑤ (max. 4x15 min./Schicht)
MAK (AT)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	① 200 ppm (500 mg/m³)
MAK (AT) from 11 Sept 2007	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	② 15 ppm (101.2 mg/m³) ⑤ (max. 4x15 min./Schicht)
IOELV (EU)	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (67.5 mg/m³) ② 15 ppm (101.2 mg/m³)
MAK (AT) from 11 Sept 2007	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (67.5 mg/m³)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name DNEL value		① DNEL type	
		② Exposure route	
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	500 mg/m ³	DNEL worker Long-term – inhalation, systemic effects	
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	89 mg/m³	① DNEL Consumer ② Long-term – inhalation, systemic effects	
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	888 mg/kg bw/ day	DNEL worker Long-term - dermal, systemic effects	
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	319 mg/kg bw/ day	DNEL Consumer Long-term - dermal, systemic effects	
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	26 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects	
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	40.5 mg/m ³	DNEL Consumer Long-term – inhalation, systemic effects	
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	67.5 mg/m ³	① DNEL worker ② Long-term – inhalation, local effects	
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	40.5 mg/m ³	DNEL Consumer Long-term – inhalation, local effects	
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	101.2 mg/m ³	DNEL worker Acute - inhalation, local effects	

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 24 Jan 2025

Version: 4 Page 6/13



Aqua Clean Blue 101

Substance name	DNEL value	© DUEL true	
Substance name	DIVLE Value	① DNEL type ② Exposure route	
2-(2-butoxyethoxy)ethanol	60.7 mg/m ³	① DNEL Consumer	
CAS No.: 112-34-5 EC No.: 203-961-6		② Acute - inhalation, local effects	
2-(2-butoxyethoxy)ethanol	83 mg/kg bw/	① DNEL worker	
CAS No.: 112-34-5 EC No.: 203-961-6	day	② Long-term - dermal, systemic effects	
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5	50 mg/kg bw/	① DNEL Consumer	
EC No.: 203-961-6	day	② Long-term - dermal, systemic effects	
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5	6.25 mg/kg	① DNEL Consumer	
EC No.: 203-961-6		② Long-term - oral, systemic effects	
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5	5 mg/kg bw/	① DNEL Consumer	
EC No.: 203-961-6	day	② Long-term - oral, systemic effects	
Substance name	PNEC Value	① PNEC type	
propan-2-ol CAS No.: 67-63-0	140.9 mg/L	① PNEC aquatic, freshwater	
EC No.: 67-63-0			
propan-2-ol	140.9 mg/L	① PNEC aquatic, marine water	
CAS No.: 67-63-0 EC No.: 200-661-7			
propan-2-ol	2,251 mg/L	① PNEC sewage treatment plant	
CAS No.: 67-63-0 EC No.: 200-661-7			
propan-2-ol	552 mg/kg	① PNEC sediment, freshwater	
CAS No.: 67-63-0 EC No.: 200-661-7			
propan-2-ol CAS No.: 67-63-0	552 mg/kg	① PNEC sediment, marine water	
EC No.: 200-661-7			
propan-2-ol	28 mg/kg	① PNEC soil	
CAS No.: 67-63-0 EC No.: 200-661-7			
propan-2-ol	140.9 mg/L	① PNEC aquatic, intermittent release	
CAS No.: 67-63-0 EC No.: 200-661-7			
2-(2-butoxyethoxy)ethanol	1.1 mg/L	① PNEC aquatic, freshwater	
CAS No.: 112-34-5 EC No.: 203-961-6			
2-(2-butoxyethoxy)ethanol	0.11 mg/L	① PNEC aquatic, marine water	
CAS No.: 112-34-5 EC No.: 203-961-6			
2-(2-butoxyethoxy)ethanol	200 mg/L	① PNEC sewage treatment plant	
CAS No.: 112-34-5 EC No.: 203-961-6		S 2 Seriage deathers plant	
2-(2-butoxyethoxy)ethanol	4.4 mg/kg	① PNEC sediment, freshwater	
CAS No.: 112-34-5 EC No.: 203-961-6			
2-(2-butoxyethoxy)ethanol	0.44 mg/kg	① PNEC sediment, marine water	
CAS No.: 112-34-5 EC No.: 203-961-6			
2-(2-butoxyethoxy)ethanol	0.32 mg/kg	① PNEC soil	
CAS No.: 112-34-5 EC No.: 203-961-6			
2-(2-butoxyethoxy)ethanol	56 mg/kg	① PNEC secondary poisoning	
CAS No.: 112-34-5 EC No.: 203-961-6		, , ,	
LC NO 203-901-0		en / AT	

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 24 Jan 2025

Version: 4 Page 7/13



Aqua Clean Blue 10

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No information available.

8.2.2. Personal protection equipment





Eye/face protection:

Wear eye protection/face protection. (EN 166)

Skin protection:

Hand protection:

Wear gloves for protection against chemicals according to EN 374. (Breakthrough time: >10 min)

Suitable material: NBR (Nitrile rubber)
Thickness of the glove material >= 0,1 mm

A list of suitable makes with detailed information on wearing time is available on request.

Diluted application solutions <= 1%:

Protective gloves may be dispensed with, provided equivalent protective measures are taken, taking into account increased skin exposure due to wet work (e.g. use of suitable skin protection ointments).

Body protection: Wear suitable work clothing.

Respiratory protection:

When using the HD method or spraying over large areas: combination filter A1/P2 (EN 143, EN 14387). Use only in well-ventilated areas.

In case of inadequate ventilation wear respiratory protection.

Thermal hazards:

No further relevant information available.

8.2.3. Environmental exposure controls

Section 6: Accidental Release Measures

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid Colour: light blue

Odour: characteristic **flammability:** No data available

Safety relevant basis data

Parameter	Value	at °C	① Method
			② Remark
рН	13 - 14	20 °C	
Melting point	≈ 0 °C		
Freezing point	≈ 0 °C		
Initial boiling point and boiling range	≈ 100 °C		
Flash point	43 °C		
Evaporation rate	No data available		
Auto-ignition temperature	No data available		
Upper/lower flammability or explosive limits	No data available		
Vapour pressure	No data available		
Vapour density	No data available		
Density	1.03 g/cm³	20 °C	
Bulk density	not applicable		

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 24 Jan 2025

Version: 4 Page 8/13



Aqua Clean Blue 10

Parameter	Value		Method Remark
Water solubility	completely miscible		
Dynamic viscosity	< 10 mPa* s	25 °C	
Kinematic viscosity	No data available		

9.2. Other information

Sustaining combustion: Not sustaining combustion.

SECTION 10: Stability and reactivity

10.1. Reactivity

Exothermic reaction with: Acid

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Acid

10.4. Conditions to avoid

The product is stable under storage at normal ambient temperatures.

10.5. Incompatible materials

Acid

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

st 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7 **LD₅₀ oral:** >2,000 mg/kg (Rat) LD_{50} dermal: >2,000 mg/kg (Rat) LC₅₀ Acute inhalation toxicity (gas): >25 ppmV 4 h (Rat) LC₅₀ Acute inhalation toxicity (vapour): >20 mg/L 6 h (Rat) **2-(2-butoxyethoxy)ethanol** CAS No.: 112-34-5 EC No.: 203-961-6 **LD₅₀ oral:** >2,000 mg/kg (Rat) **LD₅₀ dermal:** >2,000 mg/kg (Rat) LC₅₀ Acute inhalation toxicity (vapour): >20 mg/L (Rat) disodium metasilicate CAS No.: 6834-92-0 EC No.: 229-912-9 **LD₅₀ oral:** >2,000 mg/kg (Rat) **LD₅₀ dermal:** >2,000 mg/kg (Rat)LC₅₀ Acute inhalation toxicity (dust/mist): >5 mg/L Alkyl polyethoxilate CAS No.: 68439-50-9 **LD₅₀ oral:** 500 mg/kg (Rat) **LD₅₀ dermal:** >2,000 mg/kg (Rat) LC₅₀ Acute inhalation toxicity (dust/mist): >5 mg/L (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 24 Jan 2025

Version: 4 Page 9/13



Aqua Clean Blue 10

Skin corrosion/irritation:

Causes severe skin burns and eye damage.

Serious eye damage/irritation:

Causes severe skin burns and eye damage.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause respiratory irritation.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties:

No information available.

SECTION 12: Ecological information

* 12.1. Toxicity

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	
LC₅₀: >1,000 mg/L 4 d (fish)	
EC₅₀: >1,000 mg/L 2 d (crustaceans)	
LC ₅₀ : 9,640 mg/L 4 d (fish, Pimephales promelas)	
LC ₅₀ : 9,714 mg/L 1 d (Daphnia magna)	

EC₅₀: >100 mg/L (Algae/water plant, Bacteria)

LOEC: 1,000 mg/L (Alge)

EC₅₀: >100 mg/L 2 d (crustaceans, Daphnia magna)

ErC₅₀: >100 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus)

LOEC: 1,000 mg/L (Algae/water plant, Algae)

2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6

LC₅₀: 2,780 mg/L 4 d (fish, Pimephales promelas)

EC₅₀: 4,950 mg/L 2 d (crustaceans, Daphnia magna (Big water flea))

ErC₅₀: >100 mg/L (Algae/water plant, Scenedesmus subspicatus)

EC₅₀: >100 mg/L 2 d (Daphnia magna) OECD 202

ErC₅₀: >100 mg/L (Algae/water plant, Scenedesmus sp.) OECD 201

disodium metasilicate CAS No.: 6834-92-0 EC No.: 229-912-9

LC₅₀: 210 mg/L 4 d (fish, Danio rerio)

EC₅₀: 1,700 mg/L 2 d (crustaceans, Daphnia magna)

Alkyl polyethoxilate CAS No.: 68439-50-9

 LC_{50} : >1 mg/L 4 d (fish)

EC₅₀: >1 mg/L 2 d (crustaceans)

ErC₅₀: >1 mg/L (Algae/water plant)

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 24 Jan 2025

Version: 4 Page 10/13



Aqua Clean Blue 101

12.2. Persistence and degradability

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Biodegradation: Yes, rapidly

Remark: Readily biodegradable (according to OECD criteria).

2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6

Biodegradation: Yes, rapidly

Remark: Readily biodegradable (according to OECD criteria).

Alkyl polyethoxilate CAS No.: 68439-50-9

Biodegradation: Yes, rapidly

Remark: Readily biodegradable (according to OECD criteria).

Biodegradation:

The surfactants contained in this mixture comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

12.3. Bioaccumulative potential

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Log Kow: 0.05

2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6

Log Kow: 0.56

Accumulation / Evaluation:

No indication of bioaccumulation potential.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Results of PBT and vPvB assessment: —

2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6

Results of PBT and vPvB assessment: —

disodium metasilicate CAS No.: 6834-92-0 EC No.: 229-912-9

Results of PBT and vPvB assessment: —
Alkyl polyethoxilate CAS No.: 68439-50-9

Aikyi polyetnoxilate CAS No.: 68439-50-9

Results of PBT and vPvB assessment: -

Nonionic surfactants

Results of PBT and vPvB assessment: -

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation. Delivery to an approved waste disposal company.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV Waste code product

07 06 01 * aqueous washing liquids and mother liquors

*: Evidence for disposal must be provided.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 24 Jan 2025

Version: 4 Page 11/13



Aqua Clean Blue 10

Waste code packaging

15 01 02 Plastic packaging

Waste treatment options

Appropriate disposal / Package:

Non-contaminated packages may be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)	(ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)				
14.1. UN number or ID number							
UN 1719	UN 1719	UN 1719	UN 1719				
14.2. UN proper ship	14.2. UN proper shipping name						
CAUSTIC ALKALI LIQUID, N.O.S. (disodium metasilicate)	CAUSTIC ALKALI LIQUID, N.O.S. (disodium metasilicate)	CAUSTIC ALKALI LIQUID, N.O.S. (disodium metasilicate)	CAUSTIC ALKALI LIQUID, N.O.S. (disodium metasilicate)				
14.3. Transport haza	rd class(es)						
8	8	8	8				
14.4. Packing group	<u> </u>	•					
III	III	III	III				
14.5. Environmental	hazards	-					
No	No	No	No				
14.6. Special precau	tions for user						
Special Provisions: 274	Special Provisions: 274	Special Provisions: 223 274	Special Provisions: A3 A803				
Limited quantity (LQ): 5 L	Limited quantity (LQ): 5 L	Limited quantity (LQ): 5 L	Limited quantity (LQ): Y841				
Excepted Quantities (EQ):	Excepted Quantities (EQ):	Excepted Quantities (EQ):	Excepted Quantities (EQ): E1				
Hazard identification number (Kemler No.): 80 Classification code: C5 Tunnel restriction code: (E)	Classification code: C5	EmS-No.: F-A, S-B	Remark: IATA Packing Instructions - Passenger: 852 IATA Maximum Quantity - Passenger: 5 L IATA- Verpackungsanweisung - Cargo: 856 IATA Maximum Quantity - Cargo: 60 L				

14.7. Maritime transport in bulk according to IMO instruments not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Restrictions on use (REACH, Annex XVII) Entry 3, Entry 40, Entry 55, Entry 75

Other regulations (EU):

This product is not assigned to a hazard category.

en / AT

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 24 Jan 2025

Version: 4 Page 12/13



Aqua Clean Blue 101

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 5.5 Vol-%

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

15.3. Additional information

Regulation (EC) No. 648/2004 [Detergents regulation]

SECTION 16: Other information

16.1. Indication of changes

3.2.	Mixtures
8.1.	Control parameters
9.1.	Information on basic physical and chemical properties
11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008
12.1.	Toxicity
14.3.	Transport hazard class(es)
16.1.	Indication of changes
16.2.	Abbreviations and acronyms

1

16.2. Ab	breviations and acronyms
ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DNEL	derived no-effect level
EC ₅₀	Effective Concentration 50%
EN	European Standard
ES	Exposure scenario
EWC	European Waste Catalogue
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
L/C	

KG body weight

LC₅₀ Lethal (fatal) Concentration 50%

LD₅₀ Lethal (fatal) Dose 50%

MAK Maximum concentration in the workplace air (CH)

National Fire Protection Association **NFPA**

NIOSH National Institute for Occupational Safety & Health OECD Organisation for Economic Cooperation and Development

Occupational Safety & Health Administration OSHA

persistent and bioaccumulative and toxic PBT

PC Product category

PNEC Predicted No Effect Concentration

PROC Process Category

REACH Registration, Evaluation and Authorization of Chemicals Dangerous goods regulations for transport by rail RID

SCL Specific concentration limit

TRGS Technische Regeln für Gefahrstoffe

UN **United Nations**

VOC Volatile organic compounds ZNS central nervous system

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Mar 2023 Print date: 24 Jan 2025

Version: 4 Page 13/13



Agua Clean Blue 10

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Skin corrosion/irritation (Skin Corr. 1B)	l .	
	eye damage.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements			
H290	May be corrosive to metals.		
H302	Harmful if swallowed.		
H314	Causes severe skin burns and eye damage.		
H318	Causes serious eye damage.		
H335	May cause respiratory irritation.		
H412	Harmful to aquatic life with long lasting effects.		

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

* [)ata	changed	l compared	with	the	previous	version.	
-----	------	---------	------------	------	-----	----------	----------	--