Aqua Clean Blue 25l

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1. Product identifier

Trade name/designation:

Aqua Clean Blue 25l

Article No.:
T121025

UFI:
90SH-C3JQ-632H-RY3D

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:
All-purpose cleaner without abrasives

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH
Hartleitnerstraße 3
4653 Eberstalzell
Austria
Telephone: +43 (0) 7241 213 79
E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Skin corrosion/irritation *(Skin Corr. 1B)*	H314: Causes severe skin burns and eye damage.	

Additional information:
The product is not self-sustainingly combustible. Despite a flash point < 60 °C, classification as flammable is therefore not applicable.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS05
Corrosion

Signal word: Danger

Hazard components for labelling:
disodium metasilicate

Hazard statements for health hazards	
H314	Causes severe skin burns and eye damage.

Supplemental hazard information: none

Precautionary statements Prevention	
P280	Wear protective gloves/protective clothing and eye protection/face protection.

Precautionary statements Response	
P301 + P330 + P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER.

2.3. Other hazards

Other adverse effects:
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
The inhalation of dust/mist or aerosols causes irritation of the respiratory tract.

SECTION 3: Composition/information on ingredients

*

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 67-63-0 EC No.: 200-661-7 REACH No.: 01-2119457558-25	**propan-2-ol** The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP]. **Acute Toxicity Estimate** ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, gases) > 25 ppmV ATE (inhalation, vapour) > 20 mg/L	5 – < 10 Vol-%
CAS No.: 112-34-5 EC No.: 203-961-6 REACH No.: 01-2119475104-44	**2-(2-butoxyethoxy)ethanol** Substance with a community workplace exposure limit. **Acute Toxicity Estimate** ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, vapour) > 20 mg/L	1 – < 5 Vol-%
CAS No.: 6834-92-0 EC No.: 229-912-9 Index No.: 014-010-00-8 REACH No.: 01-2119449811-37	**disodium metasilicate** Met. Corr. 1 (H290), STOT SE 3 (H335), Skin Corr. 1B (H314)  Danger **Acute Toxicity Estimate** ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, dust/mist) > 5 mg/L	1 – < 5 Vol-%
CAS No.: 68439-50-9	**Alkyl polyethoxilate** Acute Tox. 4 (H302), Aquatic Chronic 3 (H412), Eye Dam. 1 (H318)  Danger **Acute Toxicity Estimate** ATE (oral) 500 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, dust/mist) > 5 mg/L	1 – < 5 Vol-%
	Nonionic surfactants The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].	< 5 Vol-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:
Remove contaminated, saturated clothing immediately.

Following inhalation:
Provide fresh air.

In case of skin contact:
After contact with skin, wash immediately with plenty of water and soap.
Take off contaminated clothing and wash it before reuse.

After eye contact:
Rinse immediately carefully and thoroughly with eye-bath or water.

Following ingestion:
Rinse mouth immediately and drink 1 glass of of water.
Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:
Water spray jet, alcohol resistant foam, Carbon dioxide, Extinguishing powder

Unsuitable extinguishing media:
Full water jet

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products:
Carbon dioxide, Carbon monoxide

5.3. Advice for firefighters

Co-ordinate fire-fighting measures to the fire surroundings.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:
General information:
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.

Emergency procedures:
Ventilate affected area.

6.1.2. For emergency responders

Personal protection equipment:
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

For containment:
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up:
Treat the recovered material as prescribed in the section on waste disposal.

Other information:
Collect in closed and suitable containers for disposal. Ventilate affected area.

6.4. Reference to other sections

Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:
Avoid contact with skin, eyes and clothes.
Do not mix with other chemicals.
Use personal protection equipment.
When using do not eat, drink, smoke, sniff.
Do not breathe gas/fumes/vapour/spray.
Use only in well-ventilated areas.

Fire prevent measures:
No special fire protection measures are necessary.

Advices on general occupational hygiene

Take off contaminated clothing.
Wash hands before breaks and after work.
When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:
Keep container tightly closed.

Hints on storage assembly:
No special measures are necessary.

Storage class (TRGS 510, Germany): 8B – Non-combustible corrosive substances

7.3. Specific end use(s)

Recommendation:
Cleaning agent

Industrial sector specific solutions:
Stripper, corrosive, solvent-based

GISCODE:
GG80

SECTION 8: Exposure controls/personal protection

*

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	**propan-2-ol** CAS No.: 67-63-0 EC No.: 200-661-7	② 800 ppm (2,000 mg/m³) ⑤ (max. 4x15 min./Schicht)
MAK (AT)	**propan-2-ol** CAS No.: 67-63-0 EC No.: 200-661-7	① 200 ppm (500 mg/m³)
MAK (AT) from 11 Sept 2007	**2-(2-butoxyethoxy)ethanol** CAS No.: 112-34-5 EC No.: 203-961-6	② 15 ppm (101.2 mg/m³) ⑤ (max. 4x15 min./Schicht)
IOELV (EU)	**2-(2-butoxyethoxy)ethanol** CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (67.5 mg/m³) ② 15 ppm (101.2 mg/m³)
MAK (AT) from 11 Sept 2007	**2-(2-butoxyethoxy)ethanol** CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (67.5 mg/m³)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	500 mg/m³	① DNEL worker ② Long-term – inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	89 mg/m³	① DNEL Consumer ② Long-term – inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	888 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	319 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	26 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	40.5 mg/m³	① DNEL Consumer ② Long-term – inhalation, systemic effects
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	67.5 mg/m³	① DNEL worker ② Long-term – inhalation, local effects
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	40.5 mg/m³	① DNEL Consumer ② Long-term – inhalation, local effects
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	101.2 mg/m³	① DNEL worker ② Acute - inhalation, local effects

Aqua Clean Blue 25l

Substance name	DNEL value	① DNEL type ② Exposure route
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	60.7 mg/m³	① DNEL Consumer ② Acute - inhalation, local effects
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	83 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	50 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	6.25 mg/kg	① DNEL Consumer ② Long-term - oral, systemic effects
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	5 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	2,251 mg/L	① PNEC sewage treatment plant
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	28 mg/kg	① PNEC soil
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, intermittent release
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	1.1 mg/L	① PNEC aquatic, freshwater
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	0.11 mg/L	① PNEC aquatic, marine water
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	200 mg/L	① PNEC sewage treatment plant
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	4.4 mg/kg	① PNEC sediment, freshwater
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	0.44 mg/kg	① PNEC sediment, marine water
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	0.32 mg/kg	① PNEC soil
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	56 mg/kg	① PNEC secondary poisoning

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No information available.

8.2.2. Personal protection equipment



Eye/face protection:

Wear eye protection/face protection. (EN 166)

Skin protection:

Hand protection:
Wear gloves for protection against chemicals according to EN 374. (Breakthrough time: >10 min)
Suitable material: NBR (Nitrile rubber)
Thickness of the glove material >= 0,1 mm
A list of suitable makes with detailed information on wearing time is available on request.

Diluted application solutions <= 1%:
Protective gloves may be dispensed with, provided equivalent protective measures are taken, taking into account increased skin exposure due to wet work (e.g. use of suitable skin protection ointments).

Body protection: Wear suitable work clothing.

Respiratory protection:

When using the HD method or spraying over large areas: combination filter A1/P2 (EN 143, EN 14387).
Use only in well-ventilated areas.
In case of inadequate ventilation wear respiratory protection.

Thermal hazards:

No further relevant information available.

8.2.3. Environmental exposure controls

Section 6: Accidental Release Measures

SECTION 9: Physical and chemical properties

* 9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid
Colour: light blue
Odour: characteristic
flammability: No data available

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	13 – 14	20 °C	
Melting point	≈ 0 °C		
Freezing point	≈ 0 °C		
Initial boiling point and boiling range	≈ 100 °C		
Flash point	43 °C		
Evaporation rate	*No data available*		
Auto-ignition temperature	*No data available*		
Upper/lower flammability or explosive limits	*No data available*		
Vapour pressure	*No data available*		
Vapour density	*No data available*		
Density	1.03 g/cm³	20 °C	
Bulk density	*not applicable*		

Aqua Clean Blue 25l

Parameter	Value	at °C	① Method ② Remark
Water solubility	completely miscible		
Dynamic viscosity	< 10 mPa* s	25 °C	
Kinematic viscosity	*No data available*		

9.2. Other information
Sustaining combustion: Not sustaining combustion.

SECTION 10: Stability and reactivity

10.1. Reactivity
Exothermic reaction with: Acid

10.2. Chemical stability
The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions
Exothermic reaction with: Acid

10.4. Conditions to avoid
The product is stable under storage at normal ambient temperatures.

10.5. Incompatible materials
Acid

10.6. Hazardous decomposition products
No known hazardous decomposition products.

SECTION 11: Toxicological information

*

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
LD_{50} oral: >2,000 mg/kg (Rat)
LD_{50} dermal: >2,000 mg/kg (Rat)
LC_{50} Acute inhalation toxicity (gas): >25 ppmV 4 h (Rat)
LC_{50} Acute inhalation toxicity (vapour): >20 mg/L 6 h (Rat)
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6
LD_{50} oral: >2,000 mg/kg (Rat)
LD_{50} dermal: >2,000 mg/kg (Rat)
LC_{50} Acute inhalation toxicity (vapour): >20 mg/L (Rat)
disodium metasilicate CAS No.: 6834-92-0 EC No.: 229-912-9
LD_{50} oral: >2,000 mg/kg (Rat)
LD_{50} dermal: >2,000 mg/kg (Rat)
LC_{50} Acute inhalation toxicity (dust/mist): >5 mg/L
Alkyl polyethoxilate CAS No.: 68439-50-9
LD_{50} oral: 500 mg/kg (Rat)
LD_{50} dermal: >2,000 mg/kg (Rat)
LC_{50} Acute inhalation toxicity (dust/mist): >5 mg/L (Rat)

Acute oral toxicity:
Based on available data, the classification criteria are not met.

Acute dermal toxicity:
Based on available data, the classification criteria are not met.

Acute inhalation toxicity:
Based on available data, the classification criteria are not met.

Skin corrosion/irritation:
Causes severe skin burns and eye damage.

Serious eye damage/irritation:
Causes severe skin burns and eye damage.

Respiratory or skin sensitisation:
Based on available data, the classification criteria are not met.

Germ cell mutagenicity:
Based on available data, the classification criteria are not met.

Carcinogenicity:
Based on available data, the classification criteria are not met.

Reproductive toxicity:
Based on available data, the classification criteria are not met.

STOT-single exposure:
May cause respiratory irritation.

STOT-repeated exposure:
Based on available data, the classification criteria are not met.

Aspiration hazard:
Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties:
No information available.

SECTION 12: Ecological information

*

12.1. Toxicity

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
LC_{50}: >1,000 mg/L 4 d (fish)
EC_{50}: >1,000 mg/L 2 d (crustaceans)
LC_{50}: 9,640 mg/L 4 d (fish, Pimephales promelas)
LC_{50}: 9,714 mg/L 1 d (Daphnia magna)
EC_{50}: >100 mg/L (Algae/water plant, Bacteria)
LOEC: 1,000 mg/L (Alge)
EC_{50}: >100 mg/L 2 d (crustaceans, Daphnia magna)
ErC_{50}: >100 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus)
LOEC: 1,000 mg/L (Algae/water plant, Algae)
2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6
LC_{50}: 2,780 mg/L 4 d (fish, Pimephales promelas)
EC_{50}: 4,950 mg/L 2 d (crustaceans, Daphnia magna (Big water flea))
ErC_{50}: >100 mg/L (Algae/water plant, Scenedesmus subspicatus)
EC_{50}: >100 mg/L 2 d (Daphnia magna) OECD 202
ErC_{50}: >100 mg/L (Algae/water plant, Scenedesmus sp.) OECD 201
disodium metasilicate CAS No.: 6834-92-0 EC No.: 229-912-9
LC_{50}: 210 mg/L 4 d (fish, Danio rerio)
EC_{50}: 1,700 mg/L 2 d (crustaceans, Daphnia magna)
Alkyl polyethoxilate CAS No.: 68439-50-9
LC_{50}: >1 mg/L 4 d (fish)
EC_{50}: >1 mg/L 2 d (crustaceans)
ErC_{50}: >1 mg/L (Algae/water plant)

12.2. Persistence and degradability

propan-2-ol	CAS No.: 67-63-0 EC No.: 200-661-7
Biodegradation: Yes, rapidly	
Remark: Readily biodegradable (according to OECD criteria).	
2-(2-butoxyethoxy)ethanol	CAS No.: 112-34-5 EC No.: 203-961-6
Biodegradation: Yes, rapidly	
Remark: Readily biodegradable (according to OECD criteria).	
Alkyl polyethoxilate	CAS No.: 68439-50-9
Biodegradation: Yes, rapidly	
Remark: Readily biodegradable (according to OECD criteria).	

Biodegradation:
The surfactants contained in this mixture comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

12.3. Bioaccumulative potential

propan-2-ol	CAS No.: 67-63-0 EC No.: 200-661-7
Log K_{OW}: 0.05	
2-(2-butoxyethoxy)ethanol	CAS No.: 112-34-5 EC No.: 203-961-6
Log K_{OW}: 0.56	

Accumulation / Evaluation:
No indication of bioaccumulation potential.

12.4. Mobility in soil
The product has not been tested.

12.5. Results of PBT and vPvB assessment

propan-2-ol	CAS No.: 67-63-0 EC No.: 200-661-7
Results of PBT and vPvB assessment: —	
2-(2-butoxyethoxy)ethanol	CAS No.: 112-34-5 EC No.: 203-961-6
Results of PBT and vPvB assessment: —	
disodium metasilicate	CAS No.: 6834-92-0 EC No.: 229-912-9
Results of PBT and vPvB assessment: —	
Alkyl polyethoxilate	CAS No.: 68439-50-9
Results of PBT and vPvB assessment: —	
Nonionic surfactants	
Results of PBT and vPvB assessment: —	

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties
This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects
No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods
Dispose of waste according to applicable legislation. Delivery to an approved waste disposal company.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV
Waste code product

07 06 01 *	aqueous washing liquids and mother liquors

**: Evidence for disposal must be provided.*

Waste code packaging

15 01 02	Plastic packaging

Waste treatment options

Appropriate disposal / Package:

Non-contaminated packages may be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 1719	UN 1719	UN 1719	UN 1719
14.2. UN proper shipping name			
CAUSTIC ALKALI LIQUID, N.O.S. (disodium metasilicate)	CAUSTIC ALKALI LIQUID, N.O.S. (disodium metasilicate)	CAUSTIC ALKALI LIQUID, N.O.S. (disodium metasilicate)	CAUSTIC ALKALI LIQUID, N.O.S. (disodium metasilicate)
* **14.3. Transport hazard class(es)**			
 8	 8	 8	 8
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
No	No	No	No
14.6. Special precautions for user			
Special Provisions: 274 **Limited quantity (LQ):** 5 L **Excepted Quantities (EQ):** E1 **Hazard identification number (Kemler No.):** 80 **Classification code:** C5 **Tunnel restriction code:** (E)	**Special Provisions:** 274 **Limited quantity (LQ):** 5 L **Excepted Quantities (EQ):** E1 **Classification code:** C5	**Special Provisions:** 223 | 274 **Limited quantity (LQ):** 5 L **Excepted Quantities (EQ):** E1 **EmS-No.:** F-A, S-B	**Special Provisions:** A3 | A803 **Limited quantity (LQ):** Y841 **Excepted Quantities (EQ):** E1 **Remark:** IATA Packing Instructions - Passenger: 852 IATA Maximum Quantity - Passenger: 5 L IATA-Verpackungsanweisung - Cargo: 856 IATA Maximum Quantity - Cargo: 60 L

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Restrictions on use (REACH, Annex XVII)
Entry 3, Entry 40, Entry 55, Entry 75

Other regulations (EU):

This product is not assigned to a hazard category.

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:
Volatile organic compounds (VOC) content in percent by weight: 5.5 Vol-%

15.1.2. National regulations
No data available

15.2. Chemical Safety Assessment
Chemical safety assessments for substances in this mixture were not carried out.

15.3. Additional information
Regulation (EC) No. 648/2004 [Detergents regulation]

SECTION 16: Other information

*
16.1. Indication of changes

3.2.	Mixtures
8.1.	Control parameters
9.1.	Information on basic physical and chemical properties
11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008
12.1.	Toxicity
14.3.	Transport hazard class(es)
16.1.	Indication of changes
16.2.	Abbreviations and acronyms

*
16.2. Abbreviations and acronyms

ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DNEL	derived no-effect level
EC_{50}	Effective Concentration 50%
EN	European Standard
ES	Exposure scenario
EWC	European Waste Catalogue
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
KG	body weight
LC_{50}	Lethal (fatal) Concentration 50%
LD_{50}	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
OECD	Organisation for Economic Cooperation and Development
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PC	Product category
PNEC	Predicted No Effect Concentration
PROC	Process Category
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
SCL	Specific concentration limit
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations
VOC	Volatile organic compounds
ZNS	central nervous system

16.3. Key literature references and sources for data
No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Skin corrosion/irritation *(Skin Corr. 1B)*	H314: Causes severe skin burns and eye damage.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

16.6. Training advice
No data available

16.7. Additional information
To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

* Data changed compared with the previous version.