according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Jan 2025 Print date: 24 Jan 2025 Version: 5

Page 1/14

Techno Solv Eco 5

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1. Product identifier Trade name/designation:

Techno Solv Eco 51

Article No.: T110233 UFI:

N3KP-YUUK-MAQ5-88UK

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Solvent mixture for removing adhesives

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH Hartleitnerstraße 3 4653 Eberstalzell Austria Telephone: +43 (0) 7241 213 79 E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
Respiratory or skin sensitisation (Skin Sens. 1B)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
Acute toxicity (inhalative) (Acute Tox. 3)	H331: Toxic if inhaled.	
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	

Additional information:

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. The product must be accompanied by a safety data sheet in accordance with the provisions of Regulation (EU) 2020/878. For further information on health hazards: see section 11. For further information on ecological hazards: see section 12.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Jan 2025 Print date: 24 Jan 2025 Version: 5

Page 2/14

Techno Solv Eco 5

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:





GHS09 Environment



Skull and crossbones

Signal word: Danger

Hazard components for labelling:

(R)-p-mentha-1,8-diene; C11-14 cyclic isoalkane hydrocarbons < 2 % aromatic; 2-butoxyethanol

Hazard statements for health hazards		
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H331	Toxic if inhaled.	
Hazard statements for environmental bazards		

Hazard statements for environmental hazards H411

Toxic to aquatic life with long lasting effects.

Supplemental hazard information: none

Precautionary statements Prevention		
P273	Avoid release to the environment.	
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/ .	

Precautionary statements Response		
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/ .	
P331	Do NOT induce vomiting.	
P391 Collect spillage.		

Precautionary statements Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

Other adverse effects:

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%. The product does not contain any substances with endocrine-disrupting properties in concentrations of \geq 0.1%.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Jan 2025 Print date: 24 Jan 2025 Version: 5

Page 3/14

Techno Solv Eco 5

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
EC No.: 927-285-2 REACH No.: 01-2119480162-45	C11-14 cyclic isoalkane hydrocarbons < 2 % aromatic Asp. Tox. 1 (H304)	≥ 50 - < 54 weight-%
CAS No.: 111-76-2 EC No.: 203-905-0 Index No.: 603-014-00-0 REACH No.: 01-2119475108-36-XXXX	2-butoxyethanol Acute Tox. 3 (H331), Acute Tox. 4 (H302), Eye Irrit. 2 (H319), Skin Irrit. 2 (H315)	≥ 30 - < 32.5 weight-%
CAS No.: 5989-27-5 EC No.: 227-813-5 Index No.: 601-096-00-2 REACH No.: 01-2119529223-47	 (R)-p-mentha-1,8-diene Aquatic Acute 1 (H400), Aquatic Chronic 3 (H412), Asp. Tox. 1 (H304), Flam. Liq. 3 (H226), Skin Irrit. 2 (H315), Skin Sens. 1B (H317) (1) (1) (2) (3) (4) (4)	≥ 19.5 - < 21 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

If in doubt or if symptoms occur, consult a doctor and show them this document. In the event of severe symptoms, call the emergency services immediately.

Following inhalation:

The person concerned shall be carried outside, away from the scene of the accident. If breathing stops, artificial respiration shall be given. Where appropriate artificial ventilation. If unconscious but breathing normally, place in recovery position and seek medical advice.

In case of skin contact:

Take off immediately all contaminated clothing. Wash with plenty of water. A doctor must be consulted immediately. Avoid contact with contaminated clothing.

After eye contact:

Any contact lenses must be removed. One must immediately and extensively wash with water for at least 15 minutes, opening the eyelids well. A doctor must be consulted immediately.

Following ingestion:

Do not induce vomiting unless explicitly authorised by a doctor. Never give anything by mouth to an unconscious person or a person with cramps. A doctor must be consulted immediately.

Self-protection of the first aider:

Use personal protection equipment. The type of equipment depends on the hazardousness of the substance or mixture, the type of exposure and the extent of contamination. If no further specific information is given, disposable gloves should be worn in case of possible contact with biological fluids. For further information on personal protective equipment: see section 8.

4.2. Most important symptoms and effects, both acute and delayed

There is no known specific information on symptoms and effects caused by this product.



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Jan 2025 Print date: 24 Jan 2025 Version: 5 TECH MASTERS

Page 4/14

Techno Solv Eco 5

4.3. Indication of any immediate medical attention and special treatment needed IF SWALLOWED: Immediately call a POISON CENTER/doctor.

In case of skin contact, Eye contact: Wash with plenty of water/soap.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide Foam, Powder-, Water mist

Unsuitable extinguishing media:

Nothing special.

5.2. Special hazards arising from the substance or mixture

Avoid inhalation of combustion products.

5.3. Advice for firefighters

The containers shall be cooled with water jets to prevent the decomposition of the product and the formation of potentially harmful substances. Complete fire protective clothing shall be worn at all times. Extinguishing water that is not allowed to enter the sewage pipes shall be collected. The water used for extinguishing and the fire residues shall be taken up in accordance with the regulations in force.

Personal protection: Normal firefighting clothing, e.g. an open-circuit compressed air respirator (EN 137) firefighting kit (EN469), firefighting gloves (EN 659) and firefighting boots (HO A 29 or A30)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

The leakage may be blocked if there is no danger. Appropriate protective devices (including personal protective devices as per para. 8 from the safety instructions) shall be put on to prevent contamination of skin, eyes and personal clothing. These instructions apply to both reprocessing supervisors and emergency stop interventions.

6.1.2. For emergency responders

Personal protection equipment:

Normal firefighting clothing, e.g. an open-circuit compressed air respirator (EN 137) firefighting kit (EN469), firefighting gloves (EN 659) and firefighting boots (HO A 29 or A30)

6.2. Environmental precautions

Prevent the product from entering waste water, surface water, ground water.

6.3. Methods and material for containment and cleaning up

Other information:

The spilled product must be sucked into a suitable container. The container to be used shall be tested for compatibility with the product, subject to section 10. The residual product shall be absorbed with inert absorbent material. Adequate ventilation of the affected area shall be provided. Contaminated material must be disposed of in accordance with the regulations in section 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Keep away from heat, sparks and free flame, refrain from smoking and use of matches or lighters. Without the necessary ventilation, vapours may accumulate in the lower layers near the floor and may also ignite remotely with the risk of flashback. Accumulation of electrostatic charges must be avoided.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Jan 2025 Print date: 24 Jan 2025 Version: 5

Page 5/14

Techno Solv Eco 5

TECH MASTERS world of innovations

Eating, drinking and smoking are prohibited during product use. Wetted clothing and protective devices must be removed before entering the eating area. Avoid dispersal of the product in the environment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Store only in original containers. It must be stored in a cool and well-ventilated place, away from heat sources, free flame, sparks and other sources of ignition. The containers must be kept away from any incompatible materials, whereby reference must be made to section 10. **Storage class (TRGS 510, Germany):** 3 – Flammable liquids

7.3. Specific end use(s)

Recommendation:

Data not available.

SECTION 8: Exposure controls/personal protection

* 8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
MAK (AT)	2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	 2 40 ppm (200 mg/m³) (max. 4x30 min./Schicht, kann über die Haut aufgenommen werden) H
IOELV (EU)	2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	 20 ppm (98 mg/m³) 50 ppm (246 mg/m³) (may be absorbed through the skin)
МАК (АТ)	2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	 20 ppm (98 mg/m³) (kann über die Haut aufgenommen werden) H

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type
		② Exposure route
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	98 mg/m ³	 DNEL worker Long-term - inhalation, systemic effects
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	59 mg/m ³	 DNEL Consumer Long-term - inhalation, systemic effects
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	1,091 mg/m ³	 DNEL worker Acute - inhalation, systemic effects
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	426 mg/m ³	 DNEL Consumer Acute - inhalation, systemic effects
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	147 mg/m ³	 DNEL Consumer Acute - inhalation, local effects
2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0	10.3 mg/kg bw/day	 DNEL worker Long-term - dermal, systemic effects

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Jan 2025 Print date: 24 Jan 2025 Version: 5 TECH MASTERS

Page 6/14

Techno Solv Eco 5

Substance name	DNEL value	① DNEL type
		 Exposure route
2-butoxyethanol	26.7 mg/kg	① DNEL Consumer
CAS No.: 111-76-2	bw/day	② Acute – dermal, systemic effects
EC No.: 203-905-0		
2-butoxyethanol CAS No.: 111-76-2	6.3 mg/kg bw/ day	① DNEL Consumer
EC No.: 203-905-0	uay	② Long-term - oral, systemic effects
(R)-p-mentha-1,8-diene	33.3 mg/m ³	① DNEL worker
CAS No.: 5989-27-5		 2 Long-term – inhalation, systemic effects
EC No.: 227-813-5		· · · · · · · · · · · · · · · · · · ·
(R)-p-mentha-1,8-diene CAS No.: 5989-27-5	8.3 mg/m ³	① DNEL Consumer
EC No.: 227-813-5		② Long-term – inhalation, systemic effects
(R)-p-mentha-1,8-diene	0.222 mg/kg	① DNEL worker
CAS No.: 5989-27-5		 Acute - dermal, local effects
EC No.: 227-813-5		
(R)-p-mentha-1,8-diene	0.111 mg/kg	1 DNEL Consumer
CAS No.: 5989-27-5 EC No.: 227-813-5		② Acute - dermal, local effects
(R)-p-mentha-1,8-diene	4.76 mg/kg	① DNEL Consumer
CAS No.: 5989-27-5		 Diversional Consumer Long-term - oral, systemic effects
EC No.: 227-813-5		
Substance name	PNEC Value	① PNEC type
2-butoxyethanol	8.8 mg/L	PNEC aquatic, marine water
CAS No.: 111-76-2	5	
EC No.: 203-905-0		
2-butoxyethanol CAS No.: 111-76-2	463 mg/L	${f 1}$ PNEC sewage treatment plant
EC No.: 203-905-0		
2-butoxyethanol	0.88 mg/L	① PNEC sediment, freshwater
CAS No.: 111-76-2	5	
EC No.: 203-905-0		
2-butoxyethanol	3.46 mg/L	${f 1}$ PNEC sediment, marine water
CAS No.: 111-76-2 EC No.: 203-905-0		
2-butoxyethanol	8.14 mg/kg	① PNEC soil
CAS No.: 111-76-2	5.2	
EC No.: 203-905-0		
(R)-p-mentha-1,8-diene	0.0054 mg/L	${f 1}$ PNEC aquatic, freshwater
CAS No.: 5989-27-5 EC No.: 227-813-5		
(R)-p-mentha-1,8-diene	0.00054 mg/L	PNEC aquatic, marine water
CAS No.: 5989-27-5	siccos ing/L	
EC No.: 227-813-5		
(R)-p-mentha-1,8-diene	1.8 mg/L	${f 1}$ PNEC sewage treatment plant
CAS No.: 5989-27-5 EC No.: 227-813-5		
(R)-p-mentha-1,8-diene	1.32 mg/kg	1 DNEC codimont freshwater
CAS No.: 5989-27-5	1.52 mg/kg	① PNEC sediment, freshwater
EC No.: 227-813-5		
(R)-p-mentha-1,8-diene	0.13 mg/kg	① PNEC sediment, marine water
CAS No.: 5989-27-5		
EC No.: 227-813-5	0.202	
(R)-p-mentha-1,8-diene CAS No.: 5989-27-5	0.262 mg/kg	① PNEC soil
CAJ NU., JJUJ-2/-J		
EC No.: 227-813-5		
	3.33 mg/kg	(1) PNEC secondary poisoning
EC No.: 227-813-5 (R)-p-mentha-1,8-diene CAS No.: 5989-27-5 EC No.: 227-813-5	3.33 mg/kg	① PNEC secondary poisoning

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Jan 2025 Print date: 24 Jan 2025 Version: 5

Page 7/14

Techno Solv Eco 5

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No data available

8.2.2. Personal protection equipment

Eye/face protection:

The use of penetration-proof goggles is recommended (ref. standard EN 166).

Skin protection:

Hand protection:

The hands must be protected with category III work gloves (ref. standard EN 374). For the final choice of material for the work gloves, the following aspects must be included: Compatibility, degradation, breaking time and permeability. In the case of preparations, the work glove resistance to chemical agents must be tested before use, as it is unpredictable. Glove wear time is conditioned by exposure time and modes of use.

Skin protection:

Work clothing with long sleeves and category II accident protection shoes must be worn (see Regulation 2016/425 and standard EN ISO 20344). After taking off the protective clothing, one must wash with soap and water.

Respiratory protection:

If the threshold value (e.g. TLV-TWA) of the substance or one or more substances contained in the product is exceeded, it is advisable to wear a mask with a type A filter, the class of which (1, 2 or 3) should be selected according to the highest concentration used. (Ref. standard EN 14387). In the presence of gases or vapours of a different nature and/or gases or vapours containing particles (aerosol, smoke, mist, etc.), use combined filters. If the technical measures taken are not sufficient to reduce the exposure of the worker to the thresholds considered, the use of respiratory protective devices is necessary. The protection provided by the mask is limited in any case.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 137). For a correct choice of respiratory protection device, see standard EN 529.

Other protection measures:

Considering that appropriate protective measures should always take precedence over personal protective clothing, ensure that the workplace is well ventilated by effective local exhaust ventilation. For the selection of personal protective equipment, the trusted chemical manufacturers may need to be consulted. The personal protective equipment must be CE marked to indicate its suitability for the applicable regulations.

Emergency stop showers with face-eye-rinsing are to be provided.

8.2.3. Environmental exposure controls

Emissions from manufacturing processes, including those from ventilation equipment, should be checked for compliance with environmental legislation. Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid	Colour: colourless
Odour: characteristic	flammability: No data available

Safety relevant basis data

Parameter	Value	 Method Remark
рН	No data available	
Melting point	No data available	
Freezing point	No data available	
Initial boiling point and boiling range	No data available	
Flash point	> 62 °C	



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Jan 2025 Print date: 24 Jan 2025 Version: 5



Page 8/14

Techno Solv Eco 5l

Parameter	Value	 Method 	
		② Remark	
Evaporation rate	No data available		
Auto-ignition temperature	No data available		
Upper/lower flammability or explosive limits	No data available		
Vapour pressure	No data available		
Vapour density	No data available		
Density	0.83 mg/L		
Bulk density	not applicable		
Water solubility	practically insoluble		
Dynamic viscosity	No data available		
Kinematic viscosity	No data available		

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No special reaction hazards with other substances under normal conditions of use. 2-butoxyethanol: Decomposes under the influence of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

2-butoxyethanol: : May react dangerously with: Aluminium, Oxidizing agent Forms peroxides with: Air.

10.4. Conditions to avoid

Avoid heating. Accumulation of electrostatic charges must be avoided. Keep away from sources of ignition - No smoking.

2-butoxyethanol: Avoid exposure to: Heat sources, open flames

10.5. Incompatible materials

Data not available.

10.6. Hazardous decomposition products

Vapours potentially hazardous to health may be formed by thermal decomposition or in case of fire. 2-butoxyethanol: Can develop: Hydrogen

SECTION 11: Toxicological information

* 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological information

Acute Toxicity Estimate for Mixtures

ATE (inhalation, vapour): 9.23 mg/L

C11-14 cyclic isoalkane hydrocarbons < 2 % aromatic EC No.: 927-285-2

LD₅₀ oral: >2,000 mg/kg (Ratte) OECD TG

LD₅₀ dermal: >2,000 mg/kg (Kaninchen)

LC₅₀ Acute inhalation toxicity (vapour): 5,000 mg/L 4 h (Ratte) OCSE 4030

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Jan 2025 Print date: 24 Jan 2025 Version: 5

Page 9/14

Techno Solv Eco 51

100 A	. **
TECH	
MASTER	S
world of innovation	ns

2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0

ATE (inhalation, vapour)1: 3 mg/L

LD₅₀ oral: 300 mg/kg (Kaninchen)

LD₅₀ dermal: 2,000 mg/kg (Rabbit)

LC₅₀ Acute inhalation toxicity (vapour): 2.2 mg/L (Rat)

¹: Acute Toxicity Estimate. Harmonised (legal) classification.

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation: Sensitising to the skin

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

toxic

Additional information:

As no experimental toxicological data on the product are available, the possible health risks were evaluated on the properties of the substances contained according to the criteria of the reference standards for classification. For the evaluation of toxicological effects in case of product exposure, the concentrations of the individual pollutants possibly listed under para. 3 have to be considered.

11.2. Information on other hazards

Other information:

According to the available data, the product does not contain any substances included in the main European lists of potential or suspected endocrine disruptors with effects on human health to be assessed.

water hazard class 2: hazardous to water

SECTION 12: Ecological information

12.1. Toxicity

C11-14 cyclic isoalkane hydrocarbons < 2 % aromatic EC No.: 927-285-2

LC₅₀: >1,000 mg/L 4 d (fish, Oncorhynchus mykiss)

EC₅₀: >1,000 mg/L 2 d (crustaceans, Daphnia magna)

EC50: >1,000 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Jan 2025 Print date: 24 Jan 2025 Version: 5



Page 10/14

Techno Solv Eco 51

2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0

LC₅₀: 1,490 mg/L (fish, Lepomis macrochirus)

LC₅₀: 1,464 mg/L 4 d (fish, Oncorhynchus mykiss)

EC₅₀: 911 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

EC₅₀: 1,800 mg/L 2 d (crustaceans, Daphnia magna)

NOEC: 88 mg/L (Algae/water plant, Pseudokirchneriella subcapitata)

(R)-p-mentha-1,8-diene CAS No.: 5989-27-5 EC No.: 227-813-5

LC₅₀: 35 mg/L 4 d (fish, Oncorhynchus mykiss)

EC₅₀: 69.6 mg/L 2 d (crustaceans, Daphnia pulex)

Additional ecotoxicological information:

The product must be considered environmentally hazardous and is toxic to aquatic life. In the long term, it can cause negative effects in the aquatic environment.

12.2. Persistence and degradability

C11-14 cyclic isoalkane hydrocarbons < 2 % aromatic EC No.: 927-285-2

Biodegradation: Yes, rapidly

2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0

Biodegradation: Yes, rapidly

Remark: 1000 - 10000 mg/L

(R)-p-mentha-1,8-diene CAS No.: 5989-27-5 EC No.: 227-813-5

Biodegradation: Yes, rapidly

12.3. Bioaccumulative potential

2-butoxyethanol CAS No.: 111-76-2 EC No.: 203-905-0

Log K_{OW}: 0.81

(R)-p-mentha-1,8-diene CAS No.: 5989-27-5 EC No.: 227-813-5

Log K_{OW}: 4.83

Bioconcentration factor (BCF): 1,022

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

C11-14 cyclic isoalkane hydrocarbons < 2 % aromatic EC No.: 927-285-2		
Results of PBT and vPvB assessment: —		
2-butoxyethanol	CAS No.: 111-76-2 EC No.: 203-905-0	
Results of PBT and vPvB assessment: —		
(R)-p-mentha-1,8-	diene CAS No.: 5989-27-5 EC No.: 227-813-5	
Results of PBT and vPvB assessment: —		

Based on the available information, the product does not contain any PBT or vPvB substances in content percentages $\geq 0.1\%$.

12.6. Endocrine disrupting properties

According to the available data, the product does not contain any substances included in the main European lists of potential or suspected endocrine disruptors with environmental effects to be assessed.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Reuse if possible. Product residues are to be considered as hazardous waste. The hazardousness of the waste partially containing this product must be evaluated on the basis of the legal provisions in

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Jan 2025 Print date: 24 Jan 2025 Version: 5

Page 11/14

Techno Solv Eco 5

TECH MASTERS world of innovations

force. Disposal must be entrusted to a company authorised for waste management, taking into account national and, where applicable, local regulations. The transport of the waste may be subject to ADR.

Waste treatment options

Appropriate disposal / Package:

Contaminated packaging material must be sent for recycling or disposal in accordance with the country's waste management regulations.

SECTION 14: Transport information						
Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)			
14.1. UN number or	14.1. UN number or ID number					
UN 3082	UN 3082	UN 3082	UN 3082			
14.2. UN proper ship	14.2. UN proper shipping name					
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((R)-p- mentha-1,8-diene)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((R)-p- mentha-1,8-diene)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((R)-p- mentha-1,8-diene)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((R)-p- mentha-1,8-diene)			
14.3. Transport haza	•					
9 14.4. Packing group	9	9 9	9			
14.5. Environmental		1				
		MARINE POLLUTANT	×			
14.6. Special precau	tions for user	•				
Special Provisions: 274 335 375 601 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Hazard identification number (Kemler No.): 90 Classification code: - Tunnel restriction code: (-) Remark: This product is not subject to the provisions of ADR/ RID according to special provision 375 if it is transported in individual or inner packagings ≤ 5kg/L.	No data available	Limited quantity (LQ): 5 L EmS-No.: F-A, S-F Remark: This product is not subject to the provisions of the IMDG Code, subsection 2.10.2.7. when transported in individual or inner packagings ≤ 5kg/L. Packaging details 964	 Special Provisions: A97 A158 A197 A215 Remark: This product is not subject to IATA Dangerous Goods Regulations according to Special Provision A197 when transported in individual or inner packagings ≤ 5kg/L. IATA Maximum Quantity - Cargo:450L IATA Maximum Quantity - Passenger: 450L Packaging details 964 			

14.7. Maritime transport in bulk according to IMO instruments No data available

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Jan 2025 Print date: 24 Jan 2025 Version: 5

Page 12/14

Techno Solv Eco 5

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Seveso category - Directive 2012/18/EU: H2-E2

Restrictions on the product or substances according to Annex XVII Regulation (EC) 1907/2006: Product point 3-40

Substances contained point 75

Regulation (EU) 2019/1148 (marketing and use of explosives precursors): not applicable

Substances according to Candidate List (Art. 59 REACH): Based on the available information, the product does not contain SVHC substances in percentages $\geq 0.1\%$.

Substances subject to authorisation (Annex XIV REACH): none

Substances subject to export notification Regulation (EU) 649/2012: none

Substances subject to the Rotterdam Convention: none

Substances subject to the Stockholm Convention: none

Preventive medical check-ups: No precautionary examinations are required when working with this product. This is only on condition that the results of the risk assessment prove that there is only a moderate risk to the safety and health of workers and that the measures provided for by Directive 98/24/ EC are sufficient to limit the risk.

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 100 weight-%

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out: C11-14 cyclic isoalkane hydrocarbons < 2 % aromatic 2-butoxyethanol

SECTION 16: Other information

* 16.1. Indication of changes

- 8.1. Control parameters
- 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
- 16.1. Indication of changes
- 16.2. Abbreviations and acronyms
- 16.7. Additional information

* 16.2. Abbreviations and acronyms

- ACGIH American Conference of Governmental Industrial Hygienists
- ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- ADR European Agreement concerning the International Carriage of Dangerous Goods by Road
- BCF Bioconcentration Factor
- CAS Chemical Abstracts Service
- CLP Classification, Labelling and Packaging
- DIN German Institute for Standardization / German Industrial Standard
- DNEL derived no-effect level
- EC₅₀ Effective Concentration 50%
- EN European Standard
- ES Exposure scenario
- ICAO International Civil Aviation Organization
- IMDG International Maritime Dangerous Goods
- IMO International Maritime Organization
- KG body weight
- LC₅₀ Lethal (fatal) Concentration 50%



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Jan 2025 Print date: 24 Jan 2025 Version: 5 TECH MASTERS

Page 13/14

Techno Solv Eco 5

LD ₅₀	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OEL	Threshold Limit Value
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations
VOC	Volatile organic compounds

16.3. Key literature references and sources for data No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
Respiratory or skin sensitisation (Skin Sens. 1B)	H317: May cause an allergic skin reaction.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
Acute toxicity (inhalative) (Acute Tox. 3)	H331: Toxic if inhaled.	
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

16.6. Training advice

No data available

* **16.7. Additional information**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 13 Jan 2025 Print date: 24 Jan 2025 Version: 5

Page 14/14

Techno Solv Eco 5

* Data changed compared with the previous version.

