according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878 Revision date: 23 Jan 2023

Revision date: 23 Jan 2023 Print date: 24 Jan 2025 Version: 3

Page 1/13

Red Lube 2400 500ml

TECH MASTERS world of innovations

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1. Product identifier Trade name/designation:

Red Lube 2400 500ml

Article No.: T314001 UFI:

P1E1-DERV-WV0J-QF6S

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Lubricating agent

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH Hartleitnerstraße 3 4653 Eberstalzell Austria Telephone: +43 (0) 7241 213 79 E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 3</i>)	H412: Harmful to aquatic life with long lasting effects.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 23 Jan 2023 Print date: 24 Jan 2025 Version: 3



Page 2/13

Red Lube 2400 500ml

Hazard components for labelling:

pentane

Hazard statements for physical hazards		
H222	Extremely flammable aerosol.	
H229	Pressurised container: May burst if heated.	

Hazard statements	for health hazards
H336	May cause drowsiness or dizziness.

Hazard statements for environmental hazards

H412 Harmful to aquatic life with long lasting effects.

Supplemental hazard information		
EUH066	Repeated exposure may cause skin dryness or cracking.	
EUH208	Contains Naphthenic acids, zinc salts, basic. May produce an allergic reaction.	

Precautionary statements Prevention		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P260	Do not breathe dust/fume/gas/mist/vapours/spray.	
P271	Use only outdoors or in a well-ventilated area.	
P273	Avoid release to the environment.	
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.	

Precautionary statements Response

P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Precautionary stat	ements Storage
P403	Store in a well-ventilated place.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary statements Disposal

Return contents/container to the point of sale or to a special waste collection point.

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description:

Active ingredient mixture with propellant gas

Additional information:

Aerosols and containers fitted with a solid nebuliser containing substances or mixtures classified as hazardous by aspiration must not be labelled for this hazard.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 23 Jan 2023 Print date: 24 Jan 2025 Version: 3



Page 3/13

Red Lube 2400 500ml

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 109-66-0 EC No.: 203-692-4 Index No.: 601-006-00-1 REACH No.: 01-2119459286-30-XXXX	pentane Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 2 (H225), STOT SE 3 (H336) • • • • • • • • • • • • • • •	10 - < 25 %
CAS No.: 106-97-8 EC No.: 203-448-7 Index No.: 601-004-00-0 REACH No.: 01-2119474691-32	Butane (with < 0,1 % butadiene (203-450-8)) Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) ♦ Danger	10 - < 25 %
CAS No.: 74-98-6 EC No.: 200-827-9 Index No.: 601-003-00-5 REACH No.: 01-2119486944-21	propane Flam. Gas 1A (H220), Press. Gas (Comp.) (H280)	10 - < 25 %
CAS No.: 75-28-5 EC No.: 200-857-2 REACH No.: 01-2119485395-27	Isobutane Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger Acute Toxicity Estimate ATE (inhalation, vapour) 1,237 mg/L	2.5 - < 10 %
CAS No.: 84418-50-8 EC No.: 282-762-6 REACH No.: 01-2119988500-34 Full text of H- and FUH-phra	Naphthenic acids, zinc salts, basic Aquatic Chronic 3 (H412), Skin Sens. 1 (H317) Varning	0.1 - < 1 %

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Following inhalation:

Fresh air supply, consult a doctor in case of complaints.

In case of skin contact:

In general, the product is not irritating to skin.

After eye contact:

Rinse opened eye for several minutes under running water. Consult a doctor if symptoms persist **Following ingestion:**

Do not induce vomiting, seek medical help immediately.

4.2. Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water mist, Extinguishing powder, Carbon dioxide (CO2), alcohol resistant foam

Unsuitable extinguishing media:

Water in full jet

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 23 Jan 2023 Print date: 24 Jan 2025 Version: 3

Page 4/13

Red Lube 2400 500ml

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Special protective equipment: Put on breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear protective equipment. Keep unprotected persons away.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of spillage into water or sewage system, inform the competent authorities.

6.3. Methods and material for containment and cleaning up

For cleaning up:

Do not wash away with water or aqueous detergents.

Other information:

Provide adequate ventilation.

6.4. Reference to other sections

Further information on proper storage: see section 7. For further information on personal protective equipment: see section 8. For further information on disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Ensure good ventilation/extraction at the workplace.

Fire prevent measures:

Do not spray on naked flames or any incandescent material. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Container is under pressure. Protect from sunlight and temperatures above 50°C (e.g. from incandescent lamps). Do not open by force or burn even after use.

7.2. Conditions for safe storage, including any incompatibilities Requirements for storage rooms and vessels:

Store in a cool place. The official regulations for the storage of pressurised gas packages must be observed.

Hints on storage assembly:

The official regulations for the storage of pressurised gas packages must be observed.

Storage class (TRGS 510, Germany): 2B - Aerosol dispensers and lighters

Further information on storage conditions:

Store in a cool, dry place in well-sealed containers. Protect from heat and direct sunlight.

7.3. Specific end use(s)

Recommendation:

No further relevant information available.



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878 Revision date: 23 Jan 2023 Print date: 24 Jan 2025

Version: 3 Page 5/13

Red Lube 2400 500ml

SECTION 8: Exposure controls/personal protection

* 8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
MAK (AT)	pentane CAS No.: 109-66-0 EC No.: 203-692-4	 ② 1,200 ppm (3,600 mg/m³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
IOELV (EU)	pentane CAS No.: 109-66-0 EC No.: 203-692-4	① 1,000 ppm (3,000 mg/m³)
MAK (AT)	pentane CAS No.: 109-66-0 EC No.: 203-692-4	① 600 ppm (1,800 mg/m³)
MAK (AT)	Butane (with < 0,1 % butadiene (203-450-8)) CAS No.: 106-97-8 EC No.: 203-448-7	① 800 ppm (1,900 mg/m³)
MAK (AT)	Butane (with < 0,1 % butadiene (203-450-8)) CAS No.: 106-97-8 EC No.: 203-448-7	 ② 1,600 ppm (3,800 mg/m³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
MAK (AT)	propane CAS No.: 74-98-6 EC No.: 200-827-9	 2,000 ppm (3,600 mg/m³) (max. 3x60 min./Schicht, Momentanwert)
MAK (AT)	propane CAS No.: 74-98-6 EC No.: 200-827-9	① 1,000 ppm (1,800 mg/m ³)
MAK (AT)	Isobutane CAS No.: 75-28-5 EC No.: 200-857-2	 2 1,600 ppm (3,800 mg/m³) 5 (max. 3x60 min./SchichtMomentanwert)
MAK (AT)	Isobutane CAS No.: 75-28-5 EC No.: 200-857-2	① 800 ppm (1,900 mg/m³)

8.1.2. Biological limit values No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	 DNEL type
		② Exposure route
pentane CAS No.: 109-66-0 EC No.: 203-692-4	3,000 mg/m ³	 DNEL worker Long-term - inhalation, systemic effects
pentane CAS No.: 109-66-0 EC No.: 203-692-4	643 mg/m ³	 DNEL Consumer Long-term - inhalation, systemic effects
pentane CAS No.: 109-66-0 EC No.: 203-692-4	432 mg/kg bw/ day	 DNEL worker Long-term - dermal, systemic effects
pentane CAS No.: 109-66-0 EC No.: 203-692-4	214 mg/kg bw/ day	 DNEL Consumer Long-term - dermal, systemic effects



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 23 Jan 2023 Print date: 24 Jan 2025 Version: 3



Page 6/13

Red Lube 2400 500ml

Substance name	DNEL value	 DNEL type Exposure route
pentane CAS No.: 109-66-0 EC No.: 203-692-4	214 mg/kg bw/ day	 DNEL Consumer Long-term - oral, systemic effects
Substance name	PNEC Value	① PNEC type
pentane CAS No.: 109-66-0 EC No.: 203-692-4	0.23 mg/L	 PNEC aquatic, freshwater
pentane CAS No.: 109-66-0 EC No.: 203-692-4	0.23 mg/L	① PNEC aquatic, marine water
pentane CAS No.: 109-66-0 EC No.: 203-692-4	3.6 mg/L	 PNEC sewage treatment plant
pentane CAS No.: 109-66-0 EC No.: 203-692-4	1.2 mg/kg bw/ day	 PNEC sediment, freshwater
pentane CAS No.: 109-66-0 EC No.: 203-692-4	1.2 mg/kg	 PNEC sediment, marine water
pentane CAS No.: 109-66-0 EC No.: 203-692-4	0.55 mg/kg	① PNEC soil
pentane CAS No.: 109-66-0 EC No.: 203-692-4	0.88 mg/L	(1) PNEC aquatic, intermittent release

8.2. Exposure controls

8.2.1. Appropriate engineering controls No further details. See section 7.

8.2.2. Personal protection equipment



Eye/face protection:

Safety goggles (EN-166)

Skin protection:

Hand protection:

Gloves / solvent resistant

Breakthrough times and swelling properties of the material must be taken into consideration. Glove material:

The selection of a suitable glove depends not only on the material but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use. NBR (Nitrile rubber)

Recommended material thickness: \geq 0,5 mm

Permeation time (maximum wear duration):

For continuous contact we recommend gloves with a breakthrough time of at least 240 minutes, with the preference for a breakthrough time greater than 480 minutes. For short term or splash protection we recommend the same. We are aware that suitable gloves offering this protection are not available. In this case, a shorter breakthrough time is permissible, provided the procedures for maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance the gloves give against a chemical substance, as this depends on the exact composition of the material of the gloves. The exact breakthrough time should be checked with the glove manufacturer and adhered to. Body protection:

Use protective suit. (EN-13034/6)

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 23 Jan 2023 Print date: 24 Jan 2025 Version: 3

Page 7/13

Red Lube 2400 500ml

TECH MASTERS

Antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688 EN13034-6).

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Filter A2/P2

Other protection measures:

General protective and hygienic measures: Keep away from food, drink and animal feed. Wash hands before breaks and after work. Do not inhale gases/vapours/aerosols. General ventilation.

8.2.3. Environmental exposure controls

Use a suitable container to prevent environmental pollution.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Form: Aerosol Odour: characteristic **Colour:** According to product designation **flammability:** No data available

Safety relevant basis data

Parameter	Value	at °C	1 Method
			② Remark
рН	not applicable		② Mixture is not polar/aprotic.
Initial boiling point and boiling range	-44.5 °C		
Flash point	-97 °C		
Evaporation rate	No data available		
Auto-ignition temperature	285 °C		
Upper/lower flammability or explosive limits	1.4 - 10.9 Vol-%		
Vapour pressure	8,300 hPa	20 °C	
Density	0.67 g/cm ³	20 °C	
Water solubility	not applicable		② Not miscible or only slightly miscible.

* 9.2. Other information

The product is not self-igniting. The product is not explosive, but the formation of explosive vapour/air mixtures is possible. formation of explosive vapour/air mixtures is possible.

9.2.1. Information with regard to physical hazard classes

Explosives: Not applicable Flammable gases: Not applicable Aerosols: Extremely flammable aerosol. Pressurized container: May burst if heated. Oxidizing gases: Not applicable **Gases under pressure:** Not applicable Flammable liquids: Not applicable Flammable solids: Not applicable Self-reactive substances and mixtures: Not applicable **Pyrophoric liquids:** Not applicable **Pyrophoric solids:** Not applicable

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 23 Jan 2023 Print date: 24 Jan 2025 Version: 3

Page 8/13

Red Lube 2400 500ml

TECH MASTERS world of innovations

Self-heating substances and mixtures:

Not applicable

Substances or mixtures which, in contact with water, emit flammable gases:

Not applicable Oxidizing liquids:

Not applicable

Oxidizing solids: Not applicable

Organic peroxides: Not applicable

Corrosive to metals: Not applicable

Desensitised explosives: Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

Thermal decomposition / Conditions to avoid: No decomposition when used as directed.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

pentane CAS No.: 109-66-0 EC No.: 203-692-4 LD₅₀ oral: >5,000 mg/kg (Rat) LD₅₀ dermal: >2,000 mg/kg (Rat) LC₅₀ Acute inhalation toxicity (gas): >20 ppmV 4 h (rat) LC₅₀ Acute inhalation toxicity (vapour): >25.3 mg/L 4 h (Rat) OECD 403 Acute oral toxicity: Based on available data, the classification criteria are not met. Acute dermal toxicity: Based on available data, the classification criteria are not met. Acute inhalation toxicity: Based on available data, the classification criteria are not met. Skin corrosion/irritation: Based on available data, the classification criteria are not met. Serious eye damage/irritation: Based on available data, the classification criteria are not met. **Respiratory or skin sensitisation:** Based on available data, the classification criteria are not met. Germ cell mutagenicity: Based on available data, the classification criteria are not met.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 23 Jan 2023 Print date: 24 Jan 2025 Version: 3

Page 9/13

Red Lube 2400 500ml

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties:

None of the ingredients are included.

SECTION 12: Ecological information

* 12.1. Toxicity

pentane CAS No.: 109-66-0 EC No.: 203-692-4
LC₅₀: 4.26 mg/L 4 d (fish, Oncorhynchus mykiss)
EC₅₀: 10.7 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)
EC₅₀: 2.7 mg/L 2 d (crustaceans, Daphnia magna)
NOEC: 7.51 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)
NOEC: 7.51 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)
EC₅₀: 10.7 mg/L 3 d (Algae/water plant, Pseudokirchnerie lla subcapitata)
propane CAS No.: 74-98-6 EC No.: 200-827-9
LC₅₀: 9,640 mg/L 4 d (fish, Pimephales promelas)
LC₅₀: 0.41 mg/L 4 d (fish, Oncorhynchus mykiss)
LC ₅₀ : 49.9 mg/L 4 d (fish) The Ecosar class program has been develo
EC ₅₀ : >100 mg/L (Algae/water plant, Bacteria)
EC ₅₀ : 0.17 mg/L 3 d (Algae/water plant, Selenastrum capricornutum)
EC ₅₀ : 69.43 mg/L 2 d (crustaceans, Daphnia) Calculation using ECOSAR Program v1.00.
NOEC: 0.017 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)
ErC ₅₀ : 19.37 mg/L 4 d (Algae/water plant, Algae) Calculation using ECOSAR Program v1.00.
LOEC: 1,000 mg/L (Algae/water plant, Algae)
LOEC: 1,000 mg/L (Algae/water plant, Alge)
Isobutane CAS No.: 75-28-5 EC No.: 200-857-2
LC₅₀: 91.42 mg/L 4 d (fish)
EC₅₀: 69.43 mg/L 2 d (crustaceans, Daphnia sp.)
ErC ₅₀ : 19.37 mg/L 4 d (Algae/water plant)

Aquatic toxicity:

No further relevant information available.

12.2. Persistence and degradability

pentane CAS No.: 109-66-0 EC No.: 203-692-4

Biodegradation: Yes, rapidly

propane CAS No.: 74-98-6 EC No.: 200-827-9

Biodegradation: Yes, rapidly

Biodegradation:

Not readily biodegradable.

Additional information:

No further relevant information available.



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878 Revision date: 23 Jan 2023

Print date: 23 Jan 20 **Print date:** 24 Jan 2025 **Version:** 3

Page 10/13

Red Lube 2400 500ml

12.3. Bioaccumulative potential

 pentane
 CAS No.: 109-66-0
 EC No.: 203-692-4

 Log K_{OW}: 3.39
 CAS No.: 74-98-6
 EC No.: 200-827-9

Log K_{OW}: 1.09

Isobutane CAS No.: 75-28-5 EC No.: 200-857-2

Log K_{OW}: 1.09

Accumulation / Evaluation:

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

pentane CAS No.: 109-66-0 EC No.: 203-692-4

Results of PBT and vPvB assessment: —

Butane (with < 0,1 % butadiene (203-450-8)) CAS No.: 106-97-8 EC No.: 203-448-7

Results of PBT and vPvB assessment: —

propane CAS No.: 74-98-6 EC No.: 200-827-9

Results of PBT and vPvB assessment: -

Isobutane CAS No.: 75-28-5 EC No.: 200-857-2

Naphthenic acids, zinc salts, basic CAS No.: 84418-50-8 EC No.: 282-762-6

Results of PBT and vPvB assessment: -

The product does not meet the PBT/vPvB criteria.

12.6. Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties.

12.7. Other adverse effects

Harmful to fish.

Do not allow to enter into surface water or drains.

Drinking water hazard even when small quantities leak into the subsoil.

Harmful to aquatic life.

water hazard class 2: obviously hazardous to water

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Must not be disposed of together with household waste. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Directive 2008/98/EC (Waste Framework Directive)

HP 3	Flammable
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 14	Ecotoxic

Waste treatment options

Appropriate disposal / Package:

Uncleaned packaging: Dispose of waste according to applicable legislation.



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 23 Jan 2023 Print date: 24 Jan 2025 Version: 3

Page 11/13

Red Lube 2400 500ml

SECTION 14: Transport information Land transport (ADR/RID) Inland waterway craft Air transport (ICAO-TI / Sea transport (IMDG) (ADN) IATA-DGR) 14.1. UN number or ID number UN 1950 UN 1950 UN 1950 UN 1950 14.2. UN proper shipping name AEROSOLS AEROSOLS AEROSOLS AEROSOLS, flammable 14.3. Transport hazard class(es) 2.1 2.1 2.1 2.1 14.4. Packing group 14.5. Environmental hazards No No No No 14.6. Special precautions for user **Special Provisions: Special Provisions: Special Provisions:** Special Provisions: 190 | 327 | 344 | 625 190 | 327 | 344 | 625 63 | 190 | 277 | 327 | 344 | A145 | A167 381 | 959 Limited quantity (LQ): Limited quantity (LQ): Limited quantity (LQ): Limited quantity (LQ): 1 L 1 L Y203 **Excepted Quantities** Siehe SV277 **Excepted Quantities Excepted Quantities** (EQ): (EQ): **Excepted Quantities** (EQ): E0 E0 (EQ): E0 F0 **Classification code: Classification code: Remark:** EmS-No.: Attention: Gases 5F 5F **Tunnel restriction code:** Remark: F-D, S-U (D) Attention: Gases Remark: Attention: Gases **Remark:** Attention: Gases

14.7. Maritime transport in bulk according to IMO instruments No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Directive 2012/18/EU

Named dangerous substances - ANNEX I: None of the ingredients are included.

Restrictions on use:

Regulation (EC) No 1907/2006 ANNEX XVII: Restriction conditions: 3

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II: None of the ingredients are included.

Regulation (EU) 2019/1148

Annex I - RESTRICTED EXPORT SUBSTANCES FOR EXPLOSIVES (upper concentration limit for a permit pursuant to Article 5(3)): None of the ingredients are included.

Annex II - EXPLOSIVES REPORTABLE FOR EXPLOSIVES: None of the ingredients are included.

Regulation (EC) No 273/2004 on drug precursors: None of the ingredients are included.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade in drug precursors between the Community and third countries: None of the ingredients are included.

Other regulations (EU):

Hazard categories:



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 23 Jan 2023 Print date: 24 Jan 2025 Version: 3 TECH MASTERS

Page 12/13

Red Lube 2400 500ml

• P3a 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids

Named dangerous substances:

• Liquefied flammable gases, Category 1 or 2 (including liquefied petroleum gas) and natural gas **Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:** Volatile organic compounds (VOC) content in percent by weight: 435.4 g/L

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

* 16.1. Indication of changes

- 8.1. Control parameters
- 9.1. Information on basic physical and chemical properties
- 9.2. Other information 12.1. Toxicity
- 12.7. Other adverse effects
- 16.1. Indication of changes
- 16.2. Abbreviations and acronyms

* 16.2. Abbreviations and acronyms

American Conference of Governmental Industrial Hygienists ACGIH ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterwavs European Agreement concerning the International Carriage of Dangerous Goods by Road ADR CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging DNEL derived no-effect level Effective Concentration 50% EC_{50} European Standard ΕN ES Exposure scenario European Waste Catalogue EWC International Civil Aviation Organization **ICAO** IMDG International Maritime Dangerous Goods IMO International Maritime Organization body weight KG Lethal (fatal) Concentration 50% LC_{50} Lethal (fatal) Dose 50% LD_{50} Maximum concentration in the workplace air (CH) MAK National Fire Protection Association NFPA National Institute for Occupational Safety & Health NIOSH NOEC No Observed Effect Concentration Organisation for Economic Cooperation and Development OECD OSHA Occupational Safety & Health Administration persistent and bioaccumulative and toxic PBT PNEC Predicted No Effect Concentration Registration, Evaluation and Authorization of Chemicals REACH RID Dangerous goods regulations for transport by rail Technische Regeln für Gefahrstoffe TRGS United Nations UN VOC Volatile organic compounds ZNS central nervous system 16.3. Key literature references and sources for data No data available

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 23 Jan 2023 Print date: 24 Jan 2025 Version: 3

Page 13/13

Red Lube 2400 500ml

TECH MASTERS world of innovations

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (Aquatic Chronic 3)	H412: Harmful to aquatic life with long lasting effects.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements		
H220	Extremely flammable gas.	
H225	Highly flammable liquid and vapour.	
H280	Contains gas under pressure; may explode if heated.	
H304	May be fatal if swallowed and enters airways.	
H317	May cause an allergic skin reaction.	
H336	May cause drowsiness or dizziness.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

* Data changed compared with the previous version.