according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 30 Jan 2025 Print date: 30 Jan 2025

Version: 5 Page 1/12



Supersolv 6kg

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Supersolv 6kg

Article No.:

T498006

UFI:

XRT3-X0HM-AA0U-KHEN

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Cleaning agent

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH

Hartleitnerstraße 3 4653 Eberstalzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
STOT-single exposure (STOT SE 3)	H335: May cause respiratory irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Carcinogenicity (Carc. 2)	H351: Suspected of causing cancer.	
STOT-repeated exposure (STOT RE 2)	H373: May cause damage to organs through prolonged or repeated exposure. (If swallowed)	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



GHS07 Exclamation mark



GHS08 Health hazard

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 30 Jan 2025 Print date: 30 Jan 2025

Version: 5 Page 2/12



Supersolv 6kg

Signal word: Warning

Hazard components for labelling:

dichloromethane

Hazard state	Hazard statements for health hazards		
H315	Causes skin irritation.		
H319	Causes serious eye irritation.		
H335	May cause respiratory irritation.		
H336	May cause drowsiness or dizziness.		
H351	Suspected of causing cancer.		
H373	May cause damage to organs through prolonged or repeated exposure. (If swallowed)		

Precautionary statements Prevention		
P201	Obtain special instructions before use.	
P260	Do not inhale mist, vapour.	
P271	Use only outdoors or in a well-ventilated area.	
P280	Wear protective gloves/protective clothing and eye protection/face protection.	

Precautionary statements Response		
P308 + P313	IF exposed or concerned: Get medical advice/attention.	
P337 + P313	If eye irritation persists: Get medical advice/attention.	

Additional information:

30% and more: halogenated hydrocarbons

2.3. Other hazards

Adverse physicochemical effects:

This substance does not pose a physical risk. See recommendations on other products on site. This substance does not pose an environmental risk. Under normal conditions of use, no environmentally harmful effect is known or foreseeable.

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 75-09-2 EC No.: 200-838-9 REACH No.: 01-2119480404-41	dichloromethane Carc. 2 (H351), Eye Irrit. 2 (H319), STOT RE 2 (H373), STOT SE 3 (H335, H336), Skin Irrit. 2 (H315) Warning Acute Toxicity Estimate ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, vapour) 86 mg/L	100 Vol-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

When in doubt or if symptoms are observed, get medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

Following inhalation:

In case of inhalation of large quantities, remove the person to fresh air, keep warm and immobilise. Place unconscious person in recovery position. In any case, notify a doctor to assess whether observation and in-patient symptomatic treatment are required. If breathing is irregular or stopped, give artificial respiration and call a doctor. Consult a doctor.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 30 Jan 2025 Print date: 30 Jan 2025

Version: 5 Page 3/12



Supersolv 6kg

In case of skin contact:

Remove soiled and soaked clothing and wash skin thoroughly with soap and water or a suitable detergent. Check for product residues between skin and clothing, wristwatch, shoes, etc. In the event of extensive contamination and/or injury to the skin, a doctor must be consulted or the affected person transferred to hospital. In case of irritation, consult a doctor.

After eve contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

In case of eye irritation consult an ophthalmologist.

Following ingestion:

Do not allow anything to be taken by mouth. If small amounts are ingested (not more than one sip), rinse mouth with water and consult a doctor. Keep at rest. Do NOT induce vomiting. Seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

For further information on health hazards: see section 11.

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Non-flammable.

Water mist, Foam, ABC-powder, BC-powder, Carbon dioxide

Unsuitable extinguishing media:

Water jet

5.2. Special hazards arising from the substance or mixture

In case of fire, dense black smoke is often produced. Exposure to decomposition products can be harmful to health. Do not inhale smoke.

Hazardous combustion products:

Carbon monoxide (CO), Carbon dioxide (CO2), Carbon monoxide dichloride (CCl2O), Hydrogen chloride (HCl), Chlorine (Cl2)

5.3. Advice for firefighters

Due to the toxicity of the gases produced during thermal decomposition, use self-contained breathing apparatus (insulating equipment). Collect contaminated extinguishing water separately. Do not empty it into the pipes. Cool tanks and parts exposed to heat flow that are not on fire with water. Remove all sources of ignition.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear personal protection equipment (refer to section 8). Avoid breathing vapours. Avoid contact with eyes and skin. In case of spillage/release of large quantities, remove uninvolved persons and allow only trained personnel with protective equipment to intervene.

6.1.2. For emergency responders

Personal protection equipment:

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Stop and collect leaks or spills with liquid-binding, non-combustible material, e.g.: Sand, earth, universal binder, diatomaceous earth in drums for disposal of waste. Prevent entry into drains or watercourses. If the product pollutes watercourses, rivers or sewage systems, inform the competent authorities in accordance with the prescribed procedure. Set up canisters for disposal of waste generated in accordance with applicable regulations (see section 13).

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 30 Jan 2025 Print date: 30 Jan 2025

Version: 5 Page 4/12



Supersolv 6kg

6.3. Methods and material for containment and cleaning up

For cleaning up:

In the event of soil contamination and after collecting the product by absorption with neutral, non-flammable binder, wash the contaminated area with plenty of water. Preferably clean with a detergent, do not use organic solvents.

6.4. Reference to other sections

See section 7 for further information on safe handling.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Precautions for safe handling:

Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Ensure good ventilation/extraction at the workplace. Avoid contact with skin, eyes and clothes. Avoid breathing dust/mist.

Advices on safe handling:

For personal protection, see section 8. Observe label information and occupational health and safety regulations. Do not inhale aerosol. Avoid inhalation of vapours. Carry out any industrial work with possible formation of vapours/mist etc. in closed apparatus. Provide vapour extraction at the source of emission and general room ventilation. In addition, provide suitable respiratory protective equipment for short-term work and emergency interventions. Always collect emissions at source. Do not allow mixture to come into contact with skin and eyes. Store opened packaging carefully closed and upright.

Improper equipment and method of operation:

Smoking, eating and drinking are prohibited in the premises where the mixture is used. Never open packages with pressure.

Fire prevent measures:

Use only outdoors or in a well-ventilated area.

Prevent access for unauthorised persons.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Store in a well-ventilated place. Keep container tightly closed. Store in a cool dry place. Keep only in original packaging. The floor must be impermeable and form a catch basin so that no liquid can leak out in the event of an unforeseen spillage.

Further information on storage conditions:

Store away from heat, weather, moisture and frost.

7.3. Specific end use(s)

Recommendation:

No further relevant information available.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 30 Jan 2025 Print date: 30 Jan 2025

Version: 5 Page 5/12



Supersolv 6kg

SECTION 8: Exposure controls/personal protection

* 8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark 	
MAK (AT)	dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	① 50 ppm (175 mg/m³) ⑤ (kann über die Haut aufgenommen werden) III B, H	
MAK (AT)	dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	② 200 ppm (700 mg/m³) ⑤ (max. 2x30 min./Schicht, kann über die Haut aufgenommen werden) III B, H	
IOELV (EU) from 22 Feb 2017	dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	① 100 ppm (353 mg/m³) ② 200 ppm (706 mg/m³) ⑤ (may be absorbed through the skin)	

8.1.2. Biological limit values

Limit value type (country of origin)	Substance name	Limit value	① Parameter② Test material③ Time of sampling:④ Remark
BLV (EU) from 1 Jun 2014	dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	3 mg	① Methylene chloride② urine③ no restriction
BLV (EU) from 1 Jun 2014	dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	1 mg/L	① Methylene chloride② blood③ no restriction

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type
		② Exposure route
dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	353 mg/m ³	① DNEL worker ② Long-term – inhalation, systemic effects
dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	706 mg/m ³	① DNEL worker ② Long-term – inhalation, systemic effects
dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	88.3 mg/m ³	DNEL Consumer Long-term – inhalation, systemic effects
dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	353 mg/m ³	DNEL worker Long-term – inhalation, local effects
dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	12 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	5.82 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 30 Jan 2025 Print date: 30 Jan 2025

Version: 5 Page 6/12



Supersolv 6kg

Substance name		① DNEL type ② Exposure route
dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	hw/day	① DNEL Consumer ② Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	0.31 mg/L	① PNEC aquatic, freshwater
dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	0.031 mg/L	① PNEC aquatic, marine water
dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	26 mg/L	① PNEC sewage treatment plant
dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	2.57 mg/kg	① PNEC sediment, freshwater
dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	0.26 mg/kg	① PNEC sediment, marine water
dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9	0.33 mg/kg	① PNEC soil

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No data available

8.2.2. Personal protection equipment

Eye/face protection:

Avoid contact with eyes. Use eye protection against liquid splashes. Safety goggles complying with standard EN 166 must be worn at all times during use. In case of increased danger, use a face shield to protect the face. Wearing prescription glasses does not constitute protection. Contact lens wearers are advised to use corrective lenses during work where irritating fumes may be generated. Provide eye shower systems in the premises where the product is used.

Skin protection:

Hand protection:

Wear suitable protective gloves in case of prolonged or repeated skin contact.

Use suitable chemical-resistant protective gloves according to standard EN ISO 374-1. Gloves must be chosen according to the use and duration of use in the workplace. Protective gloves must be chosen according to the workplace: other chemicals could be changed, physical protection required (cutting, pricking, thermal protection), dexterity required.

Glove material:

- PVA (Polyvinyl alcohol)
- PE (polvethylene)
- Polytetrafluoroethylene (PTFE)
- Hexafluoropropylene-vinylidene fluoride copolymer

Body protection:

Avoid prolonged skin contact.

In case of heavy splashing, wear liquid-tight chemical protective clothing (type 3) according to EN 14605/A1 to avoid any skin contact. If there is a risk of splashing, wear chemical protective clothing (type 6) according to EN 13034/A1 to avoid any skin contact. Personnel must wear regularly washed work clothes. After contact with the product, all soiled parts of the body must be washed.

Respiratory protection:

Avoid breathing vapours.

In case of inadequate ventilation wear respiratory protection.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 30 Jan 2025 Print date: 30 Jan 2025

Version: 5 Page 7/12



Supersolv 6kg

When workers are exposed to concentrations exceeding the exposure limits, they must wear appropriate and approved respiratory protective equipment.

Gas and steam filter (combi-filter) according to standard EN 14387:

- A1 (brown)
- AX (brown)

Respiratory protection in case of vapour / aerosol release: combination filter against gases / vapours of organic compounds and against solid and liquid particles (type AX-P).

Other protection measures:

Use clean and properly maintained personal protective equipment. Keep personal protective equipment in a clean place, away from the work area. Do not eat, drink or smoke during use. Remove and wash contaminated clothing before reuse. Provide adequate ventilation, especially in enclosed spaces.

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid Colour: not determined

Odour: not determined flammability: No data available

Safety relevant basis data

Parameter	Value	at °C	① Method
			② Remark
рН	No data available		
Melting point	-97 °C		
Freezing point	No data available		
Initial boiling point and boiling range	40 °C		
Flash point	No data available		
Evaporation rate	No data available		
Auto-ignition temperature	No data available		
Upper/lower flammability or explosive limits	13 - 22 Vol-%		
Vapour pressure	No data available		
Vapour density	No data available		
Density	No data available		
Relative density	1.3	20 °C	
Bulk density	not applicable		
Water solubility	partially soluble		
Partition coefficient: n-octanol/water	1.25		
Dynamic viscosity	No data available		
Kinematic viscosity	No data available		
Self ignition temperature	605 °C		

9.2. Other information

No further relevant information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 30 Jan 2025 Print date: 30 Jan 2025

Version: 5 Page 8/12



Supersolv 6kg

10.3. Possibility of hazardous reactions

At high temperatures, the mixture may release hazardous decomposition products, such as carbon monoxide, carbon dioxide, smoke or nitrogen oxide.

10.4. Conditions to avoid

Heat, exposure to light

Remove all sources of ignition.

10.5. Incompatible materials

Oxidizing agent, metals, Acids, alkalines

10.6. Hazardous decomposition products

Carbon monoxide (CO), Carbon dioxide (CO2), Carbon monoxide dichloride (CCl2O), Hydrogen chloride (HCl), Chlorine (Cl2)

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9

ATE (inhalation, vapour): 86 mg/L

LD₅₀ oral: >2,000 mg/kg (Rat)

LD₅₀ dermal: >2,000 mg/kg (Rat) OECD 402

LC₅₀ Acute inhalation toxicity (vapour): 86 mg/L 4 h (Mouse)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

May cause reversible skin damage such as skin inflammation or redness and scabbing or appearance of oedema as a result of exposure for a duration of up to 4 hours. Prolonged or repeated contact with the substance may eliminate the natural oily film of the skin and therefore cause non-allergic contact dermatitis and penetration of the epidermis.

Serious eye damage/irritation:

May cause reversible effects to the eye, such as eye irritation, which completely resolves in an observation period of 21 days. Splashes in the eyes may cause irritation and reversible damage.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Suspected human carcinogenic effect.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

\P:b10f7ed4-e21e-4010-ab71-4f328a49b43f\

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional information:

Irritant effects may lead to functional impairment of the respiratory system and may be accompanied by symptoms such as coughing, pain, dyspnoea and general difficulty in breathing. Narcotic effects may occur, such as drowsiness, narcotic effect, decreased alertness, loss of reflexes, incoordination and dizziness. They may also manifest as severe headache or nausea and lead to decreased judgment, drowsiness, irritability, fatigue or memory impairment. May cause damage to organs through prolonged or repeated exposure. Risk of serious injury to the lungs (through inhalation). Liver injury may occur. Damage to the central nervous system, liver, kidneys, blood and spinal cord if swallowed.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 30 Jan 2025 Print date: 30 Jan 2025

Version: 5 Page 9/12



Supersolv 6kg

11.2. Information on other hazards

Endocrine disrupting properties:

No further relevant information available.

SECTION 12: Ecological information

12.1. Toxicity

dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9

LC₅₀: 193 mg/L 4 d (fish, Pimephales promelas)

NOEC: 83 mg/L 28 d (fish, Pimephales promelas)

EC₅₀: 27 mg/L 2 d (crustaceans, Daphnia magna)

ErC₅₀: >662 mg/L 4 d (Algae/water plant, Pseudokirchnerella subcapitata)

Aquatic toxicity:

No further relevant information available.

Assessment/classification:

No further relevant information available.

12.2. Persistence and degradability

dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9

Biodegradation: Yes, slowly

Additional information:

No further relevant information available.

12.3. Bioaccumulative potential

dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9

Log Kow: 1.25

Bioconcentration factor (BCF): < 100

Partition coefficient: n-octanol/water:

1.25

Accumulation / Evaluation:

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

dichloromethane CAS No.: 75-09-2 EC No.: 200-838-9

Results of PBT and vPvB assessment: -

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No further relevant information available.

12.7. Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains.

Waste treatment options

Appropriate disposal / Package:

Uncleaned packaging: Only dispose of the container when it is empty. Do not remove the label(s) on the container. Return to an authorised disposal company.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 30 Jan 2025 Print date: 30 Jan 2025

Version: 5 Page 10/12



Supersolv 6kg

13.2. Additional information

Waste disposal must be carried out without risk to people and the environment, in particular to water, air, soil, fauna and flora. Disposal or recycling in accordance with valid legislation preferably by an authorised waste collector or a specialist waste management company. Do not contaminate soil or groundwater, do not dispose of waste in the environment.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or	ID number		
UN 1593	UN 1593	UN 1593	UN 1593
14.2. UN proper ship	ping name		
DICHLOROMETHANE	DICHLOROMETHANE	DICHLOROMETHANE	DICHLOROMETHANE
14.3. Transport haza	rd class(es)	,	
6.1	6.1	6.1	6.1
14.4. Packing group	-		
III	III	III	III
14.5. Environmental	hazards	`	
No	No	No	No data available
14.6. Special precau	tions for user		
Special Provisions: 516 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Hazard identification number (Kemler No.): 60 Classification code: T1 Tunnel restriction code: (E)	Special Provisions: 516 802 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Classification code: T1	Special Provisions: Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 EmS-No.: F-A, S-A	Excepted Quantities (EQ): E1 Remark: IATA Packing Instructions - Passenger: 655 IATA Maximum Quantity - Passenger: 60 L IATA- Verpackungsanweisung - Cargo: 663 IATA Maximum Quantity - Cargo: 220 L

14.7. Maritime transport in bulk according to IMO instruments not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Regulation (EC) No 1272/2008, as amended by Regulation (EU) No 2018/669 (ATP 11).

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 100 Vol-%

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 30 Jan 2025 Print date: 30 Jan 2025

Page 11/12

Version: 5



Supersolv 6kg

SECTION 16: Other information

16.1. Indication of changes

	8.1.	Control parameters
	16.1.	Indication of changes
ſ	16.2.	Abbreviations and acronyms

16.2. Abbreviations and acronyms

American Conference of Governmental Industrial Hygienists ACGIH

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland

Waterways

European Agreement concerning the International Carriage of Dangerous Goods by Road ADR

BCF Bioconcentration Factor CAS Chemical Abstracts Service

Classification, Labelling and Packaging CLP

DNEL derived no-effect level Effective Concentration 50% EC_{50}

European Standard ΕN

Exposure scenario ES

ICAO International Civil Aviation Organization **IMDG** International Maritime Dangerous Goods International Maritime Organization IMO

KG body weight

Lethal (fatal) Concentration 50% LC_{50}

Lethal (fatal) Dose 50% LD_{50}

MAK Maximum concentration in the workplace air (CH)

National Fire Protection Association **NFPA**

National Institute for Occupational Safety & Health NIOSH

NOEC No Observed Effect Concentration

OECD Organisation for Economic Cooperation and Development

OEL Threshold Limit Value

Occupational Safety & Health Administration **OSHA** PBT persistent and bioaccumulative and toxic

PNEC Predicted No Effect Concentration

Registration, Evaluation and Authorization of Chemicals **REACH** Dangerous goods regulations for transport by rail **RID**

TRGS Technische Regeln für Gefahrstoffe

UN **United Nations**

VOC Volatile organic compounds

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
STOT-single exposure (STOT SE 3)	H335: May cause respiratory irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Carcinogenicity (Carc. 2)	H351: Suspected of causing cancer.	
STOT-repeated exposure (STOT RE 2)	H373: May cause damage to organs through prolonged or repeated exposure. (If swallowed)	

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 30 Jan 2025 Print date: 30 Jan 2025

Version: 5 Page 12/12



Supersolv 6kg

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements			
H315	Causes skin irritation.		
H319	Causes serious eye irritation.		
H335	May cause respiratory irritation.		
H336	May cause drowsiness or dizziness.		
H351	Suspected of causing cancer.		
H373	May cause damage to organs through prolonged or repeated exposure.		

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

st Data changed compared with the previous versic	on.
--	-----