according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878 Revision date: 25 Feb 2025 Print date: 25 Feb 2025 Version: 5

Page 1/13

Safe Clean NSF 500ml

TECH MASTERS world of innovations

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1. Product identifier Trade name/designation:

Safe Clean NSF 500ml

Article No.: T204101 UFI: 9A23-02K1-ET0H-NXP6

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Cold cleaner

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH Hartleitnerstraße 3 4653 Eberstalzell Austria Telephone: +43 (0) 7241 213 79 E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:





according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 25 Feb 2025 Print date: 25 Feb 2025 Version: 5



Page 2/13

Safe Clean NSF 500ml

Hazard components for labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane; propan-2-ol

Hazard statements for physical hazards	
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

Hazard statements for health hazardsH315Causes skin irritation.

H315Causes skin irritation.H336May cause drowsiness or dizziness.

Hazard statements for environmental hazards

H411 Toxic to aquatic life with long lasting effects.

Supplemental hazard information: none

Precautionary statements Prevention		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P260	Do not breathe mist/vapours/spray.	
P271	Use only outdoors or in a well-ventilated area.	
P273	Avoid release to the environment.	
P280	Wear protective gloves and eye protection/face protection.	

P302 + P352 IF ON SKIN: Wash with plenty of water and soap.	
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.	J.
P312 Call a POISON CENTER if you feel unwell.	

Precautionary statements Storage

P403	Store in a well-ventilated place.	
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	

Precautionary statements Disposal

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

* 3.2. Mixtures

Description:

Cleaning agent

Additional information:

Aerosols and containers fitted with a solid nebuliser containing substances or mixtures classified as hazardous by aspiration must not be labelled for this hazard.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878 Revision date: 25 Feb 2025 Print date: 25 Feb 2025 Version: 5



Page 3/13

Safe Clean NSF 500ml

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
EC No.: 921-024-6 REACH No.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n- hexane Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 2 (H225), STOT SE 3 (H336), Skin Irrit. 2 (H315) Danger Acute Toxicity Estimate ATE (oral) > 5,000 mg/kg ATE (dermal) > 2,920 mg/kg ATE (inhalation, gases) > 20 ppmV ATE (inhalation, vapour) > 25.2 mg/L	75 - < 100 Vol-%
	Aliphatic hydrocarbons The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].	≥ 30 Vol-%
CAS No.: 67-63-0 EC No.: 200-661-7 Index No.: 603-117-00-0 REACH No.: 01-2119457558-25	propan-2-ol Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) •••••••••••••••••••••••••••••	2.5 - < 10 Vol-%
CAS No.: 124-38-9 EC No.: 204-696-9	carbon dioxide Press. Gas (Liq.) (H280) Warning Acute Toxicity Estimate ATE (oral) ≥ 5,000 mg/kg ATE (dermal) ≥ 5,000 mg/kg ATE (inhalation, vapour) 259,354 mg/L ATE (inhalation, dust/mist) ≥ 50 mg/L	2.5 - < 10 Vol-%

SECTION 4: First aid measures

* 4.1. Description of first aid measures Following inhalation: If unconscious, position and transport in stable lateral position. In case of skin contact: Wash off immediately with soap and water and rinse well. After eye contact: Rinse opened eye for several minutes under running water. Consult a doctor if symptoms persist Following ingestion: Do not induce vomiting, seek medical help immediately. 4.2. Most important symptoms and effects, both acute and delayed No data available 4.3. Indication of any immediate medical attention and special treatment needed No data available Visual Action of any immediate medical attention and special treatment needed No data available Output Description: Description:

SECTION 5: Firefighting measures

* 5.1. Extinguishing media

Suitable extinguishing media:

Spray mist, Powder, Carbon dioxide, alcohol resistant foam

5.2. Special hazards arising from the substance or mixture

No data available

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 25 Feb 2025 Print date: 25 Feb 2025 Version: 5

Page 4/13

Safe Clean NSF 500ml

5.3. Advice for firefighters

Special protective equipment: Put on breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear protective equipment. Keep unprotected persons away.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of spillage into water or sewage system, inform the competent authorities.

6.3. Methods and material for containment and cleaning up

For cleaning up:

Do not wash away with water or aqueous detergents.

Other information:

Provide adequate ventilation.

6.4. Reference to other sections

Further information on proper storage: see section 7. For further information on personal protective equipment: see section 8. For further information on disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Ensure good ventilation/extraction at the workplace.

Fire prevent measures:

Do not spray against a flame or on a glowing object. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Container is under pressure. Protect from sunlight and temperatures above 50°C (e.g. from incandescent lamps). Do not open by force or burn even after use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Store in a cool place. The official regulations for the storage of pressurised gas packages must be observed.

Hints on storage assembly:

The official regulations for the storage of pressurised gas packages must be observed. **Storage class (TRGS 510, Germany):** 2B – Aerosol dispensers and lighters

Further information on storage conditions:

Store in a cool, dry place in well-sealed containers. Protect from heat and direct sunlight.

* 7.3. Specific end use(s)

No data available

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878 Revision date: 25 Feb 2025 Print date: 25 Feb 2025 Version: 5

Page 5/13

Safe Clean NSF 500ml

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
МАК (АТ)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	 2 800 ppm (2,000 mg/m³) (max. 4x15 min./Schicht)
МАК (АТ)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	 200 ppm (500 mg/m³)
МАК (АТ)	carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9	 5,000 ppm (9,000 mg/m³)
MAK (AT)	carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9	 2 10,000 ppm (18,000 mg/m³) (max. 3x60 min./Schicht, Momentanwert)
IOELV (EU)	carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9	① 5,000 ppm (9,000 mg/m³)

8.1.2. Biological limit values No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	 DNEL type
		② Exposure route
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane EC No.: 921-024-6	2,035 mg/m ³	 DNEL worker Long-term - inhalation, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane EC No.: 921-024-6	608 mg/m ³	 DNEL Consumer Long-term - inhalation, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane EC No.: 921-024-6	773 mg/kg bw/ day	 DNEL worker Long-term - dermal, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane EC No.: 921-024-6	300 mg/kg bw/ day	 DNEL worker Long-term - dermal, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane EC No.: 921-024-6	699 mg/kg bw/ day	 DNEL Consumer Long-term - dermal, systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane EC No.: 921-024-6	699 mg/kg bw/ day	 DNEL Consumer Long-term - oral, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	500 mg/m ³	 DNEL worker Long-term - inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	89 mg/m³	 DNEL Consumer Long-term - inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	888 mg/kg bw/ day	 DNEL worker Long-term - dermal, systemic effects



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 25 Feb 2025 Print date: 25 Feb 2025 Version: 5



Page 6/13

Safe Clean NSF 500ml

Substance name	DNEL value	① DNEL type
		② Exposure route
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	319 mg/kg bw/ day	 DNEL Consumer Long-term - dermal, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	26 mg/kg bw/ day	 DNEL Consumer Long-term - oral, systemic effects
Substance name	PNEC Value	① PNEC type
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	 PNEC aquatic, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	2,251 mg/L	 PNEC sewage treatment plant
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	 PNEC sediment, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	28 mg/kg	① PNEC soil
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, intermittent release

* 8.2. Exposure controls

8.2.1. Appropriate engineering controls No further details. See section 7.

8.2.2. Personal protection equipment



Eye/face protection:

Tight-fitting safety goggles (EN 166)

Skin protection:

Hand protection:

Gloves / solvent resistant

Selection of glove material considering breakthrough times, permeation rates and degradation. Glove material:

The selection of a suitable glove depends not only on the material but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use. NBR (Nitrile rubber); Recommended material thickness: ≥ 0.5 mm

Penetration time of the glove material: For continuous contact we recommend gloves with a breakthrough time of at least 240 minutes, with the preference for a breakthrough time greater than 480 minutes. For short term or splash protection we recommend the same. We are aware that suitable gloves offering this protection are not available. In this case, a shorter breakthrough time is permissible, provided the procedures for maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance the gloves give against a chemical substance, as this depends on the exact composition of the material of the gloves. The exact breakthrough time should be checked with the glove manufacturer and adhered to.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 25 Feb 2025 Print date: 25 Feb 2025 Version: 5

Page 7/13

Safe Clean NSF 500ml

Body protection:

Use protective suit. (EN-13034/6). It is recommended to wear antistatic, chemical and oil-resistant clothing and safety shoes that completely cover the skin. (EN1149; EN340&EN ISO 13688; EN13034-6).

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Filter A2/P2

Other protection measures:

General protective and hygienic measures: Keep away from food, drink and animal feed. Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work. Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin. General ventilation.

8.2.3. Environmental exposure controls

Use a suitable container to prevent environmental pollution.

SECTION 9: Physical and chemical properties

* 9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid Colour: colourless flammability: No data available Form: Aerosol Odour: characteristic

Safety relevant basis data

Parameter	Value	at °C	1 Method
			② Remark
рН	not applicable		② Mixture is not polar/aprotic.
Melting point	No data available		
Freezing point	No data available		
Initial boiling point and boiling range	82 °C		② propan-2-ol
Flash point	-9 °C		② Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane
Evaporation rate	not applicable		
Auto-ignition temperature	> 200 °C		
Upper/lower flammability or explosive limits	0.8 - 12 Vol-%		
Vapour pressure	5,500 hPa	20 °C	
Vapour density	No data available		
Density	0.72 g/cm ³	20 °C	
Bulk density	not applicable		
Water solubility	completely miscible		
Dynamic viscosity	No data available		
Kinematic viscosity	≤ 20.5 mm²/s	40 °C	

* 9.2. Other information

The product is not self-igniting. The product is not explosive, but the formation of explosive vapour/air mixtures is possible. formation of explosive vapour/air mixtures is possible. Organic solvents: 96,5%

Solid content 0,0 %

9.2.1. Information with regard to physical hazard classes

Aerosols:

Extremely flammable aerosol. Pressurized container: May burst if heated.

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 25 Feb 2025 Print date: 25 Feb 2025 Version: 5

Page 8/13

Safe Clean NSF 500ml

10.2. Chemical stability

Thermal decomposition / Conditions to avoid No decomposition when used as directed.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

5				
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane	EC No.: 921-024-6			
LD ₅₀ oral: >5,000 mg/kg (Rat) OECD 401				
LD ₅₀ dermal: >2,920 mg/kg (Rabbit)				
LC ₅₀ Acute inhalation toxicity (gas): >20 ppmV 4 h (Rat) OECD 403				
LC ₅₀ Acute inhalation toxicity (vapour): >25.2 mg/L 4 h (Rat)				
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7				
LD ₅₀ oral: >2,000 mg/kg (Rat)				
LD ₅₀ dermal: >2,000 mg/kg (Rat)				
LC ₅₀ Acute inhalation toxicity (gas): >25 ppmV 4 h (Rat)				

LC₅₀ Acute inhalation toxicity (vapour): >20 mg/L 6 h (Rat)

carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9

ATE (inhalation, vapour): 259,354 mg/L

LD₅₀ oral: ≥5,000 mg/kg (Ratte)

LD₅₀ dermal: ≥5,000 mg/kg (Kaninchen)

LC₅₀ Acute inhalation toxicity (dust/mist): ≥50 mg/L 4 h (Ratte)

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met. **Carcinogenicity:**

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties:

None of the ingredients are included.



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 25 Feb 2025 Print date: 25 Feb 2025 Version: 5

Page 9/13

Safe Clean NSF 500ml

SECTION 12: Ecological information

12.1. Toxicity

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane</th>EC No.: 921-024-6LC₅₀: 11.4 mg/L 4 d (fish, Oncorhynchus mykiss) OECD 203EC₅₀: 3 mg/L 2 d (crustaceans, Daphnia magna) OECD 202NOEC: 0.17 mg/L 21 d (crustaceans, Daphnia magna)LOEC: 0.32 mg/L 21 d (crustaceans, Daphnia magna)EC₅₀: 30 - 100 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)LC₅₀: >1 - 10 mg/L 4 d (fish, Pimephales promelas)EC₅₀: >1 - 10 mg/L 2 d (crustaceans, Daphnia magna)NOEC: 2.045 mg/L 28 d (fish, Oncorhynchus mykiss)NOEC: 1 mg/L 21 d (crustaceans, Daphnia magna)EC₅₀: >1 - 30 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata) OECD 201LOEC: 0.32 mg/L 21 d (crustaceans, Daphnia magna)NOEC: 1 mg/L 24 d (fish, Oncorhynchus mykiss)NOEC: 1 mg/L 21 d (crustaceans, Daphnia magna) OECD 211ErC₅₀: 10 - 30 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata) OECD 201LOEC: 0.32 mg/L 21 d (Daphnia magna)LOEC: 0.32 mg/L 21 d (Daphnia magna)

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

LC₅₀: >1,000 mg/L 4 d (fish)

EC₅₀: >1,000 mg/L 2 d (crustaceans)

LC50: 9,640 mg/L 4 d (fish, Pimephales promelas)

LC₅₀: 9,714 mg/L 1 d (Daphnia magna)

EC₅₀: >100 mg/L (Algae/water plant, Bacteria)

LOEC: 1,000 mg/L (Alge)

EC₅₀: >100 mg/L 2 d (crustaceans, Daphnia magna)

ErC₅₀: >100 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus)

LOEC: 1,000 mg/L (Algae/water plant, Algae)

ErC₅₀: >100 mg/L 3 d (Algae/water plant, Scenedesmus subspicatus)

LOEC: 1,000 mg/L

12.2. Persistence and degradability

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane EC No.: 921-024-6

Biodegradation: Yes, rapidly

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Biodegradation: Yes, rapidly

Remark: Readily biodegradable (according to OECD criteria).

Biodegradation:

Not readily biodegradable.

12.3. Bioaccumulative potential

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane EC No.: 921-024-6

Log K_{OW}: 5.2 Bioconcentration factor (BCF): 250

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Log Kow: 0.05

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, <5% n-hexane EC No.: 921-024-6 Results of PBT and vPvB assessment: —



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878 **Revision date:** 25 Feb 2025

Print date: 25 Feb 2025 Version: 5



Page 10/13

Safe Clean NSF 500ml

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Results of PBT and vPvB assessment: —

carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9

Results of PBT and vPvB assessment: -

Aliphatic hydrocarbons

Results of PBT and vPvB assessment: -

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties.

* 12.7. Other adverse effects

Toxic to fish.

Toxic to aquatic life. water hazard class 2: obviously hazardous to water Do not allow to enter drains/surface water/ground water. Drinking water hazard even when small quantities leak into the subsoil.

SECTION 13: Disposal considerations

* 13.1. Waste treatment methods

Must not be disposed of together with household waste. Do not allow to enter drains/surface water/ ground water.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV Directive 2008/98/EC (Waste Framework Directive)

_			
	HP 3	Flammable	
	HP 4	Irritant — skin irritation and eye damage	
	HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
	HP 14	Ecotoxic	

Waste treatment options

Appropriate disposal / Package:

Dispose of waste according to applicable legislation.

Recommended cleaning agent: Water, if necessary with the addition of cleaning agents.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or	ID number	х	
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shi	oping name		-
AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS
14.3. Transport haza	ard class(es)		
2.1	2.1	2.1	2.1
14.4. Packing group			
		-	
14.5. Environmenta	hazards		-
	×2	MARINE POLLUTANT	No data available

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878 Revision date: 25 Feb 2025 Print date: 25 Feb 2025 Version: 5



Page 11/13

*

Safe Clean NSF 500ml

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.6. Special precau	tions for user		
14.6. Special precau Special Provisions: Attention: Gases Excepted Quantities (EQ): E0 Classification code: 5F Tunnel restriction code: (D) Remark: Transport category 2	· ·	Special Provisions: Attention: Gases Limited quantity (LQ): 1L Excepted Quantities (EQ): E0 EmS-No.: F-D, S-U Remark: Stowage Code: SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. Segregation Code: SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE	Special Provisions: Attention: Gases

14.7. Maritime transport in bulk according to IMO instruments No data available

SECTION 15: Regulatory information

* 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Directive 2012/18/EU Named dangerous substances - ANNEX I: None of the ingredients are included.

Restrictions on use:

Seveso category E2 Hazardous to the aquatic environment in Category Chronic 2 P3b FLAMMABLE AEROSOLS Quantity threshold (in tons) for use in lower class farms 200 t Quantity threshold (in tons) for use in upper-tier establishments 500 t Regulation (EC) No 1907/2006 ANNEX XVII Restriction conditions: 3 Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II: None of the ingredients are included. Regulation (EU) 2019/1148

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 25 Feb 2025 Print date: 25 Feb 2025 Version: 5



Page 12/13

Safe Clean NSF 500ml

Annex I - RESTRICTED EXPORT SUBSTANCES FOR EXPLOSIVES (upper concentration limit for a permit pursuant to Article 5(3)): None of the ingredients are included.

Annex II - EXPLOSIVES REPORTABLE FOR EXPLOSIVES: None of the ingredients are included.

Regulation (EC) No 273/2004 on drug precursors: None of the ingredients are included. Regulation (EC) No 111/2005 laying down rules for the monitoring of trade in drug precursors between the Community and third countries: None of the ingredients are included.

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds: Volatile organic compounds (VOC) content in percent by weight: 694.8 g/L

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

* 16.1. Indication of changes

3.2. Mixtures Description of first aid measures 4.1. 5.1. Extinguishing media Specific end use(s) 7.3. 8.2. Exposure controls 9.1. Information on basic physical and chemical properties 9.2. Other information 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 12.7. Other adverse effects 13.1. Waste treatment methods 14.6. Special precautions for user 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Indication of changes 16.1. 16.2. Abbreviations and acronyms

* 16.2. Abbreviations and acronyms

ACGIH American Conference of Governmental Industrial Hygienists ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterwavs European Agreement concerning the International Carriage of Dangerous Goods by Road ADR BCF **Bioconcentration Factor** Chemical Abstracts Service CAS Classification, Labelling and Packaging CLP DNEL derived no-effect level Effective Concentration 50% EC₅₀ FN European Standard Exposure scenario FS EWC European Waste Catalogue International Civil Aviation Organization **ICAO** IMDG International Maritime Dangerous Goods IMO International Maritime Organization KG body weight Lethal (fatal) Concentration 50% LC₅₀ Lethal (fatal) Dose 50% LD_{50} Maximum concentration in the workplace air (CH) MAK National Fire Protection Association NFPA NIOSH National Institute for Occupational Safety & Health NOFC No Observed Effect Concentration Organisation for Economic Cooperation and Development OECD Occupational Safety & Health Administration OSHA

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 25 Feb 2025 Print date: 25 Feb 2025 Version: 5

Page 13/13

Safe Clean NSF 500ml



PBT	persistent and bioaccumulative and toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations
VOC	Volatile organic compounds

16.3. Key literature references and sources for data No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements		
H225	Highly flammable liquid and vapour.	
H280	Contains gas under pressure; may explode if heated.	
H304	May be fatal if swallowed and enters airways.	Π
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	٦
H336	May cause drowsiness or dizziness.	
H411	Toxic to aquatic life with long lasting effects.	

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

* Data changed compared with the previous version.