

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4



Page 1/19

Alu Guard 500ml

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Alu Guard 500ml

Article No.:

T112003

UFI:

8ATC-R5VV-T30S-9THD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Aerosol coating

* 1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH

Hartleitnerstraße 3

4653 Eberstälzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters (<i>Aerosol 1</i>)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	
Aspiration hazard (<i>Asp. Tox. 1</i>)	H304: May be fatal if swallowed and enters airways.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 3</i>)	H412: Harmful to aquatic life with long lasting effects.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4



Page 2/19

Alu Guard 500ml

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS07
Exclamation mark

Signal word: Danger

Hazard components for labelling:

acetone; Hydrocarbons, C9, aromatics; Xylene; Reaction mass of ethylbenzene and xylene

Hazard statements for physical hazards	
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

Hazard statements for health hazards	
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Hazard statements for environmental hazards	
H412	Harmful to aquatic life with long lasting effects.

Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.

Precautionary statements Prevention	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing and eye protection/face protection.

Precautionary statements Response	
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.

Precautionary statements Storage	
P403	Store in a well-ventilated place.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary statements Disposal	
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4



Page 3/19

Alu Guard 500ml

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description:

Active ingredient mixture with propellant gas

Additional information:

Aerosols and containers fitted with a solid nebuliser containing substances or mixtures classified as hazardous by aspiration must not be labelled for this hazard.

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 67-64-1 EC No.: 200-662-2 Index No.: 606-001-00-8 REACH No.: 01-2119471330-49	acetone Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger EUH066 Acute Toxicity Estimate ATE (oral) 5,800 mg/kg ATE (dermal) 20,000 mg/kg ATE (inhalation, gases) 76 ppmV ATE (inhalation, vapour) 5,540 mg/L ATE (inhalation, dust/mist) 76 mg/L	25 - < 50 Vol-%
CAS No.: 106-97-8 EC No.: 203-448-7 Index No.: 601-004-00-0 REACH No.: 01-2119474691-32	Butane (with < 0,1 % butadiene (203-450-8)) Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger	10 - < 25 Vol-%
CAS No.: 74-98-6 EC No.: 200-827-9 Index No.: 601-003-00-5 REACH No.: 01-2119486944-21	propane Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger Acute Toxicity Estimate ATE (oral) 5,840 mg/kg ATE (dermal) 13,900 mg/kg ATE (inhalation, gases) > 25 ppmV ATE (inhalation, vapour) ≥ 50 mg/L	10 - < 25 Vol-%
CAS No.: 128601-23-0 EC No.: 918-668-5 REACH No.: 01-2119455851-35	Hydrocarbons, C9, aromatics Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 3 (H226), STOT SE 3 (H335, H336) Danger Acute Toxicity Estimate ATE (oral) 3,492 mg/kg ATE (dermal) > 3,160 mg/kg ATE (inhalation, gases) > 6,193 ppmV	10 - < 25 Vol-%
CAS No.: 75-28-5 EC No.: 200-857-2 REACH No.: 01-2119485395-27	Isobutane (with < 0.1 % butadiene (203-450-8)) Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger	2.5 - < 10 Vol-%
CAS No.: 1330-20-7 EC No.: 215-535-7 REACH No.: 01-2119488216-32	Xylene Acute Tox. 4 (H312, H332), Asp. Tox. 1 (H304), Eye Irrit. 2 (H319), Flam. Liq. 3 (H226), STOT RE 2 (H373), STOT SE 3 (H335), Skin Irrit. 2 (H315) Danger Acute Toxicity Estimate ATE (oral) 2,100 mg/kg ATE (dermal) 1,100 mg/kg ATE (inhalation, dust/mist) > 20 mg/L	1 - < 2.5 Vol-%

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4



Page 4/19

Alu Guard 500ml

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 64742-48-9 EC No.: 918-481-9 REACH No.: 01-2119457273-39	Kohlenwasserstoffe, C10-C13, n-Alkane, cyclische, <2% Aromaten Benzol <0.1% Asp. Tox. 1 (H304), Flam. Liq. 3 (H226), STOT SE 3 (H336) Danger Acute Toxicity Estimate ATE (oral) > 8,000 mg/kg ATE (dermal) > 3,160 mg/kg ATE (inhalation, vapour) 4,951 mg/L	1 - < 2.5 Vol-%
EC No.: 905-588-0 REACH No.: 01-2119488216-32-XXXX	Reaction mass of ethylbenzene and xylene Acute Tox. 4 (H312, H332), Asp. Tox. 1 (H304), Eye Irrit. 2 (H319), Flam. Liq. 3 (H226), STOT RE 2 (H373), STOT SE 3 (H335), Skin Irrit. 2 (H315) Danger Acute Toxicity Estimate ATE (oral) > 3,523 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, gases) 27.571 ppmV ATE (inhalation, vapour) 29,000 mg/L	1 - < 2.5 Vol-%
CAS No.: 100-41-4 EC No.: 202-849-4 Index No.: 601-023-00-4 REACH No.: 01-2119489370-35	ethylbenzene Acute Tox. 4 (H332), Aquatic Chronic 3 (H412), Asp. Tox. 1 (H304), Flam. Liq. 2 (H225), STOT RE 2 (H373) Danger Acute Toxicity Estimate ATE (oral) 3,500 mg/kg ATE (dermal) 15,354 mg/kg ATE (inhalation, gases) 17.2 ppmV ATE (inhalation, dust/mist) 17.2 mg/L	0.1 - < 1 Vol-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Following inhalation:

Fresh air supply, consult a doctor in case of complaints.

In case of skin contact:

In general, the product is not irritating to skin.

After eye contact:

Rinse opened eye for several minutes under running water. Consult a doctor if symptoms persist

Following ingestion:

Do not induce vomiting, seek medical help immediately.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water mist, Extinguishing powder, Carbon dioxide, alcohol resistant foam

Unsuitable extinguishing media:

Water in full jet

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Special protective equipment: Put on breathing apparatus.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4

Page 5/19



Alu Guard 500ml

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear protective equipment. Keep unprotected persons away.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of spillage into water or sewage system, inform the competent authorities.

6.3. Methods and material for containment and cleaning up

Other information:

Provide adequate ventilation. Do not wash away with water or aqueous detergents.

6.4. Reference to other sections

See section 7 for further information on safe handling.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Ensure good ventilation/extraction at the workplace.

Fire prevent measures:

Do not spray on naked flames or any incandescent material. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Container is under pressure. Protect from sunlight and temperatures above 50°C (e.g. from incandescent lamps). Do not open by force or burn even after use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Store in a cool place. The official regulations for the storage of pressurised gas packages must be observed.

Hints on storage assembly:

The official regulations for the storage of pressurised gas packages must be observed.

Storage class (TRGS 510, Germany): 2B – Aerosol dispensers and lighters

Further information on storage conditions:

Store in a cool, dry place in well-sealed containers. Protect from heat and direct sunlight.

7.3. Specific end use(s)

Recommendation:

No further relevant information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4

Page 6/19



Alu Guard 500ml

SECTION 8: Exposure controls/personal protection

* 8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	acetone CAS No.: 67-64-1 EC No.: 200-662-2	② 2,000 ppm (4,800 mg/m ³) ⑤ (max. 4x15 min./Schicht)
IOELV (EU)	acetone CAS No.: 67-64-1 EC No.: 200-662-2	① 500 ppm (1,210 mg/m ³)
MAK (AT)	acetone CAS No.: 67-64-1 EC No.: 200-662-2	① 500 ppm (1,200 mg/m ³)
MAK (AT)	Butane (with < 0,1 % butadiene (203-450-8)) CAS No.: 106-97-8 EC No.: 203-448-7	① 800 ppm (1,900 mg/m ³)
MAK (AT)	Butane (with < 0,1 % butadiene (203-450-8)) CAS No.: 106-97-8 EC No.: 203-448-7	② 1,600 ppm (3,800 mg/m ³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
MAK (AT)	propane CAS No.: 74-98-6 EC No.: 200-827-9	② 2,000 ppm (3,600 mg/m ³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
MAK (AT)	propane CAS No.: 74-98-6 EC No.: 200-827-9	① 1,000 ppm (1,800 mg/m ³)
MAK (AT)	Isobutane (with < 0.1 % butadiene (203-450-8)) CAS No.: 75-28-5 EC No.: 200-857-2	② 1,600 ppm (3,800 mg/m ³) ⑤ (max. 3x60 min./Schicht Momentanwert)
MAK (AT)	Isobutane (with < 0.1 % butadiene (203-450-8)) CAS No.: 75-28-5 EC No.: 200-857-2	① 800 ppm (1,900 mg/m ³)
MAK (AT) from 25 Sept 2018	Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	② 100 ppm (442 mg/m ³) ⑤ (max. 4x15 min./Schicht)
IOELV (EU)	Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	① 50 ppm (221 mg/m ³) ② 100 ppm (442 mg/m ³) ⑤ (may be absorbed through the skin)
MAK (AT) from 25 Sept 2018	Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	① 50 ppm (221 mg/m ³)
MAK (AT)	Kohlenwasserstoffe, C10-C13, n-Alkane, cyclische, <2% Aromaten Benzol <0.1% CAS No.: 64742-48-9 EC No.: 918-481-9	① 200 mL/m ³ ② 400 mL/m ³ ⑤ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von weniger als 1 %, an n-Hexan von weniger als 5 % und an Cyclo-/Isohexanen von weniger als 25 %)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4



Page 7/19

Alu Guard 500ml

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	Kohlenwasserstoffe, C10-C13, n-Alkane, cyclische, <2% Aromaten Benzol <0.1% CAS No.: 64742-48-9 EC No.: 918-481-9	① 170 mL/m ³ ② 340 mL/m ³ ⑤ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von weniger als 1 %, an n-Hexan von weniger als 5 % und an Cyclo-/Isohexanen von 25 % oder mehr)
MAK (AT) from 25 Sept 2018	Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	② 100 ppm (442 mg/m ³) ⑤ (max. 4x15 min./Schicht)
IOELV (EU)	Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	① 50 ppm (221 mg/m ³) ② 100 ppm (442 mg/m ³) ⑤ (may be absorbed through the skin)
MAK (AT) from 25 Sept 2018	Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	① 50 ppm (221 mg/m ³)
MAK (AT)	ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4	① 100 ppm (440 mg/m ³) ⑤ (kann über die Haut aufgenommen werden) H
MAK (AT)	ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4	② 200 ppm (880 mg/m ³) ⑤ (max. 8x5 min./Schicht, Momentanwert, kann über die Haut aufgenommen werden) H
IOELV (EU)	ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4	① 100 ppm (442 mg/m ³) ② 200 ppm (884 mg/m ³) ⑤ (may be absorbed through the skin)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
acetone CAS No.: 67-64-1 EC No.: 200-662-2	1,210 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	200 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	2,420 mg/m ³	① DNEL worker ② Acute - inhalation, local effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	186 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	62 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	62 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
Hydrocarbons, C9, aromatics CAS No.: 128601-23-0 EC No.: 918-668-5	100 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4



Page 8/19

Alu Guard 500ml

Substance name	DNEL value	① DNEL type ② Exposure route
Hydrocarbons, C9, aromatics CAS No.: 128601-23-0 EC No.: 918-668-5	32 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
Hydrocarbons, C9, aromatics CAS No.: 128601-23-0 EC No.: 918-668-5	25 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
Hydrocarbons, C9, aromatics CAS No.: 128601-23-0 EC No.: 918-668-5	11 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
Hydrocarbons, C9, aromatics CAS No.: 128601-23-0 EC No.: 918-668-5	11 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	221 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	65.3 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	442 mg/m ³	① DNEL worker ② Acute - inhalation, systemic effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	260 mg/m ³	① DNEL Consumer ② Acute - inhalation, systemic effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	221 mg/m ³	① DNEL worker ② Long-term - inhalation, local effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	65.3 mg/m ³	① DNEL Consumer ② Long-term - inhalation, local effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	442 mg/m ³	① DNEL worker ② Acute - inhalation, local effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	260 mg/m ³	① DNEL Consumer ② Acute - inhalation, local effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	212 mg/kg	① DNEL worker ② Long-term - dermal, systemic effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	125 mg/kg	① DNEL Consumer ② Long-term - dermal, systemic effects
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	12.5 mg/kg	① DNEL Consumer ② Long-term - oral, systemic effects
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	77 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	14.8 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	289 mg/m ³	① DNEL worker ② Acute - inhalation, local effects
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	180 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4



Page 9/19

Alu Guard 500ml

Substance name	DNEL value	① DNEL type ② Exposure route
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	108 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	1.6 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4	77 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4	15 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4	293 mg/m ³	① DNEL worker ② Acute - inhalation, local effects
ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4	180 mg/kg	① DNEL worker ② Long-term - dermal, systemic effects
ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4	1.6 mg/kg	① DNEL Consumer ② Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
acetone CAS No.: 67-64-1 EC No.: 200-662-2	10.6 mg/L	① PNEC aquatic, freshwater
acetone CAS No.: 67-64-1 EC No.: 200-662-2	1.06 mg/L	① PNEC aquatic, marine water
acetone CAS No.: 67-64-1 EC No.: 200-662-2	100 mg/L	① PNEC sewage treatment plant
acetone CAS No.: 67-64-1 EC No.: 200-662-2	30.4 mg/kg	① PNEC sediment, freshwater
acetone CAS No.: 67-64-1 EC No.: 200-662-2	3.04 mg/kg	① PNEC sediment, marine water
acetone CAS No.: 67-64-1 EC No.: 200-662-2	29.5 mg/kg	① PNEC soil
acetone CAS No.: 67-64-1 EC No.: 200-662-2	21 mg/L	① PNEC aquatic, intermittent release
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	0.327 mg/L	① PNEC aquatic, freshwater
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	0.327 mg/L	① PNEC aquatic, marine water
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	12.46 mg/kg	① PNEC sediment, freshwater
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	12.46 mg/kg	① PNEC sediment, marine water
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	2.31 mg/kg	① PNEC soil

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4



Page 10/19

Alu Guard 500ml

Substance name	PNEC Value	① PNEC type
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7	0.327 mg/L	① PNEC aquatic, intermittent release
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	0.327 mg/L	① PNEC aquatic, marine water
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	6.58 mg/L	① PNEC sewage treatment plant
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	12.46 mg/L	① PNEC sediment, freshwater
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	12.46 mg/L	① PNEC sediment, marine water
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	2.31 mg/kg	① PNEC soil
ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4	0.1 mg/L	① PNEC aquatic, freshwater
ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4	0.01 mg/L	① PNEC aquatic, marine water
ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4	13.7 mg/kg	① PNEC sediment, freshwater
ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4	1.37 mg/kg	① PNEC sediment, marine water
ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4	2.68 mg/kg	① PNEC soil
ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4	0.1 mg/L	① PNEC aquatic, intermittent release

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No further details. See section 7.

8.2.2. Personal protection equipment



Eye/face protection:

Safety goggles (EN-166)

Skin protection:

Hand protection:

Gloves / solvent resistant

Breakthrough times and swelling properties of the material must be taken into consideration.

Glove material:

The selection of a suitable glove depends not only on the material but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

NBR (Nitrile rubber)

Recommended material thickness: $\geq 0,5$ mm

Permeation time (maximum wear duration):

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4

Page 11/19



Alu Guard 500ml

For continuous contact we recommend gloves with a breakthrough time of at least 240 minutes, with the preference for a breakthrough time greater than 480 minutes. For short term or splash protection we recommend the same. We are aware that suitable gloves offering this protection are not available. In this case, a shorter breakthrough time is permissible, provided the procedures for maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance the gloves give against a chemical substance, as this depends on the exact composition of the material of the gloves. The exact breakthrough time should be checked with the glove manufacturer and adhered to.

Body protection:

Use protective suit. (EN-13034/6)

Antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149 EN340&EN ISO 13688 EN13034-6).

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Filter A2/P2

Other protection measures:

General protective and hygienic measures:

Keep away from food, drink and animal feed.

Remove contaminated, saturated clothing immediately.

Wash hands before breaks and after work.

Do not inhale gases/vapours/aerosols.

Avoid contact with eyes and skin.

General ventilation.

8.2.3. Environmental exposure controls

Use a suitable container to prevent environmental pollution.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Form: Aerosol

Colour: According to product designation

Odour: characteristic

flammability: No data available

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	<i>not applicable</i>		② Mixture is not polar/aprotic.
Initial boiling point and boiling range	-44.5 °C		
Flash point	-97 °C		
Evaporation rate	<i>No data available</i>		
Auto-ignition temperature	365 °C		
Upper/lower flammability or explosive limits	0.7 - 13 Vol-%		
Vapour pressure	8,300 hPa	20 °C	
Density	0.72 g/cm ³	20 °C	
Water solubility	Immiscible		
Kinematic viscosity	≤ 20.5 mm ² /s	40 °C	

9.2. Other information

The product is not self-igniting. The product is not explosive, but the formation of explosive vapour/air mixtures is possible. formation of explosive vapour/air mixtures is possible.

Organic solvents: 94,4%

Solid content: 5,7%

9.2.1. Information with regard to physical hazard classes

Explosives:

Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4



Page 12/19

Alu Guard 500ml

Flammable gases:

Not applicable

Aerosols:

Extremely flammable aerosol. Pressurized container: May burst if heated.

Oxidizing gases:

Not applicable

Gases under pressure:

Not applicable

Flammable liquids:

Not applicable

Flammable solids:

Not applicable

Self-reactive substances and mixtures:

Not applicable

Pyrophoric liquids:

Not applicable

Pyrophoric solids:

Not applicable

Self-heating substances and mixtures:

Not applicable

Substances or mixtures which, in contact with water, emit flammable gases:

Not applicable

Oxidizing liquids:

Not applicable

Oxidizing solids:

Not applicable

Organic peroxides:

Not applicable

Corrosive to metals:

Not applicable

Desensitised explosives:

Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

Thermal decomposition / Conditions to avoid: No decomposition when used as directed.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No dangerous decomposition products known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4

Page 13/19



Alu Guard 500ml

SECTION 11: Toxicological information

* 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

acetone CAS No.: 67-64-1 EC No.: 200-662-2
ATE (oral): 5,800 mg/kg
ATE (dermal): 20,000 mg/kg
ATE (inhalation, dust/mist): 76 mg/L
LD₅₀ oral: 5,800 mg/kg (Rat)
LD₅₀ dermal: >15,800 mg/kg (Rabbit)
LC₅₀ Acute inhalation toxicity (gas): 76 ppmV 4 h (Rat)
LC₅₀ Acute inhalation toxicity (vapour): 5,540 mg/L 4 d (Oncorhynchus mykiss (Rainbow trout))
LC₅₀ Acute inhalation toxicity (dust/mist): 76 mg/L 4 h (Rat)
propane CAS No.: 74-98-6 EC No.: 200-827-9
LD₅₀ oral: 5,840 mg/kg (Rat)
LD₅₀ dermal: 13,900 mg/kg (Rabbit)
LC₅₀ Acute inhalation toxicity (gas): >25 ppmV 4 h (Rat)
LC₅₀ Acute inhalation toxicity (vapour): ≥50 mg/L 4 h (Rat)
Hydrocarbons, C9, aromatics CAS No.: 128601-23-0 EC No.: 918-668-5
LD₅₀ oral: 3,492 mg/kg (Rat)
LD₅₀ dermal: >3,160 mg/kg (Rabbit)
LC₅₀ Acute inhalation toxicity (gas): >6,193 ppmV 4 h (Rat)
Xylene CAS No.: 1330-20-7 EC No.: 215-535-7
LD₅₀ oral: 2,100 mg/kg (Rat)
LD₅₀ dermal: 1,100 mg/kg (Rat)
LC₅₀ Acute inhalation toxicity (dust/mist): >20 mg/L
Kohlenwasserstoffe, C10-C13, n-Alkane, cyclische, <2% Aromaten Benzol <0.1% CAS No.: 64742-48-9 EC No.: 918-481-9
LD₅₀ oral: >8,000 mg/kg (Rat)
LD₅₀ dermal: >3,160 mg/kg (Rabbit)
LC₅₀ Acute inhalation toxicity (vapour): 4,951 mg/L 4 h (Rat)
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0
LD₅₀ oral: >3,523 mg/kg (Rat)
LD₅₀ dermal: >2,000 mg/kg (Rabbit)
LC₅₀ Acute inhalation toxicity (gas): 27.571 ppmV 4 h (Rat)
LC₅₀ Acute inhalation toxicity (vapour): 29,000 mg/L 4 h (Rat)
ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4
LD₅₀ oral: 3,500 mg/kg (Rat)
LD₅₀ dermal: 15,354 mg/kg (Rabbit)
LC₅₀ Acute inhalation toxicity (gas): 17.2 ppmV 4 h (Rat)
LC₅₀ Acute inhalation toxicity (dust/mist): 17.2 mg/L (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4



Page 14/19

Alu Guard 500ml

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Endocrine disrupting properties:

octamethylcyclotetrasiloxane (556-67-2)

SECTION 12: Ecological information

* 12.1. Toxicity

acetone	CAS No.: 67-64-1	EC No.: 200-662-2
LC ₅₀ : 8,300 mg/L 4 d (fish)		
LC ₅₀ : 8,450 mg/L 2 d (crustaceans, water flea)		
LC ₅₀ : 8,300 mg/L 4 d (fish)		
EC ₅₀ : 7,200 mg/L 4 d (Algae/water plant)		
EC ₅₀ : 7,200 mg/L 4 d (Algae)		
EC ₅₀ : 8,800 mg/L (Daphnia magna)		
NOEC: 2,212 mg/L (crustaceans, Daphnia magna)		
propane	CAS No.: 74-98-6	EC No.: 200-827-9
LC ₅₀ : 9,640 mg/L 4 d (fish, Pimephales promelas)		
LC ₅₀ : 0.41 mg/L 4 d (fish, Oncorhynchus mykiss)		
LC ₅₀ : 49.9 mg/L 4 d (fish)		
EC ₅₀ : >100 mg/L (Algae/water plant, Bacteria)		
EC ₅₀ : 0.17 mg/L 3 d (Algae/water plant, Selenastrum capricornutum)		
EC ₅₀ : 69.43 mg/L 2 d (crustaceans, Daphnia) Calculation with the ECOSAR programme v1.00.		
NOEC: 0.017 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)		
ErC ₅₀ : 19.37 mg/L 4 d (Algae/water plant, Algae) Calculation with the ECOSAR programme v1.00.		
LOEC: 1,000 mg/L (Algae/water plant, Algae)		
LOEC: 1,000 mg/L (Algae/water plant, Algae)		
IC ₅₀ : 11.3 mg/L 3 d (Algae/water plant)		
Hydrocarbons, C9, aromatics	CAS No.: 128601-23-0	EC No.: 918-668-5
EC ₅₀ : 3.2 mg/L 2 d (crustaceans, Daphnia magna)		
EC ₅₀ : 2.75 mg/L 3 d (Algae/water plant, Pseudokirchneriella Subcapitata)		
EC ₅₀ : 9.2 mg/L 4 d (fish)		
Xylene	CAS No.: 1330-20-7	EC No.: 215-535-7
LC ₅₀ : >10 - 100 mg/L 4 d (fish)		
EC ₅₀ : >10 - 100 mg/L 2 d (crustaceans)		
EC ₅₀ : >10 - 100 mg/L 3 d (Algae/water plant)		
NOEC: 1.3 mg/L (fish, Oncorhynchus mykiss)		
NOEC: 1.17 mg/L (crustaceans, Ceriodaphnia dubia)		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4



Page 15/19

Alu Guard 500ml

Kohlenwasserstoffe, C10-C13, n-Alkane, cyclische, <2% Aromaten Benzol <0.1% CAS No.: 64742-48-9
EC No.: 918-481-9

LC₅₀: >1,000 mg/L 4 d (fish, *Oncorhynchus mykiss* (Rainbow trout))

EC₅₀: >1,000 mg/L 2 d (crustaceans, *Daphnia magna* (Big water flea))

ErC₅₀: >1,000 mg/L 4 d (Algae/water plant, *Scenedesmus subspicatus*)

Reaction mass of ethylbenzene and xylene EC No.: 905-588-0

LC₅₀: 8.9 – 16.4 mg/L 4 d (fish, *Pimephales promelas*)

EC₅₀: 3.2 – 9.5 mg/L 2 d (crustaceans, *Daphnia magna*)

NOEC: 0.44 mg/L 3 d (Algae/water plant)

LC₅₀: 2.6 mg/L 4 d (fish, *Oncorhynchus mykiss*)

EC₅₀: 2.2 mg/L 3 d (Algae/water plant, *Chlorella vulgaris*)

NOEC: >1.39 mg/L (fish, *Oncorhynchus kisutch*)

NOEC: 0.74 mg/L (crustaceans, *Ceriodaphnia dubia*)

LC₅₀: 8.9 – 16.4 mg/L 4 d (*Pimephales promelas*)

EC₅₀: 3.2 – 9.5 mg/L 2 d (*Daphnia magna*)

ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4

LC₅₀: 42.3 mg/L 4 d (fish, *Pimephales promelas*)

EC₅₀: 75 mg/L 2 d (crustaceans, *Daphnia magna*)

EC₅₀: 63 mg/L (Algae/water plant, *Chlorella vulgaris*)

NOEC: 0.96 mg/L (crustaceans, *Ceriodaphnia dubia*)

EC₅₀: 63 mg/L (Algae/water plant, *Chlorella vulgaris*)

Aquatic toxicity:

No further relevant information available.

Assessment/classification:

No further relevant information available.

12.2. Persistence and degradability

acetone CAS No.: 67-64-1 EC No.: 200-662-2

Biodegradation: Yes, rapidly

propane CAS No.: 74-98-6 EC No.: 200-827-9

Biodegradation: Yes, rapidly

Biodegradation:

Not readily biodegradable.

12.3. Bioaccumulative potential

acetone CAS No.: 67-64-1 EC No.: 200-662-2

Log K_{OW}: -0.24

propane CAS No.: 74-98-6 EC No.: 200-827-9

Log K_{OW}: 1.09

Reaction mass of ethylbenzene and xylene EC No.: 905-588-0

Log K_{OW}: 3.16

Bioconcentration factor (BCF): 29

ethylbenzene CAS No.: 100-41-4 EC No.: 202-849-4

Log K_{OW}: 3.15

Accumulation / Evaluation:

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4



Page 16/19

Alu Guard 500ml

12.5. Results of PBT and vPvB assessment

acetone	CAS No.: 67-64-1	EC No.: 200-662-2
Results of PBT and vPvB assessment: —		
Butane (with < 0,1 % butadiene (203-450-8))	CAS No.: 106-97-8	EC No.: 203-448-7
Results of PBT and vPvB assessment: —		
propane	CAS No.: 74-98-6	EC No.: 200-827-9
Results of PBT and vPvB assessment: —		
Hydrocarbons, C9, aromatics	CAS No.: 128601-23-0	EC No.: 918-668-5
Results of PBT and vPvB assessment: —		
Xylene	CAS No.: 1330-20-7	EC No.: 215-535-7
Results of PBT and vPvB assessment: —		
Kohlenwasserstoffe, C10-C13, n-Alkane, cyclische, <2% Aromaten Benzol <0.1%	CAS No.: 64742-48-9	EC No.: 918-481-9
Results of PBT and vPvB assessment: —		
Reaction mass of ethylbenzene and xylene	EC No.: 905-588-0	
Results of PBT and vPvB assessment: —		
ethylbenzene	CAS No.: 100-41-4	EC No.: 202-849-4
Results of PBT and vPvB assessment: —		

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Drinking water hazard even when small quantities leak into the subsoil.

Harmful to aquatic life.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Must not be disposed of together with household waste. Do not allow to enter into surface water or drains.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV Directive 2008/98/EC (Waste Framework Directive)

HP 3	Flammable
HP 4	Irritant — skin irritation and eye damage
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 14	Ecotoxic

Waste treatment options

Appropriate disposal / Package:

Uncleaned packaging: Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name			
AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4



Page 17/19

Alu Guard 500ml

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.3. Transport hazard class(es)			
 2.1	 2.1	 2.1	 2.1
14.4. Packing group			
		-	
14.5. Environmental hazards			
No	No	No	No
14.6. Special precautions for user			
Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F Tunnel restriction code: (D) Remark: Attention: Gases	Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F Remark: Attention: Gases	Special Provisions: 63 190 277 327 344 381 959 Limited quantity (LQ): Siehe SV277 Excepted Quantities (EQ): E0 EmS-No.: F-D, S-U Remark: Attention: Gases	Special Provisions: A145 A167 Limited quantity (LQ): Y203 Excepted Quantities (EQ): E0 Remark: Attention: Gases

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Directive 2012/18/EU

Named dangerous substances - ANNEX I: None of the ingredients are included.

Restrictions on use:

Regulation (EC) No 1907/2006 ANNEX XVII: Restriction conditions: 3

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II: None of the ingredients are included.

Regulation (EU) 2019/1148

Annex I - RESTRICTED EXPORT SUBSTANCES FOR EXPLOSIVES (upper concentration limit for a permit pursuant to Article 5(3)): None of the ingredients are included.

Annex II - EXPLOSIVES REPORTABLE FOR EXPLOSIVES: Acetone (67-64-1)

Regulation (EC) No 273/2004 on drug precursors: Acetone (67-64-1), Toluene (108-88-3)

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade in drug precursors between the Community and third countries: Acetone (67-64-1), toluene (108-88-3)

Other regulations (EU):

Hazard categories:

- P3a 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids

Named dangerous substances:

- Liquefied flammable gases, Category 1 or 2 (including liquefied petroleum gas) and natural gas

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 679.7 g/L

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4



Page 18/19

Alu Guard 500ml

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

* 16.1. Indication of changes

1.3.	Details of the supplier of the safety data sheet
8.1.	Control parameters
11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008
12.1.	Toxicity
16.1.	Indication of changes

16.2. Abbreviations and acronyms

ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DNEL	derived no-effect level
EC ₅₀	Effective Concentration 50%
EN	European Standard
ES	Exposure scenario
EWC	European Waste Catalogue
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
KG	body weight
LC ₅₀	Lethal (fatal) Concentration 50%
LD ₅₀	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OEL	Threshold Limit Value
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
SCL	Specific concentration limit
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations
VOC	Volatile organic compounds
ZNS	central nervous system

16.3. Key literature references and sources for data

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 7 Jul 2025

Version: 4



Page 19/19

Alu Guard 500ml

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	
Hazardous to the aquatic environment (Aquatic Chronic 3)	H412: Harmful to aquatic life with long lasting effects.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

* Data changed compared with the previous version.