

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 9 Jul 2025

Version: 3

Page 1/13



Multi Tech Clear 500ml

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Multi Tech Clear 500ml

Article No.:

T214002

UFI:

CNWE-KJMF-JU0V-P32X

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Lubricating agent

* 1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH

Hartleitnerstraße 3

4653 Eberstälzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS07
Exclamation mark



GHS09
Environment

Signal word: Danger

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 9 Jul 2025

Version: 3



Page 2/13

Multi Tech Clear 500ml

Hazard components for labelling:

pentane

Hazard statements for physical hazards

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

Hazard statements for health hazards

H336	May cause drowsiness or dizziness.
------	------------------------------------

Hazard statements for environmental hazards

H411	Toxic to aquatic life with long lasting effects.
------	--

Supplemental hazard information

EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains Orange, süß, Extrakt. May produce an allergic reaction.

Precautionary statements Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Precautionary statements Response

P312	Call a POISON CENTER if you feel unwell.
------	--

Precautionary statements Storage

P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary statements Disposal

P501	Dispose of contents/container to an appropriate recycling or disposal facility.
------	---

Additional information:

Formation of explosive mixtures possible without adequate ventilation.

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 9 Jul 2025

Version: 3

Page 3/13



Multi Tech Clear 500ml

SECTION 3: Composition/information on ingredients

* 3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 109-66-0 EC No.: 203-692-4 REACH No.: 01-2119459286-30	pentane Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 1 (H224), STOT SE 3 (H336) Danger Acute Toxicity Estimate ATE (oral) > 5,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, gases) > 20 ppmV ATE (inhalation, vapour) > 25.3 mg/L	25 - < 50 Vol-%
CAS No.: 8028-48-6 EC No.: 232-433-8 REACH No.: 01-2119493353-35	Orange, sweet, extract Asp. Tox. 1 (H304), Flam. Liq. 3 (H226), Skin Irrit. 2 (H315), Skin Sens. 1 (H317) Danger M-factor (acute): 1 M-factor (chronic): 1 Acute Toxicity Estimate ATE (oral) 200 mg/kg ATE (dermal) > 5,000 mg/kg ATE (inhalation, dust/mist) 500 mg/L	0.1 - < 0.25 Vol-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Following inhalation:

Remove affected person from the danger area and lay down. Fresh air supply, consult a doctor in case of complaints. If unconscious but breathing normally, place in recovery position and seek medical advice.

In case of skin contact:

Wash with plenty of water and soap. Wash contaminated clothing immediately. In case of skin reactions, consult a physician.

After eye contact:

IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion:

Rinse mouth thoroughly with water. Do not induce vomiting, seek medical help immediately. If swallowed, immediately drink: Water. If vomiting occurs, keep head low so that stomach contents do not enter the lungs.

Self-protection of the first aider:

First aider: Pay attention to self-protection! Never give anything by mouth to an unconscious person!

4.2. Most important symptoms and effects, both acute and delayed

Irritation to respiratory tract, Cough, Headache, Dizziness, Confusion, Drying of the skin, Dermatitis, Allergic reactions

IF SWALLOWED: Nausea, Vomiting

Aspiration hazard: Pulmonary oedema, Chemical pneumonitis

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water spray jet, alcohol resistant foam, Carbon dioxide (CO₂), Dry extinguishing powder

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 9 Jul 2025

Version: 3



Page 4/13

Multi Tech Clear 500ml

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon oxides, Sulphur oxides, Hydrogen fluoride, toxic gases

Heating causes rise in pressure with risk of bursting.

In use, may form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

Personal protection equipment: see section 8.

Do not inhale explosion and combustion gases.

Use suitable breathing apparatus.

Full protection suit

Immerse in cold water for a prolonged period.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Dispose of waste according to applicable legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Personal protection equipment: see section 8.

Provide adequate ventilation.

Remove all sources of ignition.

Avoid dust formation with solid or powdery products.

Keep away from sources of ignition - No smoking.

Avoid contact with skin, eyes and clothes.

Special danger of slipping by leaking/spilling product.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of spillage into water or sewage system, inform the competent authorities.

6.3. Methods and material for containment and cleaning up

For cleaning up:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information:

Provide adequate ventilation.

6.4. Reference to other sections

Further information on proper storage: see section 7.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

6.5. Additional information

Use appropriate container to avoid environmental contamination.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Ensure good ventilation/extraction at the workplace. Avoid breathing vapours. Avoid contact with skin, eyes and clothes. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Do not use on hot surfaces.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 9 Jul 2025

Version: 3



Page 5/13

Multi Tech Clear 500ml

Advices on general occupational hygiene

The usual precautions when handling chemicals must be observed. Do not eat, drink, smoke or snort while working. Do not inhale dust/fume/mist. Keep away from food, drink and animal feed. Wash hands before breaks and at the end of work.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Store out of reach of unauthorised persons. Do not store the product in passageways and stairways. Store product only in the original packaging and closed. Observe special instructions for aerosols. Observe special storage conditions. Do not store together with oxidising or spontaneously combustible substances. Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a cool dry place. Store in a well-ventilated place.

Storage class (TRGS 510, Germany): 2B – Aerosol dispensers and lighters

7.3. Specific end use(s)

Recommendation:

No further relevant information available.

Industrial sector specific solutions:

No further relevant information available.

SECTION 8: Exposure controls/personal protection

* 8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	pentane CAS No.: 109-66-0 EC No.: 203-692-4	② 1,200 ppm (3,600 mg/m ³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
IOELV (EU)	pentane CAS No.: 109-66-0 EC No.: 203-692-4	① 1,000 ppm (3,000 mg/m ³)
MAK (AT)	pentane CAS No.: 109-66-0 EC No.: 203-692-4	① 600 ppm (1,800 mg/m ³)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
pentane CAS No.: 109-66-0 EC No.: 203-692-4	3,000 mg/m ³	① DNEL worker ② Long-term – inhalation, systemic effects
pentane CAS No.: 109-66-0 EC No.: 203-692-4	643 mg/m ³	① DNEL Consumer ② Long-term – inhalation, systemic effects
pentane CAS No.: 109-66-0 EC No.: 203-692-4	432 mg/kg bw/day	① DNEL worker ② Long-term – dermal, systemic effects
pentane CAS No.: 109-66-0 EC No.: 203-692-4	214 mg/kg bw/day	① DNEL Consumer ② Long-term – dermal, systemic effects
pentane CAS No.: 109-66-0 EC No.: 203-692-4	214 mg/kg bw/day	① DNEL Consumer ② Long-term – oral, systemic effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 9 Jul 2025

Version: 3



Page 6/13

Multi Tech Clear 500ml

Substance name	DNEL value	① DNEL type ② Exposure route
Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8	31.1 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8	7.78 mg/m ³	① DNEL worker ② Acute - inhalation, local effects
Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8	8.89 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8	4.44 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8	0.929 mg/cm ²	① DNEL worker ② Acute - dermal, local effects
Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8	4.44 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
pentane CAS No.: 109-66-0 EC No.: 203-692-4	0.23 mg/L	① PNEC aquatic, freshwater
pentane CAS No.: 109-66-0 EC No.: 203-692-4	0.23 mg/L	① PNEC aquatic, marine water
pentane CAS No.: 109-66-0 EC No.: 203-692-4	3.6 mg/L	① PNEC sewage treatment plant
pentane CAS No.: 109-66-0 EC No.: 203-692-4	1.2 mg/kg bw/ day	① PNEC sediment, freshwater
pentane CAS No.: 109-66-0 EC No.: 203-692-4	1.2 mg/kg	① PNEC sediment, marine water
pentane CAS No.: 109-66-0 EC No.: 203-692-4	0.55 mg/kg	① PNEC soil
pentane CAS No.: 109-66-0 EC No.: 203-692-4	0.88 mg/L	① PNEC aquatic, intermittent release
Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8	5.4 mg/kg	① PNEC aquatic, freshwater
Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8	0.54 mg/kg	① PNEC aquatic, marine water
Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8	2.1 mg/kg	① PNEC sewage treatment plant
Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8	1.3 mg/L	① PNEC sediment, freshwater
Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8	0.13 mg/L	① PNEC sediment, marine water
Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8	0.261 mg/kg	① PNEC soil

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 9 Jul 2025

Version: 3

Page 7/13



Multi Tech Clear 500ml

Substance name	PNEC Value	① PNEC type
Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8	5.77 mg/L	① PNEC aquatic, intermittent release

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure good ventilation/extraction at the workplace. If this is not sufficient to keep the concentration below the occupational exposure limits (OEL), suitable respiratory protection must be worn. Applies only if exposure limit values are listed here. Appropriate assessment methods for checking the effectiveness of the protective measures taken include metrological and non-measured determination methods. Such methods are described by e.g. EN 14042, TRGS 402 (Germany). EN 14042 "Workplace atmospheres. Guidance for the application and use of methods and equipment for the determination of chemical and biological agents". TRGS 402 "Determining and assessing the hazards of activities involving hazardous substances - Inhalation exposure".

8.2.2. Personal protection equipment



Eye/face protection:

Safety goggles with side shields (EN 166).

Skin protection:

Hand protection:

Chemical-resistant protective gloves (EN ISO 374). Protective gloves made of Neoprene® / polychloroprene (EN ISO 374). Protective gloves made of nitrile (EN ISO 374). Protective gloves in Viton® / in fluoroelastomer (EN ISO 374). Minimum layer thickness in mm: 0.5. Permeation time (breakthrough time) in minutes: 480. The breakthrough times determined according to EN 16523-1 were not carried out under practical conditions. A maximum wearing time corresponding to 50% of the breakthrough time is recommended. Hand protection cream recommended.

Skin protection:

Protective work clothing (e.g. safety shoes EN ISO 20345, long-sleeved work clothing).

Respiratory protection:

Filter A2/P2 (EN 14387)

Observe the wear time limits as specified by the manufacturer.

Thermal hazards:

not relevant

Other protection measures:

The usual precautions when handling chemicals must be observed. Do not eat, drink, smoke or snort while working. Do not inhale dust/fume/mist. Keep away from food, drink and animal feed. Wash hands before breaks and at the end of work.

8.2.3. Environmental exposure controls

No further relevant information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Form: Aerosol

Colour: light yellow

Odour: characteristic

flammability: No data available

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	No data available		
Melting point	No data available		
Freezing point	No data available		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 9 Jul 2025

Version: 3

Page 8/13



Multi Tech Clear 500ml

Parameter	Value	at °C	① Method ② Remark
Initial boiling point and boiling range	No data available		
Flash point	-60 °C		
Evaporation rate	No data available		
Auto-ignition temperature	No data available		
Upper/lower flammability or explosive limits	No data available		
Vapour pressure	3,100 hPa	20 °C	
Vapour density	No data available		
Density	≈ 0.65 g/cm ³		
Relative density			
Bulk density	not applicable		
Water solubility	practically insoluble		
Dynamic viscosity	No data available		
Kinematic viscosity	No data available		

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Explosives:

The product is not self-igniting. The product is not explosive, but the formation of explosive vapour/air mixtures is possible. formation of explosive vapour/air mixtures is possible.

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

Heat. Remove all sources of ignition. Pressurised container: May burst if heated.

10.5. Incompatible materials

Avoid contact with strong oxidising agents.

10.6. Hazardous decomposition products

No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

pentane CAS No.: 109-66-0 EC No.: 203-692-4
LD₅₀ oral: >5,000 mg/kg (Rat)
LD₅₀ dermal: >2,000 mg/kg (Rat)
LC₅₀ Acute inhalation toxicity (gas): >20 ppmV 4 h (rat)
LC₅₀ Acute inhalation toxicity (vapour): >25.3 mg/L 4 h (Rat) OECD 403
Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8
LD₅₀ oral: 200 mg/kg (Rat)
LD₅₀ dermal: >5,000 mg/kg (Rat)
LC₅₀ Acute inhalation toxicity (dust/mist): 500 mg/L 4 h (Rat)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 9 Jul 2025

Version: 3

Page 9/13



Multi Tech Clear 500ml

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

non-irritant. Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation:

slightly irritant.

Respiratory or skin sensitisation:

non-irritant.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Aspiration hazard

Additional information:

No data available

11.2. Information on other hazards

Endocrine disrupting properties:

No further relevant information available.

SECTION 12: Ecological information

12.1. Toxicity

pentane CAS No.: 109-66-0 EC No.: 203-692-4

LC₅₀: 4.26 mg/L 4 d (fish, *Oncorhynchus mykiss*)

EC₅₀: 10.7 mg/L 3 d (Algae/water plant, *Pseudokirchneriella subcapitata*)

EC₅₀: 2.7 mg/L 2 d (crustaceans, *Daphnia magna*)

NOEC: 7.51 mg/L 3 d (Algae/water plant, *Pseudokirchneriella subcapitata*)

NOEC: 7.51 mg/L 3 d (Algae/water plant, *Pseudokirchneriella subcapitata*)

EC₅₀: 10.7 mg/L 3 d (Algae/water plant, *Pseudokirchneriella subcapitata*)

Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8

LC₅₀: 0.7 mg/L 4 d (fish, *Pimephales promelas*) OECD 203

EC₅₀: 0.67 mg/L 2 d (crustaceans, *Daphnia magna*) OECD 202

NOEC: 72 – 83.4 mg/L 28 d OECD 301 B

ErC₅₀: 150 mg/L 3 d (Algae/water plant, *Desmodesmus subspicatus*) OECD 201

Aquatic toxicity:

Toxic to aquatic life with long lasting effects.

Additional ecotoxicological information:

No further relevant information available.

12.2. Persistence and degradability

pentane CAS No.: 109-66-0 EC No.: 203-692-4

Biodegradation: Yes, rapidly

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 9 Jul 2025

Version: 3

Page 10/13



Multi Tech Clear 500ml

Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8
--

Biodegradation: Yes, rapidly

Additional information:

The substance(s) contained in this preparation contained surfactant(s) fulfils the conditions of the biological degradability as specified in the Regulation (EC) No. 648/2004 on Detergents are laid down. Documents which this confirm this, are made available to the competent authorities of the Member States held ready and only to these either to their direct or at the request of a Detergents detergent manufacturer available provided.

12.3. Bioaccumulative potential

pentane CAS No.: 109-66-0 EC No.: 203-692-4
--

Log K_{OW}: 3.39

Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8
--

Log K_{OW}: > 4

Accumulation / Evaluation:

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

pentane CAS No.: 109-66-0 EC No.: 203-692-4
--

Results of PBT and vPvB assessment: —
--

Orange, sweet, extract CAS No.: 8028-48-6 EC No.: 232-433-8
--

Results of PBT and vPvB assessment: —
--

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No further relevant information available.

12.7. Other adverse effects

None known

SECTION 13: Disposal considerations

13.1. Waste treatment methods

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

07 06 99	Wastes not otherwise specified
----------	--------------------------------

16 05 04 *	Gases in pressure containers (including halons) containing hazardous substances
------------	---

*: Evidence for disposal must be provided.

Waste code packaging

15 01 04	metallic packaging
----------	--------------------

Waste treatment options

Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal. Dispose of waste according to applicable legislation.

Appropriate disposal / Package:

Dispose of waste according to applicable legislation.

Other disposal recommendations:

Do not allow to enter into surface water or drains.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 9 Jul 2025








Version: 3

Page 11/13



Multi Tech Clear 500ml

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name			
AEROSOLS	AEROSOLS	AEROSOLS (PENTANES)	AEROSOLS, flammable
14.3. Transport hazard class(es)			
 2.1	 2.1	 2.1	 2.1
14.4. Packing group			
		-	
14.5. Environmental hazards			
		 MARINE POLLUTANT	No
14.6. Special precautions for user			
Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F Tunnel restriction code: (D) Remark: Persons engaged in the carriage of dangerous goods shall be instructed. Safety regulations shall be observed by all persons involved in the carriage. Precautions shall be taken to prevent damage.	Special Provisions: 190 327 344 625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F Remark: Persons engaged in the carriage of dangerous goods shall be instructed. Safety regulations shall be observed by all persons involved in the carriage. Precautions shall be taken to prevent damage.	Special Provisions: 63 190 277 327 344 381 959 Limited quantity (LQ): Siehe SV277 Excepted Quantities (EQ): E0 EmS-No.: F-D, S-U Remark: Persons engaged in the carriage of dangerous goods shall be instructed. Safety regulations shall be observed by all persons involved in the carriage. Precautions shall be taken to prevent damage.	Special Provisions: A145 A167 Limited quantity (LQ): Y203 Excepted Quantities (EQ): E0 Remark: Persons engaged in the carriage of dangerous goods shall be instructed. Safety regulations shall be observed by all persons involved in the carriage. Precautions shall be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

* 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Other regulations (EU):

Hazard categories:

- P3a 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids
- E2 Hazardous to the Aquatic Environment in Category Chronic 2

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 77.5 Vol-%

15.1.2. National regulations

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 9 Jul 2025

Version: 3

Page 12/13



Multi Tech Clear 500ml

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

* 16.1. Indication of changes

1.3.	Details of the supplier of the safety data sheet
3.2.	Mixtures
8.1.	Control parameters
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture
16.1.	Indication of changes

16.2. Abbreviations and acronyms

ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DNEL	derived no-effect level
EC ₅₀	Effective Concentration 50%
EN	European Standard
ES	Exposure scenario
EWC	European Waste Catalogue
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
KG	body weight
LC ₅₀	Lethal (fatal) Concentration 50%
LD ₅₀	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OEL	Threshold Limit Value
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PNEC	Predicted No Effect Concentration
QSAR	Quantitative Structure-Activity Relationship
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations
VOC	Volatile organic compounds

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 9 Jul 2025

Version: 3



Page 13/13

Multi Tech Clear 500ml

Hazard classes and hazard categories	Hazard statements	Classification procedure
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 2</i>)	H411: Toxic to aquatic life with long lasting effects.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H224	Extremely flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

* Data changed compared with the previous version.