according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 9 Jul 2025

**Version:** 4 Page 1/14



# Multi Tech Dry 500ml

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name/designation:

# Multi Tech Dry 500ml

#### **Article No.:**

T318001

UFI:

9KFF-ETTR-FTJQ-Y752

# 1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Lubricating agent

#### Relevant identified uses:

**Product Categories [PC]** 

PC 24: Lubricants, greases, release products

**Process categories [PROC]** 

PROC 7: Industrial sprayingPROC 11: Non industrial spraying

#### \* 1.3. Details of the supplier of the safety data sheet

#### Supplier:

#### **KANDO Service GmbH**

Hartleitnerstraße 3 4653 Eberstalzell

Austria

**Telephone:** +43 (0) 7241 213 79

E-mail: msds@kando.eu

# 1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 9 Jul 2025

**Version:** 4 Page 2/14



# Multi Tech Dry 500ml

## 2.2. Label elements

# Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:







**GHS07** Exclamation mark



**GHS09** Environment

Signal word: Danger

#### Hazard components for labelling:

pentane; propan-2-ol

Hazard statements for physical hazards		
H222	Extremely flammable aerosol.	
H229	Pressurised container: May burst if heated.	

Hazard statements for health hazards	
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Hazard statements	for environmental hazards
H411	Toxic to aquatic life with long lasting effects.

Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.

Precautionary statements Prevention		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P260	Do not breathe spray.	

Precautionary statements Storage	
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary statements Disposal	
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

#### **Additional information:**

Formation of explosive mixtures possible without adequate ventilation.

#### 2.3. Other hazards

#### Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# **SECTION 3: Composition/information on ingredients**

#### \* 3.2. Mixtures

#### **Description:**

Mixture of substances listed below with non-hazardous admixtures.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 9 Jul 2025

Version: 4 Page 3/14



# Multi Tech Dry 500ml

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 109-66-0 EC No.: 203-692-4 Index No.: 601-006-00-1 REACH No.: 01-2119459286-30	pentane Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 2 (H225), STOT SE 3 (H336)  Danger EUH066 Acute Toxicity Estimate ATE (oral) > 5,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, gases) > 20 ppmV ATE (inhalation, vapour) > 25.3 mg/L	25 - < 50 Vol-%
CAS No.: 74-98-6 EC No.: 200-827-9 Index No.: 601-003-00-5 REACH No.: 01-2119486944-21	propane Flam. Gas 1A (H220), Press. Gas (Comp.) (H280)  Danger Acute Toxicity Estimate ATE (oral) 5,840 mg/kg ATE (dermal) 13,900 mg/kg ATE (inhalation, gases) > 25 ppmV ATE (inhalation, vapour) ≥ 50 mg/L	20 - < 25 Vol-%
CAS No.: 106-97-8 EC No.: 203-448-7 Index No.: 601-004-00-0 REACH No.: 01-2119474691-32	Butane (with < 0,1 % butadiene (203-450-8)) Flam. Gas 1A (H220), Press. Gas (Comp.) (H280)  Danger	12.5 - < 20 Vol-%
CAS No.: 75-28-5 EC No.: 200-857-2 REACH No.: 01-2119485395-27	Isobutane (with < 0.1 % butadiene (203-450-8))   Flam. Gas 1A (H220), Press. Gas (Comp.) (H280)	12.5 - < 20 Vol-%
CAS No.: 67-63-0 EC No.: 200-661-7 Index No.: 603-117-00-0 REACH No.: 01-2119457558-25	propan-2-ol Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336)  Danger Acute Toxicity Estimate ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, yapour) > 20 mg/L	10 - < 12.5 Vol-%

Full text of H- and EUH-phrases: see section 16.

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### Following inhalation:

Fresh air supply, consult a doctor in case of complaints.

#### In case of skin contact:

In general, the product is not irritating to skin.

#### After eye contact:

Rinse opened eye for several minutes under running water. Consult a doctor if symptoms persist

#### Following ingestion:

Drink plenty of water. Provide fresh air. Call a physician immediately.

# 4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

# 4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 9 Jul 2025

**Version:** 4 Page 4/14



# **Multi Tech Dry 500ml**

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

#### Suitable extinguishing media:

Adapt fire extinguishing measures to the surroundings.

#### 5.2. Special hazards arising from the substance or mixture

Formation of toxic gases when heated or in case of fire.

#### 5.3. Advice for firefighters

Special protective equipment: Put on breathing apparatus.

## **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

#### **Personal precautions:**

Use of respiratory protective equipment.

Wear protective equipment. Keep unprotected persons away.

Keep away from sources of ignition - No smoking.

## 6.1.2. For emergency responders

No data available

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of spillage into water or sewage system, inform the competent authorities.

## 6.3. Methods and material for containment and cleaning up

#### Other information:

Dispose of contaminated material as waste according to section 13...

Provide adequate ventilation.

#### 6.4. Reference to other sections

See section 7 for further information on safe handling.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

## **Protective measures**

#### Advices on safe handling:

Ensure good ventilation/extraction at the workplace.

#### Fire prevent measures:

Do not spray on naked flames or any incandescent material. Keep away from sources of ignition - No smoking. Have breathing apparatus ready.

# 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels:

The official regulations for the storage of pressurised gas packages must be observed.

#### Hints on storage assembly:

Not required.

Storage class (TRGS 510, Germany): 2B - Aerosol dispensers and lighters

## Further information on storage conditions:

Keep container tightly closed.

#### 7.3. Specific end use(s)

#### **Recommendation:**

No further relevant information available.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 9 Jul 2025

**Version:** 4 Page 5/14



Multi Tech Dry 500ml

# **SECTION 8: Exposure controls/personal protection**

# \* 8.1. Control parameters

# 8.1.1. Occupational exposure limit values

	Substance name	<ol> <li>Long-term occupational exposure limit value</li> <li>Short-term occupational exposure limit value</li> <li>Instantaneous value</li> <li>Monitoring and observation processes</li> <li>Remark</li> </ol>
MAK (AT)	<b>pentane</b> CAS No.: 109-66-0 EC No.: 203-692-4	② 1,200 ppm (3,600 mg/m³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
IOELV (EU)	<b>pentane</b> CAS No.: 109-66-0 EC No.: 203-692-4	① 1,000 ppm (3,000 mg/m³)
MAK (AT)	<b>pentane</b> CAS No.: 109-66-0 EC No.: 203-692-4	① 600 ppm (1,800 mg/m³)
MAK (AT)	<b>propane</b> CAS No.: 74-98-6 EC No.: 200-827-9	② 2,000 ppm (3,600 mg/m³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
MAK (AT)	<b>propane</b> CAS No.: 74-98-6 EC No.: 200-827-9	① 1,000 ppm (1,800 mg/m³)
MAK (AT)	Butane (with < 0,1 % butadiene (203-450-8)) CAS No.: 106-97-8 EC No.: 203-448-7	① 800 ppm (1,900 mg/m³)
MAK (AT)	Butane (with < 0,1 % butadiene (203-450-8)) CAS No.: 106-97-8 EC No.: 203-448-7	② 1,600 ppm (3,800 mg/m³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
MAK (AT)	Isobutane (with < 0.1 % butadiene (203-450-8)) CAS No.: 75-28-5 EC No.: 200-857-2	② 1,600 ppm (3,800 mg/m³) ⑤ (max. 3x60 min./SchichtMomentanwert)
MAK (AT)	Isobutane (with < 0.1 % butadiene (203-450-8)) CAS No.: 75-28-5 EC No.: 200-857-2	① 800 ppm (1,900 mg/m³)
MAK (AT)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	② 800 ppm (2,000 mg/m³) ⑤ (max. 4x15 min./Schicht)
MAK (AT)	<b>propan-2-ol</b> CAS No.: 67-63-0 EC No.: 200-661-7	① 200 ppm (500 mg/m³)

# 8.1.2. Biological limit values

No data available

# 8.1.3. DNEL-/PNEC-values

11.5. DIVLE-71 NEC-Values		
Substance name	DNEL value	① DNEL type ② Exposure route
<b>pentane</b> CAS No.: 109-66-0 EC No.: 203-692-4	3,000 mg/m <sup>3</sup>	DNEL worker     Dong-term – inhalation, systemic effects
<b>pentane</b> CAS No.: 109-66-0 EC No.: 203-692-4	643 mg/m <sup>3</sup>	DNEL Consumer     Long-term – inhalation, systemic effects

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 9 Jul 2025 Version: 4

Page 6/14



# Multi Tech Dry 500ml

Substance name	DNEL value	① DNEL type
		② Exposure route
<b>pentane</b> CAS No.: 109-66-0 EC No.: 203-692-4	432 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
<b>pentane</b> CAS No.: 109-66-0 EC No.: 203-692-4	214 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
<b>pentane</b> CAS No.: 109-66-0 EC No.: 203-692-4	214 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects
<b>propan-2-ol</b> CAS No.: 67-63-0 EC No.: 200-661-7	500 mg/m <sup>3</sup>	① DNEL worker ② Long-term – inhalation, systemic effects
<b>propan-2-ol</b> CAS No.: 67-63-0 EC No.: 200-661-7	89 mg/m³	① DNEL Consumer ② Long-term – inhalation, systemic effects
<b>propan-2-ol</b> CAS No.: 67-63-0 EC No.: 200-661-7	888 mg/kg bw/ day	DNEL worker     Long-term - dermal, systemic effects
<b>propan-2-ol</b> CAS No.: 67-63-0 EC No.: 200-661-7	319 mg/kg bw/ day	DNEL Consumer     Long-term - dermal, systemic effects
<b>propan-2-ol</b> CAS No.: 67-63-0 EC No.: 200-661-7	26 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects
Substance name	PNEC Value	① PNEC type
<b>pentane</b> CAS No.: 109-66-0 EC No.: 203-692-4	0.23 mg/L	① PNEC aquatic, freshwater
nontano	0.22 mg/l	® PMEC 1: : :

Substance name	PNEC Value	① PNEC type
<b>pentane</b> CAS No.: 109-66-0 EC No.: 203-692-4	0.23 mg/L	① PNEC aquatic, freshwater
<b>pentane</b> CAS No.: 109-66-0 EC No.: 203-692-4	0.23 mg/L	① PNEC aquatic, marine water
<b>pentane</b> CAS No.: 109-66-0 EC No.: 203-692-4	3.6 mg/L	① PNEC sewage treatment plant
<b>pentane</b> CAS No.: 109-66-0 EC No.: 203-692-4	1.2 mg/kg bw/ day	① PNEC sediment, freshwater
<b>pentane</b> CAS No.: 109-66-0 EC No.: 203-692-4	1.2 mg/kg	① PNEC sediment, marine water
<b>pentane</b> CAS No.: 109-66-0 EC No.: 203-692-4	0.55 mg/kg	① PNEC soil
<b>pentane</b> CAS No.: 109-66-0 EC No.: 203-692-4	0.88 mg/L	① PNEC aquatic, intermittent release
<b>propan-2-ol</b> CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, freshwater
<b>propan-2-ol</b> CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, marine water
<b>propan-2-ol</b> CAS No.: 67-63-0 EC No.: 200-661-7	2,251 mg/L	① PNEC sewage treatment plant
<b>propan-2-ol</b> CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, freshwater

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 9 Jul 2025

Version: 4 Page 7/14



# **Multi Tech Dry 500ml**

Substance name	PNEC Value	① PNEC type
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	28 mg/kg	① PNEC soil
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, intermittent release

#### 8.2. Exposure controls

# 8.2.1. Appropriate engineering controls

No further details. See section 7.

#### 8.2.2. Personal protection equipment







#### Eye/face protection:

Safety goggles with side shields (EN 166).

#### Skin protection:

Hand protection:

Wear protective gloves.

Glove material: Butyl caoutchouc (butyl rubber)

The selection of a suitable glove depends not only on the material but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use. Permeation time (maximum wear duration):

Gloves made of butyl rubber with a material thickness of 0.4mm are resistant to: Acetone 480 min; Butyl acetate 60 min; Ethyl acetate 170 min; Xylene 42 min

Gloves made of butyl rubber with a layer thickness of 0.4 mm are resistant to solvents for 42 - 480 minutes. As a precautionary measure, we recommend users and those responsible for occupational safety to take a resistance of 42 minutes as a basis. Taking into account the information in chapter 3 of the MSDS, it is possible to assume a higher resistance in individual cases.

#### Respiratory protection:

In case of short or low exposure use breathing filter apparatus; in case of intensive or prolonged exposure use self-contained breathing apparatus. Filter A2/P3

## Other protection measures:

General protective and hygienic measures:

Keep away from food, drink and animal feed.

Remove contaminated, saturated clothing immediately.

Wash hands before breaks and after work.

Do not inhale gases/vapours/aerosols.

Avoid contact with eyes and skin.

### 8.2.3. Environmental exposure controls

No data available

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

#### **Appearance**

Form: Aerosol Colour: whitish

Odour: solvent-like flammability: No data available

Odour threshold: not determined

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 9 Jul 2025

Version: 4 Page 8/14



# Multi Tech Dry 500ml

## Safety relevant basis data

Parameter	Value	at °C	① Method
			② Remark
Initial boiling point and boiling range	not applicable		
Flash point	not applicable		
Evaporation rate	No data available		
Auto-ignition temperature	285 °C		② pentane (109-66-0)
Upper/lower flammability or explosive limits	1.4 - 12 Vol-%		② pentane (109-66-0); propan-2-ol (67-63-0)
Vapour pressure	3,500 hPa	20 °C	
Density	0.6 g/cm <sup>3</sup>	20 °C	
Water solubility	practically insoluble		

#### 9.2. Other information

Organic solvents: 99,8% Solid content:0,2%

# 9.2.1. Information with regard to physical hazard classes

#### **Explosives:**

Not applicable

# Flammable gases:

Not applicable

#### Aerosols:

Extremely flammable aerosol. Pressurized container: May burst if heated.

# Oxidizing gases:

Not applicable

#### **Gases under pressure:**

Not applicable

#### Flammable liquids:

Not applicable

# Flammable solids:

Not applicable

#### **Self-reactive substances and mixtures:**

Not applicable

#### **Pyrophoric liquids:**

Not applicable

#### **Pyrophoric solids:**

Not applicable

#### Self-heating substances and mixtures:

Not applicable

#### Substances or mixtures which, in contact with water, emit flammable gases:

Not applicable

# **Oxidizing liquids:**

Not applicable

#### Oxidizing solids:

Not applicable

### **Organic peroxides:**

Not applicable

## **Corrosive to metals:**

Not applicable

#### **Desensitised explosives:**

Not applicable

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 9 Jul 2025

Version: 4 Page 9/14



# **Multi Tech Dry 500ml**

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No further relevant information available.

#### 10.2. Chemical stability

Thermal decomposition / Conditions to avoid No decomposition when used as directed.

# 10.3. Possibility of hazardous reactions

No dangerous reactions known.

#### 10.4. Conditions to avoid

No further relevant information available.

#### 10.5. Incompatible materials

No further relevant information available.

#### 10.6. Hazardous decomposition products

No dangerous decomposition products known.

# **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

pentane CAS No.: 109-66-0 EC No.: 203-692-4

**LD<sub>50</sub> oral:** >5,000 mg/kg (Rat)

**LD<sub>50</sub> dermal:** >2,000 mg/kg (Rat)

LC<sub>50</sub> Acute inhalation toxicity (gas): >20 ppmV 4 h (rat)

LC<sub>50</sub> Acute inhalation toxicity (vapour): >25.3 mg/L 4 h (Rat) OECD 403

**propane** CAS No.: 74-98-6 EC No.: 200-827-9

LD<sub>50</sub> oral: 5,840 mg/kg (Rat)

LD<sub>50</sub> dermal: 13,900 mg/kg (Rabbit)

LC<sub>50</sub> Acute inhalation toxicity (gas): >25 ppmV 4 h (Rat)

LC<sub>50</sub> Acute inhalation toxicity (vapour): ≥50 mg/L 4 h (Rat)

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

**LD<sub>50</sub> oral:** >2,000 mg/kg (Rat)

**LD<sub>50</sub> dermal:** >2,000 mg/kg (Rat)

LC<sub>50</sub> Acute inhalation toxicity (gas): >25 ppmV 4 h (Rat)

 $LC_{50}$  Acute inhalation toxicity (vapour): >20 mg/L 6 h (Rat)

#### Acute oral toxicity:

Based on available data, the classification criteria are not met.

#### Acute dermal toxicity:

Based on available data, the classification criteria are not met.

#### Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation:

Based on available data, the classification criteria are not met. No irritant effect.

#### Serious eve damage/irritation:

Causes serious eye irritation.

#### Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met. No sensitising effect known.

#### Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

## **Carcinogenicity:**

Based on available data, the classification criteria are not met.

#### Reproductive toxicity:

Based on available data, the classification criteria are not met.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 9 Jul 2025

Version: 4 Page 10/14



# **Multi Tech Dry 500ml**

#### **STOT-single exposure:**

May cause drowsiness or dizziness.

#### STOT-repeated exposure:

Based on available data, the classification criteria are not met.

#### **Aspiration hazard:**

Based on available data, the classification criteria are not met.

#### 11.2. Information on other hazards

#### **Endocrine disrupting properties:**

None of the ingredients are included.

# **SECTION 12: Ecological information**

#### \* 12.1. Toxicity

pentane CAS No.: 109-66-0 EC No.: 203-692-4

LC<sub>50</sub>: 4.26 mg/L 4 d (fish, Oncorhynchus mykiss)

EC<sub>50</sub>: 10.7 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

EC<sub>50</sub>: 2.7 mg/L 2 d (crustaceans, Daphnia magna)

NOEC: 7.51 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

NOEC: 7.51 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

EC<sub>50</sub>: 10.7 mg/L 3 d (Algae/water plant, Pseudokirchnerie lla subcapitata)

propane CAS No.: 74-98-6 EC No.: 200-827-9

LC<sub>50</sub>: 9,640 mg/L 4 d (fish, Pimephales promelas)

LC<sub>50</sub>: 0.41 mg/L 4 d (fish, Oncorhynchus mykiss)

LC<sub>50</sub>: 49.9 mg/L 4 d (fish)

EC<sub>50</sub>: >100 mg/L (Algae/water plant, Bacteria)

EC<sub>50</sub>: 0.17 mg/L 3 d (Algae/water plant, Selenastrum capricornutum)

EC50: 69.43 mg/L 2 d (crustaceans, Daphnia) Calculation with the ECOSAR programme v1.00.

NOEC: 0.017 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

ErC<sub>50</sub>: 19.37 mg/L 4 d (Algae/water plant, Algae) Calculation with the ECOSAR programme v1.00.

LOEC: 1,000 mg/L (Algae/water plant, Algae)

**LOEC:** 1,000 mg/L (Algae/water plant, Alge)

IC<sub>50</sub>: 11.3 mg/L 3 d (Algae/water plant)

**propan-2-ol** CAS No.: 67-63-0 EC No.: 200-661-7

**LC<sub>50</sub>:** >1,000 mg/L 4 d (fish)

LC<sub>50</sub>: 9,640 mg/L 4 d (fish, Pimephales promelas)

LC<sub>50</sub>: 9,714 mg/L 1 d (Daphnia magna)

**EC<sub>50</sub>:** >1,000 mg/L 2 d (crustaceans)

EC<sub>50</sub>: >100 mg/L (Algae/water plant, Bacteria)

**EC<sub>50</sub>:** >100 mg/L 2 d (crustaceans, Daphnia magna)

ErC<sub>50</sub>: >100 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus)

ErC<sub>50</sub>: >100 mg/L 3 d (Algae/water plant, Scenedesmus subspicatus)

LOEC: 1,000 mg/L (Alge)

LOEC: 1,000 mg/L (Algae/water plant, Algae)

**LOEC:** 1,000 mg/L

#### Assessment/classification:

No further relevant information available.

#### 12.2. Persistence and degradability

pentane CAS No.: 109-66-0 EC No.: 203-692-4

Biodegradation: Yes, rapidly

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 9 Jul 2025

Version: 4 Page 11/14



# Multi Tech Dry 500ml

**propane** CAS No.: 74-98-6 EC No.: 200-827-9

**Biodegradation:** Yes, rapidly

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

**Biodegradation:** Yes, rapidly

Remark: Readily biodegradable (according to OECD criteria).

#### Additional information:

No further relevant information available.

#### 12.3. Bioaccumulative potential

pentane CAS No.: 109-66-0 EC No.: 203-692-4

Log Kow: 3.39

**propane** CAS No.: 74-98-6 EC No.: 200-827-9

Log Kow: 1.09

**propan-2-ol** CAS No.: 67-63-0 EC No.: 200-661-7

Log K<sub>OW</sub>: 0.05

#### **Accumulation / Evaluation:**

No further relevant information available.

#### 12.4. Mobility in soil

No further relevant information available.

#### 12.5. Results of PBT and vPvB assessment

pentane CAS No.: 109-66-0 EC No.: 203-692-4

Results of PBT and vPvB assessment: -

**propane** CAS No.: 74-98-6 EC No.: 200-827-9

Results of PBT and vPvB assessment: -

Butane (with < 0,1 % butadiene (203-450-8)) CAS No.: 106-97-8 EC No.: 203-448-7

Results of PBT and vPvB assessment: -

**propan-2-ol** CAS No.: 67-63-0 EC No.: 200-661-7

Results of PBT and vPvB assessment: -

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties.

#### 12.7. Other adverse effects

Toxic to fish.

Toxic to aquatic life.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage

Drinking water hazard even when small quantities leak into the subsoil.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Must not be disposed of together with household waste. Do not allow to enter into surface water or drains.

For Austria: Full and empty containers are to be disposed of by private end users at the responsible hazardous waste collection centre.

#### 13.1.1. Product/Packaging disposal

#### Waste codes/waste designations according to EWC/AVV Waste code product

\*: Evidence for disposal must be provided.

#### Waste code packaging

15 01 04 metallic packaging

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 9 Jul 2025

Version: 4 Page 12/14



# Multi Tech Dry 500ml

#### **Waste treatment options**

#### Appropriate disposal / Package:

Uncleaned packaging: Dispose of waste according to applicable legislation.

# **SECTION 14: Transport information**

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or	ID number		
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper ship	ping name		
AEROSOLS, ENVIRONMENTALLY HAZARDOUS	AEROSOLS, ENVIRONMENTALLY HAZARDOUS	AEROSOLS (PENTANES), MARINE POLLUTANT	AEROSOLS, flammable
14.3. Transport haza	ard class(es)		
2.1	2.1	2.1	2.1
14.4. Packing group			
14.5. Environmental	hazards	-	
(L)	¥2>	MARINE POLLUTANT	No
14.6. Special precau	tions for user		
Special Provisions: 190   327   344   625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F Tunnel restriction code: (D)	Special Provisions: 190   327   344   625 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F	Special Provisions: 63   190   277   327   344   381   959  Limited quantity (LQ): SV277  Excepted Quantities (EQ): E0  EmS-No.: F-D, S-U	Special Provisions: A145   A167 Limited quantity (LQ): Y203 Excepted Quantities (EQ): E0

# **14.7.** Maritime transport in bulk according to IMO instruments not applicable

# **SECTION 15: Regulatory information**

# \* 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.1.1. EU legislation

#### **Authorisations:**

Named dangerous substances - ANNEX I: None of the ingredients are included.

#### **Restrictions on use:**

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II: None of the ingredients are included.

Regulation (EU) 2019/1148

Regulation (EC) No 273/2004 on drug precursors: None of the ingredients are included.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade in drug precursors between the Community and third countries: None of the ingredients are included.

#### Other regulations (EU):

Hazard categories:

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 9 Jul 2025

Version: 4 Page 13/14



# Multi Tech Dry 500ml

- P3a 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids
- E2 Hazardous to the Aquatic Environment in Category Chronic 2

Named dangerous substances:

• Liquefied flammable gases, Category 1 or 2 (including liquefied petroleum gas) and natural gas Regulation (EC) No 1907/2006 ANNEX XVII Restriction conditions: 3

# Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 99.8 Vol-%

#### 15.1.2. National regulations

No data available

### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

## **SECTION 16: Other information**

## 16.1. Indication of changes

1.3.	Details of the supplier of the safety data sheet
3.2.	Mixtures
8.1.	Control parameters
12.1.	Toxicity
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture
16.1.	Indication of changes
16.2.	Abbreviations and acronyms

#### \*

16.2.	Appreviations and acronyms
16.2. Al	obreviations and acronyms
ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland
	Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DNEL	derived no-effect level
EC <sub>50</sub>	Effective Concentration 50%
EN	European Standard
ES	Exposure scenario
EWC	European Waste Catalogue
IC <sub>50</sub>	Inhibition Concentration 50 %
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
KG	body weight
LC <sub>50</sub>	Lethal (fatal) Concentration 50%
LD <sub>50</sub>	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PC	Product category
PNEC	Predicted No Effect Concentration
PROC	Process Category
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 9 Jul 2025

Version: 4 Page 14/14



# **Multi Tech Dry 500ml**

SCL Specific concentration limit

TRGS Technische Regeln für Gefahrstoffe

UN United Nations

VOC Volatile organic compounds

#### 16.3. Key literature references and sources for data

No data available

# 16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	

# 16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.

## 16.6. Training advice

No data available

# 16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

<sup>\*</sup> Data changed compared with the previous version.