according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 10 Jul 2025 Version: 5

Page 1/15

Safe Clean 500ml

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1. Product identifier Trade name/designation:

Safe Clean 500ml

Article No.: T204001 UFI: 529D-17GA-8H0A-4UPR

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Surface cleaner

* 1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH Hartleitnerstraße 3 4653 Eberstalzell Austria Telephone: +43 (0) 7241 213 79 E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 10 Jul 2025 Version: 5



Page 2/15

Safe Clean 500ml

Hazard components for labelling:

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, <2% aromatics; propan-2-ol

Hazard statements for physical hazards		
H222	Extremely flammable aerosol.	
H229	Pressurised container: May burst if heated.	
Hazard statements for health hazards		

nazara statements for nearth nazaras			
H319	Causes serious eye irritation.		
H336	May cause drowsiness or dizziness.		

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements Prevention		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P260	Do not breathe mist/vapours/spray.	
P271	Use only outdoors or in a well-ventilated area.	
P280	Wear protective gloves and eye protection/face protection.	

Precautionary statements Response

	· · · · · · · · · · · · · · · · · · ·			
P304 + P340	304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.			
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.			

Precautionary statements Storage

riceautonary statements otorage		
P403	Store in a well-ventilated place.	
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.		

Precautionary statements DisposalP501Dispose of conten

Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description:

Active ingredient mixture with propellant gas

Additional information:

Aerosols and containers fitted with a solid nebuliser containing substances or mixtures classified as hazardous by aspiration must not be labelled for this hazard.

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 64742-48-9 EC No.: 919-857-5 REACH No.: 01-2119463258-33-XXXX	Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, <2% aromatics Asp. Tox. 1 (H304), Flam. Liq. 3 (H226), STOT SE 3 (H336)	75 - < 100 Vol-%
	Aliphatic hydrocarbons The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].	≥ 30 Vol-%

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 10 Jul 2025 Version: 5



Page 3/15

Safe Clean 500ml

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
REACH No.: 01-2119486136-34	Aromatic hydrocarbons The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].	≥ 5 - < 15 Vol-%
CAS No.: 67-63-0 EC No.: 200-661-7 Index No.: 603-117-00-0 REACH No.: 01-2119457558-25	propan-2-ol Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336)	2.5 - < 10 Vol-%
EC No.: 905-588-0 REACH No.: 01-2119488216-32-XXXX	Reaction mass of ethylbenzene and xylene Acute Tox. 4 (H312, H332), Asp. Tox. 1 (H304), Eye Irrit. 2 (H319), Flam. Liq. 3 (H226), STOT RE 2 (H373), STOT SE 3 (H335), Skin Irrit. 2 (H315) Image: Comparison of the system of the s	2.5 - < 10 Vol-%
CAS No.: 124-38-9 EC No.: 204-696-9	carbon dioxide Press. Gas (Liq.) (H280) \bigcirc Warning Acute Toxicity Estimate ATE (oral) ≥ 5,000 mg/kg ATE (dermal) ≥ 5,000 mg/kg ATE (inhalation, vapour) 259,354 mg/L ATE (inhalation, dust/mist) ≥ 50 mg/L ATE (oral so conting 16	2.5 - < 10 Vol-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Following inhalation:

Fresh air supply, consult a doctor in case of complaints.

In case of skin contact:

In general, the product is not irritating to skin.

After eye contact:

Rinse opened eye for several minutes under running water. Consult a doctor if symptoms persist **Following ingestion:**

Do not induce vomiting, seek medical help immediately.

4.2. Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water mist, Extinguishing powder, Carbon dioxide (CO2), alcohol resistant foam

Unsuitable extinguishing media:

Water in full jet

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 10 Jul 2025 Version: 5 TECH MASTERS world of innovations

Page 4/15

Safe Clean 500ml

5.3. Advice for firefighters

Special protective equipment: Put on breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear protective equipment. Keep unprotected persons away.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of spillage into water or sewage system, inform the competent authorities.

6.3. Methods and material for containment and cleaning up

For cleaning up:

Do not wash away with water or aqueous detergents.

Other information:

Provide adequate ventilation.

6.4. Reference to other sections

Further information on proper storage: see section 7. For further information on personal protective equipment: see section 8. For further information on disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Ensure good ventilation/extraction at the workplace.

Fire prevent measures:

Do not spray on naked flames or any incandescent material. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Container is under pressure. Protect from sunlight and temperatures above 50°C (e.g. from incandescent lamps). Do not open by force or burn even after use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Store in a cool place. The official regulations for the storage of pressurised gas packages must be observed.

Hints on storage assembly:

The official regulations for the storage of pressurised gas packages must be observed.

Storage class (TRGS 510, Germany): 2B - Aerosol dispensers and lighters

Further information on storage conditions:

Store in a cool, dry place in well-sealed containers. Protect from heat and direct sunlight.

7.3. Specific end use(s)

Recommendation:

No further relevant information available.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878 Revision date: 7 Jul 2025

Revision date: 7 Jul 2025 Print date: 10 Jul 2025 Version: 5

Page 5/15

Safe Clean 500ml

SECTION 8: Exposure controls/personal protection

* 8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value
		③ Instantaneous value
		④ Monitoring and observation processes
		⑤ Remark
MAK (AT)	Hydrocarbons, C9-C11, n-alkanes, iso- alkanes, <2% aromatics	 200 mL/m³ 400 mL/m³
	CAS No.: 64742-48-9 EC No.: 919-857-5	⑤ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von weniger als 1 %, an n-Hexan von weniger als 5 % und an Cyclo-/ Isohexanen von weniger als 25 %)
MAK (AT)	Hydrocarbons, C9-C11, n-alkanes, iso- alkanes, <2% aromatics CAS No.: 64742-48-9 EC No.: 919-857-5	 170 mL/m³ 340 mL/m³ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von weniger als 1 %, an n-Hexan von weniger als 5 % und an Cyclo-/ Isohexanen von 25 % oder mehr)
MAK (AT)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	 2 800 ppm (2,000 mg/m³) (b) (max. 4x15 min./Schicht)
MAK (AT)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	① 200 ppm (500 mg/m³)
MAK (AT) from 25 Sept 2018	Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	 2 100 ppm (442 mg/m³) (max. 4x15 min./Schicht)
IOELV (EU)	Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	 50 ppm (221 mg/m³) 100 ppm (442 mg/m³) (may be absorbed through the skin)
MAK (AT) from 25 Sept 2018	Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	 50 ppm (221 mg/m³)
MAK (AT)	carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9	① 5,000 ppm (9,000 mg/m³)
MAK (AT)	carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9	 2 10,000 ppm (18,000 mg/m³) (max. 3x60 min./Schicht, Momentanwert)
IOELV (EU)	carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9	① 5,000 ppm (9,000 mg/m³)

8.1.2. Biological limit values

No data available

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 10 Jul 2025 Version: 5



Page 6/15

Safe Clean 500ml

Substance name	DNEL value	
	DIVLE Value	① DNEL type
		② Exposure route
Hydrocarbons, C9-C11, n-alkanes, iso- alkanes, <2% aromatics CAS No.: 64742-48-9 EC No.: 919-857-5	185 mg/m³	 DNEL worker Long-term - inhalation, systemic effects
Hydrocarbons, C9-C11, n-alkanes, iso- alkanes, <2% aromatics CAS No.: 64742-48-9 EC No.: 919-857-5	871 mg/m³	 DNEL worker Long-term - inhalation, systemic effects
Hydrocarbons, C9-C11, n-alkanes, iso- alkanes, <2% aromatics CAS No.: 64742-48-9 EC No.: 919-857-5	125 mg/kg bw/ day	 DNEL Consumer Long-term - dermal, systemic effects
Hydrocarbons, C9-C11, n-alkanes, iso- alkanes, <2% aromatics CAS No.: 64742-48-9 EC No.: 919-857-5	day	② Long-term - dermal, systemic effects
Hydrocarbons, C9-C11, n-alkanes, iso- alkanes, <2% aromatics CAS No.: 64742-48-9 EC No.: 919-857-5	125 mg/kg bw/ day	 DNEL Consumer Long-term - oral, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	500 mg/m ³	 DNEL worker Long-term - inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	89 mg/m³	 DNEL Consumer Long-term - inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	888 mg/kg bw/ day	 DNEL worker Long-term - dermal, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	319 mg/kg bw/ day	 DNEL Consumer Long-term - dermal, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	26 mg/kg bw/ day	 DNEL Consumer Long-term - oral, systemic effects
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	77 mg/m³	 DNEL worker Long-term - inhalation, systemic effects
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	14.8 mg/m ³	 DNEL Consumer Long-term - inhalation, systemic effects
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	289 mg/m ³	 DNEL worker Acute - inhalation, local effects
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	180 mg/kg bw/ day	 DNEL worker Long-term - dermal, systemic effects
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	108 mg/kg bw/ day	 DNEL Consumer Long-term - dermal, systemic effects

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 10 Jul 2025 Version: 5 TECH MASTERS

Page 7/15

Safe Clean 500ml

Substance name	DNEL value	1 DNEL type
		② Exposure route
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	1.6 mg/kg bw/ day	 DNEL Consumer Long-term - oral, systemic effects
Substance name	PNEC Value	① PNEC type
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	 PNEC aquatic, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	 PNEC aquatic, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	2,251 mg/L	(1) PNEC sewage treatment plant
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	 PNEC sediment, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	28 mg/kg	① PNEC soil
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	 PNEC aquatic, intermittent release
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	0.327 mg/L	 PNEC aquatic, marine water
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	6.58 mg/L	① PNEC sewage treatment plant
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	12.46 mg/L	① PNEC sediment, freshwater
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	12.46 mg/L	① PNEC sediment, marine water
Reaction mass of ethylbenzene and xylene EC No.: 905-588-0	2.31 mg/kg	① PNEC soil

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No further details. See section 7.

8.2.2. Personal protection equipment



Eye/face protection: Safety goggles (EN-166)

Skin protection:

Hand protection:

The glove material must be impermeable and resistant to the product/the substance/the preparation. Due to the lack of tests, no recommendation can be made on the glove material for the product/preparation/

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 10 Jul 2025 Version: 5 TECH MASTERS

Page 8/15

Safe Clean 500ml

mixture of chemicals. mixture of chemicals. Selection of glove material considering breakthrough times, permeation rates and degradation.

Wear gloves for protection against chemicals according to EN 374.

Gloves / solvent resistant

Breakthrough times and swelling properties of the material must be taken into consideration. Glove material:

The selection of a suitable glove depends not only on the material but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use. NBR (Nitrile rubber)

Recommended material thickness: \geq 0,5 mm

Permeation time (maximum wear duration):

For continuous contact we recommend gloves with a breakthrough time of at least 240 minutes, with the preference for a breakthrough time greater than 480 minutes. For short term or splash protection we recommend the same. We are aware that suitable gloves offering this protection are not available. In this case, a shorter breakthrough time is permissible, provided the procedures for maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance the gloves give against a chemical substance, as this depends on the exact composition of the material of the gloves. The exact breakthrough time should be checked with the glove manufacturer and adhered to. Body protection:

Use protective suit. (EN-13034/6)

Antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688 EN13034-6).

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Filter A2/P2

Other protection measures:

General protective and hygienic measures: Keep away from food, drink and animal feed. Wash hands before breaks and after work. Do not inhale gases/vapours/aerosols. General ventilation.

8.2.3. Environmental exposure controls

Use a suitable container to prevent environmental pollution.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Form: Aerosol

Odour: characteristic

Colour: According to product designation **flammability:** No data available

Safety relevant basis data

Parameter	Value	at °C	 Method
			② Remark
рН	not applicable		② Mixture is not polar/aprotic.
Initial boiling point and boiling range	82 °C		② propan-2-ol
Flash point	13 °C		
Evaporation rate	No data available		
Auto-ignition temperature	270 °C		
Upper/lower flammability or explosive limits	0.6 - 12 Vol-%		
Vapour pressure	1 hPa	20 °C	
Density	0.79 g/cm ³	20 °C	
Water solubility			② Not miscible or only slightly miscible.

9.2. Other information

The product is not self-igniting. The product is not explosive, but the formation of explosive vapour/air mixtures is possible. formation of explosive vapour/air mixtures is possible.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 10 Jul 2025 Version: 5

Page 9/15

Safe Clean 500ml



9.2.1. Information with regard to physical hazard classes **Explosives:** Not applicable Flammable gases: Not applicable Aerosols: Extremely flammable aerosol. Pressurized container: May burst if heated. **Oxidizing gases:** Not applicable Gases under pressure: Not applicable Flammable liquids: Not applicable Flammable solids: Not applicable Self-reactive substances and mixtures: Not applicable **Pyrophoric liquids:** Not applicable **Pyrophoric solids:** Not applicable Self-heating substances and mixtures: Not applicable Substances or mixtures which, in contact with water, emit flammable gases: Not applicable **Oxidizing liquids:** Not applicable **Oxidizing solids:** Not applicable **Organic peroxides:** Not applicable **Corrosive to metals:** Not applicable **Desensitised explosives:** Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

Thermal decomposition / Conditions to avoid: No decomposition when used as directed.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No dangerous decomposition products known.

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 10 Jul 2025 Version: 5

Page 10/15

Safe Clean 500ml

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7 LD₅₀ oral: >2,000 mg/kg (Rat)

LD₅₀ dermal: >2,000 mg/kg (Rat)

LC₅₀ Acute inhalation toxicity (gas): >25 ppmV 4 h (Rat)

LC₅₀ Acute inhalation toxicity (vapour): >20 mg/L 6 h (Rat)

Reaction mass of ethylbenzene and xylene EC No.: 905-588-0

LD₅₀ oral: >3,523 mg/kg (Rat)

LD₅₀ dermal: >2,000 mg/kg (Rabbit)

LC₅₀ Acute inhalation toxicity (gas): 27.571 ppmV 4 h (Rat)

LC₅₀ Acute inhalation toxicity (vapour): 29,000 mg/L 4 h (Rat)

carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9

ATE (inhalation, vapour): 259,354 mg/L

LD₅₀ oral: ≥5,000 mg/kg (Ratte)

LD₅₀ dermal: ≥5,000 mg/kg (Kaninchen)

LC₅₀ Acute inhalation toxicity (dust/mist): ≥50 mg/L 4 h (Ratte)

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, <2% aromatics CAS No.: 64742-48-9 EC No.: 919-857-5

LD₅₀ oral: >5,000 mg/kg (Rat)

LD₅₀ dermal: 3,160 mg/kg (Rabbit)

LC₅₀ Acute inhalation toxicity (dust/mist): >4,951 mg/L 4 h (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met. **Reproductive toxicity:**

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties:

None of the ingredients are included.



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 10 Jul 2025 Version: 5

Page 11/15

Safe Clean 500ml

SECTION 12: Ecological information

* 12.1. Toxicity

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7 LC₅₀: >1,000 mg/L 4 d (fish) LC₅₀: 9,640 mg/L 4 d (fish, Pimephales promelas) LC₅₀: 9,714 mg/L 1 d (Daphnia magna) EC50: >1,000 mg/L 2 d (crustaceans) EC₅₀: >100 mg/L (Algae/water plant, Bacteria) EC₅₀: >100 mg/L 2 d (crustaceans, Daphnia magna) ErC₅₀: >100 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus) ErC₅₀: >100 mg/L 3 d (Algae/water plant, Scenedesmus subspicatus) LOEC: 1,000 mg/L (Alge) LOEC: 1,000 mg/L (Algae/water plant, Algae) LOEC: 1,000 mg/L Reaction mass of ethylbenzene and xylene EC No.: 905-588-0 LC₅₀: 8.9 – 16.4 mg/L 4 d (fish, Pimephales promelas) EC₅₀: 3.2 - 9.5 mg/L 2 d (crustaceans, Daphnia magna) NOEC: 0.44 mg/L 3 d (Algae/water plant) LC₅₀: 2.6 mg/L 4 d (fish, Oncorhynchus mykiss) EC₅₀: 2.2 mg/L 3 d (Algae/water plant, Chlorella vulgaris) **NOEC:** >1.39 mg/L (fish, Oncorhynchus kisutch) NOEC: 0.74 mg/L (crustaceans, Ceriodaphnia dubia)

LC₅₀: 8.9 – 16.4 mg/L 4 d (Pimephales promelas)

EC₅₀: 3.2 – 9.5 mg/L 2 d (Daphnia magna)

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, <2% aromatics CAS No.: 64742-48-9 EC No.: 919-857-5 LC₅₀: 1,000 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout)) OECD 203

LC₅₀: 1,000 mg/L 2 d (crustaceans, Daphnia magna (Big water flea)) OECD 202

LC₅₀: >1,000 mg/L 4 d (fish, Regenbogenforell)) OECD 203

EC₅₀: 1,000 mg/L 2 d (crustaceans, Daphnia magna) OECD 202

EC50: 1,000 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata) OECD 201

Aquatic toxicity:

No further relevant information available.

12.2. Persistence and degradability

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Biodegradation: Yes, rapidly

Remark: Readily biodegradable (according to OECD criteria).

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, <2% aromatics CAS No.: 64742-48-9 EC No.: 919-857-5 Biodegradation: Yes, rapidly

Biodegradation:

Not readily biodegradable.

Additional information:

No further relevant information available.

12.3. Bioaccumulative potential

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Log K_{OW}: 0.05



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878 **Revision date:** 7 |ul 2025

Print date: 10 Jul 2025 Version: 5

Page 12/15

Safe Clean 500ml

Reaction mass of ethylbenzene and xylene EC No.: 905-588-0

Log K_{OW}: 3.16

Bioconcentration factor (BCF): 29

 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, <2% aromatics</th>
 CAS No.: 64742-48-9
 EC No.: 919-857-5

 Log K_{OW}: 4
 Case of the second second

Accumulation / Evaluation:

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7

Results of PBT and vPvB assessment: --

Reaction mass of ethylbenzene and xylene EC No.: 905-588-0

Results of PBT and vPvB assessment:

carbon dioxide CAS No.: 124-38-9 EC No.: 204-696-9

Results of PBT and vPvB assessment: –

Aliphatic hydrocarbons

Results of PBT and vPvB assessment: —

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, <2% aromatics CAS No.: 64742-48-9 EC No.: 919-857-5 Results of PBT and vPvB assessment: —

Aromatic hydrocarbons

Results of PBT and vPvB assessment: -

The product does not meet the PBT/vPvB criteria.

12.6. Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties.

12.7. Other adverse effects

Do not allow to enter into surface water or drains. Drinking water hazard even when small quantities leak into the subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Must not be disposed of together with household waste. Do not allow to enter into surface water or drains.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Directive 2008/98/EC (Waste Framework Directive)

	HP 3	Flammable		
	HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity		
M	Waste code packaging			

15 01 04 metallic packaging

Waste treatment options

Appropriate disposal / Package:

Uncleaned packaging: Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	• • •	Air transport (ICAO-TI / IATA-DGR)	
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	



according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878 Revision date: 7 Jul 2025

Revision date: 7 Jul 2025 Print date: 10 Jul 2025 Version: 5



Page 13/15

Safe Clean 500ml

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.2. UN proper shi	oping name		
AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable
14.3. Transport haza	ard class(es)		
<u>*</u>		*	*
	3	2	2
2.1	2.1	2.1	2.1
14.4. Packing group		•	<u></u>
		-	
14.5. Environmental	hazards	•	
No	No	No	No
14.6. Special precau	itions for user	•	,
Special Provisions:	Special Provisions:	Special Provisions:	Special Provisions:
190 327 344 625	190 327 344 625	63 190 277 327 344	-
Limited quantity (LQ):	Limited quantity (LQ):	381 959	Limited quantity (LQ):
1L	1L	Limited quantity (LQ):	Y203
Excepted Quantities	Excepted Quantities	Siehe SV277	Excepted Quantities
(EQ):	(EQ):	Excepted Quantities	(EQ):
E0	EO	(EQ): E0	EO
Classification code: 5F	Classification code:		Remark:
5.	5F	EmS-No.:	Attention: Gases
Tunnel restriction code:	Remark:	F-D, S-U	
(D)	Attention: Gases	Remark:	
Remark:		Attention: Gases	
Attention: Gases			

14.7. Maritime transport in bulk according to IMO instruments No data available

SECTION 15: Regulatory information

* 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Directive 2012/18/EU

Named dangerous substances - ANNEX I: None of the ingredients are included.

Restrictions on use:

Regulation (EC) No 1907/2006 ANNEX XVII: Restriction conditions: 3

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II: None of the ingredients are included.

Regulation (EU) 2019/1148

Annex I - RESTRICTED EXPORT SUBSTANCES FOR EXPLOSIVES (upper concentration limit for a permit pursuant to Article 5(3)): None of the ingredients are included.

Annex II - EXPLOSIVES REPORTABLE FOR EXPLOSIVES: None of the ingredients are included.

Regulation (EC) No 273/2004 on drug precursors: None of the ingredients are included.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade in drug precursors between the Community and third countries: None of the ingredients are included.

Other regulations (EU):

Hazard categories:

• P3b 'Flammable' aerosols Category 1 or 2, not containing flammable gases Category 1 or 2 nor flammable liquids Category 1

Named dangerous substances:

• Liquefied flammable gases, Category 1 or 2 (including liquefied petroleum gas) and natural gas

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 10 Jul 2025 Version: 5 TECH MASTERS

Page 14/15

Safe Clean 500ml

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds: Volatile organic compounds (VOC) content in percent by weight: 770.3 g/L

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

* 16.1. Indication of changes

10.1.1	indication of changes
1.3.	Details of the supplier of the safety data sheet
8.1.	Control parameters
12.1.	Toxicity
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture
161	Indication of changes

16.1. Indication of changes

16.2. Abbreviations and acronyms

ACGIH American Conference of Governmental Industrial Hygienists

- ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- ADR European Agreement concerning the International Carriage of Dangerous Goods by Road BCF Bioconcentration Factor
- CAS Chemical Abstracts Service
- CLP Classification, Labelling and Packaging
- DNEL derived no-effect level
- EC₅₀ Effective Concentration 50%
- EN European Standard
- ES Exposure scenario
- EWC European Waste Catalogue
- ICAO International Civil Aviation Organization
- IMDG International Maritime Dangerous Goods
- IMO International Maritime Organization
- KG body weight
- LC₅₀ Lethal (fatal) Concentration 50%
- LD₅₀ Lethal (fatal) Dose 50%
- MAK Maximum concentration in the workplace air (CH)
- NFPA National Fire Protection Association
- NIOSH National Institute for Occupational Safety & Health
- NOEC No Observed Effect Concentration
- OECD Organisation for Economic Cooperation and Development
- OSHA Occupational Safety & Health Administration
- PBT persistent and bioaccumulative and toxic
- PNEC Predicted No Effect Concentration
- REACH Registration, Evaluation and Authorization of Chemicals
- RID Dangerous goods regulations for transport by rail
- TRGS Technische Regeln für Gefahrstoffe
- UN United Nations
- VOC Volatile organic compounds
- ZNS central nervous system

16.3. Key literature references and sources for data

No data available

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025 Print date: 10 Jul 2025 Version: 5



Page 15/15

Safe Clean 500ml

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements		
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H280	Contains gas under pressure; may explode if heated.	
H304	04 May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H373	May cause damage to organs through prolonged or repeated exposure.	

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

* Data changed compared with the previous version.