

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 10 Jul 2025

Version: 4

Page 1/14



## Power Lube 200ml PP

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name/designation:

Power Lube 200ml PP

Article No.:

T221005

UFI:

9SXM-GHFJ-EP01-2H3S

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Lubricating agent

#### \* 1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH

Hartleitnerstraße 3

4653 Eberstälzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: msds@kando.eu

#### 1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

| Hazard classes and hazard categories                        | Hazard statements                                      | Classification procedure |
|---|--|--------------------------|
| Serious eye damage/eye irritation<br>(Eye Dam. 1)           | H318: Causes serious eye damage.                       |                          |
| Hazardous to the aquatic environment<br>(Aquatic Acute 1)   | H400: Very toxic to aquatic life.                      |                          |
| Hazardous to the aquatic environment<br>(Aquatic Chronic 2) | H411: Toxic to aquatic life with long lasting effects. |                          |
| aerosol dispensers and lighters<br>(Aerosol 3)              | H229: Pressurised container: May burst if heated.      |                          |

#### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



**GHS05**  
Corrosion



**GHS09**  
Environment

Signal word: Danger

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 10 Jul 2025

Version: 4



Page 2/14

## Power Lube 200ml PP

### Hazard components for labelling:

calcium dihydroxide

#### Hazard statements for physical hazards

H229 Pressurised container: May burst if heated.

#### Hazard statements for health hazards

H318 Causes serious eye damage.

#### Hazard statements for environmental hazards

H410 Very toxic to aquatic life with long lasting effects.

#### Supplemental hazard information

EUH208 Contains Benzenesulfonic acid, di-C10-18-alkyl derivs., calcium salts. May produce an allergic reaction.

#### Precautionary statements Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

#### Precautionary statements Response

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P391 Collect spillage.

#### Precautionary statements Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### Precautionary statements Disposal

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

### 2.3. Other hazards

#### Other adverse effects:

This mixture does not contain substances classified as PBT or vPvB substances.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Additional information:

There are no additional ingredients present which, according to the supplier's current knowledge, are classified as harmful to health or the environment in the applicable concentrations, are PBT or vPvB substances or substances of equivalent concern, or which have an occupational exposure limit and would therefore need to be reported in this section.

The wording of the listed hazard statements can be found in section 16.

#### Hazardous ingredients / Hazardous impurities / Stabilisers:

| Product identifiers  | Substance name<br>Classification according to Regulation (EC) No 1272/2008 [CLP]  | Concentration |
|--|---|---------------|
| CAS No.: 1305-62-0<br>EC No.: 215-137-3<br>REACH No.:<br>01-2119475151-45                            | <b>calcium dihydroxide</b><br>Eye Dam. 1 (H318), STOT SE 3 (H335), Skin Irrit. 2 (H315)<br>Danger<br><b>Acute Toxicity Estimate</b><br>ATE (oral) 7,340 mg/kg | < 10<br>%     |
| CAS No.: 7429-90-5<br>EC No.: 231-072-3<br>Index No.: 013-002-00-1<br>REACH No.:<br>01-2119529243-45 | <b>Aluminium powder</b><br>Flam. Sol. 1 (H228), Water-react. 2 (H261)<br>Danger   | ≤ 6<br>%      |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 10 Jul 2025

Version: 4



Page 3/14

## Power Lube 200ml PP

| Product identifiers  | Substance name<br>Classification according to Regulation (EC) No 1272/2008 [CLP]  | Concentration |
|--|---|---------------|
| CAS No.: 7440-50-8<br>EC No.: 231-159-6<br>Index No.: 029-024-00-X<br>REACH No.:<br>01-2119480154-42 | <b>copper</b><br>Acute Tox. 4 (H302), Aquatic Acute 1 (H400), Aquatic Chronic 2 (H411)<br>Warning<br>M-factor (acute): 10<br><b>Acute Toxicity Estimate</b><br>ATE (oral) > 2,000 mg/kg<br>ATE (dermal) 300 - 2,500 mg/kg<br>ATE (inhalation, gases) 5.11 ppmV<br>ATE (inhalation, dust/mist) 5.11 mg/L | ≤ 5<br>%      |
| CAS No.: 1314-13-2<br>EC No.: 215-222-5<br>Index No.: 030-013-00-7<br>REACH No.:<br>01-2119463881-32 | <b>zinc oxide</b><br>Aquatic Acute 1 (H400), Aquatic Chronic 1 (H410)<br>Warning<br>M-factor (acute): 1 M-factor (chronic): 1<br><b>Acute Toxicity Estimate</b><br>ATE (oral) > 5,000 mg/kg<br>ATE (dermal) > 2,000 mg/kg<br>ATE (inhalation, gases) > 5,700 ppmV                                       | ≤ 3<br>%      |
| CAS No.: 93820-57-6<br>EC No.: 298-637-4   | <b>Benzenesulfonic acid, di-C10-18-alkyl derivs., calcium salts</b><br>Skin Sens. 1 (H317)<br>Warning   | < 1<br>%      |

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Following inhalation:

Immediately call Poison Control Centre or a doctor. Remove the affected person to fresh air and immobilise in a position that facilitates breathing. If vapours are still suspected, the rescuer must wear a suitable respirator or self-contained breathing apparatus. If breathing is absent or irregular or if respiratory arrest occurs, artificial respiration or oxygen administration shall be initiated by trained personnel. It may be dangerous for the person giving first aid to give mouth-to-mouth resuscitation. If unconscious, place in the recovery position and seek immediate medical attention. Keep the airway open. Loosen tight-fitting clothing (e.g. collar, tie, belt or waistband).

#### In case of skin contact:

Immediately call Poison Control Centre or a doctor. Rinse contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing or wear gloves when doing so. Rinse continuously for at least 10 minutes. Chemical burns must be treated immediately by a doctor. Wash clothing before wearing again. Clean shoes thoroughly before reuse.

#### After eye contact:

Immediately call Poison Control Centre or a doctor. Immediately flush eyes with plenty of water and occasionally lift upper and lower eyelids. Check for contact lenses and remove if present. Rinse continuously for at least 10 minutes. Chemical burns must be treated immediately by a doctor.

#### Following ingestion:

Immediately call Poison Control Centre or a doctor. Rinse mouth with water. Remove dentures if present. If the substance has been swallowed and the person is conscious, give small amounts of water to drink. If nausea occurs, do not allow to continue drinking as vomiting can be dangerous. Do not induce vomiting unless specifically instructed to do so by medical personnel. If vomiting occurs, keep the head low so that the vomit does not enter the lungs. Chemical burns must be treated immediately by a doctor. Never administer anything by mouth to an unconscious person. If unconscious, place in recovery position and seek immediate medical attention. Keep airways open. Loosen tight-fitting clothing (e.g. collar, tie, belt or waistband).

#### Self-protection of the first aider:

No action should be taken that involves personal risk or has not been adequately trained. If it is suspected that there are still vapours are still present, the rescuer must wear a suitable respirator or self-contained breathing apparatus. It may be dangerous for the person giving first aid to perform mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it or wear gloves when doing so.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

**Revision date:** 7 Jul 2025

**Print date:** 10 Jul 2025

**Version:** 4

Page 4/14



## Power Lube 200ml PP

### 4.2. Most important symptoms and effects, both acute and delayed

Following inhalation: Cough, Irritation to respiratory tract  
In case of skin contact: Pain, Redness, Blistering may occur.  
After eye contact: Pain, Tear flow, Redness  
Following ingestion: Stomach pain

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. In case of ingestion or inhalation of large quantities, contact the Poison Control Centre specialist immediately.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media:

Use an extinguishing agent that is also suitable for adjacent fires.

#### Unsuitable extinguishing media:

None known.

### 5.2. Special hazards arising from the substance or mixture

There is a risk of fire and explosion if it enters the sewage system. When heated or on fire, a pressure rise occurs and the container may burst, creating an explosion hazard. Gas can accumulate in low-lying or enclosed areas or spread very far to an ignition source and cause flashback with fire or explosion. In the event of fire, bursting aerosol canisters can fly around at great speed. This material is very toxic to aquatic organisms. This material is toxic to aquatic organisms and has long-term effects. Extinguishing water contaminated with this material must be contained and must not enter water bodies, sewers or drains.

#### Hazardous combustion products:

Carbon dioxide, Carbon monoxide, halogenated compounds, Metal Oxides/Oxides

### 5.3. Advice for firefighters

In case of fire, immediately seal off the scene and evacuate all persons from the danger area. No action should be taken that involves personal risk or has not been adequately trained.

### 5.4. Additional information

Firefighters should wear appropriate protective clothing and self-contained breathing apparatus with full facepiece operated in positive pressure mode. Clothing for firefighters (including helmet, protective boots and protective gloves) that complies with the European Standard EN 469 gives a basic protection in case of accidents with chemicals.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

##### Personal precautions:

No action should be taken that involves personal risk or has not been adequately trained. Evacuate the area. Deny access to non-essential and unprotected personnel. Do not touch or walk on spilled substance. Do not breathe vapour or mist. Ensure adequate ventilation. Wear respirator if ventilation is inadequate. Put on suitable personal protective equipment.

#### 6.1.2. For emergency responders

##### Personal protection equipment:

If special clothing is needed to handle the spill, refer to section 8 on suitable and unsuitable materials. See also information in "Non-emergency trained personnel".

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of spillage into water or sewage system, inform the competent authorities. Substance is water polluting. May be harmful to the environment if released in large quantities. Absorb spilled quantities.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 10 Jul 2025

Version: 4



Page 5/14

## Power Lube 200ml PP

### 6.3. Methods and material for containment and cleaning up

#### For cleaning up:

Eliminate leakage if safe to do so. Remove container from the discharge area. Dilute with water and wipe up if water soluble. Alternatively, or if insoluble in water, absorb with an inert dry material and place in a suitable waste container. Dispose of via a recognised waste disposal company.

### 6.4. Reference to other sections

Further information on proper storage: see section 7.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Protective measures

##### Advices on safe handling:

Put on suitable protective equipment (see section 8). Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not swallow. Avoid release to the environment. If the material presents a respiratory hazard in normal use, use only with adequate ventilation or wear suitable respiratory protection. Store in the original container or an approved replacement container made of a compatible material. Keep tightly closed when not in use. Empty containers contain product residues and may be hazardous. Do not reuse containers.

##### Advices on general occupational hygiene

The usual precautions when handling chemicals must be observed. Do not eat, drink, smoke or snort while working. Do not inhale dust/fume/mist. Keep away from food, drink and animal feed. Wash hands before breaks and at the end of work.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions:

Store according to local regulations. Store only in the original container. Protect from direct sunlight. Store only in dry, cool and well-ventilated areas. Do not store with incompatible substances (see section 10) or with food or drink. Store under lock and key. Keep containers tightly closed and sealed until use. Containers which have been opened should be carefully closed and stored upright to prevent leakage. Do not store in unlabelled containers. Use suitable containers to avoid environmental contamination.

**Storage class (TRGS 510, Germany):** 2B – Aerosol dispensers and lighters

### 7.3. Specific end use(s)

#### Recommendation:

No data available

#### Industrial sector specific solutions:

No data available

## SECTION 8: Exposure controls/personal protection

### \* 8.1. Control parameters

#### 8.1.1. Occupational exposure limit values

| Limit value type<br>(country of origin) | Substance name  | ① Long-term occupational exposure limit value<br>② Short-term occupational exposure limit value<br>③ Instantaneous value<br>④ Monitoring and observation processes<br>⑤ Remark |
|---|---|--|
| MAK (AT)                                | <b>calcium dihydroxide</b><br>CAS No.: 1305-62-0<br>EC No.: 215-137-3 | ② 4 mg/m <sup>3</sup><br>⑤ (eintatembare Fraktion max. 8x5 min./Schicht, Momentanwert)   |
| IOELV (EU)<br>from 21 Feb 2017          | <b>calcium dihydroxide</b><br>CAS No.: 1305-62-0<br>EC No.: 215-137-3 | ① 1 mg/m <sup>3</sup><br>② 4 mg/m <sup>3</sup><br>⑤ (respirable fraction)  |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 10 Jul 2025

Version: 4



Page 6/14

## Power Lube 200ml PP

| Limit value type<br>(country of origin) | Substance name  | ① Long-term occupational exposure limit value<br>② Short-term occupational exposure limit value<br>③ Instantaneous value<br>④ Monitoring and observation processes<br>⑤ Remark |
|---|---|--|
| MAK (AT)<br>from 2 Sept 2020            | <b>calcium dihydroxide</b><br>CAS No.: 1305-62-0<br>EC No.: 215-137-3 | ① 1 mg/m <sup>3</sup><br>⑤ (eintembare Fraktion)   |
| MAK (AT)<br>from 11 Sept 2007           | <b>Aluminium powder</b><br>CAS No.: 7429-90-5<br>EC No.: 231-072-3    | ① 10 mg/m <sup>3</sup><br>⑤ (eintembare Fraktion)  |
| MAK (AT)<br>from 11 Sept 2007           | <b>Aluminium powder</b><br>CAS No.: 7429-90-5<br>EC No.: 231-072-3    | ② 20 mg/m <sup>3</sup><br>⑤ (eintembare Fraktion, max. 2x60 min./Schicht)  |
| MAK (AT)<br>from 11 Sept 2007           | <b>Aluminium powder</b><br>CAS No.: 7429-90-5<br>EC No.: 231-072-3    | ① 5 mg/m <sup>3</sup><br>⑤ (alveolengängige Fraktion)  |
| MAK (AT)<br>from 11 Sept 2007           | <b>Aluminium powder</b><br>CAS No.: 7429-90-5<br>EC No.: 231-072-3    | ② 10 mg/m <sup>3</sup><br>⑤ (alveolengängige Fraktion, max. 2x60 min./Schicht)   |
| MAK (AT)                                | <b>copper</b><br>CAS No.: 7440-50-8<br>EC No.: 231-159-6              | ① 1 mg/m <sup>3</sup><br>② 4 mg/m <sup>3</sup><br>⑤ (eintembare Fraktion, max. 4x15 min./Schicht)  |
| MAK (AT)                                | <b>copper</b><br>CAS No.: 7440-50-8<br>EC No.: 231-159-6              | ① 0.1 mg/m <sup>3</sup><br>② 0.4 mg/m <sup>3</sup><br>⑤ (alveolengängige Fraktion max. 4x15 min./Schicht)  |
| MAK (AT)                                | <b>zinc oxide</b><br>CAS No.: 1314-13-2<br>EC No.: 215-222-5          | ① 5 mg/m <sup>3</sup><br>⑤ (alveolengängige Fraktion)  |

### 8.1.2. Biological limit values

No data available

### 8.1.3. DNEL-/PNEC-values

| Substance name  | DNEL value           | ① DNEL type<br>② Exposure route                             |
|---|----------------------|---|
| <b>calcium dihydroxide</b><br>CAS No.: 1305-62-0<br>EC No.: 215-137-3 | 1 mg/m <sup>3</sup>  | ① DNEL worker<br>② Long-term - inhalation, systemic effects |
| <b>calcium dihydroxide</b><br>CAS No.: 1305-62-0<br>EC No.: 215-137-3 | 4 mg/m <sup>3</sup>  | ① DNEL worker<br>② Acute - inhalation, systemic effects     |
| <b>calcium dihydroxide</b><br>CAS No.: 1305-62-0<br>EC No.: 215-137-3 | 1 mg/m <sup>3</sup>  | ① DNEL worker<br>② Long-term - inhalation, local effects    |
| <b>calcium dihydroxide</b><br>CAS No.: 1305-62-0<br>EC No.: 215-137-3 | 1 mg/m <sup>3</sup>  | ① DNEL Consumer<br>② Long-term - inhalation, local effects  |
| <b>calcium dihydroxide</b><br>CAS No.: 1305-62-0<br>EC No.: 215-137-3 | 4 mg/m <sup>3</sup>  | ① DNEL worker<br>② Acute - inhalation, local effects        |
| <b>calcium dihydroxide</b><br>CAS No.: 1305-62-0<br>EC No.: 215-137-3 | 4 mg/m <sup>3</sup>  | ① DNEL Consumer<br>② Acute - inhalation, local effects      |
| <b>copper</b><br>CAS No.: 7440-50-8<br>EC No.: 231-159-6              | 20 mg/m <sup>3</sup> | ① DNEL worker<br>② Acute - inhalation, systemic effects     |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 10 Jul 2025

Version: 4



Page 7/14

## Power Lube 200ml PP

| Substance name   | DNEL value            | ① DNEL type<br>② Exposure route                               |
|--|-----------------------|---|
| <b>copper</b><br>CAS No.: 7440-50-8<br>EC No.: 231-159-6     | 20 mg/m <sup>3</sup>  | ① DNEL Consumer<br>② Acute - inhalation, systemic effects     |
| <b>copper</b><br>CAS No.: 7440-50-8<br>EC No.: 231-159-6     | 1 mg/m <sup>3</sup>   | ① DNEL Consumer<br>② Long-term - inhalation, local effects    |
| <b>copper</b><br>CAS No.: 7440-50-8<br>EC No.: 231-159-6     | 1 mg/m <sup>3</sup>   | ① DNEL Consumer<br>② Acute - inhalation, local effects        |
| <b>copper</b><br>CAS No.: 7440-50-8<br>EC No.: 231-159-6     | 137 mg/kg bw/day      | ① DNEL worker<br>② Long-term - dermal, systemic effects       |
| <b>copper</b><br>CAS No.: 7440-50-8<br>EC No.: 231-159-6     | 137 mg/kg bw/day      | ① DNEL Consumer<br>② Long-term - dermal, systemic effects     |
| <b>copper</b><br>CAS No.: 7440-50-8<br>EC No.: 231-159-6     | 273 mg/kg bw/day      | ① DNEL worker<br>② Acute - dermal, systemic effects           |
| <b>copper</b><br>CAS No.: 7440-50-8<br>EC No.: 231-159-6     | 273 mg/kg bw/day      | ① DNEL Consumer<br>② Acute - dermal, systemic effects         |
| <b>copper</b><br>CAS No.: 7440-50-8<br>EC No.: 231-159-6     | 0.041 mg/kg bw/day    | ① DNEL Consumer<br>② Long-term - oral, systemic effects       |
| <b>zinc oxide</b><br>CAS No.: 1314-13-2<br>EC No.: 215-222-5 | 5 mg/m <sup>3</sup>   | ① DNEL worker<br>② Long-term - inhalation, systemic effects   |
| <b>zinc oxide</b><br>CAS No.: 1314-13-2<br>EC No.: 215-222-5 | 2.5 mg/m <sup>3</sup> | ① DNEL Consumer<br>② Long-term - inhalation, systemic effects |
| <b>zinc oxide</b><br>CAS No.: 1314-13-2<br>EC No.: 215-222-5 | 0.5 mg/m <sup>3</sup> | ① DNEL worker<br>② Long-term - inhalation, local effects      |
| <b>zinc oxide</b><br>CAS No.: 1314-13-2<br>EC No.: 215-222-5 | 83 mg/kg bw/day       | ① DNEL worker<br>② Long-term - dermal, systemic effects       |
| <b>zinc oxide</b><br>CAS No.: 1314-13-2<br>EC No.: 215-222-5 | 83 mg/kg bw/day       | ① DNEL Consumer<br>② Long-term - dermal, systemic effects     |
| <b>zinc oxide</b><br>CAS No.: 1314-13-2<br>EC No.: 215-222-5 | 0.83 mg/kg bw/day     | ① DNEL Consumer<br>② Long-term - oral, systemic effects       |

| Substance name   | PNEC Value | ① PNEC type                   |
|--|------------|-------------------------------|
| <b>zinc oxide</b><br>CAS No.: 1314-13-2<br>EC No.: 215-222-5 | 6.1 mg/L   | ① PNEC aquatic, marine water  |
| <b>zinc oxide</b><br>CAS No.: 1314-13-2<br>EC No.: 215-222-5 | 52 mg/L    | ① PNEC sewage treatment plant |
| <b>zinc oxide</b><br>CAS No.: 1314-13-2<br>EC No.: 215-222-5 | 117 mg/L   | ① PNEC sediment, freshwater   |
| <b>zinc oxide</b><br>CAS No.: 1314-13-2<br>EC No.: 215-222-5 | 56.5 mg/L  | ① PNEC sediment, marine water |
| <b>zinc oxide</b><br>CAS No.: 1314-13-2<br>EC No.: 215-222-5 | 35.6 mg/kg | ① PNEC soil                   |



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 10 Jul 2025

Version: 4



Page 8/14

## Power Lube 200ml PP

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

If the work generates dust, fumes, gas, vapours or mists, use process chambers, local exhaust ventilation systems or other technical devices to keep worker exposure below recommended or legally required limits.

#### 8.2.2. Personal protection equipment

##### Eye/face protection:

If the risk assessment so requires, protective goggles complying with a recognised standard should be worn to prevent exposure to liquid splashes, mists, gases or dusts. If contact is possible then the following protective equipment must be worn unless the assessment requires a higher level of protection: chemical splash goggles and/or face shield. In the case of inhalation hazards, a full face respirator may be required instead.

##### Skin protection:

Hand protection:

When handling chemical products, chemical-resistant, impervious gloves complying with a recognised standard must always be worn if a risk assessment so requires. Taking into account the parameters specified by the glove manufacturer, it must be checked during use that the gloves still ensure their protective properties. It should be noted that the breakthrough time for glove material may vary for different glove manufacturers. Recommended : 1-4 hours (penetration time): Nitrile rubber ; 4-8 hours (penetration time): Viton®/Butyl rubber

Body protection:

Before handling this product, personal protective equipment should be selected based on the task to be performed and the risks involved, and approved by a specialist.

Non-slip work footwear

##### Respiratory protection:

Based on the hazard and risk of exposure, select the respirator that meets the appropriate standards and has the appropriate certifications. Respirators must be used in accordance with the respiratory protection programme to ensure proper fit, adequate training and other important aspects of use. Recommended: Filters against organic vapours (type AX) and particles.

##### Other protection measures:

General protective and hygienic measures:

The usual precautions when handling chemicals must be observed. Do not eat, drink, smoke or snort while working. Do not inhale dust/fume/mist. Keep away from food, drink and animal feed. Wash hands before breaks and at the end of work.

#### 8.2.3. Environmental exposure controls

Emissions from ventilation and process equipment should be checked to ensure that they meet the requirements of environmental legislation. In some cases, exhaust air scrubbers, filters or engineering changes to process equipment will be required to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

Form: Aerosol

Colour: grey

Odour: Benzene

flammability: No data available

#### Safety relevant basis data

| Parameter                               | Value                 | at °C | ① Method<br>② Remark |
|---|-----------------------|-------|----------------------|
| Initial boiling point and boiling range | No data available     |       |                      |
| Flash point                             | 93.3 °C               |       |                      |
| Evaporation rate                        | No data available     |       |                      |
| Vapour pressure                         |                       |       |                      |
| Density                                 | 1.2 g/cm <sup>3</sup> | 20 °C |                      |
| Water solubility                        | not applicable        |       | ② Immiscible         |



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 10 Jul 2025

Version: 4



Page 9/14

## Power Lube 200ml PP

### 9.2. Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No further relevant information available.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Remove all sources of ignition.

### 10.4. Conditions to avoid

No further relevant information available.

### 10.5. Incompatible materials

No further relevant information available.

### 10.6. Hazardous decomposition products

Reactive or incompatible with the following substances: oxidising materials and acids.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

|   |                    |                   |
|---|--------------------|-------------------|
| <b>calcium dihydroxide</b>  | CAS No.: 1305-62-0 | EC No.: 215-137-3 |
| <b>LD<sub>50</sub> oral:</b> 7,340 mg/kg (Ratte)                              |                    |                   |
| <b>copper</b>   | CAS No.: 7440-50-8 | EC No.: 231-159-6 |
| <b>LD<sub>50</sub> oral:</b> >2,000 mg/kg (Rat)                               |                    |                   |
| <b>LD<sub>50</sub> dermal:</b> 300 – 2,500 mg/kg (Rat)                        |                    |                   |
| <b>LC<sub>50</sub> Acute inhalation toxicity (gas):</b> 5.11 ppmV 4 h (Rat)   |                    |                   |
| <b>LC<sub>50</sub> Acute inhalation toxicity (dust/mist):</b> 5.11 mg/L (Rat) |                    |                   |
| <b>zinc oxide</b>   | CAS No.: 1314-13-2 | EC No.: 215-222-5 |
| <b>LD<sub>50</sub> oral:</b> >5,000 mg/kg (Rat)                               |                    |                   |
| <b>LD<sub>50</sub> dermal:</b> >2,000 mg/kg (Rat)                             |                    |                   |
| <b>LC<sub>50</sub> Acute inhalation toxicity (gas):</b> >5,700 ppmV 4 h (Rat) |                    |                   |

#### Acute oral toxicity:

ATE (oral): 16666.67 mg/kg

#### Acute dermal toxicity:

Based on available data, the classification criteria are not met.

#### Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

#### Serious eye damage/irritation:

Causes serious eye damage.

#### Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

#### Carcinogenicity:

Based on available data, the classification criteria are not met.

#### Reproductive toxicity:

Based on available data, the classification criteria are not met.

#### STOT-single exposure:

Irritation to respiratory tract

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 10 Jul 2025

Version: 4

Page 10/14



## Power Lube 200ml PP

### STOT-repeated exposure:

Based on available data, the classification criteria are not met.

### Aspiration hazard:

Based on available data, the classification criteria are not met.

### Additional information:

No data available

### 11.2. Information on other hazards

No data available

## SECTION 12: Ecological information

### 12.1. Toxicity

|   |
|---|
| <b>calcium dihydroxide</b> CAS No.: 1305-62-0 EC No.: 215-137-3   |
| LC <sub>50</sub> : 33.8844 mg/L 4 d (fish, <i>Clarias gariepinus</i> )                                      |
| <b>copper</b> CAS No.: 7440-50-8 EC No.: 231-159-6  |
| LC <sub>50</sub> : 0.000072 mg/L 2 d (crustaceans, Krustazeen)  |
| LC <sub>50</sub> : 0.000072 mg/L 2 d (crustaceans, Krustazeen, Adultus)                                     |
| LC <sub>50</sub> : 0.000072 mg/L 2 d (crustaceans, Amphipoda)   |
| EC <sub>50</sub> : 0.0021 mg/L 2 d (crustaceans, Daphnia)   |
| NOEC: 0.0008 mg/L (fish, <i>Oreochromis niloticus</i> )   |
| NOEC: 0.0008 mg/L (crustaceans, Krustazeen)   |
| IC <sub>50</sub> : 0.016 mg/L 3 d (Algae/water plant, <i>Chlorella pyrenoidosa</i> )                        |
| IC <sub>50</sub> : 0.016 mg/L 3 d (Algae/water plant, <i>Chlorella pyrenoidosa</i> )                        |
| <b>zinc oxide</b> CAS No.: 1314-13-2 EC No.: 215-222-5  |
| LC <sub>50</sub> : 1.1 - 2.5 mg/L 4 d (fish, <i>Oncorhynchus mykiss</i> )                                   |
| IC <sub>50</sub> : 1.85 mg/L 4 d (Algae/water plant, <i>Skeletonema costatum</i> )                          |
| LC <sub>50</sub> : 3.31 - 8.062 mg/L 4 d (fish, <i>Brachydanio rerio</i> )                                  |
| LC <sub>50</sub> : >320 mg/L 4 d (fish, <i>Lepomis macrochirus</i> )  |
| EC <sub>50</sub> : 1 mg/L 2 d (crustaceans, <i>Daphnia magna</i> ) OECD 202                                 |
| EC <sub>50</sub> : 0.412 - 0.83 mg/L 2 d (crustaceans, <i>Ceriodaphnia spec.</i> ) U.S. EPA ECOTOX Database |

### 12.2. Persistence and degradability

#### Additional information:

No further relevant information available.

### 12.3. Bioaccumulative potential

|  |
|--|
| <b>zinc oxide</b> CAS No.: 1314-13-2 EC No.: 215-222-5 |
| Log K <sub>OW</sub> : 2.2                              |
| Bioconcentration factor (BCF): 28,960                  |

### 12.4. Mobility in soil

No further relevant information available.

### 12.5. Results of PBT and vPvB assessment

|   |
|---|
| <b>calcium dihydroxide</b> CAS No.: 1305-62-0 EC No.: 215-137-3   |
| Results of PBT and vPvB assessment: —   |
| <b>copper</b> CAS No.: 7440-50-8 EC No.: 231-159-6  |
| Results of PBT and vPvB assessment: —   |
| <b>zinc oxide</b> CAS No.: 1314-13-2 EC No.: 215-222-5  |
| Results of PBT and vPvB assessment: —   |
| <b>Benzenesulfonic acid, di-C10-18-alkyl derivs., calcium salts</b> CAS No.: 93820-57-6 EC No.: 298-637-4 |
| Results of PBT and vPvB assessment: —   |

This mixture does not contain substances classified as PBT or vPvB substances.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 10 Jul 2025

Version: 4

Page 11/14



## Power Lube 200ml PP

### 12.6. Endocrine disrupting properties

No further relevant information available.

### 12.7. Other adverse effects

None known

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### 13.1.1. Product/Packaging disposal

#### Waste codes/waste designations according to EWC/AVV

##### Waste code product

|            |   |
|------------|---|
| 16 05 04 * | Gases in pressure containers (including halons) containing hazardous substances |
|------------|---|

\*: Evidence for disposal must be provided.

##### Waste code packaging

|          |                    |
|----------|--------------------|
| 15 01 04 | metallic packaging |
|----------|--------------------|

#### Waste treatment options

##### Appropriate disposal / Product:

Waste generation should be avoided or minimised wherever possible. Disposal of this product and its solutions and by-products must at all times be carried out in compliance with environmental protection requirements and waste disposal legislation and the requirements of local authorities. be carried out. Dispose of surpluses and products not suitable for recycling via a recognised waste disposal company. Do not discharge waste untreated into the sewerage system unless all applicable regulations of the authorities are complied with.








##### Appropriate disposal / Package:

Waste generation should be avoided or minimised where possible. Packaging waste should be recycled. Incineration or landfilling should only be considered if recycling is not feasible.

##### Other disposal recommendations:

Waste and containers must be disposed of in a safe manner. Take care when handling empty containers that have not been cleaned or rinsed out. Empty dispersal and run-off of released material and contact with soil, water bodies, drains and sewers.

## SECTION 14: Transport information

| Land transport (ADR/RID)   | Inland waterway craft (ADN)  | Sea transport (IMDG)   | Air transport (ICAO-TI / IATA-DGR)   |
|--|--|--|--|
| <b>14.1. UN number or ID number</b>  |  |  |  |
| UN 1950  | UN 1950  | UN 1950  | UN 1950  |
| <b>14.2. UN proper shipping name</b>   |  |  |  |
| AEROSOLS (copper, zinc oxide)  | AEROSOLS (copper, zinc oxide)  | AEROSOLS (copper, zinc oxide)  | AEROSOLS, NON-FLAMMABLE  |
| <b>14.3. Transport hazard class(es)</b>  |  |  |  |
| <br>2.2 | <br>2.2 | <br>2.2           | <br>2.2 |
| <b>14.4. Packing group</b>   |  |  |  |
|  |  | -  |  |
| <b>14.5. Environmental hazards</b>   |  |  |  |
|         |         |  MARINE POLLUTANT | No   |
| <b>14.6. Special precautions for user</b>  |  |  |  |
| <b>Special Provisions:</b><br>190   327   344   625  | <b>Special Provisions:</b><br>190   327   344   625  | <b>Special Provisions:</b><br>63   190   277   327   344   381   959                                 | <b>Special Provisions:</b><br>A98   A145   A167  |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 10 Jul 2025

Version: 4



Page 12/14

## Power Lube 200ml PP

| Land transport (ADR/RID)   | Inland waterway craft (ADN)  | Sea transport (IMDG)   | Air transport (ICAO-TI / IATA-DGR)   |
|--|--|--|--|
| <b>Limited quantity (LQ):</b><br>1 L<br><b>Excepted Quantities (EQ):</b><br>E0<br><b>Classification code:</b><br>5A<br><b>Tunnel restriction code:</b><br>(E)<br><b>Remark:</b><br>Labelling as an environmentally hazardous substance is not required if this substance is transported in quantities of $\leq 5$ l or $\leq 5$ kg.<br>Transport on the factory premises: only transport in closed containers that are upright and firm. Persons transporting the product must be instructed in the correct behaviour in case of accidents, leakage or spillage. | <b>Limited quantity (LQ):</b><br>1 L<br><b>Excepted Quantities (EQ):</b><br>E0<br><b>Classification code:</b><br>5A<br><b>Remark:</b><br>Labelling as an environmentally hazardous substance is not required if this substance is transported in quantities of $\leq 5$ l or $\leq 5$ kg.<br>Transport on the factory premises: only transport in closed containers that are upright and firm. Persons transporting the product must be instructed in the correct behaviour in case of accidents, leakage or spillage. | <b>Limited quantity (LQ):</b><br>Siehe SV277<br><b>Excepted Quantities (EQ):</b><br>E0<br><b>EmS-No.:</b><br>F-D, S-U<br><b>Remark:</b><br>Labelling as a marine pollutant is not required if this substance is transported in quantities of $\leq 5$ l or $\leq 5$ kg.<br>Transport on the factory premises: only transport in closed containers that are upright and firm. Persons transporting the product must be instructed in the correct behaviour in case of accidents, leakage or spillage. | <b>Limited quantity (LQ):</b><br>Y203<br><b>Excepted Quantities (EQ):</b><br>E0<br><b>Remark:</b><br>Labelling as an environmentally hazardous substance may be present if required by other transport regulations.<br>Quantity limit: Passenger and Cargo Aircraft: 75 kg.<br>Packing Instructions: 203.<br>Cargo Aircraft Only: 150 kg.<br>Packing Instructions: 203.<br>Limited Quantities - Passenger Aircraft: 30 kg.<br>Packing Instructions: Y203.<br>Transport on the factory premises: only transport in closed containers that are upright and firm. Persons transporting the product must be instructed in the correct behaviour in case of accidents, leakage or spillage. |

### 14.7. Maritime transport in bulk according to IMO instruments

No data available

## SECTION 15: Regulatory information

### \* 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU legislation

##### Authorisations:

Regulation (EC) No 1907/2006 ANNEX XVII

Annex XIV - List of substances subject to authorisation: None of the ingredients are included.

Ozone depleting substances (1005/2009/EU): Not listed.

Prior Informed Consent (PIC) (649/2012/EU): Not listed.

Restrictions on the production, placing on the market and use of persistent organic pollutants: Not listed.

##### Other regulations (EU):

Hazard categories:

- E1 Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1
- E2 Hazardous to the Aquatic Environment in Category Chronic 2

#### 15.1.2. National regulations

No data available

### 15.2. Chemical Safety Assessment

No data available

## SECTION 16: Other information

### \* 16.1. Indication of changes

|       |  |
|-------|--|
| 1.3.  | Details of the supplier of the safety data sheet   |
| 8.1.  | Control parameters   |
| 15.1. | Safety, health and environmental regulations/legislation specific for the substance or mixture |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 7 Jul 2025

Print date: 10 Jul 2025

Version: 4



Page 13/14

## Power Lube 200ml PP

16.1. Indication of changes

### 16.2. Abbreviations and acronyms

|                  |   |
|------------------|---|
| ACGIH            | American Conference of Governmental Industrial Hygienists                                       |
| ADN              | European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways |
| ADR              | European Agreement concerning the International Carriage of Dangerous Goods by Road             |
| BCF              | Bioconcentration Factor   |
| CAS              | Chemical Abstracts Service  |
| CLP              | Classification, Labelling and Packaging   |
| DIN              | German Institute for Standardization / German Industrial Standard                               |
| DNEL             | derived no-effect level   |
| EC <sub>50</sub> | Effective Concentration 50%   |
| EN               | European Standard   |
| ES               | Exposure scenario   |
| EWC              | European Waste Catalogue  |
| IC <sub>50</sub> | Inhibition Concentration 50 %   |
| ICAO             | International Civil Aviation Organization   |
| IMDG             | International Maritime Dangerous Goods  |
| IMO              | International Maritime Organization   |
| ISO              | International Standards Organisation  |
| KG               | body weight   |
| LC <sub>50</sub> | Lethal (fatal) Concentration 50%  |
| LD <sub>50</sub> | Lethal (fatal) Dose 50%   |
| MAK              | Maximum concentration in the workplace air (CH)   |
| NFPA             | National Fire Protection Association  |
| NIOSH            | National Institute for Occupational Safety & Health   |
| NOEC             | No Observed Effect Concentration  |
| OECD             | Organisation for Economic Cooperation and Development   |
| OSHA             | Occupational Safety & Health Administration   |
| PBT              | persistent and bioaccumulative and toxic  |
| PNEC             | Predicted No Effect Concentration   |
| REACH            | Registration, Evaluation and Authorization of Chemicals   |
| RID              | Dangerous goods regulations for transport by rail   |
| TRGS             | Technische Regeln für Gefahrstoffe  |
| UN               | United Nations  |

### 16.3. Key literature references and sources for data

No data available

### 16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

| Hazard classes and hazard categories                                 | Hazard statements                                      | Classification procedure |
|--|--|--------------------------|
| Serious eye damage/eye irritation<br>( <i>Eye Dam. 1</i> )           | H318: Causes serious eye damage.                       |                          |
| Hazardous to the aquatic environment<br>( <i>Aquatic Acute 1</i> )   | H400: Very toxic to aquatic life.                      |                          |
| Hazardous to the aquatic environment<br>( <i>Aquatic Chronic 2</i> ) | H411: Toxic to aquatic life with long lasting effects. |                          |
| aerosol dispensers and lighters<br>( <i>Aerosol 3</i> )              | H229: Pressurised container: May burst if heated.      |                          |

### 16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

| Hazard statements |   |
|-------------------|---|
| H228              | Flammable solid.                                |
| H261              | In contact with water releases flammable gases. |
| H302              | Harmful if swallowed.                           |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

**Revision date:** 7 Jul 2025

**Print date:** 10 Jul 2025

**Version:** 4



Page 14/14

## Power Lube 200ml PP

| Hazard statements |   |
|-------------------|---|
| H315              | Causes skin irritation.                               |
| H317              | May cause an allergic skin reaction.                  |
| H318              | Causes serious eye damage.                            |
| H335              | May cause respiratory irritation.                     |
| H400              | Very toxic to aquatic life.                           |
| H410              | Very toxic to aquatic life with long lasting effects. |
| H411              | Toxic to aquatic life with long lasting effects.      |

### 16.6. Training advice

No data available

### 16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

\* Data changed compared with the previous version.