

Automotive LPG HP

ADL

HIGH PERFORMANCE ADDITIVE FOR LPG AND CNG ENGINES

- Prevents petrol fuel oxidation due to age
- Prevents deposits in the fuel system thanks to its Keep Clean Effect
- Optimally protects against valve impact damage
- Minimizes wear and tear
- Protects the entire fuel system against corrosion
- Prevents the formation of residue



General Information

LPG BENZINE HP is a specially developed concentrate for LPG (Liquefied Petroleum Gas) and CNG (Compressed Natural Gas)

engines. LPG BENZINE HP reduces valve wear and tear (impact damage) and safeguards long-term fuel stability.

Technical Information

Form: liquid
Colour: yellow, clear
Odour: solvent like
Initial boiling point: 139°C
Flash point: 24°C

Lower explosion limits: 0,6 vol. %
Upper explosion limits: 7 vol. %
Oxidizing properties: Not oxidizing.
Density (at 20°C): 0,8235 g/cm³
Viscosity / kinematic (at 40°C): < 7 mm²/s

Application and Use

- **APPLICATION**
When converting to LPG
When servicing the system
When repairing the system
Also suitable for CNG engines
- **USE**
Add the contents of the tin to the petrol tank.
Dosage:
One tin suffices for up to 80 litres of fuel.
Minimum filling level 10 litres.
- **USING STRONG:**
With the engine off, disconnect the inlet tube of the gas (LPG or CNG) from fluted injectors after the filter of low pressure.
With a dispenser enter up to 50 ml of LPG GASOLINE HP in the tube. Replace and tighten the tube.
Turn on the car (petrol), as the system will be converted to LPG or CNG turn off the car or switchover of gasoline for 10-15 minutes, so the product will act directly on the injectors gas. If necessary repeat the process until you have the perfect operation of the injectors. The rest of the product (250 ml) should be poured into the gas tank (soft treatment: 300ml only in the fuel tank).

Article nr	Name	Content	Shelf Life	Catalog
T712001	LPG Benzine HP 300ml	300ml	see imprint + 24 months	ADDITIVES



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



ADDITIVES

WWW.TECH-MASTERS.EU

